

ASME PTB-1-2014

ASME Section VIII – Division 2 Criteria and Commentary

Currently in preview, click buy full version



PTB-1-2014

ASME Section VIII – Division 2 Criteria and Commentary

David A. Osage, P.E.

James C. Sowinski, P.E.

The Equity Engineering Group, Inc.



Date of Issuance: May 27, 2014

This document was prepared as an account of work sponsored by ASME Pressure Technology Codes and Standards (PTCS) through the ASME Standards Technology, LLC (ASME ST-LLC).

Neither ASME, the author, nor others involved in the preparation or review of this document, nor any of their respective employees, members or persons acting on their behalf, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe upon privately owned rights.

Reference herein to any specific commercial product, process or service by trade name, trademark, manufacturer or otherwise does not necessarily constitute or imply its endorsement, recommendation or favoring by ASME or others involved in the preparation or review of this document, or any agency thereof. The views and opinions of the authors, contributors and reviewers of the document expressed herein do not necessarily reflect those of ASME or others involved in the preparation or review of this document, or any agency thereof.

ASME does not “approve,” “rate”, or “endorse” any item, construction, proprietary device or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) associated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME is the registered trademark of The American Society of Mechanical Engineers.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

ISBN No. 978-0-7918-6927-7

Copyright © 2014 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS

All rights reserved

Printed in the U.S.A.



TABLE OF CONTENTS

Foreword.....	xi
Acknowledgements	xiii
Organization and Use	xiv
1 GENERAL REQUIREMENTS.....	1
1.1 General.....	1
1.1.1 Introduction	1
1.1.2 Organization.....	1
1.1.3 Definitions	2
1.2 Scope	2
1.2.1 Overview	2
1.2.2 Additional Requirements for Very High Pressure Vessels	3
1.2.3 Geometric Scope of This Division.....	3
1.2.4 Classifications Outside the Scope of this Division	3
1.2.5 Combination Units.....	4
1.2.6 Field Assembly of Vessels	4
1.2.7 Pressure Relief Devices.....	4
1.3 Standards Referenced by This Division	4
1.4 Units of Measurement	4
1.5 Tolerances.....	4
1.6 Technical Inquires	5
1.7 Annexes	5
2 RESPONSIBILITIES AND DUTIES	6
2.1 General.....	6
2.2 User Responsibilities.....	6
2.3 Manufacturer's Responsibilities	7
2.3.1 Code Compliance	7
2.3.2 Materials Selection.....	7
2.3.3 Manufacturer's Design Report	7
2.3.4 Manufacturer's Data Report	8
2.3.5 Manufacturer's Construction Records	8
2.3.6 Quality Control System	8
2.3.7 Certification of Subcontracted Services.....	8
2.3.8 Inspection and Examination.....	9
2.3.9 Application of Certification Mark	9
2.4 The Inspector	9
2.5 Criteria and Commentary Tables	13
3 MATERIALS REQUIREMENTS	15
3.1 General Requirements	15
3.2 Materials Permitted for Construction of Vessel Parts	15
3.3 Supplemental Requirements for Ferrous Materials	16
3.4 Supplemental Requirements for Cr-Mo Steels	17
3.5 Supplemental Requirements for Q&T Steels with Enhanced Tensile Properties	17
3.6 Supplemental Requirements for Nonferrous Materials	17
3.7 Supplemental Requirements for Bolting	17
3.8 Supplemental Requirements for Castings	18
3.9 Supplemental Requirements for Hubs Machined From Plate.....	18
3.10 Material Test Requirements	18
3.11 Material Toughness Requirements	18
3.11.1 General	18
3.11.2 Carbon and Low Alloy Steels Except Bolting	19

3.11.3	Quenched and Tempered Steels	24
3.11.4	High Alloy Steels Except Bolting	24
3.11.5	Non-Ferrous Alloys	24
3.11.6	Bolting Materials	24
3.11.7	Toughness Testing Procedures	24
3.11.8	Impact Testing of Welding Procedures and Test Plates of Ferrous Materials	24
3.12	Allowable Design Stresses	24
3.13	Strength Parameters	27
3.14	Physical Properties	27
3.15	Design Fatigue Curves	27
3.16	Nomenclature	27
3.17	Definitions	27
3.18	Annexes	27
3.19	Criteria and Commentary References	31
3.20	Criteria and Commentary Nomenclature	32
3.21	Criteria and Commentary Tables	36
3.22	Criteria and Commentary Figures	49
4	DESIGN-BY-RULE REQUIREMENTS	71
4.1	General Requirements	71
4.1.1	Scope	71
4.1.2	Minimum Thickness Requirements	72
4.1.3	Material Thickness Requirements	72
4.1.4	Corrosion Allowance in Design Equations	72
4.1.5	Design Basis	72
4.1.6	Design Allowable Stress	75
4.1.7	Materials in Combination	75
4.1.8	Combination Units	75
4.1.9	Cladding and Weld Overlay	76
4.1.10	Internal Linings	76
4.1.11	Flanges and Pipe Fittings	76
4.1.12	Nomenclature	76
4.2	Design Rules for Welded Joints	76
4.2.1	Scope	76
4.2.2	Weld Category	76
4.2.3	Weld Joint Type	77
4.2.4	Weld Joint Factor	77
4.2.5	Types of Joints Permitted	77
4.2.6	Nomenclature	77
4.3	Design Rules for Shells Under Internal Pressure	77
4.3.1	Scope	77
4.3.2	Shell Tolerances	77
4.3.3	Cylindrical Shells	78
4.3.4	Conical Shells	83
4.3.5	Cylindrical Shells and Hemispherical Heads	83
4.3.6	Toruspherical Heads	85
4.3.7	Ellipsoidal Heads	88
4.3.8	Local Thin Areas	88
4.3.9	Drilled Holes not Penetrating Through the Vessel Wall	89
4.3.10	Combined Loadings and Allowable Stresses	89
4.3.11	Cylindrical-To-Conical Shell Transition Junctions Without a Knuckle	90
4.3.12	Cylindrical-To-Conical Shell Transition Junctions With a Knuckle	90
4.3.13	Nomenclature	91
4.4	Design Rules for Shells Under External Pressure and Allowable Compressive Stresses	91
4.4.1	Scope	91
4.4.2	Design Factors	92



4.4.3	Material Properties	92
4.4.4	Shell Tolerances	93
4.4.5	Cylindrical Shells.....	93
4.4.6	Conical Shell	94
4.4.7	Spherical Shell and Hemispherical Head	94
4.4.8	Torispherical Head.....	95
4.4.9	Ellipsoidal Head	95
4.4.10	Local Thin Areas.....	95
4.4.11	Drilled Holes not Penetrating Through the Vessel Wall.....	95
4.4.12	Combined Loadings and Allowable Compressive Stresses	95
4.4.13	Cylindrical-To-Conical Shell Transition Junctions Without a Knuckle	95
4.4.14	Cylindrical-To-Conical Shell Transition Junctions With a Knuckle	95
4.4.15	Nomenclature.....	95
4.5	Design Rules for Shells Openings in Shells and Heads	95
4.6	Design Rules for Flat Heads	97
4.7	Design Rules for Spherically Dished Bolted Covers	97
4.8	Design Rules for Quick Actuating (Quick Opening) Closures.....	98
4.9	Design Rules for Braced and Stayed Surfaces.....	98
4.10	Design Rules for Ligaments	98
4.11	Design Rules for Jacketed Vessels	98
4.12	Design Rules for NonCircular Vessels	99
4.13	Design Rules for Layered Vessels	100
4.14	Evaluation of Vessels Outside of Tolerance.....	100
4.14.1	Shell Tolerances	100
4.14.2	Local Thin Areas	100
4.14.3	Marking and Reports.....	100
4.15	Design Rules for Supports and Attachment.....	100
4.15.1	Scope	100
4.15.2	Design of Supports	100
4.15.3	Saddle Supports for Horizontal Vessels	101
4.15.4	Skirt Supports for Vertical Vessels	101
4.15.5	Lug and Leg Supports.....	101
4.15.6	Nomenclature.....	102
4.16	Design Rules for Flanged Joints	102
4.17	Design Rules for Clamped Connections	103
4.18	Design Rules for Shell and Tube Heat Exchangers.....	103
4.19	Design Rules for Bellows Expansion Joints	104
4.20	Criteria and Commentary References.....	105
4.21	Criteria and Commentary Nomenclature	108
4.22	Criteria and Commentary	116
4.23	Criteria and Commentary Figures	126
5	DESIGN-BY-ANALYSIS REQUIREMENTS.....	142
5.1	General Requirements	142
5.1.1	Scope	142
5.1.2	Numerical Analysis	143
5.1.3	Loading Conditions	143
5.2	Protection Against Plastic Collapse	146
5.2.1	Overview	146
5.2.2	Elastic Stress Analysis Method.....	147
5.2.3	Limit-Load Analysis Method.....	151
5.2.4	Elastic-Plastic Stress Analysis Method	153
5.3	Protection Against Local Failure	154
5.3.1	Overview	154
5.3.2	Elastic Analysis	154
5.3.3	Elastic-Plastic Analysis	155



5.4	Protection Against Collapse from Buckling.....	158
5.5	Protection Against Failure from Cyclic Loading.....	159
5.5.1	Overview.....	159
5.5.2	Screening Criteria for Fatigue Analysis.....	160
5.5.3	Fatigue Assessment – Elastic Stress Analysis and Equivalent Stresses.....	165
5.5.4	Fatigue Assessment – Elastic-Plastic Stress Analysis and Equivalent Strains.....	172
5.5.5	Fatigue Assessment of Welds – Elastic Stress Analysis and Structural Stress.....	173
5.5.6	Ratcheting – Elastic Stress Analysis.....	180
5.5.7	Ratcheting Assessment – Elastic-Plastic Stress Analysis.....	183
5.6	Supplemental Requirements for Stress Classification in Nozzle Necks.....	184
5.7	Supplemental Requirements for Bolts.....	185
5.8	Supplemental Requirements for Perforated Plates.....	187
5.9	Supplemental Requirements for Layered Vessels.....	185
5.10	Experimental Stress Analysis.....	186
5.11	Fracture Mechanic Evaluations.....	185
5.12	Definitions.....	185
5.13	Annexes.....	186
5.14	Criteria and Commentary References.....	187
5.15	Criteria and Commentary Nomenclature.....	189
5.16	Criteria and Commentary.....	198
5.17	Criteria and Commentary Figures.....	216
6	FABRICATION REQUIREMENTS.....	226
6.1	General Fabrication Requirements.....	226
6.1.1	Materials.....	226
6.1.2	Forming.....	227
6.1.3	Base Metal Preparation.....	227
6.1.4	Fitting and Alignment.....	228
6.1.5	Cleaning of Surfaces to be Welded.....	228
6.1.6	Alignment Tolerances for Edges to be Butted.....	228
6.2	Welding Fabrication Requirements.....	228
6.2.1	Welding Processes.....	228
6.2.2	Welding Qualifications and Records.....	229
6.2.3	Precautions to be Taken Before Welding.....	229
6.2.4	Specific Requirements for Welded Joints.....	229
6.2.5	Miscellaneous Welding Requirements.....	230
6.2.6	Summary of Joints Permitted and Their Examination.....	230
6.2.7	Repair of Weld Defects.....	230
6.2.8	Special Requirements for Welding Test Plates for Titanium Materials.....	230
6.3	Special Requirements for Tube-To-Tubesheet Welds.....	230
6.4	Preheating and Postweld Heat Treatment of Weldments.....	231
6.4.1	Requirements for Preheating of Welds.....	231
6.4.2	Requirements for Postweld Heat Treatment.....	231
6.4.3	Procedures for Postweld Heat Treatment.....	233
6.4.4	Operation of Postweld Heat Treatment.....	234
6.4.5	Postweld Heat Treatment After Repairs.....	234
6.4.6	Postweld Heat Treatment of Nonferrous Materials.....	235
6.5	Special Requirements for Clad or Weld Overlay Linings, and Lined Parts.....	235
6.6	Special Requirements for Tensile Property Enhanced Q&T Ferritic Steels.....	236
6.7	Special Requirements for Forged Vessel Fabrication.....	237
6.8	Special Fabrication Requirements for Layered Vessels.....	237
6.9	Special Fabrication Requirements for Expansion Joints.....	237
6.10	Criteria and Commentary References.....	237
6.11	Criteria and Commentary Nomenclature.....	238
6.12	Criteria and Commentary Tables.....	238



7	INSPECTION AND EXAMINATION REQUIREMENTS	239
7.1	General	239
7.2	Responsibilities and Duties	239
7.3	Qualification of Nondestructive Examination Personnel	239
7.3.1	Nondestructive Examination Requirements	240
7.3.2	Examination Groups for Pressure Vessels	240
7.3.3	Extent of Nondestructive Examination	241
7.3.4	Selection of Examination Methods for Internal (Volumetric) Flaws	241
7.3.5	Selection of Examination Methods for Surface Flaws	242
7.3.6	Surface Condition and Preparation	242
7.3.7	Supplemental Examination for Cyclic Service	242
7.3.8	Examination and Inspection of Vessels with Protective Linings and Cladding	242
7.3.9	Examination and Inspection of Tensile Property Enhanced Q and T Vessels	242
7.3.10	Examination Requirements of Integrally Forged Vessels	242
7.3.11	Examination and Inspection of Fabricated Layered Vessels	242
7.3.12	Examination and Inspection of Expansion Joints	242
7.4	Examination Method and Acceptance Criteria	243
7.4.1	General	243
7.4.2	Visual Examination	243
7.4.3	Radiographic Examination	243
7.4.4	Ultrasonic Examination	243
7.4.5	Magnetic Particle Examination (MT)	245
7.4.6	Liquid Penetrant Examinations (PT)	245
7.4.7	Eddy Current Surface Examination Procedure Requirements (ET)	245
7.4.8	Evaluation and Retest for Partial Examination	245
7.5	Final Examination of Vessel	245
7.5.1	Surface Examination After Hydrotest	245
7.5.2	Inspection of Lined Vessel Interior After Hydrotest	245
7.6	Leak Testing	246
7.7	Acoustic Emission	246
7.8	Annexes	246
7.9	Criteria and Commentary References	246
7.10	Criteria and Commentary Tables	247
8	PRESSURE TESTING REQUIREMENTS	253
8.1	General Requirements	253
8.2	Hydrostatic Testing	254
8.3	Pneumatic Testing	254
8.4	Alternative Pressure Testing	255
8.5	Documentation	255
8.6	Nomenclature	255
8.7	Criteria and Commentary References	255
8.8	Criteria and Commentary Nomenclature	255
9	PRESSURE VESSEL OVERPRESSURE PROTECTION	256
9.1	General Requirements	256
9.2	Pressure Relief Valves	256
9.3	Non-Reclosing Pressure Relief Devices	256
9.4	Calculation of Rated Capacity for Different Relieving Pressures and/or Fluids	256
9.5	Marking and Stamping	256
9.6	Provisions for Installation of Pressure Relieving Devices	256
9.7	Overpressure Protection by Design	257
9.8	Criteria and Commentary References	257
ANNEX A		258

LIST OF FIGURES

Figure 2-1: Typical Certification of Compliance of the User's Design Specification (VIII-2 Table 2-A.1)	13
Figure 2-2: Typical Certification of Compliance of the Manufacturer's Design Report (VIII-2 Table 2-B.1)	14
Figure 3-1: Material Assignment Table Based on Exemption Curves and Notes for Figure 3-16 and 3-17	36
Figure 3-2: Criteria for Establishing Allowable Stress Values for ASME B&PV Code Section II, Part D, Tables 5A and 5B	38
Figure 3-3: Criteria for Establishing Allowable Stress Values for ASME B&PV Code Section II, Part D, Tables 5A and 5B	39
Figure 3-4: Criteria for Establishing Allowable Stress Values for ASME B&PV Code Section II, Part D, Table 4	40
Figure 3-5: Criteria for Establishing the Nominal Design Stress for Pressure Parts Other than Bolt per EN13445	41
Figure 3-6: Criteria for Establishing the Nominal Design Stress for Bolting per EN13445	42
Figure 3-7: Strength Parameters and Allowable Stress for SA 516 Grade 70 and P295GH	43
Figure 3-8: Strength Parameters and Allowable Stress for SA 240 Type 304 and X5CrNi18-10	44
Figure 3-9: (VIII-2 Table 3.D.1) – Stress-Strain Curve Parameters	45
Figure 3-10: (VIII-2 Table 3.D.2) – Cyclic Stress-Strain Curve Data	46
Figure 3-11: Uniform Material Law for Estimating Cyclic Stress-Strain and Strain Life Properties	48
Figure 3-12: (VIII-2 Figure 3.3) – Charpy V-Notch Impact Test Requirements for Full-Size Specimens for Carbon and Low Alloy Steels As a Function of the Specified Minimum Yield Strength – Parts Not Subject to PWHT	49
Figure 3-13: (VIII-2 Figure 3.4) – Charpy V-Notch Impact Test Requirements for Full-Size Specimens for Carbon and Low Alloy Steels As a Function of the Specified Minimum Yield Strength – Parts Subject to PWHT	50
Figure 3-14: (VIII-2 Figure 3.5) – Illustration of Lateral Expansion in a Broken Charpy V-Notch Specimen	51
Figure 3-15: (VIII-2 Figure 3.6) – Lateral Expansion Requirements	52
Figure 3-16: (VIII-2 Figure 3.7) – Impact Test Exemption Curves – Parts Not Subject to PWHT	52
Figure 3-17: (VIII-2 Figure 3.8) – Impact Test Exemption Curves - Parts Subject to PWHT and Non-welded Parts	53
Figure 3-18: (VIII-2 Figure 3.9) – Typical Vessel Details Illustrating the Governing Thickness	54
Figure 3-19: (VIII-2 Figure 3.10) – Typical Vessel Details Illustrating the Governing Thickness	55
Figure 3-20: (VIII-2 Figure 3.11) – Typical Vessel Details Illustrating the Governing Thickness	56
Figure 3-21: (VIII-2 Figure 3.12) – Reduction in the MDMT without Impact Testing – Parts Not Subject to PWHT	57
Figure 3-22: (VIII-2 Figure 3.13) – Reduction in the MDMT without Impact Testing - Parts Subject to PWHT and Non-welded Parts	57
Figure 3-23: SA 516 Grade 70 and P295GH Yield Strength – 0.2% Offset	58
Figure 3-25: SA 240 Type 304 and X5CrNi18-10 Yield Strength – 0.2 Percent Offset	59
Figure 3-27: SA 240 Type 304 and X5CrNi18-10 – Tensile Strength	60
Figure 3-29: Section VIII, Division 2 Wall Thickness Comparison: SA 516 Grade 70	61
Figure 3-30: Section VIII, Division 2 Wall Thickness Comparison: SA 537 Class 1, ≤ 2.5 in	62
Figure 3-31: Section VIII, Division 2 Wall Thickness Comparison: SA 537 Class 2, ≤ 2.5 in	63
Figure 3-32: Section VIII, Division 2 Wall Thickness Comparison: SA 737 Grade B	64

Figure 3-33: Section VIII, Division 2 Wall Thickness Comparison: SA 737 Grade C.....	65
Figure 3-34: Section VIII, Division 2 Wall Thickness Comparison: SA 387 Grade 22, Class 1	66
Figure 3-36: Section VIII, Division 2 Wall Thickness Comparison: SA 382 Grade 22V	68
Figure 3-37: Stress-Strain Curve with Yield Plateau	69
Figure 3-38: Effect of Cold Work on the Stress-Strain Curve Yield Plateau	69
Figure 3-39: Monotonic and Cyclic Stress-Strain Curve	70
Figure 4-1: (VIII-2 Table 4.1.1) Design Loads	116
Figure 4-2: (VIII-2 Table 4.1.2) – Design Load Combinations.....	116
Figure 4-3: (VIII-2 Table 4.2.1) – Definition Of Weld Categories	117
Figure 4-4: (VIII-2 Table 4.2.2) – Definition Of Weld Joint Types	118
Figure 4-5: (VIII-2 Table 4.2.5) – Some Acceptable Weld Joints For Formed Heads.....	119
Figure 4-6: (VIII-2 Table 4.2.11) – Some Acceptable Pad Welded Nozzle Attachment And Other Connections To Shells	121
Figure 4-7: (VIII-2 Table 4.12.1) – Noncircular Vessel Configurations And Types	123
Figure 4-8: (VIII-2 Table 4.12.2) – Stress Calculations and Acceptance Criteria for Type 1 Noncircular Vessels (Rectangular Cross Section)	124
Figure 4-9: (VIII-2 Figure 4.2.1) – Weld Joint Locations Typical of categories A, B, C, D, and E.....	126
Figure 4-10: Cylindrical Shell Wall Thickness Equation Comparison Between VIII-2 and Old VIII-2	126
Figure 4-11: Percent Difference in Cylindrical Shell Wall Thickness Equation Between VIII-2 and Old VIII-2.....	127
Figure 4-12: Tresca Yield Criterion.....	127
Figure 4-13: Von Mises Yield Criterion.....	128
Figure 4-14: Tresca Yield Criterion and Von Mises Yield Criterion.....	128
Figure 4-15: Equilibrium of Cylindrical Element	129
Figure 4-16: Equilibrium of Spherical Element.....	129
Figure 4-17: (VIII-2 Figure 4.3.1) – Conical Shell.....	130
Figure 4-18: (VIII-2 Figure 4.3.2) – Offset Conical Transition	130
Figure 4-19: Spherical Shell Wall Thickness Equation Comparison Between VIII-2 and Old VIII-2..	131
Figure 4-20: Percent Difference in Spherical Shell Wall Thickness Equation Between VIII-2 and Old VIII-2.....	131
Figure 4-21: (VIII-2 Figure 4.3.6) – Local Thin Band in a Cylindrical Shell	132
Figure 4-22: (VIII-2 Figure 4.7.1) – Type A Dished Cover with a Bolting Flange.....	133
Figure 4-23: (VIII-2 Figure 4.7.2) – Type B Spherically Dished Cover with a Bolting Flange	133
Figure 4-24: (VIII-2 Figure 4.7.3) – Type C Spherically Dished Cover with a Bolting Flange	134
Figure 4-25: (VIII-2 Figure 4.7.4) – Type D Spherically Dished Cover with a Bolting Flange	134
Figure 4-26: (VIII-2 Figure 4.11.1) – Types of Jacketed Vessels.....	135
Figure 4-27: (VIII-2 Figure 4.11.2) – Types of Partial Jackets	136
Figure 4-28: (VIII-2 Figure 4.11.1) – Half Pipe Jackets	137
Figure 4-29: (VIII-2 Figure 4.12.1) – Type 1 Noncircular Vessels (Rectangular Cross Section)	138
Figure 4-30: (VIII-2 Figure 4.13.1) – Some Acceptable Layered Shell Types	139
Figure 4-31: (VIII-2 Figure 4.13.2) – Some Acceptable Layered Head Types	140
Figure 4-32: (VIII-2 Figure 4.15.8) – A Typical Hot-Box Arrangement for Skirt Supported Vertical Vessels	141
Figure 5-1: (VIII-2 Table 5.1) – Loads And Load Cases To Be Considered In A Design.....	198
Figure 5-2: (VIII-2 Table 5.2) – Load Descriptions	199



Figure 5-3: (VIII-2 Table 5.3) – Load Case Combinations and Allowable Stresses for an Elastic Analysis 200

Figure 5-4: (VIII-2 Table 5.4) – Load Case Combinations and Load Factors for a Limit Load Analysis 201

Figure 5-5: (VIII-2 Table 5.5) – Load Case Combinations and Load Factors for an Elastic-Plastic Analysis..... 202

Figure 5-6: (VIII-2 Table 5.6) – Examples Of Stress Classification 203

Figure 5-7: (VIII-2 Table 5.7) – Uniaxial Strain Limit for use in Multiaxial Strain Limit Criterion 206

Figure 5-8: (VIII-2 Table 5.8) – Temperature Factors For Fatigue Screening Criteria 207

Figure 5-9: (VIII-2 Table 5.9) – Fatigue Screening Criteria For Method A..... 208

Figure 5-10: (VIII-2 Table 5.10) – Fatigue Screening Criteria Factors For Method B 208

Figure 5-11: (VIII-2 Table 5.11) – Weld Surface Fatigue-Strength-Reduction Factors 208

Figure 5-12: (VIII-2 Table 5.12)– Quality Levels for Weld Surface Fatigue-Strength-Reduction Factors 209

Figure 5-13: (VIII-2 Table 5.13) – Fatigue Penalty Factors For Fatigue Analysis 210

Figure 5-14: (VIII-2 Table 3.F.1) – Coefficients for Fatigue Curve 110.1 – Carbon, Low Alloy, Series 4XX, High Alloy Steels, And High Tensile Strength Steels For Temperatures not Exceeding 371 °C (700°F)..... 210

Figure 5-15: (VIII-2 Table 3.F.10) – Data for Fatigue Curves in Part 3, Tables 3.F.1 through 3.F.9. 211

Figure 5-17: (VIII-2 Table 3.F.11) – Coefficients for the Welded Joint Fatigue Curves..... 213

Figure 5-18: Comparison of Fatigue Analysis Methods..... 214

Figure 5-19: Comparison of Method 1 and Method 3 Fatigue Analysis Results 215

Figure 5-20: Comparison of Failure Theories by Lode 216

Figure 5-21: Comparison of Failure Theories by Taylor and Quincy 217

Figure 5-22: (VIII-2 Figure 5.1) – Depiction of Stress Categories and Limits of Equivalent Stress Using the Hopper Diagram..... 218

Figure 5-23: True Stress True Strain Relations at Large Strains for Combinations of Yield and Tensile Strength Indicated in the Legend in US Customary Units 219

Figure 5-25: Effect of Triaxiality on the Relative Fracture Strain for Steels of Various Strain Hardening Coefficients Indicated in the Legend..... 220

Figure 5-26: Buckling Behavior of Shell Components 221

Figure 5-27: Smooth Bar Fatigue Curve in VIII-2 for Carbon, Low Alloy, Series 4XX, High Alloy Steels, and High Tensile Strength Steels 222

Figure 5-28: Weld Toe Dressing by Burr Grinding..... 223

Figure 5-29: Vessel Used for Fatigue Analysis Example, Stress Classification Lines are Shown and are Labeled A through H 223

Figure 5-30: Allowable Secondary Equivalent Stress Range from Thermal Loading with a Linear Variation Through the Wall Thickness 224

Figure 5-31: Allowable Secondary Equivalent Stress Range from Thermal Loading with a Parabolic Constantly Increasing or Decreasing Variation Through the Wall Thickness..... 225

Figure 6-1: (VIII-2 Table 6.1) – Equations For Calculating Forming Strains..... 238

Figure 7-1: (VIII-2 Table 7.1) – Examination Groups For Pressure Vessels 247

Figure 7-2: (VIII-2 Table 7.2) – Nondestructive Examination..... 248

Figure 7-3: (VIII-2 Table 7.6) – Visual Examination Acceptance Criteria 251

FOREWORD

In 1998 the ASME Boiler and Pressure Vessel Standards Committee authorized a project to rewrite the ASME B&PV Code, Section VIII, Division 2. This decision was made shortly after the design margin on specified minimum tensile strength was lowered from 4.0 to 3.5 in Section I and Section VIII, Division 1. ASME saw the need to update Section VIII, Division 2 to incorporate the latest technologies and to be more competitive. In lieu of revising the existing standard, the decision was made to perform a clean sheet rewrite. By doing so it was felt that, not only could the standard be modernized with regard to the latest technical advances in pressure vessel construction, but it could be structured in a way to make it more user-friendly for both users and the committees that maintain it.

Much new ground was broken in the development of the new Section VIII, Division 2, including the process taken to write the new standard. Traditionally, development of new standards by ASME is carried out by volunteers who serve on the different committees responsible for any given standard. Depending upon the complexity of the standard, the development of the first drafts may take up to 15 years to complete based on past history. The prospect of taking 15 or more years to develop VIII-2 was unacceptable to ASME and the volunteer leadership. The decision was made to subcontract the development of the draft to the Pressure Vessel Research Council (PVRC) who in turn formed the Task Group on Continued Modernization of Codes to oversee the development of the new Section VIII, Division 2 Code. PVRC utilized professionals with both engineering and technical writing expertise to develop new technology and the initial drafts of the new Section VIII, Division 2.

A Steering Committee made up of ASME Subcommittee VIII members was formed to provide technical oversight and direction to the development team with the goal of facilitating the eventual balloting and approval process. ASME also retained a Project Manager to manage all the activities required to bring this new standard to publication.

The project began with the development of a detailed table of contents containing every paragraph heading that would appear in the new standard and identifying the source for the content that would be placed in this paragraph. In preparing such a detailed table of contents, the lead authors were able to quickly identify areas where major development effort was required to produce updated rules. A list of some of the new technology produced for VIII-2 rewrite includes:

- Adoption of a design margin on specified minimum tensile strength of 2.4,
- Toughness requirements,
- Design-by-rule for the creep range,
- Conical transition reinforcement requirements,
- Opening reinforcement rules,
- Local strain criteria for design-by-analysis using elastic-plastic analysis,
- Limit load and plastic collapse analysis for multiple loading conditions,
- Fatigue design for welded joints based on structural stress method, and
- Ultrasonic examination in lieu of radiographic examination.

Users of the Section VIII, Division 2 Code (manufacturers and owner/operators) were surveyed at the beginning of the project to identify enhancements that they felt the industry wanted and would lead to increased use of the standard. Since the initial focus of the Code was for the construction of pressure equipment for the chemical and petrochemical industry, the people responsible for specifying equipment for this sector were very much interested in seeing that common requirements that are routinely found in vessel specifications would become a requirement within this standard. This was accomplished by close participation of the petrochemical industry during the development of this standard. Some of the enhancements included:



- Alternatives provided for U.S. and Canadian Registered Professional Engineer certification of the User Design Specification and Manufacturers Design Report,
- Consolidation of weld joint details and design requirements,
- Introduction of a weld joint efficiency and the use of partial radiographic and ultrasonic examination,
- Introduction of the concept of a Maximum Allowable Working Pressure (MAWP) identical to VIII-1,
- Significant upgrade to the design-by-rule and design-by-analysis procedures,
- Extension of the time-independent range for low chrome alloys used in heavy wall vessels,
- Extension of fatigue rules to 900°F (400°C) for low-chrome alloys used in heavy wall vessels,
- Adoption of new examination requirements and simplification of presentation of the rules,
- User-friendly extensive use of equations, tables, and figures to define rules and procedures, and
- ISO format; logical paragraph numbering system and single column format,

Many of these enhancements identified by users were included in the first release of Section VIII, Division 2 in 2007.

After publication of Section VIII, Division 2, ASME contracted with the Equity Engineering Group, Inc. to develop the ASME Section VIII, Division 2 Criteria and Commentary. Valuable background information is provided in this document to assist users in using the Code. In addition, the Criteria and Commentary also ensures that the technology introduced into the Code is properly documented.



ACKNOWLEDGEMENTS

The original manuscript for this document started as an update to Chapter 22 in the Third Edition of K.R. Rao's publication entitled Companion Guide to the ASME Boiler & Pressure Vessel Code: Criteria and Commentary on Select Aspects of the Boiler & Pressure Vessel Code and Code for Pressure Piping. The authors of Chapter 22 were: Thomas Pastor who developed Parts 1, 2, and 8; David Osage who developed Part 4; Robert Brown who developed Part 5; Clay Rodery who developed Parts 6 and 7; and Philip Henry who developed Part 9. Guido Karcher provided valuable comments and corrections as the final editor for Chapter 22. The ASME Section VIII, Division 2 Criteria and Commentary, represents a significant update to the background material originally provided in Chapter 22. Additional details, insights into Committee decisions, and analytical derivations of much of the key technology features are provided.

The Equity Engineering Group, Inc. contributed significant resources to the development of the Criteria and Commentary. In particular: Jeffery Brubaker provided assistance in the documentation of the toughness rules of Part 3; Jeremy Staats reviewed the work of Pellini and developed the documentation for operation on the lower-shelf; James Sowinski developed the background material for conical transition without knuckles or flares in Part 4; Dr. Warren Brown provided background information on both current and future directions for the flange design rules; Dr. Zhenning Cao developed the theory and documentation for the stress analysis of conical transitions with knuckles and flares in Part 4 as well as the overview of the Structural Stress and Master Curve approach for the fatigue evaluation of welds in Part 5; Joel Andreani provided background material covering the development of the load factors in Part 5; and Robert Brown assisted in the development of Part 5.

A special commendation for technology development for the new Section VIII, Division 2 is extended to Dr. Martin Prager of MPC and WRC. Dr. Prager developed many key technology features of the Code including a new universal stress-strain curve that is used for Design-By-Analysis in Part 5 and also for design for external pressure. This stress-strain curve model replaces the A-B Charts in Section II Part D. Dr. Prager developed the material models used in conjunction with the API 579-1/ASME FFS-1 FAD assessment technology for the evaluation of crack-like flaws to develop the new toughness rules of Part 3 that is based on a 20 ft-lb criteria similar to European practice. He also developed the technology for the new strain-based Protection Against Local Failure in Part 5. Together with Dr. Pingsha Dong, Dr. Prager was instrumental in introducing and incorporating the new Structural Stress and Master Fatigue Curve approach for the evaluation of welded joints. This new method is considered state-of-the-art for fatigue assessment of welded joints; it first appears in a code and standards environment in Section VIII, Division 2 and API 579-1/ASME FFS-1. Dr. Prager is currently working to develop new creep-fatigue interaction rules that may be published in future editions of VIII-2.

The authors acknowledge the following individuals for their technical and editorial peer review of this document: Gabriel Auriolles, Ramsey Mahadeen, and Jay Vattappilly.

Finally, the authors would also like to commend the efforts of Tiffany Shaughnessy for her editing and document preparation skills in the publication of this document and Debbie Samodell for her work in producing the graphic images used in most of the figures.

ORGANIZATION AND USE

The 2009 Edition of the ASME B&PV Code, Section VIII, Division 2 Criteria and Commentary, covers the 2007 Edition of Section VIII, Division 2 including the 2008 and 2009 Addenda. In addition, some of the changes planned for the 2010 Edition of the Code are also included. This document will be updated as required to keep pace with future developments in Section VIII, Division 2.

In the ASME B&PV Code, Section VIII, Division 2 Criteria and Commentary, a complete description of the Code is provided including technical background, an overview of many new features, and where significant differences now exist between the new and old Section VIII, Division 2. In this document, the editions of the ASME B&PV Section VIII Codes are identified as follows:

- VIII-1 – Section VIII, Division 1, 2007 Edition
- VIII-2 – Section VIII, Division 2, 2007 Edition
- Old VIII-2 – Section VIII, Division 2, 2004 Edition, 2006 Addenda
- VIII-3 – Section VIII, Division 3, 2007 Edition

The paragraph numbering in the Criteria and Commentary matches that of VIII-2. Figure and tables are numbered consecutively within each part of this document. If the figure or table is from VIII-2, then the VIII-2 figure or table number is provided in parenthesis. Rules for referencing paragraphs, tables and figures are described below.

- References to paragraphs, tables and figures within the Criteria and Commentary are made directly. For example, a reference to paragraph 4.2 in this document would be designated as paragraph 4.2, a reference to Figure 5-20 in this document would be designated as Figure 5-20.
- References to paragraphs, tables and figures in VIII-2 are preceded by the applicable section number. For example, a reference to paragraph 4.2 in Part 4 of VIII-2 would be designated in this document as Section 4, paragraph 4.2, a reference to Table 3.4 in Part 3 of VIII-2 would be designated as Section 3, Figure 3.4, and a reference to Figure 5-205.20 of Part 5 of VIII-2 would be designated Section 5, Figure 5-20.
- References to paragraphs, tables and figures in VIII-1, Old VIII-2, or VIII-2 are preceded by this code designation. For example, a reference to paragraph UW-26(d) in VIII-1 would be designated in this document as VIII-1, UW-26(d), a reference to Table UW-12 or VIII-1 would be designated as VIII-1, Table UW-12, and a reference to Figure UW-13.1 of VIII-1 would be designated VIII-1, Figure UW-13.1.
- References to other sections of the ASME B&PV Code are made directly. For example a reference to the ASME B&PC Code, Section II, Part D would be designated as Section II, Part D, and a reference to Article 23 of Section V would be designated as Section V, Article 23.

The term Section VIII Committee used in this document refers to the Section VIII Standards Committee of the ASME B&PV Code.

Annex A of this document includes the original criteria document for Section VIII, Division 2 entitled *Criteria of the ASME Boiler and Pressure Vessel Code for Design by Analysis in Sections III and VIII, Division 2* originally published in: *Pressure Vessels and Piping: Design and Analysis, A Decade of Progress, Volume One, Analysis, ASME, New York, N.Y., 1972, pages 61-83*. This reference is provided because some of the original criteria in Old VIII-2 have been kept in the development of VIII-2.



1 GENERAL REQUIREMENTS

1.1 General

1.1.1 Introduction

Section 1 contains general type requirements addressing the following subjects:

- Paragraph 1.1 – General; Introduction; Organization of the standard
- Paragraph 1.2 – Scope
- Paragraph 1.3 – Reference Standards
- Paragraph 1.4 – Units of Measurement
- Paragraph 1.5 – Tolerances
- Paragraph 1.6 – Technical Inquiries
- Paragraph 1.7 – Tables
- Annex 1-A – Deleted
- Annex 1-B – Definitions
- Annex 1-C – Guidance for the Use of US Customary and SI Units in the ASME Boiler and Pressure Vessel Codes

1.1.2 Organization

The requirements of VIII-2, are contained in the nine Sections listed below. Each of these Sections and related Annexes is composed of paragraphs that are identified by an alphanumeric numbering system in accordance with the ISO Standard Template for the Preparation of Normative-Type Documents. References to paragraphs are made directly by reference to the paragraph number. For example, the Scope is referenced as paragraph 1.2.

- a) Section 1 – General Requirements: provides the scope of VIII-2 and establishes the extent of coverage.
- b) Section 2 – Responsibilities and Duties: sets forth the responsibilities of the user and Manufacturer, and the duties of the Inspector.
- c) Section 3 – Material Requirements: provides the permissible materials of construction, applicable material specifications, and special requirements, physical properties, allowable stresses, and design fatigue curves.
- d) Section 4 – Design By Rule Requirements: provides requirements for design of vessels and components using rules.
- e) Section 5 – Design By Analysis Requirements: provides requirements for design of vessels and components using analytical methods.
- f) Section 6 – Fabrication Requirements: provides requirements governing the fabrication of vessels and parts of vessels.
- g) Section 7 – Examination and Inspection Requirements: provides requirements governing the examination and inspection of vessels and parts of vessels.
- h) Section 8 – Pressure Testing Requirements: provides pressure testing requirements for fabricated vessels.
- i) Section 9 – Pressure Vessel Overpressure Protection: provides rules for pressure relief devices.

The organization within each section is as follows:

- a) Rules and requirements organized in paragraphs using the ISO numbering system

- b) Nomenclature
- c) Tables
- d) Figures
- e) Normative Annexes (mandatory)
- f) Informative Annexes (non-mandatory)

Mandatory and non-mandatory requirements are provided as normative and informative annexes, respectively, to the specific Part under consideration. The Normative Annexes address specific subjects not covered elsewhere in this Division and their requirements are mandatory when the subject covered is included in construction under this Division. The Informative Annexes provide information and suggested good practices.

Unlike all of the other ASME BPV Standards, VIII-2 has been published in single column format, which facilitates use of the standard in electronic form, since its initial release in 2007. A detailed Table of Contents precedes each Part, and each is numbered independently of each other.

1.1.3 Definitions

The definitions for the terminology are provided in Annex 1-B.

1.2 Scope

1.2.1 Overview

Part 1, paragraph 1.2 defines the scope of coverage for VIII-2. The term scope refers to both the type of pressure equipment being considered in the development of these rules, as well as the geometric scope of the vessel that is stamped with the Certification Mark and U2 Designator as meeting VIII-2.

In accordance with Part 1, paragraph 1.2.1.1, pressure vessels are defined as containers for the containment of pressure, internal or external. This pressure may be obtained from any external source, or by the application of heat from a direct or indirect source, as a result of a process, or any combination thereof.

The manner in which the scope of the standard is described follows very closely to the introduction section of VIII-1. In the following paragraphs, a discussion of requirements is provided only where a significant difference exists between VIII-2 and the scope definition from VIII-1, or where a major change was made from Old VIII-2.

With regard to pressure vessels installed in non-stationary applications, Part 1, paragraph 1.2.1.2.b now permits stamping with the Certification Mark and U2 Designator of VIII-2 vessels installed on motor vehicles and railway cars. This particular application was prohibited in the Old VIII-2. Construction and stamping with the Certification Mark and U2 Designator of VIII-2 vessels in non-stationary applications requires a prior written agreement with the local jurisdictional authority covering operation and maintenance control for a specific service. This operation and maintenance control must be retained during the useful life of the pressure vessel by the user in conformance with the Users Design Specification.

Part 1, paragraph 1.2.1.2.e defines pressure vessels in which steam is generated but which are not classified as Unfired Steam Boilers that require construction in accordance with the rules of Section I or VIII-1. A third category for a vessel that generates steam that may be constructed to VIII-2 was added, paragraph 1.2.1.2.e.3: vessels in which steam is generated but not withdrawn for external use.

One significant difference between VIII-2 and the Old VIII-2 is special service vessels such as those in lethal service. In Old VIII-2, paragraph AG-301.1(c), the user and/or his designated agent had to define in the UDS if a vessel was intended for lethal service. If lethal service was specified, then additional

technical requirements (e.g. enhanced NDE, restrictions on material, etc.) were imposed on this vessel. In VIII-2, additional requirements are not specified for lethal service or any other special service condition. The rationale behind this change is that the user and/or his designated agent are responsible to describe in the UDS (see Part 2, paragraph 2.2.2), the intended operation of the vessel, and if a vessel is intended for a service that is dangerous to life and property, then the user should specify any additional requirements to mitigate the risks. Just as it has been the rule in ASME that its standards would not define when a vessel is in lethal service, what additional requirements would be appropriate for any given vessel are best defined by the user, and not by the Committee.

1.2.2 Additional Requirements for Very High Pressure Vessels

The rules of VIII-2 do not specify a limitation on pressure but are not all-inclusive for all types of construction. For very high pressures, additions to these rules may be required to meet the design principles and construction practices essential to vessels for such pressures. However, only in the event that, after application of additional design principles and construction practices, the vessel still complies with all of the requirements of the Code, may it be stamped with the Certification Mark. As an alternative to VIII-2, it is recommended that VIII-3 be considered for the construction of vessels intended for operating pressures exceeding 68.95 MPa (10,000 psi).

1.2.3 Geometric Scope of This Division

The geometric scope of VIII-2 is intended to include only the vessel and integral communicating chambers, and the boundaries set forth are the same as presented in the Introduction chapter of VIII-1. The vessel's scope is defined considering: the attachment of external piping, other vessels or mechanical device; nonpressure parts welded directly to the vessel's pressure retaining surface; pressure retaining covers and their fasteners; and the first sealing surface of connections, fittings or components that are designed to rules that are not provided in VIII-2.

1.2.4 Classifications Outside the Scope of this Division

Similar to the Introduction chapter of VIII-1, the description of pressure equipment covered by the scope of VIII-2 is handled by listing the type of equipment that is not covered under the scope of the standard. However, there is one significant difference between VIII-1 and VIII-2 in this regard. Both standards will allow a pressure vessel that is otherwise outside the scope of the standard to be stamped with the Certification Mark and appropriate U-Designator so long as all of the applicable requirements of the standard are satisfied. In VIII-1 this includes vessels that are otherwise covered under the scope of another standard. However, in Part 1, paragraph 1.2.4.2, if a pressure vessel is included in the scope of another ASME code section then it may not be constructed and stamped with the Certification Mark and U2 Designator. The rationale for this has to do with the fact that the rules in any ASME standard are developed by experts in a particular field or type of equipment. In the case of VIII-2, experts in the fields of design, fabrication, inspection and testing of pressure vessels developed the rules in this standard. For example, the developers of VIII-2 were not experts in the construction of power boilers, thus it was deemed inappropriate to allow a power boiler to be certified to VIII-2 even if it did comply with all of its rules.

Vessels that are not included in the scope of VIII-2 are shown below. Again with the exception of subparagraph a), below, all of the remainder of the use exempted vessels may be constructed and stamped with the Certification Mark and U2 Designator if all of the applicable requirements are met. But similar to VIII-1, the Local Jurisdictional Authority at the location of an installation of a vessel establishes the mandatory applicability of the Code rules.

- a) Vessels within the scope of other ASME BPV Code Sections but not other design Codes (e.g., EN 13445, BSI PD-5500, etc.).
- b) Fired process tubular heaters as defined in API RP 560.
- c) Pressure containers that are integral parts or components of rotating or reciprocating mechanical devices.
- d) Structures consisting of piping components whose primary function are the transport of fluids from