

REAFFIRMED 1999

FOR CURRENT COMMITTEE PERSONNEL
PLEASE SEE ASME MANUAL AS-11

Chassis Frames — Passenger Car and Light Truck — Ground Vehicle Practices



AN AMERICAN NATIONAL STANDARD



The American Society of
Mechanical Engineers

AN AMERICAN NATIONAL STANDARD

ENGINEERING DRAWING AND RELATED DOCUMENTATION PRACTICES

**Chassis Frames — Passenger
Car and Light Truck —
Ground Vehicle Practices**

ASME Y14.32.1M-1994

(REVISION OF ANSI Y14.32.1-1974)



The American Society of
Mechanical Engineers

345 East 47th Street, New York, N.Y. 10017

Date of Issuance: January 31, 1995

This Standard will be revised when the Society approves the issuance of a new edition. There will be no addenda or written interpretations of the requirements of this Standard issued to this edition.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Consensus Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment which provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable Letters Patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations issued in accordance with governing ASME procedures and policies which preclude the issuance of interpretations by individual volunteers.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

Copyright © 1995 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All Rights Reserved
Printed in U.S.A.

FOREWORD

(This Foreword is not part of ASME Y14.32.1M-1994.)

Subcommittee 32 of the ASME Standards Committee Y14, Engineering Drawing and Related Documentation Practices, was organized in 1968. The work of the Subcommittee resulted in the publication of the predecessor to this Standard, ANSI Y14.32.1-1974. During the ensuing years, the Y14 Committee, reacting to the increasing acceptance of the SI metric system in the United States, began to systematically update its existing standards to accommodate metric practices. Since Y14 drafting practices in most cases are dimensionally insensitive, the majority of the metrication effort involved redrawing examples using metric units. ANSI Y14.32.1 was withdrawn as an American National Standard in 1987, at which time work on this Standard began.

The vehicle chassis frame is typically an inseparable assembly of stamped or formed sheet metal structural members which support and locate the vehicle body, front sheet metal structure, chassis components (wheel, suspension, engine, steering components, drive line, exhaust system, bumpers), and miscellaneous equipment. The chassis frame provides accuracy of location as well as strength and rigidity of support for these components to assure satisfactory vehicle performance. Functional criteria and restraints are determined from a number of support drawings and a design check mock-up. These include a definition of mountings and clearances for all related chassis and underbody components, such as underbody and sheet metal structure, engine, drive line, exhaust, suspension systems, tires, brake lines, fuel lines, and bumpers.

In addition to referencing metric (SI) units, this Standard includes the definition of some key terms which are generally accepted in the industries producing ground vehicles. References are made specifically to automobiles, vans, and trucks where such distinctions are necessary. References to *vehicles* are inclusive of all types, as the concepts are generic.

References to rear suspensions are more general than in the previous standard. Since 1974, the number of types of rear suspensions in use has increased beyond the ability of this Standard to adequately cover all applications.

This Standard has been prepared for application with any system of measurement.

Suggestions for improvement of this Standard will be welcomed. They should be sent to The American Society of Mechanical Engineers, Secretary, Y14 Main Committee, 345 East 47th Street, New York, NY 10017.

This Standard was approved as an American National Standard on September 6, 1994.

ASME STANDARDS COMMITTEE Y14

Engineering Drawing and Related Documentation Practices

(The following is the roster of the Committee at the time of approval of this Standard.)

OFFICERS

F. Bakos, Jr., *Chairman*
A. R. Anderson, *Vice Chairman*
C. J. Gomez, *Secretary*

COMMITTEE PERSONNEL

A. R. Anderson, *Vice Chairman*, Trikon Corp.
F. Bakos, Jr., *Chairman*, Eastman Kodak Co.
T. D. Benoit, *Alternate*, Pratt & Whitney CEB
D. E. Bowerman, Copeland Corp.
J. V. Burleigh, The Boeing Co.
R. A. Chadderdon, Southwest Consultants
F. A. Christiana, ASEA Brown Boveri Combustion Engineering Systems
M. E. Curtis, Jr., Rexnord Corp.
R. W. Debolt, Motorola, Government Systems Technology Group
H. L. Dubocq
L. W. Foster, L. W. Foster Associates, Inc.
C. J. Gomez, *Secretary*, The American Society of Mechanical Engineers
D. Hagler, E-Systems, Inc., Garland Div.
E. L. Kardas, Pratt & Whitney CEB
C. G. Lance, Santa Cruz Technology Center
P. E. McKim, Caterpillar, Inc.
C. D. Merkley, IBM Corp.
E. Niemiec, Westinghouse Electric Corp.
R. J. Polizzi
D. L. Ragon, Deere & Co., John Deere Dubuque Works
R. P. Tremblay, U.S. Department of the Army, ARDEC
R. K. Walker, Westinghouse Marine
G. H. Whitmire, TEC/TREND
K. E. Wiegandt, Sandia National Laboratory
P. Wreede, E-Systems, Inc.

SUBCOMMITTEE 32 — CAR AND LIGHT TRUCK CHASSIS FRAME DRAWINGS

A. R. Anderson, *Chairman*, Trikon Corp.
R. E. Coombes, Caterpillar, Inc.
O. DeSchepper, General Motors Corp.
E. W. Perry, Jr., Dana Parrish Corp.
P. C. Ruehl IV, A. O. Smith Corp.
D. Seed, *Alternate*, Dana Parrish Corp.
J. J. Tur, Ford Motor Co.

CONTENTS

Foreword	iii
Standards Committee Roster	v
1 General	1
2 Drawing Types	2
3 Drawing Grid System	2
4 Datum Reference Frame	2
5 Special Considerations	3
6 Designation of Passenger Car and Van Body Mount Locations	4
7 Designation of Truck Body and Box Mounts	4
Figures	
1 Datum Reference Frame	5
2 Recommended Notation and Dimensioning Technique	6
3 Front Suspension Mounting Dimensioning	7
4 Method for Simplified Specification of Frame Camber	8

ENGINEERING DRAWING AND RELATED DOCUMENTATION PRACTICES
**CHASSIS FRAMES — PASSENGER CAR AND LIGHT TRUCK —
 GROUND VEHICLE PRACTICES**

1 GENERAL

1.1 Scope

This Standard establishes minimum requirements for the preparation of engineering drawings for passenger car and light truck chassis frames.

This Standard does not apply to heavy truck, trailer, tractor, and off-the-road vehicle chassis frames.

1.2 Units

The International System of (Metric) Units (SI) is featured in this Standard because SI units are expected to supersede United States (U.S.) customary units specified on engineering drawings. Customary units could equally well have been used without prejudice to the principles established.

1.3 Notes

Notes herein in capital letters are intended to appear on finished drawings. Notes in lower case letters are explanatory only and are not intended to appear on drawings.

1.4 Reference to Gaging

This Standard is not intended as a gaging standard. Any reference to gaging is included for explanatory purposes only.

1.5 References

When the following American National Standards referred to in this Standard are superseded by a revision approved by the American National Standards Institute, Inc., the revision shall apply.

ASME Y14.5M-1994, Dimensioning and Tolerancing

ASME Y14.24M-1989, Types and Applications of Engineering Drawings

Y14.31M (in preparation), Undimensioned Drawing Practice

1.6 Definitions

The following are defined as their use applies in this Standard.

1.6.1 Vehicle Mounts (Body and Front Sheet Metal). The area where the body and chassis frame contact. This contact is made through rubber insulators, retained with fasteners.

1.6.2 Box Mounts. The location where a truck box is rigidly mounted to the vehicle frame.

1.6.3 Compression (Jounce) Position. The position of vehicle suspension travel which represents the allowable compression of the suspension. Generally, the springs are not fully compressed, but the travel is limited by stops or bumpers.

1.6.4 Design Check Mock-Up. An assembly (usually full scale) of components used to verify the design. These components may be actual production or representative parts made of fiberglass, cardboard, plastic, or other easily formed materials. This mock-up is used to check for clearances and interferences and as a visual aid for the designer when mounting or routing other components.

1.6.5 Design Load. A value assigned to a vehicle to represent a nominal load.

1.6.6 Design Position. The position of vehicle suspension travel at which the vehicle is designed. This position represents the design load.

1.6.7 Front Suspension Arm. Components of the vehicle suspension, mounted between the frame and steering knuckle, which allow vertical movement of the wheel assembly.

1.6.8 Rebound Position. The position of vehicle suspension travel which represents the fully extended travel of the components of the suspension. This travel is usually limited by the full extension of the shock absorbers, or rebound stops.