

Australian/New Zealand Standard™

**External extruded high-density  
polyethylene coating system for pipes**



## **AS/NZS 1518:2002**

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee ME-038, Petroleum pipelines. It was approved on behalf of the Council of Standards Australia on 27 July 2001 and on behalf of the Council of Standards New Zealand on 20 February 2002.

This Standard was published on 11 March 2002.

---

The following are represented on Committee ME-038:

Australasian Corrosion Association  
Australian Institute of Petroleum  
Australian Petroleum Production and Exploration Association  
Australian Pipeline Industry Association  
Bureau of Steel Manufacturers  
Co-operative Research Centre for Materials Welding and Joining  
Department of Labour New Zealand  
Department of Minerals and Energy W.A.  
Department of Minerals and Energy W.A.  
Department of Mines and Energy N.T.  
Department of Natural Resources and Environment Vic.  
Department of Natural Resources and Mines Qld  
Gas Association of New Zealand  
Ministry of Energy and Utilities N.S.W.  
Primary Industries and Resources S.A.  
Australian Gas Association  
Welding Technology Institute of Australia

Additional Interests:

Cathodic Protection Systems  
Tyco Water Pipelines Research  
Canusa  
Brian Martin and Associates  
Bredero Shaw Australia  
Socotherm

---

### **Keeping Standards up-to-date**

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using the current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at [www.standards.com.au](http://www.standards.com.au) or Standards New Zealand web site at [www.standards.co.nz](http://www.standards.co.nz) and looking up the relevant Standard in the on-line catalogue.

Alternatively, both organizations publish an annual printed Catalogue with full details of all current Standards. For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

---

*This Standard was issued in draft form for comment as DR 00185.*

---

Australian/New Zealand Standard™

**External extruded high-density  
polyethylene coating system for pipes**

Originated as AS 1518—1979.  
Jointly revised and designated AS/NZS 1518:2002.  
Reissued incorporating Amendment No. 1 (May 2006).

**COPYRIGHT**

© Standards Australia/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Jointly published by Standards Australia, GPO Box 476, Sydney, NSW 2001 and Standards New Zealand, Private Bag 2439, Wellington 6020

ISBN 0 7337 4090 1

## PREFACE

This Standard was prepared by Standards Australia/Standards New Zealand Committee, ME-038, Petroleum pipelines, to supersede AS 1518—1979, Extruded high-density polyethylene protective coating for pipes.

This objective of this Standard is to provide the manufacturers, suppliers, specifiers and users of oil and gas pipelines with a set of requirements for external protection against corrosion, using high-density polyethylene.

*This Standard incorporates Amendment No. 1 (May 2006). The changes required by the Amendment are indicated in the text by a marginal bar and amendment number against the clause, note, table, figure or part thereof affected.*

The terms ‘normative’ and ‘informative’ have been used in this Standard to define the application of the appendix to which they apply. A ‘normative’ appendix is an integral part of a Standard, whereas an ‘informative’ appendix is only for information and guidance.

Statements expressed in mandatory terms in notes to figures and tables are deemed to be requirements of this Standard. All other notes are for information and guidance only.

## CONTENTS

	<i>Page</i>
1 SCOPE.....	4
2 REFERENCED DOCUMENTS.....	4
3 DEFINITIONS.....	5
4 MATERIAL REQUIREMENTS.....	6
5 PIPE SURFACE PREPARATION AND COATING APPLICATION.....	7
6 COATING REPAIRS AND FIELD JOINT COATINGS.....	9
7 TEST REQUIREMENTS AND PROCEDURES.....	15
8 MARKING.....	16
9 HANDLING, STORAGE AND TRANSPORT.....	16

## APPENDICES

A PURCHASING GUIDELINES.....	19
B MEANS FOR DEMONSTRATING COMPLIANCE WITH THIS STANDARD.....	21
C REQUIREMENTS FOR COATING OVER GALVANIZED STEEL PIPE.....	26
D THERMAL STABILITY TEST.....	28
E RESISTANCE TO SPLITTING TEST.....	29
F METHOD FOR DETERMINING EFFECTS OF STOCKPILE LOADING ON COATED PIPES AT ELEVATED STORAGE TEMPERATURES.....	31
G PEEL ADHESION TEST (HANGING WEIGHT PEEL TEST).....	34
H BEND TEST PROCEDURE.....	36

## STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

**Australian/New Zealand Standard****External extruded high-density polyethylene coating system for pipes****1 SCOPE**

This Standard specifies requirements for external protection against corrosion of pipeline systems, whereby a sealant layer is interposed between the pipe and the extrudate of high-density polyethylene, applied using annular or lateral extrusion techniques, to comprise the external coating.

Materials complying with this Standard are intended for use where the pipe temperature during operation is in the range of  $-20^{\circ}\text{C}$  to  $+55^{\circ}\text{C}$ . Guidance is provided on selection and testing of the coating where elevated temperatures may be encountered during storage, stockpiling or construction. The performance of the coating at high and low temperatures may not be as reflected by tests carried out at ambient temperatures. For example, mastic creep and penetration, and coating system peel strength and cathodic disbanding resistance may not be as at ambient temperatures.

The coating is intended for use in applications where it is not subject to weather or ultraviolet light exposure. A safe period of 12 months of weather exposure after manufacture is allowed for completion of the installation of the pipeline system.

## NOTES:

- 1 Guidelines for purchasers on information that should be supplied by the purchaser and those variables that should or may be agreed upon at the time of inquiry or order are given in Appendix A.
- 2 For submerged or welded pipe, additional consideration should be given to air entrapment along the length of the weld and localized stress on the polyethylene coating.

Methods for demonstrating compliance with this Standard are given in Appendix B.

Coatings applied over galvanized pipe shall comply with the requirements of Appendix C.

**2 REFERENCED DOCUMENTS**

The following documents are referred to in this Standard:

## AS

	1145	Determination of tensile properties of plastics materials
A1	1145.3	Part 3: Determination of tensile properties of plastic materials—Test conditions for films and sheets
	1199	Sampling procedures and tables for inspection by attributes
	1599	Guide to AS 1199—Sampling procedures and tables for inspection by attributes
	1627	Metal finishing—Preparation and pre-treatment of surfaces
	1627.2	Part 2: Power tool cleaning
	1627.4	Part 4: Abrasive blast cleaning
	1627.9	Part 9: Pictorial surface preparation standards for painting steel surfaces
	3894	Site testing of protective coatings
	3894.1	Part 1: Non-conductive coatings—Continuity testing—High voltage ‘brush’ method
	3894.4	Part 4: Determination of dry film thickness
	3894.5	Part 5: Determination of surface profile