

Australian/New Zealand Standard™

**Buried corrugated metal structures**

**Part 4: Helically formed sinusoidal pipes**



## **AS/NZS 2041.4:2010**

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee CE-025, Corrugated Metal Drainage Pipes and Arches. It was approved on behalf of the Council of Standards Australia on 23 June 2010 and on behalf of the Council of Standards New Zealand on 28 June 2010.  
This Standard was published on 10 August 2010.

---

The following are represented on Committee CE-025:

### **AUSTROADS**

Australasian Railway Association  
Australian Chamber of Commerce and Industry  
Australian Industry Group  
Galvanizers Association of Australia  
Main Roads Department Queensland  
New Zealand Heavy Engineering Research Association  
University of Queensland

---

### **Keeping Standards up-to-date**

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at [www.saiglobal.com.au](http://www.saiglobal.com.au) or Standards New Zealand web site at [www.standards.co.nz](http://www.standards.co.nz) and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

---

Australian/New Zealand Standard™

## Buried corrugated metal structures

### Part 4: Helically formed sinusoidal pipes

First published as AS 1761—1979.

Second edition 1985.

AS 1761—1985 jointly revised and redesignated, in part, as AS/NZS 2941.4:2010.

#### COPYRIGHT

© Standards Australia Limited/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Australia) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, Private Bag 2439, Wellington 6140

## PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee CE-025, Corrugated Metal Pipes and Arches, to supersede AS 1761—1985, adopted by Standards New Zealand as NZS 4405 in 1986.

The objective of this Standard is to provide designers, manufacturers and installers of buried helical lock-seamed sinusoidal metal pipes with requirements for the manufacture of such pipe for use in earthworks, primarily as culverts or accessways.

This Standard is Part 4 of the AS/NZS 2041 series, *Buried corrugated metal structures*, which comprises the following parts:

### AS/NZS

- 2041 Buried corrugated metal structures
- 2041.1 Part 1: Design methods
- 2041.2 Part 2: Installation
- 2041.4 Part 4: Helically formed sinusoidal pipes (this Standard)
- 2041.6 Part 6: Bolted plate structures

Other parts of the series currently being drafted include the following:

- Part 3: Assessment of existing structures
- Part 5: Helically formed ribbed pipes
- Part 7: Bolted plate structures with transverse stiffeners
- Part 8: Metal box structures

This Edition includes the following changes:

- (a) Design requirements have been moved to AS/NZS 2041.1 *Buried corrugated metal structures* Part 1: *Design methods*, which includes new limit states methods.
- (b) Installation requirements are now referred to AS/NZS 2041.2 *Buried corrugated metal structures*, Part 2: *Installation*.
- (c) Notation is based on ISO 2891 *Rules for design of structures—Notations—General symbols*.
- (d) Materials and fabrication requirements have been updated.
- (e) Materials covered include galvanized steel, polymer-coated steel, steel with aluminized coating and aluminium strip.
- (f) Reference tables for cover limits have not been included.

The terms ‘normative’ and ‘informative’ have been used in this Standard to define the application of the appendix to which they apply. A ‘normative’ appendix is an integral part of a Standard, whereas an ‘informative’ appendix is only for information and guidance.

## CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE .....	4
1.2 DESIGN AND INSTALLATION.....	4
1.3 NORMATIVE REFERENCES.....	5
1.4 DEFINITIONS .....	5
1.5 NOTATION .....	6
1.6 MARKING.....	7
SECTION 2 MATERIALS, TOLERANCES AND MANUFACTURE	
2.1 SCOPE OF SECTION.....	8
2.2 MATERIALS .....	8
2.3 TOLERANCES .....	8
2.4 MANUFACTURE.....	9
2.5 COUPLING SYSTEMS .....	12
2.6 MATCH MARKING.....	14
2.7 DEFECTS AND COATINGS.....	15
SECTION 3 CORRUGATIONS AND SECTION PROPERTIES FOR DESIGN	
3.1 SCOPE OF SECTION.....	16
3.2 DIMENSIONS AND TOLERANCES.....	16
3.3 MATERIAL AND SECTION PROPERTIES.....	17
APPENDICES	
A DESIGN INFORMATION FOR SUPPLY AND INSTALLATION.....	23
B MEANS FOR DEMONSTRATING COMPLIANCE WITH THIS STANDARD.....	27
C LOCK-SEAM STRENGTH TEST .....	29
D COUPLING BANDS.....	31
BIBLIOGRAPHY .....	32

## STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

**Australian/New Zealand Standard**  
**Buried corrugated metal structures****Part 4: Helically formed sinusoidal pipes**

## SECTION 1 SCOPE AND GENERAL

**1.1 SCOPE**

This Standard specifies minimum requirements for the materials and manufacture of buried metal pipe formed using sinusoidal profile strip. The pipe is full circular shape formed by a continuous helical lock-seam that runs helically to the longitudinal axis of the pipe.

Pipe diameters up to and including 3600 mm are covered.

Sinusoidal profiles covered include the following:

- (a) S38 (pitch 38 mm).
- (b) S68 (pitch 68 mm).
- (c) S75 (pitch 75 mm).
- (d) S125 (pitch 125 mm).

Helically formed sinusoidal pipe structures are primarily intended for use as culverts in stormwater drainage, detention/retention systems, stockpile and access tunnels. The structures are intended to support roadway and railway and other loadings. They are buried in an embankment or in a trench situation and correct installation in a soil envelope is essential to the performance of the structure.

This Standard does not consider the additional design requirements for internally pressurized applications.

## NOTES:

- 1 For helically formed pipes greater than 3600 mm diameter, the design methods in AS/NZS 2041.1 may not apply.
- 2 Guidelines on requirements that may need to be specified at the time of calling for tenders or quotations, and information to be supplied by the manufacturer are detailed in Appendix A.
- 3 Information on means of demonstrating compliance with this Standard is given in Appendix B.
- 4 When intended for use in internally pressurized applications, specialist advice should be obtained.

**1.2 DESIGN AND INSTALLATION**

Design shall be carried out in accordance with AS/NZS 2041.1 using the section properties given in Section 3 of this Standard. Installation shall be carried out in accordance with AS/NZS 2041.2.

NOTE: This Standard includes the product requirements and design properties. AS/NZS 2041.1 gives information on design issues and requirements for structural design of the metal structure. Performance of the structure depends on correct installation (particularly adequate compaction of appropriate fill material around the metal structure) for which AS/NZS 2041.2 gives the requirements.