

Australian/New Zealand Standard™

**Digital radio equipment operating in
land mobile and fixed services bands in
the frequency range 29.7 MHz to 1 GHz**

Part 1: Radiofrequency requirements



AS/NZS 4768.1:2010

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee RC-006, Radiocommunications Equipment—General. It was approved on behalf of the Council of Standards Australia on 28 September 2009 and on behalf of the Council of Standards New Zealand on 8 February 2010. This Standard was published on 23 February 2010.

The following are represented on Committee RC-006:

Airservices Australia
Australian Communications and Media Authority
Australian Industry Group
Australian Radio Communications Industry Association
Civil Aviation Safety Authority
Department of Defence, Australia
Electromagnetic Technical Evaluation Committee
Engineers Australia
Free TV Australia
Ministry of Economic Development, New Zealand
SingTel Optus
Testing Interests, New Zealand
Wireless Institute of Australia

Keeping standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.saiglobal.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

Australian/New Zealand Standard™

**Digital radio equipment operating in
land mobile and fixed services bands in
the frequency range 29.7 MHz to 1 GHz**

Part 1: Radiofrequency requirements

Original as AS/NZS 4768.1:2003.
Previous edition 2006.
Third edition 2010.

COPYRIGHT

© Standards Australia/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Jointly published by Standards Australia, GPO Box 476, Sydney, NSW 2001 and Standards New Zealand, Private Bag 2439, Wellington 6140

ISBN 978 0 7337 9374 5

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee RC-006, Radiocommunications Equipment—General, to supersede AS/NZS 4768.1:2006.

The objective of this Standard is to provide the user, manufacturer or supplier of digital radio equipment operating in the frequency range 29.7 MHz to 1 GHz of the VHF and UHF Land Mobile and Fixed Services Bands with the minimum technical performance characteristics and requirements necessary to contribute to effective management of the radiofrequency spectrum in Australia and New Zealand.

In Australia and New Zealand, it is common to import equipment from other parts of the world where there may not be harmonized spectrum management and equipment specification regimes.

The requirements specified in this Standard take into account that, in Australia and New Zealand, digital radio equipment may operate in spectrum adjacent to analogue radio equipment. This arrangement requires that digital radio equipment operate without causing harmful interference to analogue radio equipment occupying adjacent channels and vice versa.

This Standard was originally developed from AS 4295, *Analogue speech (angle modulated) equipment operating in land mobile and fixed services bands in the frequency range 29.7 MHz to 1 GHz*, the ETSI publications EN 300 113-1 V1.3.1 and EN 300 113-1 V1.4.1, and IEC 60489-6, Ed.3 (1999), *Radio equipment used in mobile services—Methods of measurement, Part 6: Data equipment*.

Following a submission by manufacturers in an effort to reduce compliance testing costs, AS/NZS 4768.1:2006 introduced an alternative path to compliance based on testing to the ETSI EN 300 113-1 Standard with some additions where necessary. While the test methods and limits in the ETSI Standard in some areas are different to the IEC methods originally used in AS/NZS 4768.1:2003, the committee judged that product compliant with such tests, (including any additional requirements) would be suitable for use locally with some minor changes. The additions, which are set out in Appendix A, extend the maximum extreme temperature to 60°C and require transmitter spurious emission testing at extremes of voltage and temperature. Some limits contained in the main body of the Standard such as transmitter power, are retained to support the licensing arrangements in both countries.

The proposed changes in this new edition, made at the request of industry, incorporate relaxations to the performance requirements for certain remote multipoint stations in view of their remote location and low duty cycle operation, as well as to encourage reduced power consumption designs.

This Standard is Part 1 of AS/NZS 4768, *Digital radio equipment operating in land mobile and fixed services bands in the frequency range 29.7 MHz to 1 GHz*, which consists of the following parts:

Part 1: Radiofrequency requirements (this Standard)

Part 2: Methods of test

This Part 1 provides the minimum radiofrequency requirements for operation of the equipment in Australia and New Zealand. Part 2 provides the test methods to be used when compliance with these limits is to be assessed. Not all of the test methods in Part 2 are required.

Statements expressed in mandatory terms in notes and footnotes to tables are deemed to be requirements of this Standard.

The term ‘normative’ has been used in this Standard to define the application of the Appendix. A normative appendix is an integral part of a Standard.

CONTENTS

	<i>Page</i>
1 SCOPE.....	4
2 REFERENCED DOCUMENTS.....	4
3 DEFINITIONS.....	5
4 GENERAL REQUIREMENTS.....	9
5 TEST CONDITIONS.....	10
6 TRANSMITTER REQUIREMENTS.....	14
7 RECEIVER REQUIREMENTS.....	16
APPENDIX A ALTERNATIVE TESTING PATH TO COMPLIANCE USING THE EUROPEAN STANDARD ETS 300 113-1 AND ASSOCIATED UNCERTAINTY REGIME.....	22

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Australian/New Zealand Standard**Digital radio equipment operating in land mobile and fixed services bands in the frequency range 29.7 MHz to 1 GHz****Part 1: Radiofrequency requirements****1 SCOPE**

This Standard provides radiofrequency requirements for constant envelope emission digital radio equipment operating in land mobile and fixed services radiofrequency bands in the frequency range 29.7 MHz to 1 GHz with channel spacings of 12.5 kHz to 25 kHz. Equipment employing non-constant envelope emissions is not within the scope of this standard.

Categories of equipment within this range include—

- (a) base, mobile, personal mobile and RF control stations operating in designated land mobile bands; and
- (b) fixed point-to-point and point-to-multipoint equipment operating in designated single channel fixed service bands.

Equipment operating in the land mobile services bands from 806 to 825 MHz and 851 to 870 MHz is not within the scope of the Standard.

NOTE: For operation of land mobile equipment in these bands refer to the relevant authorities in Australia and New Zealand.

2 REFERENCED DOCUMENTS

The following documents are referred to in this Standard:

AS/NZS

- 4295 Analogue speech (angle modulated) equipment operating in land mobile and fixed services bands in the frequency range 29.7 MHz to 1 GHz
- 4768 Digital radio equipment operating in land mobile and fixed services bands in the frequency range 29.7 MHz to 1 GHz
- 4768.2 Part 2: Methods of test

ETSI EN

- 300 113 Electromagnetic Compatibility and Radio Spectrum Matters (ERM); Land mobile V1.6.1 service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector
- 300 113-1 Part 1: Technical characteristics and methods of measurement

IEC

- 50489 Radio equipment used in mobile services—Methods of measurement
- 60489-6 Part 6: Data equipment

ITU-T

- 0.152 Error performance measuring equipment for bit rates of 64 kbit/s and $N \times 64$ kbit/s
- 0.153 Basic parameters for the measurement of error performance at bit rates below the primary rate
- 0.163 Equipment to perform in-service monitoring on 1544 kbit/s signals