

Australian/New Zealand Standard™

**Electrical apparatus for use in the
presence of combustible dust**

**Part 18: Protection by encapsulation
'mD'**

AS/NZS 61241.18:2005

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee EL-014, Electrical Equipment in Hazardous Areas. It was approved on behalf of the Council of Standards Australia on 8 April 2005 and on behalf of the Council of Standards New Zealand on 15 April 2005.
This Standard was published on 3 May 2005.

The following are represented on Committee EL-014:

Auckland Regional Chamber of Commerce
Australian Chamber of Commerce and Industry
Australian Electrical and Electronic Manufacturers Association
Australian Industry Group
Australian Institute of Petroleum Ltd
Certification Interests (Australia)
Department of Natural Resources and Mines (Qld)
Department of Primary Industries, Mine Safety (NSW)
Electrical Regulatory Authorities Council
Energy Networks Association
Engineers Australia
Institute of Electrical Inspectors
Institute of Instrumentation, Control and Automation Australia
Ministry of Economic Development (New Zealand)
National Electrical and Communications Association
New Zealand Association of Marine, Aviation and Power Engineers
New Zealand Employers and Manufacturers Association
New Zealand Hazardous Areas Electrical Coordinating Committee
The Australian Gas Association
WorkCover New South Wales

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.standards.com.au or Standards New Zealand website at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

Alternatively, both organizations publish an annual printed Catalogue with full details of all current Standards. For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

This Standard was issued in draft form for comment as DR 05077.

Australian/New Zealand StandardTM

**Electrical apparatus for use in the
presence of combustible dust**

**Part 18: Protection by encapsulation
'mD'**

First published as AS/NZS 61241.18:2005.

COPYRIGHT

© Standards Australia/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Jointly published by Standards Australia, GPO Box 5420, Sydney, NSW 2001 and Standards New Zealand, Private Bag 2439, Wellington 6020

ISBN 0 7337 6658 7

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee EL-014, Electrical Equipment in Hazardous Areas.

This Standard is identical with, and has been reproduced from IEC 61241-18, Ed.1(2004), *Electrical apparatus for use in the presence of combustible dust - Part 18: Protection by encapsulation 'mD'*.

The objective of this Standard is to specify requirements for the construction, testing and marking of electrical apparatus, parts of electrical apparatus and Ex components with the type of protection 'mD', for use in the presence of combustible dusts.

This Standard supplements the general requirements in AS/NZS 61241.0.

AS/NZS 61241 consists of the following parts under the general title: *Electrical apparatus for use in the presence of combustible dust*:

Part 0:	General requirements
Part 1:	Protection by enclosures 'tD'
Part 2:	Type of protection 'pD'*
Part 10:	Classification of areas where combustible dusts are or may be present
Part 11:	Protection by intrinsic safety 'iD'*
Part 14:	Selection and installation
Part 17:	Inspection and maintenance of electrical installations in hazardous areas (other than mines)†
Part 18:	Protection by encapsulation 'mD'
Part 20:	Test methods‡
Part 20.1:	Methods for determining the minimum ignition temperatures of dust
Part 20.2:	Method for determining the electrical resistivity of dust in layers
Part 20.3:	Method for determining minimum ignition energy of dust/air mixtures

As this Standard is reproduced from an International Standard, the following applies:

- Its number does not appear on each page of text and its identity is shown only on the cover and title page.
- In the source text 'this international standard' should read 'this Australian/New Zealand Standard'.
- A full point should be substituted for a comma when referring to a decimal marker.

The terms 'normative' and 'informative' are used to define the application of the annex to which they apply. A normative annex is an integral part of a Standard, whereas an informative annex is only for information and guidance.

* To be published (to supersede current AS/NZS 61241.4).

† To be published.

‡ Under consideration (to supersede current Parts 2.1, 2.2 and 2.3).

CONTENTS

	<i>Page</i>
INTRODUCTION	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	3
4 General	4
4.1 Temperature classification	4
4.2 Level of protection	4
4.3 Level of protection “mAD”	4
4.4 Level of protection “mBD”	4
4.5 Supply specifications	5
5 Requirements for compounds	5
5.1 General	5
5.2 Specification	5
6 Temperatures	5
6.1 General	5
6.2 Temperature limitation	6
6.3 Determination of the limiting temperature values	6
7 Constructional requirements	6
7.1 General	6
7.2 Determination of possible faults	7
7.3 Switching contacts	13
7.4 External connections	13
7.5 Protection of bare live parts	13
7.6 Cells and batteries	13
7.7 Protective devices	16
8 Type tests	17
8.1 Tests on the compound – water absorption test	17
8.2 Tests on the apparatus	17
9 Routine verification and tests	20
9.1 Visual inspections	20
9.2 Dielectric strength test	21
10 Marking	21
Annex A (informative) Basic requirements for compounds for encapsulation “mD” apparatus	22
Annex B (normative) Allocation of test samples	23
Annex C (normative) Test procedure during thermal cycling test	24

INTRODUCTION

Many dusts which are generated, processed, handled and stored, are combustible. When ignited they can burn rapidly and with considerable explosive force if mixed with air in the appropriate proportions. It is often necessary to use electrical apparatus in locations where such combustible materials are present, and suitable precautions must therefore be taken to ensure that all such apparatus is adequately protected so as to reduce the likelihood of ignition of the external explosive atmosphere. In electrical apparatus, potential ignition sources include electrical arcs and sparks, hot surfaces, and frictional sparks.

Areas where dusts, flyings and fibres in air occur in dangerous quantities are classified as hazardous and are divided into 3 zones according to the level of risk.

Generally, electrical safety is ensured by the implementation of one of two considerations, i.e. that electrical apparatus be located where reasonably practicable outside hazardous areas and that electrical apparatus be designed, installed and maintained in accordance with measures recommended for the area in which the apparatus is located.

Combustible dust can be ignited by electrical apparatus in several ways:

- by surfaces of the apparatus that are above the minimum ignition temperature of the dust concerned. The temperature at which a type of dust ignites is a function of the properties of the dust, whether the dust is in a cloud or layer, the thickness of the layer and the geometry of the heat source;
- by arcing or sparking of electrical parts such as switches, contacts, commutators, brushes, or the like;
- by discharge of an accumulated electrostatic charge;
- by radiated energy (for example, electromagnetic radiation);
- by mechanical sparking or frictional sparking or heating associated with the apparatus.

In order to avoid ignition hazards it is necessary that

- the temperature of surfaces, on which dust can be deposited, or which would be in contact with a dust cloud, is kept below the temperature limitation specified in this standard;
- any electrical sparking parts, or parts having a temperature above the temperature limit specified in IEC 61241-11:
 - are contained in an enclosure which adequately prevents the ingress of dust, or
 - the energy of electrical circuits is limited so as to avoid arcs, sparks or temperatures capable to ignite combustible dust;
- any other ignition sources are avoided.

Compliance with this standard will only provide the required level of safety if the electrical apparatus is operated within its rating and is installed and maintained according to the relevant codes of practice or requirements, for example in respect of protection against over-currents, internal short-circuits, and other electrical faults. In particular, it is essential that the severity and duration of an internal or external fault be limited to values that can be sustained by the electrical apparatus without damage.

Several techniques are available for the explosion protection of electrical apparatus in hazardous areas. This standard describes the safety features of these types of explosion-protection techniques and specifies the installation procedures to be adopted. It is most important that the correct selection and installation procedures be followed to ensure the safe use of electrical apparatus in hazardous areas.

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Australian/New Zealand Standard**Electrical apparatus for use in the presence of combustible dust
Part 18: Protection by encapsulation 'mD'****1 Scope**

This standard is to be read in conjunction with IEC 61241-0, the requirements of which apply to electrical apparatus protected by encapsulation and surface temperature limitation unless specifically excluded.

This part of IEC 61241 is applicable to electrical apparatus protected by encapsulation type of protection "mD" and surface temperature limitation for use in areas where combustible dust may be present in quantities which could lead to a fire or explosion hazard. It specifies requirements for design, construction and testing of electrical apparatus, part of electrical apparatus and Ex components where the rated voltage does not exceed 1000 V.

NOTE 1 The actual working voltage may exceed the value given above by up to 10 %.

NOTE 2 IEC 61241-14 ("Electrical apparatus for use in the presence of combustible dust – Part 14: Selection and installation") gives guidance on the selection and installation of the apparatus. Apparatus within the scope of this standard may also be subjected to additional requirements in other standards – for example, IEC 60079-0 ("Electrical apparatus for explosive gas atmospheres - Part 0: General requirements").

The application of electrical apparatus in atmospheres which may contain explosive gas as well as combustible dust, whether simultaneously or separately, requires additional protective measures.

This standard does not apply to dusts of explosives which do not require atmospheric oxygen for combustion, or to pyrophoric substances.

This standard is not applicable to electrical apparatus intended for use in underground parts of mines as well as those parts of surface installations of such mines endangered by firedamp and/or combustible dust. This standard does not take account of any risk due to an emission of flammable or toxic gas from the dust.

This standard does not include other types of protection and is only applicable to protection by encapsulation.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

References to international standards that are struck through in this clause are replaced by references to identical Australian or Australian/New Zealand Standards that are listed immediately thereafter and identified by shading.

~~IEC 60079-7:2001, *Electrical apparatus for explosive gas atmospheres – Part 7: Increased safety 'e'*~~

AS/NZS 60079.7:2002, *Electrical apparatus for explosive gas atmospheres, Part 7: Increased safety 'e'* (identical to IEC 60079-7:2001)