



ATIS-0500040

ATIS Standard on -

Unified X/Y and Z Indoor Test Methodology



As a leading technology and solutions development organization, the Alliance for Telecommunications Industry Solutions (ATIS) brings together the top global ICT companies to advance the industry's most pressing business priorities. ATIS' nearly 200 member companies are currently working to address the All-IP transition, 5G, network functions virtualization, big data analytics, cloud services, device solutions, emergency services, M2M, cyber security, network evolution, quality of service, billing support, operations, and much more. These priorities follow a fast-track development lifecycle — from design and innovation through standards, specifications, requirements, business use cases, software toolkits, open source solutions, and interoperability testing.

ATIS is accredited by the American National Standards Institute (ANSI). The organization is the North American Organizational Partner for the 3rd Generation Partnership Project (3GPP), a founding Partner of the oneM2M global initiative, a member of the International Telecommunication Union (ITU), as well as a member of the International American Telecommunication Commission (CITELE). For more information, visit www.atis.org.

Notice of Disclaimer & Limitation of Liability

The information provided in this document is directed solely to professionals who have the appropriate degree of experience to understand and interpret its contents in accordance with generally accepted engineering or other professional standards and applicable regulations. No recommendation as to products or vendors is made or should be implied.

NO REPRESENTATION OR WARRANTY IS MADE THAT THE INFORMATION IS TECHNICALLY ACCURATE OR SUFFICIENT OR CONFORMS TO ANY STATUTE, GOVERNMENTAL RULE OR REGULATION, AND FURTHER, NO REPRESENTATION OR WARRANTY IS MADE OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR AGAINST INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS. ATIS SHALL NOT BE LIABLE, BEYOND THE AMOUNT OF ANY SUM RECEIVED IN PAYMENT BY ATIS FOR THIS DOCUMENT, AND IN NO EVENT SHALL ATIS BE LIABLE FOR LOST PROFITS OR OTHER INCIDENTAL OR CONSEQUENTIAL DAMAGES. ATIS EXPRESSLY ADVISES THAT ANY AND ALL USE OF OR RELIANCE UPON THE INFORMATION PROVIDED IN THIS DOCUMENT IS AT THE RISK OF THE USER.

NOTE - The user's attention is called to the possibility that compliance with this standard may require use of an invention covered by patent rights. By publication of this standard, no position is taken with respect to whether use of an invention covered by patent rights will be required, and if any such use is required no position is taken regarding the validity of this claim or any patent rights in connection therewith. Please refer to [<http://www.atis.org/legal/patentinfo.asp>] to determine if any statement has been filed by a patent holder indicating a willingness to grant a license either without compensation or on reasonable and non-discriminatory terms and conditions to applicants desiring to obtain a license.

Published by
Alliance for Telecommunications Industry Solutions
1200 G Street, NW, Suite 500
Washington, DC 20005

Copyright © 2020 by Alliance for Telecommunications Industry Solutions
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher. For information contact ATIS at 202.628.6380. ATIS is online at < <http://www.atis.org> >.

Unified X/Y and Z Indoor Test Methodology

Alliance for Telecommunications Industry Solutions

Approved January 13, 2020

Abstract

This document provides guidelines for simultaneously measuring horizontal (X/Y-axis) and vertical (Z-axis) indoor position accuracy performance in a common testing network. It also defines a technology-agnostic testing methodology to account for emerging vertical height determination technologies, including WiFi-based techniques. Additionally, this document incorporates an approach to increase test point positional diversity, which is required to improve test sample independence for newer indoor wireless location technologies.

Foreword

The Alliance for Telecommunications Industry Solutions (ATIS) serves the public through improved understanding between carriers, customers, and manufacturers. The Emergency Service Interconnection Forum (ESIF) provides a forum to facilitate the identification and resolution of technical and/or operational issues related to the interconnection of wireline, wireless, cable, satellites, Internet, and emergency services networks.

The mandatory requirements are designated by the word *shall* and recommendations by the word *should*. Where both a mandatory requirement and a recommendation are specified for the same criterion, the recommendation represents a goal currently identifiable as having distinct compatibility or performance advantages. The word *may* denotes an optional capability that could augment the standard. The standard is fully functional without the incorporation of this optional capability.

Suggestions for improvement of this document are welcome. They should be sent to the Alliance for Telecommunications Industry Solutions, ESIF, 1200 G Street NW, Suite 500, Washington, DC 20005.

At the time of consensus on this document, ESIF, which was responsible for its development, had the following leadership.

- R. Marshall, ESIF Chair (Comtech)
- J. Green, ESIF 1st Vice Chair, ESIF ESM Co-Chair (Sprint)
- R. Muscat, ESIF 2nd Vice Chair (Bexar Metro 911)
- K. Springer, ESIF ESM Co-Chair (AT&T)

The ESM Subcommittee was responsible for the development of this document.

Table of Contents

1	SCOPE, PURPOSE, & APPLICATION	1
1.1	SCOPE.....	1
1.2	PURPOSE.....	1
1.3	APPLICATION.....	1
2	REFERENCES.....	2
2.1	NORMATIVE REFERENCES.....	2
2.2	INFORMATIVE REFERENCES	2
3	DEFINITIONS, ACRONYMS, & ABBREVIATIONS.....	3
3.1	DEFINITIONS.....	3
3.2	ACRONYMS & ABBREVIATIONS	3
4	TEST METHODOLOGY CONSIDERATIONS.....	4
4.1	TEST REGIONS, MORPHOLOGIES, AND BUILDINGS.....	4
4.1.1	<i>Number of Regions</i>	<i>4</i>
4.1.2	<i>Morphologies</i>	<i>4</i>
4.1.3	<i>Buildings per Test Region.....</i>	<i>5</i>
4.1.4	<i>Building Selection Considerations</i>	<i>5</i>
4.1.5	<i>Efforts to Avoid Over-represented Buildings and Test Points</i>	<i>6</i>
4.2	USE OF TEST POINT 'PATHS'.....	6
4.3	TEST POINT AND PATH COUNTS.....	6
4.4	TEST POINT SELECTION CRITERIA.....	7
4.4.1	<i>RF Coverage.....</i>	<i>7</i>
4.4.2	<i>Broad Selection of Use Cases.....</i>	<i>7</i>
4.4.3	<i>Interior / Near-Exterior Test Point Ratio.....</i>	<i>8</i>
4.4.4	<i>Minimum Distance from Windows</i>	<i>8</i>
4.4.5	<i>Distance from Entry Ways</i>	<i>8</i>
4.4.6	<i>Distribution of Test Points Across Floors.....</i>	<i>8</i>
4.4.7	<i>Test Points Near Atriums.....</i>	<i>8</i>
4.4.8	<i>Use of Parking Structures.....</i>	<i>8</i>
4.4.9	<i>Use of Vacant Space for Test Points</i>	<i>9</i>
4.4.10	<i>Test Point Barometric Pressure Considerations.....</i>	<i>9</i>
4.5	TEST CALL EXECUTION TIMING, SEQUENCING, AND CONSIDERATIONS	9
4.5.1	<i>Test Calls Used to Create Location Fixes</i>	<i>9</i>
4.5.2	<i>Test Call Cycles and Number of Test Calls per Cycle.....</i>	<i>9</i>
4.5.3	<i>Power Reset Following Each Cycle No Longer Needed</i>	<i>9</i>
4.5.4	<i>Call/Wait Duration</i>	<i>10</i>
4.5.5	<i>Minimum Valid Duration.....</i>	<i>10</i>
4.5.6	<i>Mid-cycle Call Termination.....</i>	<i>10</i>
4.5.7	<i>Environmental Considerations at Time of Data Collection</i>	<i>10</i>
4.5.8	<i>After-hours Data Collection.....</i>	<i>10</i>
4.6	TEST MOBILE DEVICES	10
4.6.1	<i>Source of Devices.....</i>	<i>10</i>
4.6.2	<i>Mode Selection</i>	<i>10</i>
4.6.3	<i>Test Subscriptions</i>	<i>11</i>
4.7	GROUND TRUTH.....	11
4.7.1	<i>Ground Truth Source</i>	<i>11</i>
4.7.2	<i>Ground Truth Geodetic Reference System</i>	<i>11</i>
4.7.3	<i>Required Vertical Ground Truth Accuracy.....</i>	<i>11</i>
4.7.4	<i>Required Horizontal Ground Truth Accuracy.....</i>	<i>11</i>
4.8	SPECIAL CONSIDERATIONS FOR BAROMETRIC-PRESSURE-BASED SYSTEMS	11
4.8.1	<i>Broaden and Randomize Weather Conditions Present During Test Calls</i>	<i>11</i>
4.8.2	<i>Study In-building Vertical Pressure Effects.....</i>	<i>12</i>
4.8.3	<i>Long Duration Collects.....</i>	<i>12</i>
4.8.4	<i>Reference Barometer Measurements.....</i>	<i>12</i>

5 LOCATION TECHNOLOGY METRICS..... 13

Table of Tables

TABLE 4-1 NUMBER OF TEST BUILDINGS PER REGION.....5
TABLE 4-2 EXAMPLE SET OF BUILDING TYPES5
TABLE 4-3 APPROXIMATE TEST POINT AND PATH COUNTS.....7
TABLE 4-4 APPROXIMATE MINIMUM NUMBER OF FLOORS WITH TEST POINTS AS A FUNCTION OF TOTAL FLOORS.....8
TABLE 5-1 TYPICAL LOCATION TECHNOLOGY PERFORMANCE METRICS DEFINITIONS..... 12

Currently in preview, click buy full versi