



**American Water Works  
Association**

*Dedicated to the World's Most Important Resource®*

**ANSI/AWWA B408-18**  
(Revision of ANSI/AWWA B408-10)

**AWWA Standard**

# Liquid Polyaluminum Chloride

Effective date: May 1, 2018.

First edition approved by AWWA Board of Directors Jan. 31, 1993.

This edition approved Jan. 20, 2018.

Approved by American National Standards Institute Sept. 28, 2017.




## AWWA Standard

This document is an American Water Works Association (AWWA) standard. It is not a specification. AWWA standards describe minimum requirements and do not contain all of the engineering and administrative information normally contained in specifications. The AWWA standards usually contain options that must be evaluated by the user of the standard. Until each optional feature is specified by the user, the product or service is not fully defined. AWWA publication of a standard does not constitute endorsement of any product or product type, nor does AWWA test, certify, or approve any product. The use of AWWA standards is entirely voluntary. This standard does not supersede or take precedence over or displace any applicable law, regulation, or code of any governmental authority. AWWA standards are intended to represent a consensus of the water industry that the product described will provide satisfactory service. When AWWA revises or withdraws this standard, an official notice of action will be placed in the Official Notice section of *Journal - American Water Works Association*. The action becomes effective on the first day of the month following the month of *Journal - American Water Works Association* publication of the official notice.

## American National Standard

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. An American National Standard is intended as a guide to aid the manufacturer, the consumer, and the general public. The existence of an American National Standard does not in any respect preclude anyone, whether the person has approved the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standard. American National Standards are subject to periodic review, and users are cautioned to obtain the latest editions. Producers of goods made in conformity with an American National Standard are encouraged to state on their own responsibility in advertising and promotional materials or on tags or labels that the goods are produced in conformity with particular American National Standards.

**CAUTION NOTICE:** The American National Standards Institute (ANSI) approval date on the front cover of this standard indicates completion of the ANSI approval process. This American National Standard may be revised or withdrawn at any time. ANSI procedures require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of ANSI approval. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute, 25 West 43rd Street, Fourth Floor, New York, NY 10036; 212.642.4900; or e-mailing info@ansi.org.



ISBN-13, print: 978-1-52576-286-3

eISBN-13, electronic: 978-1-61300-467-8

DOI: <http://dx.doi.org/10.12999/AWWA.B408.18>

---

All rights reserved. No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopy, recording, or any information or retrieval system, except in the form of brief excerpts or quotations for review purposes, without the written permission of the publisher.

Copyright © 2018 by American Water Works Association  
Printed in USA

## Committee Personnel

The AWWA Standards Committee on Iron Salts, Aluminum Salts, and Related Coagulant Aids, which reviewed and approved this standard, had the following personnel at the time of approval:

Glenn R. Evers, *Chair*

Jan J. Pavlicek, *Vice-Chair*

### *General Interest Members*

K.-K. Au, FMC Global Peroxychem, Naperville, Ill.

B. Bickerton, CBCL Limited, Halifax, N.S., Canada

N.J. Edman,\* Standards Group Liaison, AWWA, Denver, Colo.

J.D. Edwards, Westerville, Ohio

G.R. Evers, IS2 LLC, Hockessin, Del.

J.J. Gemin, AECOM, Kitchener, Ont., Canada

P.H. Hargette, Black & Veatch Corporation, Greenville, S.C.

G.A. Iversen, Hazen and Sawyer, Raleigh, N.C.

D. Larson,\* CEES LLC, St. Louis, Mo.

C.B. Lind, Mauser USA LLC, East Brunswick, N.J.

J.W. Patterson, J.W. Patterson Environmental Consultants, Chicago, Ill.

S.J. Posavec,\* Standards Group Liaison, AWWA, Denver, Colo.

### *Producer Members*

T.A. Badwak, USALCO LLC, Baltimore, Md.

J.P. Crass, Market Development Manager, Ventura, Calif.

D.E. Gordon, QC LLC, Owing Mills, Md.

L.N. Hjersted,† Agro Ion, Lakeland, Fla.

B. Keogh, Brierley Water Technologies, Dundas, Ont., Canada

J.J. Pavlicek, Femira Water Solutions, Detroit, Mich.

K.E. Fuehl, Chemtrade Logistics, Ballwin, Mo.

C. Snelson, Sales, Yantis, Texas

D.M. Wheeler,† PVS Chemicals Inc., Hancock, Md.

B. Wodetzki, PVS Chemicals Inc., Detroit, Mich.

---

\* Liaison, nonvoting

† Alternate

*User Members*

D. Grimes, Fairfax Water, Herndon, Va.

L.V. Landry, Consolidated Waterworks/Sewerage District Number 1, Princeton, La.

S.C. Olson, Aquarion Water Company, Hingham, Mass.

C.A. Owen, Tampa Bay Water, Clearwater, Fla.

B.K. Parsons, City of Social Circle, Social Circle, Ga.

R.S. Smith, Louisville Water Company, Louisville, Ky.

P. Stencil, Dallas Water Utilities, Sunnyvale, Texas

J.S. Trotter, City of Bloomington Utilities, Bloomington, Ind.

# Contents

*All AWWA standards follow the general format indicated subsequently. Some variations from this format may be found in a particular standard.*

SEC.	PAGE	SEC.	PAGE
<b>Foreword</b>		<b>4</b>	<b>Requirements</b>
I	vii	4.1	Physical Requirements..... 3
I.A	vii	4.2	Chemical Requirements ..... 3
I.B	viii	4.3	Impurities..... 3
I.C	ix	<b>5</b>	<b>Verification</b>
II	x	5.1	Sampling..... 4
II.A	x	5.2	Test Procedures— General ..... 4
II.B	x	5.3	PACl Content as Percent Al..... 5
		5.4	PACl Content as Percent Al <sub>2</sub> O <sub>3</sub> — Benchmark Method ..... 8
III	xi	5.5	PACl Basicity ..... 10
III.A	xi	5.6	Product Turbidity ..... 12
		5.7	Chloride..... 12
III.B	xi	5.8	Notice of Nonconformance..... 16
IV	xi	<b>6</b>	<b>Delivery</b>
V	xi	6.1	Marking ..... 17
		6.2	Packaging and Shipping ..... 17
		6.3	Affidavit of Compliance ..... 18
<b>Standard</b>		<b>Tables</b>	
<b>1</b>	<b>General</b>	1	PACl Basicity Sample Size Guideline ..... 11
1.1	1	2	Temperature Corrections for Volumetric Solutions..... 13
1.2	1		
1.3	1		
<b>2</b>	<b>References</b>		
	2		
<b>3</b>	<b>Definitions</b>		
	2		

This page intentionally blank.

Currently in preview, click buy full version

# Foreword

*This Foreword is for information only and is not a part of ANSI\*/AWWA B408.*

## I. Introduction.

I.A. *Background.* This standard covers a variety of products based on the chemistry of aluminum salt solutions, where polyaluminum oligomers become the predominant and defining form of the aluminum cation. The characteristics of the corresponding anion in these oligomer products, although more commonly entirely chloride, may be instead sulfate or even some ratio of these two anions in combination. There are, additionally, formulations of these products wherein a polymer (organic polyelectrolyte) is blended in with inorganic oligomers to provide enhancements of specific functionalities.

This standard will focus on polyaluminum chloride (PACl) products—as they are the predominant presentation of this chemistry—commercially available as liquids in the United States and Canada. This standard covers liquid PACl for use in municipal and industrial water treatment. As a note, certain parts of this standard may be used wholly, or in part, to aid the user and producer to define and measure a specific related product chemistry being offered, although only as is appropriate and mutually agreed on beforehand by both the purchaser and supplier/manufacturer. Given these conditions, it may be necessary for the purchaser to acquire and utilize additional or different information and methodologies from those offered in this standard to allow the proper management of products in this group.

Some inorganic coagulants are mixed with polymers to produce blends.<sup>†</sup>

*Polyaluminum chloride* is a misnomer, however, because these products contain a mixture of polymers (usually aggregates of oligomers) of aluminum chloride hydroxide (Chemical Abstract Service [CAS] No. 1327-41-9) with the empirical formula  $Al_n(OH)_mCl_{(3n-m)}$  for  $0 < m < 3n$ . At least the following five CAS numbers, 1327-41-9, 10284-64-7, 14215-15-7, 39290-78-3, and 12042-91-0, have been used for various types of PACl. *Basicity* (hydroxyl number) refers to the average number of hydroxide ions per aluminum atom in the PACl molecules, or  $m/n$ . In some PACl products, an anion other than chloride, such as sulfate, may also be present, but this anion should

---

\* American National Standards Institute, 25 West 43rd Street, Fourth Floor, New York, NY 10036.

† Polyelectrolytes Standards Committee, B.S. Johnson, Chair. 2004. “Characterization of Inorganic Coagulant/Polymer Blends Using Refractive Index and Specific Gravity Measurements,” Polyelectrolytes Standards Committee Report. *Journal AWWA*, 96:170.

be present in much lower concentrations than the chloride ion if the product is being sold as PACl.

The basicity of PACl products can range from 0 to 2.5, although the basicity should not be 0 if the product is being sold as PACl. The basicity is converted to “percent basicity” using the following formula:

$$\text{percent basicity} = \frac{(\text{OH}/\text{Al}) \times 100}{3}$$

where Al and OH are expressed as moles/liter.

The values for percent basicity of liquid PACl products can range from about 1.7 to 83.3. The basicity of the product does not necessarily relate directly to product performance; so the highest basicity may not give the best performance in a particular application.

Polyaluminum chloride products contain varying amounts of PACl the concentration of which is conventionally expressed as “percent by weight as Al” or “percent as Al.” The range of PACl content in PACl products is about 2.5 to 13 percent as aluminum (5 to 25 percent as Al<sub>2</sub>O<sub>3</sub>).

Polyaluminum chloride can be commercially manufactured from a number of aluminum-containing raw materials, including aluminum metal, alumina trihydrate, aluminum chloride, aluminum sulfate, and combinations of these. The products can contain byproduct salts, such as sodium/calcium/magnesium chloride or sulfate, depending on the manufacturing process. The presence of these salts is not harmful to product performance or to those handling the product. Recognizing that the purity of PACl can vary with the manufacturing process, the purchaser should ask the supplier for information concerning potential impurities.

This standard provides methods for analysis of active PACl expressed in percent as aluminum (or Al<sub>2</sub>O<sub>3</sub>), percent basicity, turbidity, and specific gravity.

**I.B. History.** In 1988, the AWWA Standards Committee on Iron Salts, Aluminum Salts, and Related Coagulant Aids organized a subcommittee to prepare a standard for PACl products. The first draft of the standard was reviewed in 1989, and the final draft was approved in 1992. The first edition of ANSI/AWWA B408, Standard for Liquid Polyaluminum Chloride, was approved by the AWWA Board of Directors on Jan. 31, 1993. Subsequent editions were approved on June 21, 1998; June 19, 2003; and June 20, 2010. This edition was approved on Jan. 20, 2018.

I.C. *Acceptance.* In May 1985, the US Environmental Protection Agency (USEPA) entered into a cooperative agreement with a consortium led by NSF International (NSF) to develop voluntary third-party consensus standards and a certification program for direct and indirect drinking water additives. Other members of the original consortium included the Water Research Foundation (formerly AwwaRF) and the Conference of State Health and Environmental Managers (COSHEM). The American Water Works Association (AWWA) and the Association of State Drinking Water Administrators (ASDWA) joined later.

In the United States, authority to regulate products for use in, or in contact with, drinking water rests with individual states.\* Local agencies may choose to impose requirements more stringent than those required by the state. To evaluate the health effects of products and drinking water additives from such products, state and local agencies may use various references, including two standards developed under the direction of NSF:† NSF/ANSI 60, Drinking Water Treatment Chemicals—Health Effects, and NSF/ANSI 61, Drinking Water System Components—Health Effects.

Various certification organizations may be involved in certifying products in accordance with NSF/ANSI 60. Individual states or local agencies have authority to accept or accredit certification organizations within their jurisdictions. Accreditation of certification organizations may vary from jurisdiction to jurisdiction.

Annex A, “Toxicology Review and Evaluation Procedures,” to NSF/ANSI 60 does not stipulate a maximum allowable level (MAL) of a contaminant for substances not regulated by a USEPA final maximum contaminant level (MCL). The MALs of an unspecified list of “unregulated contaminants” are based on toxicity testing guidelines (noncarcinogens) and risk characterization methodology (carcinogens). Use of Annex A procedures may not always be identical, depending on the certifier.

ANSI/AWWA B108 addresses additives requirements in Sec. 4.3.2 of the standard. The transfer of contaminants from chemicals to processed water or to the residual solids is becoming a problem of greater concern. The language in Sec. 4.3.2 is a recommendation only for direct additives used in the treatment of potable water to be certified by an accredited certification organization in accordance with NSF/ANSI 60, Drinking Water Treatment Chemicals—Health Effects. However, users of the standard may opt to make this certification a requirement for the product. Users of this standard should also consult the appropriate state or local agency having jurisdiction in order to

---

\* Persons outside the United States should contact the appropriate authority having jurisdiction.

† NSF International, 789 North Dixboro Road, Ann Arbor, MI 48105.

1. Determine additives requirements, including applicable standards.
2. Determine the status of certifications by parties offering to certify products for contact with, or treatment of, drinking water.

3. Determine current information on product certification.

## II. Special Issues.

II.A. *Storage and Handling Precautions.* Liquid PACl is a clear to slightly hazy solution that is acidic and corrosive to common metals. Suitable materials for construction of storage and handling facilities include synthetic rubber-lined steel, corrosion-resistant fiberglass-reinforced plastics (FRP), ceramics, tetrafluoroethylene polymer (PTFE), polyvinylidene fluoride (PVDF), polyethylene, polypropylene, and polyvinyl chloride (PVC). Steel (stainless and mild), aluminum, nickel, copper, or brass are not suitable. The supplier should be contacted for recommendations on appropriate materials of construction for the storage, handling, and packaging of any specific product.

Contact with PACl products may cause burns or irritation to the eyes or skin. Protective clothing, such as rubber gloves, boots, pants, and jackets, and eye protection, such as goggles or face masks, are recommended. Consult the manufacturer's safety data sheets for product-specific safety recommendations.

II.B. *General Guide to Solid Materials in User Product Handling Systems.* Some liquid chemical products, including liquid PACl, can amass minor or sometimes critical amounts of solid materials throughout user product handling systems while adhering to those general product requirements set forth in Section 4. These materials can be in the nature of

1. Crystallization, precipitation, and accumulation of product primary components.
2. Crystallization, precipitation, and accumulation of product derivatives.
3. Precipitation and/or accumulation of product inclusions.

These materials may not be compatible with existing product storage and feed systems. Typical management measures available to the user include site-specific specifications, inline filtering or screening, storage and feed system cleaning schedules, storage and handling system design, and inventory management. Therefore, it is recommended that the user discuss with the supplier and fully understand the following:

1. Typical product characteristics.
2. Specific application protocols or requirements for product efficacy.
3. Environmental factors that can impact product efficacy.

4. Product storage and handling system requirements.
5. Logistics and material receipt requirements.

**III. Use of This Standard.** It is the responsibility of the user of an AWWA standard to determine that the products described in that standard are suitable for use in the particular application being considered.

**III.A. Purchaser Options and Alternatives.** The following information should be provided by the purchaser:

1. Standard used—that is, ANSI/AWWA B408, Liquid Polyaluminum Chloride, of latest revision.
2. Percent active PACl expressed as percent Al or as percent  $Al_2O_3$ .
3. Whether compliance with NSF/ANSI 60, Drinking Water Treatment Chemicals—Health Effects, is required.
4. Details of other federal, state or provincial, and local requirements (Section 4).
5. Whether the purchaser will reject product from containers or packaging with missing or damaged seals. The purchaser may reject product from bulk containers or packages with missing or damaged seals unless the purchaser's tests of representative samples, conducted in accordance with Sec. 5.3 through Sec. 5.7, demonstrate that the product meets the standard. Failure to meet the standard or the absence of, or irregularities in, seals may be sufficient cause to reject the shipment.
6. Method of shipping, packaging, and container size (Sec. 6.2).
7. Whether alternative security measures have been adopted to replace or augment the security measures set out in Sec. 6.2.2 and Sec. 6.2.3.
8. An affidavit of compliance or certified analysis or both, if required (Sec. 6.3).

**III.B. Modification to Standard.** Any modification of the provisions, definitions, or terminology in this standard must be provided by the purchaser.

**IV. Major Revisions.** Major changes to the standard in this edition include the following:

1. Additional language added to the foreword (Sec. II.B).
2. Revision of Notice of Nonconformance section (Sec. 5.8).
3. Revision of Marking section (Sec. 6.1).

**V. Comments.** If you have any comments or questions about this standard, please call AWWA Engineering and Technical Services at 303.794.7711, FAX at 303.795.7603, write to the department at 6666 West Quincy Avenue, Denver, CO 80235-3098, or e-mail at [standards@awwa.org](mailto:standards@awwa.org).

This page intentionally blank.



**American Water Works  
Association**

*Dedicated to the World's Most Important Resource®*

**ANSI/AWWA B408-18**  
(Revision of ANSI/AWWA B408-10)

**AWWA Standard**

---

# Liquid Polyaluminum Chloride

---

## SECTION 1: GENERAL

---

### **Sec. 1.1 Scope**

This standard describes polyaluminum chloride (PACl) in aqueous (liquid) form for use in the treatment of potable water, wastewater, and reclaimed water.

### **Sec. 1.2 Purpose**

The purpose of this standard is to provide the minimum requirements for liquid PACl, including physical, chemical, sampling, testing, packaging, and shipping requirements.

### **Sec. 1.3 Application**

This standard can be referenced in specifications for purchasing and receiving liquid PACl and can be used as a guide for testing the physical and chemical properties of liquid PACl samples. The stipulations of this standard apply when this document has been referenced and then only to liquid PACl used in the treatment of potable water, wastewater, and reclaimed water.