

ANSI/AWWA **C232-22**
(Revision of ANSI/AWWA C232-22)

AWWA Standard

Viscoelastic Coatings for Steel Water Pipe and Fittings

Effective date: Feb. 1, 2023.

This first edition approved by Board of Directors Oct. 24, 2022
Approved by American National Standards Institute Oct. 7, 2022.



AWWA Standard

This document is an American Water Works Association (AWWA) standard. It is not a specification. AWWA standards describe minimum requirements and do not contain all of the engineering and administrative information normally contained in specifications. The AWWA standards usually contain options that must be evaluated by the user of the standard. Until each optional feature is specified by the user, the product or service is not fully defined. AWWA publication of a standard does not constitute endorsement of any product or product type, nor does AWWA test, certify, or approve any product. The use of AWWA standards is entirely voluntary. This standard does not supersede or take precedence over or displace any applicable law, regulation, or code of any governmental authority. AWWA standards are intended to represent a consensus of the water industry that the product described will provide satisfactory service. When AWWA revises or withdraws this standard, an official notice of action will be placed in the Official Notice section of *Journal AWWA*. The action becomes effective on the first day of the month following the month of *Journal AWWA* publication of the official notice.

American National Standard

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. An American National Standard is intended as a guide to aid the manufacturer, the consumer, and the general public. The existence of an American National Standard does not in any respect preclude anyone, whether that person has approved the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standard. American National Standards are subject to periodic review, and users are cautioned to obtain the latest editions. Producers of goods made in conformity with an American National Standard are encouraged to state on their own responsibility in advertising and promotional materials or on tags or labels that the goods are produced in conformity with particular American National Standards.

CAUTION NOTICE: The American National Standards Institute (ANSI) approval date on the front cover of this standard indicates completion of the ANSI approval process. This American National Standard may be revised or withdrawn at any time. ANSI procedures require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of ANSI approval. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute, 25 West 43rd Street, Fourth Floor, New York, NY 10036; (212) 642-4900; or e-mailing info@ansi.org.



ISBN-13, print: 978-1-64717-111-3

ISBN-13, electronic: 978-1-61300-650-4

DOI: <http://dx.doi.org/10.12999/AWWA.C232.22>

All rights reserved. No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including scanning, recording, or any information or retrieval system. Reproduction and commercial use of this material is prohibited, except with written permission from the publisher.

Copyright © 2022 by American Water Works Association
Printed in USA

Committee Personnel

The Steel Water Pipe-Manufacturer's Technical Advisory Committee (SWMPTAC) Task Group for AWWA C232, which developed this standard, had the following personnel at the time:

Sam Thomas, *Chair*

Edwin Welles, *Vice-Chair*

J. Buratto, Seal for Life, Pflugerville, Tex.

J. Bertsche, Seal for Life, Sandy Hook, Conn.

D. D'Ambrosio, Polyguard, Ennis, Tex.

G. Davidenko, Northwest Pipe Company, Saginaw, Tex.

A. Fletcher, Consultant representing Steel Mains Pty Ltd., Melbourne, Australia

J. Harvey, Mobile Pipe, Adelanto, Calif.

D. Libby, Chase Corporation, Westwood, Mass.

F. Maxwell, Seal for Life, Fort Collins, Colo.

R. Mielke, Northwest Pipe Company, Raleigh, N.C.

C. Patton, Seal for Life, Houston, Tex.

S. Salehpour, Seal for Life, Toronto, Ont.

B.P. Simpson, American SpiralWeld Pipe Company, Birmingham, Ala.

S. Thomas, Liberty Coating, Pelham, N.H.

H. Vugteveen, Seal for Life, Stadskanaal, Groningen, The Netherlands.

E. Welles, Denso, San Antonio, Tex.

The AWWA Standards Committee on Steel Pipe, which reviewed and approved this standard, had the following personnel at the time of approval:

John H. Bambei Jr., *Chair*

Bob J. Card, *Vice-Chair*

John L. Luka, *Secretary*

General Interest Members

A. Arnaout (*alternate*), Stantec, Dallas, Tex.

J.H. Bambei Jr., Bambei Engineering Services, Arvada, Colo.

R.J. Card, Lockwood, Andrews & Newnam Inc., Suwanee, Ga.

R.L. Coffey, Consultant, Bend, Ore.

R.L. Gibson, Freese and Nichols Inc., Fort Worth, Tex.

M.D. Gossett, HDR, Denver, Colo.
M.B. Horsley (*alternate*), Horsley Engineering LLC, Overland Park, Kans.
R. Issa, AECOM, McKinney, Tex.
C.H. Kirby (*alternate*), Lockwood, Andrews & Newnam Inc., Houston, Tex.
R.A. Kufaas, Norske Corrosion & Inspection Services Ltd., Abbotsford, B.C.
J.L. Mattson, Corrosion Control Technologies, Sandy, Utah
D.L. McPherson (*alternate*), HDR, Charlotte, N.C.
A. Murdock, Jacobs, Salt Lake City, Utah
R. Ortega, Aurora Technical Services, Houston, Tex.
E.S. Ralph (*liaison, nonvoting*), Standards Engineer Liaison, AWWA, Denver, Colo.
A.E. Romer (*alternate*), AECOM, Orange, Calif.
J.R. Snow, Stantec, Denver, Colo.
A.M. Stanton, Black & Veatch, Pasadena, Calif.
W.R. Whidden, Woolpert, Orlando, Fla.

Producer Members

H.H. Bardakjian, Consultant, Glendale, Calif.
D. Dechant, Dechant Infrastructure Services, Aurora, Colo.
D.W. Dunker, Thompson Pipe Group, Rialto, Calif.
B.D. Keil, Northwest Pipe Company, Draper, Utah
J.L. Luka, American SpiralWeld Pipe Company, Columbia, S.C.
R.D. Mielke (*alternate*), Northwest Pipe Company, Raleigh, N.C.
G.F. Ruchti (*alternate*), Consultant, Punta Gorda, Fla.
B.P. Simpson (*alternate*), American Cast Iron Pipe Company, Birmingham, Ala.
C.C. Sundberg, Victaulic, Issaquah, Wash.
R. Wu (*alternate*), Thompson Pipe Group, Grand Prairie, Tex.

User Members

L. Adams, US Bureau of Reclamation, Denver, Colo.
G.A. Andersen, New York City Bureau of Water Supply, Little Neck, N.Y.
B. Cheng, Metro Vancouver, Burnaby, B.C.
D. Fountain, San Diego County Water Authority, San Diego, Calif.
J. Fox, Tampa Bay Water, Clearwater, Fla.
S. Hattan, Tarrant Regional Water District, Fort Worth, Tex.
M. Lobik, Springfield Water & Sewer, Springfield, Mass.

T. Peng, Metropolitan Water District, Los Angeles, Calif.

G. Ramon (*liaison, nonvoting*), Standards Council Liaison, Little Rock Water Reclamation Authority, Little Rock, Ark.

V. Scutelnicu, Los Angeles Department of Water and Power, Los Angeles, Calif.

M. Turney (*alternate*), Denver Water, Denver, Colo.

Currently in preview, click buy full version

This page intentionally blank.

Currently in preview, click buy full version

Contents

All AWWA standards follow the general format indicated subsequently. Some variations from this format may be found in a particular standard.

SEC.	PAGE	SEC.	PAGE
Foreword		4.4	Surface Preparation 6
I	Introduction ix	4.5	Coating Application 7
I.A	Background ix	4.6	Coating Fittings and Special Sections 8
I.B	History ix	4.7	Coating Repair 8
II	Special Issues ix	4.8	Field Joints 8
II.A	Advisory Information on Product Application ix	4.9	Field Procedures 8
II.B	Mechanical Protection x	5	Verification
II.C	Pipe Storage x	5.1	Coating Materials Prequalification 9
III	Use of This Standard x	5.2	Prequalification Requirements of Coating System 9
III.A	Purchaser Options and Alternatives x	5.3	Quality Assurance and Records 13
III.B	Modification to Standard xi	5.4	Inspection and Testing by the Purchaser 13
IV	Major Revisions xi	5.5	Quality Control Requirements of Applied Coating System 13
V	Comments xi	5.6	Rejection 15
Standard		6	Delivery
1	General	6.1	Marking 15
1.1	Scope 1	6.2	Packaging and Shipping 15
1.2	Purpose 2	6.3	Affidavit of Compliance 16
1.3	Application 2		
2	References 3	Tables	
3	Definitions 4	1	Prequalification Requirements of Inner Layer 9
4	Requirements	2	Prequalification Requirements of Outer Layer 10
4.1	Equipment 5	3	Prequalification Requirements of Total Coating System 10
4.2	Materials and Workmanship 5	4	Quality Control Requirements of Applied Coating System 13
4.3	Coating System 5		

Currently in preview, click buy full version

Foreword

This foreword is for information only and is not a part of ANSI/AWWA C232.

I. Introduction.

I.A. *Background.* This AWWA standard describes the minimum material and application requirements for denoted hereafter viscoelastic coating systems to be field applied or plant applied to the exterior of steel water pipe, field joints, special sections, connection, and fittings for purposes of underground corrosion prevention. Viscoelastic coatings can be applied without the use of special equipment and over a broad application temperature range.

I.B. *History.* The first edition of this standard, designated ANSI/AWWA C232, Standard for Viscoelastic Coatings for Steel Water Pipe and Fittings, was approved by the Board of Directors on Oct. 24, 2022.

II. Special Issues.

II.A. *Advisory Information on Product Application.* Currently, viscoelastic coatings generally are used on pipe that has been coated before transportation to the field site.

Where allowed by the purchaser, coatings described in ANSI/AWWA C232 can be used in conjunction with pipe coatings described in:

ANSI/AWWA C203, Coal-Tar Protective Coatings and Linings for Steel Water Pipe.

ANSI/AWWA C205, Cement-Mortar Protective Lining and Coating for Steel Water Pipe 4 In. (100 mm) and Larger—Shop Applied.

ANSI/AWWA C209, Tape Coatings for Steel Water Pipe and Fittings.

ANSI/AWWA C210, Liquid-Epoxy Coatings and Linings for Steel Water Pipe and Fittings.

ANSI/AWWA C213, Fusion-Bonded Epoxy Coatings and Linings for Steel Water Pipe and Fittings.

ANSI/AWWA C214, Machine-Applied Polyolefin Tape Coatings for Steel Water Pipe.

ANSI/AWWA C215, Extruded Polyolefin Coatings for Steel Water Pipe.

ANSI/AWWA C216, Heat-Shrinkable Cross-Linked Polyolefin Coatings for Steel Water Pipe and Fittings.

* American National Standards Institute, 25 West 43rd Street, Fourth Floor, New York, NY 10036.

ANSI/AWWA C222, Polyurethane Coatings and Linings for Steel Water Pipe and Fittings.

ANSI/AWWA C224, Nylon-11–Based Polyamide Coatings and Linings for Steel Water Pipe and Fittings.

ANSI/AWWA C225, Fused Polyolefin Coatings for Steel Water Pipe.

ANSI/AWWA C229, Fusion-Bonded Polyethylene Coatings for Steel Water Pipe and Fittings.

ANSI/AWWA C232 is intended for use as the exterior coating of steel water pipelines for underground or underwater installation under normal conditions. This standard is based on the best-known experience but is not intended for unqualified use under all conditions, and the advisability of its use for any installation must be reviewed by the purchaser.

When viscoelastic coating systems are used for repair or rehabilitation, or used in conjunction with other coatings, the manufacturer of the viscoelastic coatings should be consulted to establish the degree of compatibility of the viscoelastic coating with the coating system involved. If an extended period of aboveground storage of coated pipe is anticipated, the ability of the coating to resist degradation by ultraviolet light and other atmospheric and environmental conditions should be considered.

II.B. Mechanical Protection. When construction or soil conditions exist in which mechanical damage to the coating is likely to occur, the use of an additional suitable outer wrap and reinforcements or special backfills may be required. This will depend on the conditions encountered, but in general, an additional suitable overwrap or other wrapping should be used. Under these conditions, the coating manufacturer should be consulted for specific recommendations.

II.C. Pipe Storage. Pipes should be stored at ambient temperatures of 0–120°F (-18–49°C) for no more than 90 days. If storage conditions outside this range are expected, the coating manufacturer shall be consulted to determine if additional protective layers or other considerations are necessary.

III. Use of This Standard. It is the responsibility of the user of an AWWA standard to determine that the products described in that standard are suitable for use in the particular application being considered.

III.A. Purchaser Options and Alternatives.

The following items should be specified by the purchaser:

1. Standard used—that is, ANSI/AWWA C232, Viscoelastic Coatings for Steel Water Pipe and Fittings.
2. Any exceptions to the standard that may be required.

3. Diameter.
4. Location of coating application with reference to environmental considerations, length, and location of pipeline.
5. Operating temperature range (Sec. 1.1.1).
6. Descriptions of difficult conditions or aboveground exposure (Sec. 1.1.2).
7. Outdoor storage (Sec. 1.1.2).
8. Inner-layer thickness (Sec. 4.3.1).
9. Type of outer wrap if required (Sec. 4.3.1).
10. Type of viscoelastic coating (Sec. 4.3.1).
11. Coating repair (Sec. 4.7).
12. Coating materials prequalification (Sec. 5.1).
13. Quality assurance and records (Sec. 5.3).
14. Inspection and testing (Sec. 5.4 and Sec. 5.5).
15. Facilities for inspection (Sec. 5.4.3).
16. Acceptance testing (Sec. 5.5).
17. Nonconforming pipe (Sec. 5.5).
18. Holiday detector use (Sec. 5.5.2).
19. Adhesion requirement and test frequency (Sec. 5.5.3).
20. Delivery (Section 6).
21. Packaging (Sec. 6.2.1).
22. Affidavit of compliance, if required (Sec. 6.3).

NOTE: The specific application procedure used for each type of coating system is as described by the coating manufacturer.

III.B. *Modification to Standard.* Any modification to the provisions, definitions, or terminology in this standard must be provided by the purchaser.

IV. Major Revisions.

This is a new standard.

V. Comments. If you have any comments or questions about this standard, please call AWWA Engineering and Technical Services at 303.794.7711, FAX at 303.795.7603, write to the department at 6666 West Quincy Avenue, Denver, CO 80235-3098, or email at standards@awwa.org.

This page intentionally blank.



**American Water Works
Association**

Dedicated to the World's Most Important Resource®

ANSI/AWWA C232-22
(First Edition)

AWWA Standard

Viscoelastic Coatings for Steel Water Pipe and Fittings

SECTION 1: GENERAL

Sec. 1.1 Scope

This standard describes the materials and application of viscoelastic coating systems to the exterior of steel water pipe and fittings to be used for underground and underwater service. For the purposes of this standard, the coating system has a viscoelastic compound as a corrosion-prevention layer that shall be based on either polyisobutene (PIB) or amorphous polyalphaolefin (APAO). Viscoelastic coatings systems conforming to this standard may be field-applied to repair or rehabilitate pipe and fittings, shop-applied to fittings, or used as a joint coating for pipe and fittings protected with organic coatings, such as those described in ANSI/AWWA C203, ANSI/AWWA C205, ANSI/AWWA C209, ANSI/AWWA C210, ANSI/AWWA C213, ANSI/AWWA C214, ANSI/AWWA C215, ANSI/AWWA C216, ANSI/AWWA C222, ANSI/AWWA C224, ANSI/AWWA C225, and ANSI/AWWA C229.

For normal construction considerations, viscoelastic coating systems are either applied as a two-layer system consisting of (1) a corrosion-prevention inner layer, and (2) a mechanical outer layer; or applied as a one-layer system where the corrosion-prevention inner layer and the mechanical outer layer are bonded together and applied as a single layer.