

# B11.TR6-2010

## ANSI Technical Report for Machines – Safety Control Systems for Machine Tools

**Registered: 5 DECEMBER 2010**  
by the American National Standards Institute, Inc.

Secretariat and Accredited Standards Developer, prepared by:  
**B11 Standards, Inc.**  
42293 Young Lane  
Leesburg, VA 21076



**COPYRIGHT PROTECTED DOCUMENT**

Copyright © 2010 by B11 Standards, Inc.

All rights reserved. Printed in the United States of America  
No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of B11 Standards, Inc.

## AMERICAN NATIONAL STANDARDS / TECHNICAL REPORTS

By registering this ANSI Technical Report, the ANSI Board of Standards Review confirms that the requirements for due process, consensus, balance and openness have been met by AMT – The Association For Manufacturing Technology (the ANSI-accredited standards developing organization).

American National Standards and Technical Reports are developed through a consensus process. Consensus is established when substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward resolution. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While AMT administers the process and establishes procedures to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards or guidelines.

American National Standards and Technical Reports are promulgated through ANSI for voluntary use, the existence does not in any respect preclude anyone, whether they have approved the standards/technical reports or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the these documents. However, users, distributors, regulatory bodies, certification agencies and others concerned may apply American National Standards or Technical Reports as mandatory requirements in commerce and industry.

The American National Standards Institute does not develop standards or technical reports and will in no circumstances give an interpretation of an American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the Secretariat (AMT).

AMT MAKES NO WARRANTY, EITHER EXPRESSED OR IMPLIED AS TO THE FITNESS OF MERCHANTABILITY OR ACCURACY OF THE INFORMATION CONTAINED WITHIN THIS TECHNICAL REPORT, AND DISCLAIMS AND MAKES NO WARRANTY THAT THE INFORMATION IN THIS DOCUMENT WILL FULFILL ANY OF YOUR PARTICULAR PURPOSES OR NEEDS. AMT disclaims liability for any personal injury, property or other damages of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, application or reliance on this document. AMT does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this technical report, nor does it take any position with respect to the validity of any patent rights asserted in connection with the items which are mentioned in or are the subject of this document, and AMT disclaims liability for the infringement of any patent resulting from the use of or reliance on this document. Users of this document are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

In publishing or making this document available, AMT does not undertake to render professional or other services for or on behalf of any person or entity, nor is AMT undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment, or as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

AMT has no power, nor does it undertake to police or enforce conformance to the requirements of this document. AMT does not certify, test or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of conformance to any health or safety-related information in this document shall not be attributable to AMT and is solely the responsibility of the certifier or maker of the statement.

**NOTICE:** This ANSI Technical Report may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this technical report. You may contact the Secretariat for current status information on this, or other B11 documents. Individuals interested in obtaining up-to-date information on standards can access this information at <http://www.nssn.org> (or by contacting ANSI). NSSN - A National Resource for Global Standards, provides a central point to search for standards information from worldwide sources and can connect those who seek standards to those who supply them.

Published by:

B11 Standards, Inc.  
42293 Young Lane, Leesburg, VA 20176, USA  
dfelinski@b11standards.org

Copyright © 2010 by B11 Standards, Inc. All rights reserved. Printed in the United States of America

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

TABLE OF CONTENTS	PAGE
<b>Introduction and Overview of the ANSI B11 Series.....</b>	<b>13</b>
<b>1 Scope .....</b>	<b>15</b>
<b>2 References .....</b>	<b>15</b>
<b>3 Definitions.....</b>	<b>16</b>
<b>4 General Design Considerations for Mechanical, Fluid Power and Electrical Technologies.....</b>	<b>21</b>
<b>4.1 ANSI B11.TR6 Circuit Analysis Tables .....</b>	<b>21</b>
<b>4.2 Practical Use of TR6.....</b>	<b>22</b>
4.2.1 General.....	22
4.2.2 Applying TR6 to a Sample Application.....	22
<b>4.3 Reset Function of the Safety Circuit.....</b>	<b>24</b>
<b>4.4 Start Function.....</b>	<b>24</b>
<b>4.5 Testing &amp; Verification of the Safety Function .....</b>	<b>24</b>
4.5.1 Category 2 Periodic Test.....	24
<b>4.6 Fault Consideration.....</b>	<b>24</b>
4.6.1 Fault Analysis .....	25
4.6.2 Fault Exclusion .....	25
<b>4.7 Response Time .....</b>	<b>25</b>
<b>4.8 Mechanical Considerations (general) .....</b>	<b>25</b>
<b>4.9 Fluid Power (Pneumatics &amp; Hydraulics) .....</b>	<b>25</b>
4.9.1 General Considerations.....	25
4.9.2 Basic Methodology for Safety Interfacing.....	25
4.9.3 Pressure Vessels and Accumulators .....	26
4.9.4 Stored Energy (Trapped Pressure) .....	26
4.9.5 Reapplication of Pressure .....	26
4.9.6 Hoses and Fittings.....	27
4.9.7 Fluid Power Valve Crossover Considerations.....	28
4.9.8 Single Channel Fluid Power Device.....	28

4.9.9	Single Channel Fluid Power Device with Monitoring.....	28
4.9.10	Dual channel fluid power .....	29
4.9.11	Dual Channel fluid power with Monitoring .....	29
4.9.12	Dual Channel Cross Monitoring Valve .....	29
4.9.13	Response Time Considerations .....	29
4.9.14	Fault Reset Function .....	29
4.9.15	Position Fault.....	29
4.9.16	Diminished Performance Fault.....	29
4.9.17	Failure Modes to be Considered .....	29
4.9.18	Non-Safety Devices.....	30
<b>4.10</b>	<b>Pneumatics.....</b>	<b>30</b>
4.10.1	Basic Pneumatic System Considerations .....	30
4.10.2	Safety Shut-Off and Exhaust Valve.....	30
4.10.3	Filtration.....	31
4.10.4	Regulator .....	31
4.10.5	Lubrication .....	31
4.10.6	Air Valve Mufflers .....	32
4.10.7	Environmental Influences .....	32
<b>4.11</b>	<b>Hydraulics.....</b>	<b>32</b>
4.11.1	Basic Hydraulic System Considerations .....	32
4.11.2	General.....	32
4.11.3	Accumulators.....	33
4.11.4	Fluid Management.....	33
4.11.5	Filtration.....	34
4.11.6	Relief/Pressure Reducing Valve.....	36
<b>4.12</b>	<b>Electrical Interfacing Considerations (General).....</b>	<b>36</b>
4.12.1	Basic Methodology of Safety Interfacing.....	36
4.12.2	Protective Stop Circuits .....	36
4.12.2.1	Single-Channel Control.....	36
4.12.2.2	Dual-Channel Control.....	37
4.12.3	Safety Interface Module (SIM).....	37
4.12.4	Interfacing to Protective (Safety) Stop .....	38
4.12.4.1	Positive Logic .....	38
4.12.4.2	PLC/PLC Interfacing.....	38
4.12.5	Electro-Mechanical Contact Considerations .....	39
4.12.6	Failure Modes.....	39
4.12.7	Power Supplies.....	39
4.12.8	Environmental Influences .....	39
<b>4.13</b>	<b>Safety-Related Performance.....</b>	<b>40</b>
<b>5</b>	<b>Input Devices (safeguarding devices and complementary equipment).....</b>	<b>42</b>

<b>5.1</b>	<b>Emergency Stop Devices.....</b>	<b>42</b>
5.1.1	Lowest Risk Reduction (Category 1).....	43
5.1.1.1	Single Channel E-Stop Using a Control Relay (Category 1).....	43
5.1.2	Low / Intermediate Risk Reduction (Category 2).....	44
5.1.2.1	Dual Channel E-Stop Using Redundant Control Relays (Category 2).....	44
5.1.3	Intermediate / High Risk Reduction (Category 3).....	45
5.1.3.1	Dual Channel E-Stop Using FGR Relays and Cross Monitoring (Category 3).....	45
5.1.3.2	Multiple Dual Channel E-Stop with a Safety Relay Interface Module (Category 3).....	46
5.1.4	Highest risk reduction (Category 4).....	47
5.1.4.1	Single Button Dual Channel E-Stop with a SIM (Category 4).....	47
5.1.4.2	Single Button Dual Channel E-Stop* w/ Self Monitoring and a SIM (Category 4).....	48
<b>5.2</b>	<b>Contact Interlocking.....</b>	<b>49</b>
5.2.1	Description of Positive-Opening Interlock Switches.....	49
5.2.2	Type 1 and Type 2 Considerations.....	50
5.2.2.1	Failure Modes.....	50
5.2.2.1.1	Type 1.....	50
5.2.2.1.2	Type 2.....	50
5.2.2.2	Categories.....	50
5.2.3	General Considerations.....	50
5.2.3.1	Physical installation.....	50
5.2.3.2	Electrical interface.....	50
5.2.3.2.1	PES/PLC Control System Monitoring.....	51
5.2.3.2.2	Monitoring Series Connected Positive-Opening Interlocking Switches.....	51
5.2.4	Basic Circuit (Category B).....	52
5.2.4.1	Basic Interlocked Guard Monitoring Circuit (Category B).....	52
5.2.5	Lowest Risk Reduction (Category 1).....	53
5.2.5.1	Interlocked Guard Monitoring Circuit – Single Channel (Category 1).....	53
5.2.6	Low / Intermediate Risk Reduction (Category 2).....	54
5.2.6.1	Series Connection of Interlocks to a SIM (Category 2).....	54
5.2.6.2	Interlocked Guard Monitoring – Dual Channel w/ a SIM and PES (Category 2).....	55
5.2.7	Intermediate / High Risk Reduction (Category 3).....	56
5.2.7.1	Single Interlock to a SIM (Category 3).....	56
5.2.7.2	Series Connection of Interlocks to a SIM (Category 3).....	57
5.2.8	Highest Risk Reduction (Category 4).....	58
5.2.8.1	Interlocked Guard Monitoring – Dual Channel w/ Relay/Contactor and Reset Button (Category 4).....	58
5.2.8.2	Interlocked Guard Monitoring – Dual Channel w/ a SIM (Category 4).....	59
<b>5.3</b>	<b>Guard Interlocking with Non-Contact Switches (without a Locking Function).....</b>	<b>60</b>
5.3.1	Description of Non-Contact Interlock Switches.....	60
5.3.2	General Considerations.....	60
5.3.3	Inductive Switches.....	60
5.3.4	Optical Switches.....	60
5.3.5	Magnetic Switches.....	60
5.3.6	Transponder Switches.....	61
5.3.7	Basic Risk Reduction (Category B).....	61
5.3.7.1	Non-Contact Interlocked Guard Monitoring using Standard Retro-Reflective Photo Sensor (Category B).....	61
5.3.7.2	Non-Contact Interlocked Guard Monitoring using Standard Magnetic Sensor (Category B).....	62
5.3.8	Intermediate / High Risk Reduction (Category 3).....	63

5.3.8.1	Non-Contact Interlocked Guard Monitoring Circuit (Category 3).....	63
5.3.8.2	Interlocked Guard Monitoring – Dual Channel with a SIM (Category 3).....	64
5.3.9	Highest Risk Reduction (Category 4).....	65
5.3.9.1	Interlocked Guard Monitoring – Dual Channel with a SIM (Category 4).....	65
5.3.9.2	Interlocked Guard Monitoring – Dual Channel with a SIM (Category 4).....	66
5.3.9.3	Interlocked Guard Monitoring – Dual Channel with a SIM (Category 4).....	67
5.3.9.4	Interlocked Guard Monitoring – Dual Channel with a SIM (Category 4).....	68
<b>5.4</b>	<b>Guardlocking Interlocks .....</b>	<b>69</b>
5.4.1	General Considerations.....	69
5.4.2	Low / Intermediate Risk Reduction (Category 2) .....	69
5.4.2.1	Power to Release, Inline Guardlocking Interlock (Category 2).....	69
5.4.3	Intermediate / High Risk Reduction (Category 3).....	70
5.4.3.1	Power to Release, Dual Axis Guardlocking Interlock (Category 3).....	70
5.4.4	Highest Risk Reduction (Category 4).....	71
5.4.4.1	Power to Release, Inline Guardlocking Interlock (Category 4).....	71
5.4.4.2	Power to Release, Dual Axis Interlock Connected to a SIM (Category 4).....	72
5.4.4.3	Power to Release, Dual Axis Interlock Connected to a SIM (Category 4).....	73
5.4.4.4	Power to Release, Dual Axis Interlock Connected to a SIM (Category 4).....	74
<b>5.5</b>	<b>Optical Presence Sensing Devices .....</b>	<b>75</b>
5.5.1	General Considerations.....	75
5.5.1.1	Light Curtains .....	75
5.5.1.2	Single/Multiple Beam Devices (Point or Grid Devices).....	76
5.5.1.3	Scanners .....	76
5.5.2	Lowest Risk Reduction (Category 1).....	77
5.5.2.1	IEC 61496 Type 2 Presence Sensing Device with Control Relay (Category 1).....	77
5.5.3	Low / Intermediate Risk Reduction (Category 2).....	78
5.5.3.1	IEC 61496 Type 2 Presence Sensing Device with Force-guided Relay (Category 2).....	78
5.5.3.2	IEC 61496 Type 2 Presence Sensing Device with Force-guided Relay (Category 2).....	79
5.5.4	Intermediate / High Risk Reduction (Category 3).....	80
5.5.4.1	IEC 61496 Type 3 Presence Sensing Device with Safety Interface Module (Category 3).....	80
5.5.5	Highest Risk Reduction (Category 4).....	81
5.5.5.1	IEC 61496 Type 4 Presence Sensing Device with OSSD (Category 4).....	81
5.5.5.2	IEC 61496 Type 4 Presence Sensing Device with Safety Interface Module (Category 4).....	82
<b>5.6</b>	<b>Mats / Edges .....</b>	<b>83</b>
5.6.1	General considerations .....	83
5.6.2	Low / Intermediate Risk Reduction (Category 2) .....	83
5.6.2.1	Single Safety Mat Using a Safety Interface Module (Category 2).....	83
5.6.3	Intermediate / High Risk Reduction (Category 3).....	84
5.6.3.1	Multiple Safety Mats Using a Safety Interface Module (Category 3).....	84
<b>5.7</b>	<b>Two-Hand Control .....</b>	<b>85</b>
5.7.1	General Considerations.....	85
5.7.1.1	Minimum functional requirements for a Two-hand Control as required by NFPA 79 and IEC 60204-1 (Type III):	85
5.7.1.2	Physical Installation and Electrical Interface Considerations: .....	85
5.7.1.3	Two-Hand Control Safety Interface Modules.....	86
5.7.2	Lowest Risk Reduction Two Hand Control (Type IIIa Category 1) .....	86
5.7.2.1	Two Hand Control (Type IIIa Category 1).....	86
5.7.2.2	Low / Intermediate Risk Reduction Two-Hand Control (Type IIIa Category 1).....	87
5.7.3	Intermediate / High Risk Reduction Two-Hand Control (Type IIIb Category 3).....	88

5.7.3.1	Two Hand Control (Type IIIb Category 3).....	88
5.7.4	Intermediate / High Risk Reduction Two-Hand Control (Type IIIb Category 3).....	89
5.7.4.1	Two-Hand Control (Type IIIb Category 3).....	89
5.7.5	Highest Risk Reduction Two-Hand Control (Type IIIc Category 4).....	90
<b>5.8</b>	<b>Zero (Stand Still) Speed Detection.....</b>	<b>91</b>
5.8.1	General Considerations.....	91
5.8.2	Lowest Risk Reduction (Category 1).....	92
5.8.2.1	Single Proximity Sensing (Category 1).....	92
5.8.3	Intermediate / High Risk Reduction (Category 3).....	93
5.8.3.1	Dual Proximity Sensors to Timers and Force-guided Relay Monitoring (Category 3).....	93
5.8.3.2	Dual Proximity Sensors to Timers and Force-guided Relay Monitored by a SIM (Category 3).....	94
5.8.3.3	Dual Proximity Sensors to Dual Frequency Counters Monitored by a SIM (Category 3).....	95
5.8.3.4	Dual Proximity Sensors Plus Zero Speed or Stand Still SIM (Category 3 or 4).....	96
5.8.3.5	Encoder Speed Monitoring (Category 3).....	97
5.8.3.6	Motor Drive Back EMF Detection (Category 3 or 4).....	98
<b>5.9</b>	<b>Enabling Devices.....</b>	<b>99</b>
5.9.1	General Considerations.....	99
5.9.2	Intermediate / High Risk Reduction (Category 3).....	101
5.9.3	Intermediate / High Risk Reduction (Category 3).....	102
5.9.3.1	Enabling device with overspeed (Category 3).....	102
5.9.3.2	Enabling device with manual/auto switch (Category 3).....	103
5.9.3.3	Enabling device with manual mute enable (Category 3).....	104
5.9.4	Intermediate / High Risk Reduction (Category 4).....	105
<b>6</b>	<b>Power Control Devices Interface (MPCE).....</b>	<b>106</b>
<b>6.1</b>	<b>General Considerations.....</b>	<b>106</b>
<b>6.2</b>	<b>Relays and Contactors.....</b>	<b>107</b>
6.2.1	Lowest Risk Reduction (Category 1).....	107
6.2.2	Low / Intermediate Risk Reduction (Category 2).....	108
6.2.3	Intermediate / High Risk Reduction (Category 3).....	109
6.2.4	Highest Risk Reduction (Category 4).....	110
<b>6.3</b>	<b>Variable Frequency Drives (VFD).....</b>	<b>111</b>
6.3.1	Power Drive Systems - General Considerations.....	111
6.3.2	Lowest Risk Reduction (Category 1).....	114
6.3.2.1	Single Channel Interlock Stop Category 0 of an AC Motor using Standard Rated AC Drive.....	114
6.3.2.2	Single Channel Interlock Stop Category 1 of an AC Motor using Standard Rated AC Drive.....	115
6.3.3	Intermediate / High Risk Reduction (Category 3).....	116
6.3.3.1	Stop Category 0 of an AC Motor using Safety Rated AC Drive (Category 3).....	116
6.3.3.2	Stop Category 1 (Controlled) Stop of an AC Motor using Safety Rated AC Drive.....	117
6.3.4	Highest Risk Reduction (Category 4).....	118
6.3.4.1	Dual Channel Interlock Stop Category 0 (Coast to Stop) of an AC Motor using Standard Rated AC Drive with Checking (Category 4).....	118
<b>6.4</b>	<b>Pneumatic Systems.....</b>	<b>119</b>
6.4.1	General Considerations.....	119

6.4.1.1	Pneumatic Component Selection Process .....	120
6.4.1.2	Air Preparation (Contamination Control) .....	122
6.4.1.3	Non-Lubricated (Preferred) .....	122
6.4.1.4	Lubricated (Not Recommended) .....	122
6.4.1.5	Example Supply Circuit .....	123
<b>6.4.2</b>	<b>Exhaust (Blocking, Dump) Valve .....</b>	<b>124</b>
6.4.2.1	Basic Risk Reduction (Category B) .....	124
6.4.2.1.1	Spring Centered Three Position Open Center (Category B) .....	124
6.4.2.1.2	Lowest Risk Reduction (Category 1) .....	125
6.4.2.2	Low / Intermediate Risk Reduction (Category 2) .....	126
6.4.2.2.1	Single Monitored Directional Valve (Category 2) .....	126
6.4.2.2.2	Spring Centered Three Position Open Center w/ Actuator Monitoring (Category 2) .....	127
6.4.2.3	Intermediate / High Risk Reduction (Category 3) .....	128
6.4.2.3.1	Series Dump Safety Valve with Spring Centered Three Position Open Center (Category 3) .....	128
6.4.2.3.2	Series Monitoring Circuit (Category 3) .....	129
6.4.2.4	Highest Risk Reduction Monitoring Circuit (Category 4) .....	130
6.4.2.4.1	Dual Shift Time Monitored Valves (Category 4) .....	130
6.4.2.4.2	Safety Rated Valve – Manual Valve Reset (Category 4) .....	131
6.4.2.4.3	Safety Rated Valve – Automatic Valve Reset (Category 4) .....	132
<b>6.4.3</b>	<b>Directional (Motion) Valve Selection .....</b>	<b>133</b>
6.4.3.1	Category B and 1 .....	133
6.4.3.1.1	Single Solenoid – Two Position – Spring Offset (Category B and 1) .....	133
6.4.3.1.2	Double Solenoid – Two Position – Detented (Category B and 1) .....	134
6.4.3.1.3	3 Position – Spring Centered – Open Centered (Category B and 1) .....	135
6.4.3.1.4	3 Position – Spring Centered – Close or Blocked Center (Category B and 1) .....	136
6.4.3.2	Low / Intermediate Risk Reduction (Category 2) .....	137
6.4.3.2.1	2 Position Spring Offset – Monitored Spool Position (Category 2) .....	137
6.4.3.3	Intermediate / High Risk Reduction (Category 3 and 4) .....	138
6.4.3.3.1	Dual – 2 Position Spring Offset – Monitored Spool Position(s) (Category 3 and 4) .....	138
<b>6.4.4</b>	<b>Pilot Operated Check Valves .....</b>	<b>139</b>
6.4.4.1	Basic / Lowest Risk Reduction (Category B and 1) .....	139
6.4.4.1.1	Pilot Operated Check Valve (Category B and 1) .....	139
6.4.4.2	Low / Intermediate Risk Reduction (Category 2) .....	140
6.4.4.2.1	Pilot Operated Check Valve (Category 2) .....	140
6.4.4.3	Intermediate / High Risk Reduction (Category 3) .....	141
6.4.4.3.1	Pilot Operated Check (Category 3) .....	141
6.4.4.3.2	Pilot Operated Check with Spring Centered Three Position Open Center (Category 3) .....	142
6.4.4.4	Highest Risk Reduction (Category 4) .....	143
6.4.4.4.1	Pilot Operated Check (Category 4) .....	143
<b>6.4.5</b>	<b>Rod Locks and Brakes .....</b>	<b>144</b>
<b>6.4.6</b>	<b>Flow Controls .....</b>	<b>145</b>
6.4.6.1	Meter-IN Controls the Fluid Flow Going into the Cylinder .....	146
6.4.6.2	Meter-OUT Controls the Fluid Flow Coming Out of the Cylinder .....	147
6.4.6.3	Meter-IN Flow Control Example .....	148
6.4.6.4	Meter-OUT Flow Control Example .....	149
<b>6.4.7</b>	<b>Pneumatic Air Logic Control Circuits .....</b>	<b>150</b>
6.4.7.1	Emergency Stop .....	150
6.4.7.1.1	Lowest Risk Reduction (Category 1) .....	150
6.4.7.2	Two hand control .....	151
6.4.7.2.1	Lowest Risk Reduction (Category 1) .....	151
6.4.7.2.2	Highest Risk Reduction (Category 4) .....	152
6.4.7.3	Velocity Fuse .....	153
<b>6.5</b>	<b>Hydraulic Systems .....</b>	<b>154</b>
6.5.1	General considerations .....	154
6.5.1.1	Hydraulic Component Selection Process .....	155
6.5.1.2	Fluid Preparation (Contamination Control) .....	157

6.5.2	Dump (Blocking) Valve .....	157
6.5.2.1	Basic Risk Reduction (Category B) .....	157
6.5.2.1.1	Spring Centered Three Position Exhaust Center (Category B) .....	157
6.5.2.1.2	Spring Centered Three Position Exhaust Center w/ Actuator monitoring (Category 1) .....	158
6.5.2.2	Low / Intermediate Risk Reduction (Category 2) .....	159
6.5.2.2.1	Monitored Two Way Valve (Category 2) .....	159
6.5.2.2.2	Spring Centered Three Position Exhaust Center w/ Control Circuit Functional Monitoring (Category 2) .....	160
6.5.2.3	Intermediate / High Risk Reduction (Category 3) .....	161
6.5.2.3.1	Series Monitored Blocking Valve with Circuit Spring Centered Three Position Exhaust Center (Category 3) .....	161
6.5.2.4	Highest Risk Reduction (Category 4) .....	162
6.5.2.4.1	Series Monitoring Circuit (Category 4) .....	162
6.5.3	Directional (Motion) Valve Selection .....	163
6.5.3.1	Basic / Lowest Risk Reduction (Category B and 1) .....	163
6.5.3.1.1	2 Position - Spring Offset (Category B and 1) .....	163
6.5.3.1.2	2 Position – Detented (Category B and 1) .....	164
6.5.3.1.3	3 Position – Spring Centered – Open (Float) Centered (Category B and 1) .....	165
6.5.3.1.4	3 Position – Spring Centered – Closed or Blocked Center (Category B and 1) .....	166
6.5.3.2	Low / Intermediate Risk Reduction (Category 2) .....	167
6.5.3.2.1	2 Position Spring Offset – Monitored Spool Position (Category 2) .....	167
6.5.4	Pilot Operated Check Valves .....	168
6.5.4.1	Basic / Lowest Risk Reduction (Category B and 1) .....	168
6.5.4.1.1	Pilot Operated Check – Example 1 of 2 (Category B and 1) .....	168
6.5.4.2	Pilot Operated Check – Basic / Lowest Risk Reduction; Example 2 of 2 (Category B and 1) .....	169
6.5.4.3	Low / Intermediate Risk Reduction (Category 2) .....	170
6.5.4.3.1	Pilot Operated Check – Low / Intermediate Risk Reduction (Category 2) .....	170
6.5.4.4	Pilot Operated Check – Intermediate / High Risk Reduction (Category 3) .....	171
6.5.4.4.1	Intermediate / High Risk Reduction (Category 3) .....	171
6.5.4.4.2	Monitored Pilot Operated Check with Spring Centered Three Position Exhaust Center (Category 3) .....	172
6.5.4.5	Highest Risk Reduction (Category 4) .....	173
6.5.4.5.1	Pilot Operated Check (Category 4) .....	173
6.5.5	Counter Balance Valve .....	174
6.5.6	Rod Locks and Brakes .....	175
6.5.7	Flow Controls .....	176
6.5.8	Velocity Fuse .....	177
<b>ANNEX A – Analysis of circuit considerations .....</b>		<b>178</b>
<b>ANNEX L – Safety-Related Performance Levels .....</b>		<b>183</b>
<b>ANNEX M - External Device Monitoring by the Safety-Related Function .....</b>		<b>188</b>
<b>ANNEX S – Symbols .....</b>		<b>190</b>
<b>ANNEX V – Valves .....</b>		<b>195</b>

## Foreword

Recognizing the need for a guidance document on the subject matter, the ANSI B11 Accredited Standards Committee for Machine Safety formed a subcommittee consisting of professionals that are involved in manufacturing, safety, design, integration and controls to develop a technical report giving guidance in understanding and implementing safety control functions when applied to machines covered by the ANSI B11 series of machine safety standards.

The intent is to illustrate safety control circuit design concepts to help mitigate the risks identified by a risk assessment. The following example circuits, explanations, and minimum fault exclusions are for educational purposes and do not contain complete information on electrical, fluid power, and mechanical design requirements. Substitutions, additions, or changes to the circuits, components, safety modules, or safeguarding devices should be thoroughly researched and examined as to the extent of the impact on the integrity, reliability, and the level of performance of the safety functions. The designer should refer to relevant standards, regulations, and codes to address all installation and safety requirements.

The B11.TR6 Subcommittee began with current industrial circuit applications and provided examples of common solutions in use at the time of creating this document; these are not intended to limit innovation or the advancement of technology.

Industry users expressed the desire that example circuits be depicted in a NEMA format. To provide clarity and enhance understanding the committee created symbols for safety components that previously did not exist. These new symbols distinguish safety rated components from their non-safety rated counterparts such as emergency stops and forced guided relays. This document also identifies the relationship between ANSI B11.TR3 risk level (now included within ANSI B11.0) and that of the Categories of ISO 13489.

The Circuit Analysis Table for each circuit diagram provides important guidance information on the performance of safety-related functions, identification and analysis of failures, and safety-related performance levels for categories B through 4 as referenced in section 4.13.

Publication of this Registered Technical Report has been approved by the Accredited Standards Developer. This document is registered as a Technical Report series of publications according to the procedures for the Registration of Technical Reports with ANSI. This document is not an American National Standard and the material contained herein is not normative in nature. Comments on the content of this document should be sent to the Accredited Standards Developer.