



DPC: 13 / 30281357 DC

BSI Group Headquarters

389 Chiswick High Road London W4 4AL

Tel: +44 (0)20 8996 9000

Fax: +44 (0)20 8996 7400

www.bsigroup.com

Date: 03 June 2013

Origin: European

Latest date for receipt of comments: 30 September 2013

Project No. 2013/0088

Responsible committee: B/520/4 Properties and glazing methods

Interested committees:

Title: Draft BS EN 16613 Glass in building - Laminated glass and laminated safety glass - Determination of interlayer mechanical properties

Please notify the secretary if you are aware of any keywords that might assist in classifying or identifying the standard or if the content of this standard

- i) has any issues related to 3rd party IPR, patent or copyright
- ii) affects other national standard(s)
- iii) requires additional national guidance or information

**WARNING: THIS IS A DRAFT AND MUST NOT BE REGARDED OR USED AS A BRITISH STANDARD.
THIS DRAFT IS NOT CURRENT BEYOND 30 September 2013**

This draft is issued to allow comments from interested parties; all comments will be given consideration prior to publication. No acknowledgement will normally be given. **See overleaf for information on the submission of comments.**

No copying is allowed, in any form, without prior written permission from BSI except as permitted under the Copyright, Designs and Patent Act 1988 or for circulation within a nominating organization for briefing purposes. Electronic circulation is limited to dissemination by e-mail within such an organization by committee members.

Further copies of this draft may be purchased from BSI Shop <http://shop.bsigroup.com> or from BSI Customer Services, Tel: +44(0) 20 8996 9001 or email cservices@bsigroup.com. British, International and foreign standards are also available from BSI Customer Services.

Information on the co-operating organizations represented on the committees referenced above may be obtained from <http://standardsdevelopment.bsigroup.com>

Responsible Committee Secretary: **Mr David Morris (BSI)**Direct tel: **020 8996 7509**E-mail: david.morris@bsigroup.com

Introduction

This draft standard is based on European discussions in which the UK has taken an active part. Your comments on this draft are welcome and will assist in the preparation of the consequent British Standard. Comment is particularly welcome on national, legislative or similar deviations that may be necessary.

Even if this draft standard is not approved by the UK, if it receives the necessary support in Europe, the UK will be obliged to publish the official English Language text unchanged as a British Standard and to withdraw any conflicting standard.

UK Vote

Please indicate whether you consider the UK should submit a negative (with reasons) or positive vote on this draft.

Submission of Comments

- The guidance given below is intended to ensure that all comments receive efficient and appropriate attention by the responsible BSI committee. **Annotated drafts are not acceptable and will be rejected.**
- All comments must be submitted, preferably electronically, to the Responsible Committee Secretary at the address given on the front cover. Comments should be compatible with version 6.0 or version 97 of Microsoft Word for Windows, if possible; otherwise comments in ASCII text format are acceptable. **Any comments not submitted electronically should still adhere to these format requirements.**
- All comments submitted should be presented as given in the example below. Further information on submitting comments and how to obtain a blank electronic version of a comment form are available from the BSI website at: <http://drafts.bsigroup.com/>

Template for comments and secretariat observations

| | |
|------------------|------------------------|
| Date: xx/xx/20xx | Document: ISO/DIS xxxx |
|------------------|------------------------|

| 1 | 2 | (3) | 4 | 5 | (6) | (7) |
|----|---|-------------------------------|-----------------|--|--|--|
| MB | Clause No./ Subclause No./ Annex (e.g. 3.1) | Paragraph/ Figure/ Table/Note | Type of comment | Comment (justification for change) by the MB | Proposed change by the MB | Secretariat observations on each comment submitted |
| | 3.1 | Definition 1 | ed | Definition is ambiguous and needs clarifying. | Amend to read "...so that the mains connector to which no connection..." | |
| | 6.4 | Paragraph 2 | te | The use of the UV photometer as an alternative cannot be supported as serious problems have been encountered in its use in the UK. | Delete reference to UV photometer. | |

May 2013

ICS 81.040.20

English Version

Glass in building - Laminated glass and laminated safety glass - Determination of interlayer mechanical properties

Glas im Bauwesen - Verbundglas und
Verbundsicherheitsglas - Bestimmung der mechanischen
Eigenschaften von Zwischenschichten

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 129.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN-CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

| | |
|--|-----------|
| Foreword..... | 3 |
| Introduction | 4 |
| 1 Scope | 5 |
| 2 Normative references | 5 |
| 3 Terms and definitions | 5 |
| 4 Symbols and abbreviations | 6 |
| 5 Selection of testing procedure | 7 |
| 5.1 Isotropic interlayer materials..... | 7 |
| 5.2 Non-isotropic interlayer materials | 7 |
| 5.3 Interlayers which cannot be formed into small test pieces | 8 |
| 6 Test procedure | 8 |
| 6.1 General..... | 8 |
| 6.2 Test specimens | 8 |
| 6.3 Test method..... | 9 |
| 6.3.1 Glass transition temperature, T_g | 9 |
| 6.3.2 Determination of $E_L(\theta, f)$ | 9 |
| 6.4 Determination of $E_L(T_{ref}, f)$ | 10 |
| 7 Evaluation of ω | 10 |
| 7.1 Determining $E_L(\theta, f)$ | 10 |
| 7.2 Load durations and temperature ranges..... | 11 |
| 7.3 Determining the interlayer stiffness family..... | 11 |
| 8 Test report | 13 |
| Annex A (normative) Alternative method for interlayers which cannot be formed into small test pieces..... | 15 |
| A.1 Method | 15 |
| A.2 Sample | 15 |
| A.3 Test conditions | 16 |
| A.4 Interpretation of the results | 16 |
| A.5 Extrapolation to long duration curves..... | 16 |
| A.6 Interlayer shear coefficient ω and load case..... | 16 |
| Annex B (informative) Preparation of test specimens..... | 17 |
| B.1 Folio interlayers | 17 |
| B.1.1 Polyvinyl butyral (pvb), neva, and polyurethane (pu) | 17 |
| B.1.2 Ionoplast interlayers..... | 17 |
| B.2 Cast in place interlayers | 17 |
| B.3 Intumescent interlayers | 17 |
| Annex C (informative) Interlayer stiffness family..... | 18 |
| Annex D (informative) Determination of the interlayer shear transfer coefficient from the interlayer modulus..... | 19 |
| D.1 Summary of the evaluation..... | 19 |
| D.2 Evaluation of $\omega(\theta, f)$ | 19 |
| D.2.1 Finite element calculation taking into account the interlayer properties | 19 |
| D.2.2 Upper and lower bounds..... | 20 |
| D.2.3 Determination of equivalent thickness..... | 20 |
| D.2.4 Determination of ω from h_{mono} | 21 |
| Bibliography | 22 |

Foreword

This document (prEN 16613:2013) has been prepared by Technical Committee CEN/TC 129 "Glass in building", the secretariat of which is held by NBN.

This document is currently submitted to the CEN Enquiry.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

Currently in preview, click buy full version

Introduction

The purpose of this European Standard is to provide the viscoelastic properties of interlayer materials in order that calculations for the load resistance of laminated glass panes can be undertaken.

In addition, this European Standard includes a procedure for categorising the interlayer materials into a families, which can be associated with shear transfer coefficients which are used in a simplified calculation method.

NOTE CEN/TC 129/WG 8 "Mechanical strength" is preparing a draft which includes the simplified calculation method [1].

1 Scope

This European Standard specifies a test method for determining the mechanical viscoelastic properties of interlayer materials. The interlayers under examination are those used in the production of laminated glass and/or laminated safety glass. The interlayer properties are needed in order to determine the load resistance of laminated glass as part of a general calculation method for the load resistance of glass.

NOTE CEN/TC 129/WG 8 "Mechanical strength" is preparing a draft for the calculation method [1].

From the tensile modulus in particular conditions of temperature and load duration, an interlayer can be placed into a family that relates to a specific interlayer shear transfer coefficient, ω . This value can be used in a simplified calculation method.

An informative annex explains the background to the determination of families relating to a specific interlayer shear transfer coefficient.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1288-3, *Glass in building - Determination of the bending strength of glass - Part 3: Test with specimen supported at two points (four point bending)*

ISO 6721-1, *Plastics – Determination of mechanical dynamic properties – Part 1: General principles*

ISO 6721-4, *Plastics – Determination of mechanical dynamic properties – Part 4: Tensile vibration – Non-resonance method*

ISO 6721-11, *Plastics – Determination of mechanical dynamic properties – Part 11: Glass transition temperature*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

glass transition temperature

interval of temperature in which a material changes from a rubbery state to a solid state

3.2

interlayer shear transfer coefficient

coefficient between 0 and 1 describing the ability of an interlayer material to transfer shear forces between the glass pieces of a laminated glass plate when submitted to bending

3.3

stiffness family

group of interlayers having similar properties for the temperature range and load durations considered

3.4

vitreous polymer

polymer presenting a glass transition temperature in the range of building applications