



BSI Standards Publication

## 13 A plugs, socket-outlets, adaptors and connection units

Part 1: Specification for rewirable and non-rewirable 13 A fused plugs

**Publishing and copyright information**

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2016

Published by BSI Standards Limited 2016

ISBN 978 0 580 85809 3

ICS 29.120.30

The following BSI references relate to the work on this document:

Committee reference PEL/23

Draft for comment 15/30297232 DC

**Publication history**

First published as BS 1363, September 1967

Second edition, August 1984

First published as Part 1, February 1995

Second (present) edition, August 2016

**Amendments issued since publication**

Date	Text affected
------	---------------

---

## Contents

Foreword *iii*

1	Scope	1
2	Conditions of use	1
3	Terms and definitions	2
4	General	5
5	General conditions for type testing	5
6	Classification	7
7	Marking and labelling	7
8	Clearances, creepage distances and solid insulation	9
9	Accessibility of live parts	13
10	Provision for earthing	13
11	Terminals and terminations	15
12	Construction of plugs	17
13	(Not used)	26
14	Resistance to ageing and to humidity	26
15	Insulation resistance and electric strength	27
16	Temperature rise	28
17	Breaking capacity of switches incorporated in fused plugs	29
18	Normal operation of switches	29
19	Connection of flexible cables and cable anchorage	30
20	Mechanical strength	32
21	Screws, current-carrying parts and connections	33
22	Resistance to heat	34
23	Resistance to abnormal heat and fire	35
24	Resistance to excessive residual stresses and to rusting	36
25	Electrical and thermal stress on lamp type (screwless) terminals	37
26	Overload tests	37
27	Cyclic loading test	38

### Annexes

Annex A (normative)	The construction and calibration of a calibrated link	63
Annex B (normative)	Measurement of clearance and creepage distances	64
Annex C (normative)	Determination of the Comparative Tracking Index (CTI) and Proof Tracking Index (PTI)	68
Annex D (normative)	Relation between rated impulse withstand voltage, rated voltage and Overvoltage Category	69
Annex E (normative)	Pollution degree	69
Annex F (normative)	Impulse voltage test	70
Annex G (normative)	Requirements for incorporated electronic components	71
Annex H (informative)	Specific structure of BS EN 50525 and its derivation from British Standards and from HD 21 and HD 22 (BS EN 50525-1:2011, National Annex NA)	73
Annex I (informative)	Recommendations for products that incorporate BS 1363-1 plug pins	74
Annex J (informative)	Dimensions for plug profiles	74

Bibliography 76

### List of figures

Figure 1	– Test pin (see Clause 12)	39
Figure 2a	– Apparatus for mechanical strength test on resilient covers (see Clause 9)	40
Figure 2b	– Hardwood block for Figure 2a	41
Figure 4a	– Dimensions and disposition of pins (see Clause 12)	42
Figure 4b	– Concave shrinkage allowance for ISODs	44
Figure 5	– Gauge for plug pins (see Clause 12, Clause 20 and Clause 22)	45
Figure 6	– Apparatus for testing plug cover fixing screws (see Clause 12)	46
Figure 7	– Mounting plate (see Clause 12)	47

Figure 8 – Plug pin deflection test apparatus for resilient plugs (see Clause 12)	48
Figure 9 – Apparatus for abrasion test on insulating sleeves of plug pins (see Clause 12)	50
Figure 10 – Apparatus for pressure test at high temperature (see Clause 12)	51
Figure 11 – GO gauge for socket-outlet (see Clause 13)	52
Figure 17a – Test apparatus for temperature rise test (see Clause 16)	53
Figure 17b – Dummy front plate for temperature rise (see Clause 16)	54
Figure 18 – Apparatus for flexing test (see Clause 19)	55
Figure 19 – Solid link for test on fuse clips (see Clause 20)	56
Figure 20 – Tumbling barrel (see Clause 20)	56
Figure 23 – Apparatus for pressure test (see Clause 22)	57
Figure 28 – Calibrated link (see A.1)	59
Figure 29 – Calibration jig for calibrated link (see A.2)	60
Figure 32a – Apparatus for tests on plug pins: A plug pin under test (see Clause 12)	61
Figure 32b – Apparatus for tests on plug pins: Details of anvils (see Clause 12)	62
Figure 33 – Apparatus for torsion test on pins (see Clause 12)	62
Example 1	65
Example 2	65
Example 3	65
Example 4	65
Example 5	66
Example 6	66
Example 7	66
Example 8	66
Example 9	67
Example 10	67
Example 11	68
Figure J.1 – Normal plug profile	74
Figure J.2 – Compact plug profile	75

#### List of tables

Table 1 – Schedule of tests	6
Table 2 – Rated current and maximum fuse rating in normal use, and load for flexing and cable grommets related to size of flexible cable	9
Table 3 – Minimum clearances for basic insulation	11
Table 4 – Minimum creepage distances (mm) for basic insulation	12
Table 5 – Withstand voltages for insulation types	12
Table 6 – Torque values for screws and nuts	14
Table 7 – Actuator test force	26
Table 8 – Permitted temperature rises	29
Table 9 – Connection of flexible cables	32
Table 10 – Application of glow-wire test	35
Table B.1 – Minimum values of width $X$	64
Table D.1 – Rated impulse withstand voltage for plugs energized directly from the low-voltage mains	69
Table F.1 – Test voltages for verifying clearances at sea level	70
Table H.1 – Specific structure of BS EN 50525 and its derivation from British Standards and from HD 21 and HD 22 (BS EN 50525-1:2011, National Annex NA)	73
Table I.1 – List of clauses	74

#### Summary of pages

This document comprises a front cover, an inside front cover, pages i to iv, pages 1 to 78, an inside back cover and a back cover.

## Foreword

### Publishing information

This part of BS 1363 is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 August 2016. It was prepared by Technical Committee PEL/23, *Electrical accessories*. A list of organizations represented on this committee can be obtained on request to its secretary.

### Supersession

This part of BS 1363 supersedes BS 1363-1:1995+A4:2012, which remains current and will be withdrawn on 31 August 2019.

### Information about this document

BS 1363 comprises five parts covering the following:

- *Part 1: Specification for rewirable and non-rewirable 13 A fused plugs;*
- *Part 2: Specification for 13 A switched and unswitched socket-outlets;*
- *Part 3: Specification for adaptors;*
- *Part 4: Specification for 13 A fused connection units: switched and unswitched;*
- *Part 5: Specification for fused conversion plugs.*

*NOTE* In order to prevent confusion with BS 1363:1984, the figure and clause numbers have been retained.

The structure of BS EN 50525 and its derivation from British Standards and HD 21 and HD 22 is set out in BS EN 50525-1:2011, National Annex NA. This is reproduced in Annex H for the convenience of users of this part of BS 1363.

This new edition of BS 1363-1 incorporates technical changes only. It does not represent a full review or revision of the standard, which will be undertaken in due course.

This new edition of BS 1363-1 incorporates Annex G (normative) which provides requirements for incorporated electronic components.

This new edition of BS 1363-1 incorporates Annex J (informative) which provides dimensions for plug profiles to improve compatibility with BS 1363-2:2016 socket-outlets incorporated in floor boxes and IP rated enclosures.

It is intended that Annex J will become normative in the future.

### Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its requirements are expressed in sentences in which the principal auxiliary verb is 'shall'.

*Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.*

Requirements in this standard are drafted in accordance with *Rules for the structure and drafting of UK standards*, subclause J.1.1, which states, 'Requirements should be expressed using wording such as: "When tested as described in Annex A, the product shall ...". This means that only those products that are capable of passing the specified test will be deemed to conform to this standard.

### **Contractual and legal considerations**

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

**Conformity with a British Standard cannot confer immunity from legal obligations.**

Particular attention is drawn to the following specific regulations:

- The Plugs and Sockets etc. (Safety) Regulations 1994. SI No. 1768.

Currently in preview, click buy full version

## 1 Scope

This part of BS 1363 specifies requirements for 13 A fused plugs having insulating sleeves on line and neutral pins, for household, commercial and light industrial purposes, with particular reference to safety in normal use. The plugs are suitable for the connection of portable appliances, sound-vision equipment, luminaires, etc. in a.c. circuits only, operating at voltages not exceeding 250 V r.m.s. at 50 Hz. Additional requirements are included for plugs suitable for electric vehicle charging.

Requirements are specified for plugs incorporating a fuse link conforming to BS 1362:1973. The plugs may be rewirable or non-rewirable complete with flexible cable. Two categories of plugs are specified covering normal and rewirable use. Rewirable plugs are intended for use with flexible cables conforming to the relevant parts of BS EN 50525 (see Annex H), having conductor cross-sectional areas from 0.5 mm<sup>2</sup> to 1.5 mm<sup>2</sup> inclusive.

*NOTE 1* See 19.1.

Non-rewirable plugs are intended for use with flexible cables having conductor cross-sectional areas not exceeding 1.5 mm<sup>2</sup>.

*NOTE 2* See 19.4.

This standard also applies to non-rewirable 13 A plugs which have the earth pin replaced with a similarly dimensioned protrusion made of insulating material designated as an insulated shutter opening device (ISOD) designed to operate the shutter mechanism of socket-outlet conforming to BS 1363-2:2016.

A plug is mechanical by nature of construction. The product is therefore immune from electromagnetic interference.

Plugs incorporating switches and indicator lamps are included within the scope of this part of BS 1363.

Plugs incorporating electronic components detailed in Annex G are included within the scope of this part of BS 1363.

Recommendations for plug-in equipment incorporating BS 1363-1 plug pins are given in Annex I.

*NOTE 3* The titles of the publications referred to in this part of BS 1363 are listed in the bibliography.

## 2 Conditions of use

Plugs shall be suitable for use under the following conditions:

- a) an ambient temperature in the range -5 °C to +40 °C, the average value over 24 h not exceeding 25 °C.

*NOTE* Under normal conditions of use, the available cooling air is subject to natural atmospheric variations of temperature and hence the peak temperature occurs only occasionally during the hot season, and on those days when it does not persist for lengthy periods.

- b) a situation not subject to exposure to direct radiation from the sun or other source of heat likely to raise temperatures above the limits specified in a);
- c) an altitude not exceeding 2 000 m above sea level;
- d) an atmosphere not subject to abnormal pollution by smoke, chemical fumes, rain, spray, prolonged periods of high humidity or other abnormal conditions. This is equivalent to pollution degree 2, see Annex E, and Overvoltage Category III, see Annex D.