

BS 5410-1:2014



BSI Standards Publication

Code of practice for oil firing

Part 1: Installations up to 45 kW output capacity for space heating and hot water supply purposes

bsi.

...making excellence a habit.™

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2014

Published by BSI Standards Limited 2014

ISBN 978 0 580 83414 1

ICS 27.060.10

The following BSI references relate to the work on this document:

Committee reference RHE/13

Draft for comment 14/30285453 DC

Publication history

First published as CP 3002 1 August 1961

Part revision published as BS 5410 1 March 1977

Second edition, January 1998

Third (present) edition, December 2014

Amendments issued since publication

Date	Text affected
------	---------------

Currently in preview, click buy full version

Contents

Foreword *iii*

1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Liquid fuels	3
5	Installation of oil fired appliances	3
6	Oil storage tanks and equipment	13
7	Accommodation for oil storage tanks	19
8	Installation of tanks	23
9	Oil system from storage tank to burner	26
10	Flues and chimneys	32
11	Design and installation of flues and chimneys	38
12	Room sealed balanced flue appliances	42
13	Special categories of flue system	42
14	Electrical installation and system controls	44
15	Commissioning	45
16	Maintenance	45
17	Conversion of appliances to oil firing	47
18	Biofuels	47

Annexes

Annex A (informative) Types of appliances and burners covered by this standard 49

Annex B (informative) Example of a chimney designation in accordance with BS EN 1443:2003 54

Bibliography 56

List of figures

Figure 1 – Combustion and ventilation air supply for room sealed balanced flue oil fired appliances 5

Figure 2 – Combustion and ventilation air supply for open flue oil fired appliances 6

Figure 3 – Oil supply system with bottom of oil storage tank above burner – Single pipe supply 17

Figure 4 – Oil supply system with a single pipe connected through top of tank to an oil lifter 18

Figure 5 – Oil supply system with a single pipe connected through top of tank to a de-aeration device 19

Figure 6 – Oil supply system for a vaporising cooker installation with two remote feeding fire valves 27

Figure 7 – Positions of de-aerators in relation to a flue terminal 29

Figure 8 – Flue terminal positions for oil fired appliances 36

Figure A.1 – Schematic diagram of a natural draught perforated sleeve burner 51

Figure A.2 – Schematic diagram of a natural draught pot burner 52

Figure A.3 – Schematic diagram of a mechanical draught pot burner with a central air diffuser 53

Figure A.4 – Schematic diagram of a pressure jet burner 54

List of tables

Table 1 – Types of oil storage tank and locations for which they are suitable 14

Table 2 – Recommended oil storage tank capacities 14

Table 3 – Protection of an oil storage tank located externally to a building 20
Table 4 – Distance between supports for steel oil storage tanks 24
Table 5 – Minimum performance designations for chimney and flue pipe components for use with oil fired appliances with a flue gas temperature of less than 250 °C 33

Currently in preview, click buy full version

Summary of pages

This document comprises a front cover, an inside front cover, pages i to iv, pages 1 to 58, an inside back cover and a back cover.

Foreword

Publishing information

This part of BS 5410 is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 December 2014. It was prepared by Technical Committee RHE/13, *Oil burning equipment*. A list of organizations represented on this committee can be obtained on request to its secretary.

Supersession

This part of BS 5410 supersedes BS 5410-1:1997 (incorporating Amendment No 1:2001, Amendment No 2:2001 and Amendment No 3:2006) which is withdrawn.

Relationship with other publications

BS 5410 is published in three parts:

- *Part 1: Installations up to 45 kW output capacity for space heating and hot water supply purposes;*
- *Part 2: Installations over 45 kW output capacity for space heating, hot water and steam supply services;*
- *Part 3: Installations for furnaces, kilns, ovens and other industrial purposes.*

Information about this document

This is a full revision of the standard and introduces the following principle changes:

- condensing boilers are now included;
- boilers burning biofuels are now covered.

Copyright is claimed on Figure 6 and Figure 7. Copyright holders are OFTEC, Foxwood House, Docks Lane, Kesgrave, Ipswich, IP5 2QQ.

Use of this document

As a code of practice, this part of BS 5410 takes the form of guidance and recommendations. It should not be quoted as if it were a specification and particular care should be taken to ensure that claims of compliance are not misleading.

Any user claiming compliance with this part of BS 5410 is expected to be able to justify any course of action that deviates from its recommendations.

It has been assumed in the preparation of this part of BS 5410 that the execution of its provisions will be entrusted to appropriately qualified and experienced people, for whose use it has been produced.

Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its recommendations are expressed in sentences in which the principal auxiliary verb is "should".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

In particular, attention is drawn to the following specific regulations.

- The Boiler (Efficiency) Regulations 1993 as amended by the Boiler (Efficiency) (Amendment) Regulations 1994 and the Boiler (Efficiency) (Amendment) Regulations 2006 [1];
- The Building Regulations [2], [3], [4];
- The Environmental Protection Act 1990 [5];
- The Control of Pollution (Special Waste) (Amendment) Regulations 1988 [6];
- The Control of Pollution (Oil Storage) (England) Regulations 2001 [7];
- The Control of Pollution (Oil Storage) (Amendment) Regulations (Northern Ireland) 2011 [8];
- The Water Environment (Oil Storage) (Scotland) Regulation 2005 [9];
- The Hazardous Waste (England and Wales) Regulations 2005 (as amended) [10];
- The Hazardous Waste Regulations (Northern Ireland) 2005 [11];
- The Special Waste (Amendment) (England and Wales) Regulations 2001 [12];
- The Special Waste Amendment (Scotland) Amendment Regulations 2004 [13];
- The Building (Approved Inspectors etc.) Regulations 2010 [14];
- The Building (Forms) (Scotland) Regulations 2005 (as amended) [15].

1 Scope

This part of BS 5410 gives recommendations and guidance on the design, installation, commissioning and maintenance of oil burning installations up to 45 kW output capacity for space heating and hot water supply purposes. It also gives recommendations and guidance on the selection and installation of oil tanks of capacity up to 3 500 L, when installed at buildings used primarily as dwellings. The standard is also applicable to oil fired cookers where these are connected to flues. This part of BS 5410 is not applicable to oil fired systems for marine and transportable installations, or for flueless heaters.

This part of BS 5410 is applicable to installations burning liquid fuel conforming to BS 2869:2010+A1, including biofuels conforming to BS EN 14214, and blends thereof.

This standard is intended for use by designers, specifiers, installers, and service and commissioning engineers.

NOTE 1 The types of appliances and burners covered by this part of BS 5410 are described in Annex A.

NOTE 2 Oil tank installations at buildings used primarily as dwellings, with an oil storage capacity greater than 3 500 L are covered by BS 5410-2:2013.

NOTE 3 Oil tank installations at buildings other than dwellings, with oil storage capacity up to 3 500 L, are covered by BS 5410-2:2013, 1.7.

2 Normative references

Standards publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

BS 41:1973, *Specification for cast iron spigot and socket flue or smoke pipes and fittings*

BS 799-5, *Oil burning equipment – Part 5: Carbon steel oil storage tanks – Specification*

BS 2869:2010+A1:2011, *Fuel oils for agricultural, domestic and industrial engines and boilers – Specification*

BS 5410-2:2013, *Code of practice for oil firing – Part 2: Installations over 45 kW output capacity for space heating, hot water and steam supply services*

BS 6999:1989, *Specification for vitreous-enamelled low-carbon-steel fluepipes, other components and accessories for solid-fuel-burning appliances with a maximum rated output of 45 kW*

BS 7671, *Requirements for electrical installations – IEE Wiring Regulations – Seventeenth edition*

BS EN 1057:2006+A1;2010, *Copper and copper alloys – Seamless, round copper tubes for water and gas in sanitary and heating applications*

BS EN 14125:2013, *Thermoplastic and flexible metal pipework for underground installation at petrol filling stations*

BS EN 1254-2:1998, *Copper and copper alloys – Plumbing fittings – Part 2: Fittings with compression ends for use with copper tubes*

BS EN 1856-1:2003, *Chimneys – Requirements for metal chimneys – Part 1: System chimney products*