

BS 594987:2015



BSI Standards Publication

Asphalt for roads and other paved areas – Specification for transport, laying, compaction and product-type testing protocols

bsi.

...making excellence a habit.™

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2015

Published by BSI Standards Limited 2015

ISBN 978 0 580 83073 0

ICS 93.080.20

The following BSI references relate to the work on this document:

Committee reference B/510

Draft for comment 14/30283618 DC

Publication history

First published, June 2007

Second edition, December 2010

Third (present) edition, March 2015

Amendments issued since publication

Date	Text affected
------	---------------

Currently in preview, click buy full version

Contents

Foreword *iii*

1	Scope	1
2	Normative references	1
3	Terms and definitions	3
4	Transport and delivery	3
5	Preparatory works at the laying site	4
6	Laying	10
7	Chipping of hot rolled asphalt (HRA)	14
8	Texture depth	15
9	Compaction	16
10	Opening to traffic	23

Annexes

Annex A (informative)	Recommended delivery and rolling temperatures for recipe AC, HRA and SMA to BS EN 13108	24
Annex B (informative)	Approximate rates of spread of asphalt	25
Annex C (informative)	Protocol for determining void content of dense base and binder AC mixtures conforming to BS EN 13108-1 from trial strips for the purposes of product-type testing to BS EN 13108-20	25
Annex D (informative)	Protocol for determining resistance to permanent deformation of binder course and base asphalt mixtures conforming to BS EN 13108-1 (asphalt concrete) from trial strips for the purposes of type testing to BS EN 13108-20	28
Annex E (informative)	Protocol for determining void content and stiffness of EME2 base and binder AC mixtures conforming to BS EN 13108-1 from trial strips for the purposes of product-type testing to BS EN 13108-20	29
Annex F (informative)	Protocol for determining void content, binder volume and resistance to permanent deformation of performance-related surface course HRA mixtures conforming to BS EN 13108-4 from trial strips for the purposes of product-type testing to BS EN 13108-20	32
Annex G (informative)	Protocol for determining void content and resistance to permanent deformation of SMA binder course and regulating courses to BS EN 13108-5 from trial strips for the purposes of product-type testing to BS EN 13108-20	32
Annex H (informative)	Protocol for determining the design binder content of designed HRA surface course mixtures to BS EN 13108-4	37
Annex I (informative)	Protocol for calibrating and operating indirect density gauges	42
Annex J (informative)	Tack coats	42
Annex K (informative)	Protocol for determination of the maximum binder content of porous asphalt and other bituminous mixtures without excessive binder drainage	43
Annex L (informative)	Guidance for the mix design of BBA for airfields to BS EN 13108-1	46

Bibliography 48

List of figures

Figure C.1	– Spacing of cores	26
Figure E.1	– Spacing of cores	30
Figure F.1	– Spacing of cores	33
Figure G.1	– Spacing of cores	36
Figure H.1	– Example of mixture design	41
Figure K.1	– Typical diagram of mortar or binder drained	45

List of tables

Table 1A – Nominal target and minimum compacted layer thicknesses for asphalt concrete (AC) mixtures conforming to BS EN 13108-1 (see PD 6691:2015, Annex B)	6
Table 1B – Nominal target and minimum compacted layer thicknesses for HRA mixtures conforming to BS EN 13108-4 (see PD 6691:2015, Annex C)	6
Table 1C – Nominal target and minimum compacted layer thicknesses for SMA surface course mixtures conforming to BS EN 13108-5 (see PD 6691:2015, Annex D)	7
Table 1D – Nominal target and minimum compacted layer thicknesses for other SMA mixtures conforming to BS EN 13108-5 (see PD 6691:2015, Annex D)	7
Table 2 – An example of bond coat minimum target rate of spread in litres per square metre of emulsion	8
Table 3 – Accuracy of finish	13
Table 4 – Minimum rolling temperature for HRA mixtures	15
Table 5 – Minimum rolling temperatures for designed AC dense, heavy duty and high-modulus binder course and base (including EME2)	18
Table A.1 – Minimum delivery and rolling temperatures for recipe AC, HRA and SMA mixtures	24
Table B.1 – Approximate rate of spread	25
Table H.1 – Tests on material	37
Table H.2 – Aggregate proportions for mix design	38
Table H.3 – Binder proportions required for mix design procedure	39
Table H.4 – Mass of aggregate (coarse, fine and filler) and suggested binder contents for trial mixes	39
Table H.5 – Factors for the calculation of design binder content	40
Table K.1 – Test temperatures for porous asphalt with unmodified bitumen	44

Summary of pages

This document comprises a front cover, an inside front cover, pages i to iv, pages 1 to 48, an inside back cover and a back cover.

Foreword

Publishing information

This British Standard is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 March 2015. It was prepared by Subcommittee B/510/1, *Asphalt products* and under the authority of Technical Committee B/510, *Road materials*. A list of organizations represented on this committee can be obtained on request to its secretary.

Supersession

This British Standard supersedes BS 594987:2010, which is withdrawn.

Relationship with other publications

This British Standard is published concurrently with PD 6691:2015 as the two documents have been revised and cross reference each other.

Information about this document

This edition takes into account the change from the Construction Products Directive to the Construction Products Regulation [1] and that CE marking in the UK is now mandatory.

It also clarifies errors and anomalies in the previous version and removes references to previous British standards which have been superseded by the European standards.

This British Standard specifies requirements for transporting asphalt mixtures, for preparatory site work and for laying and compacting asphalt mixtures, including the covering of concrete and sett paving. Annexes contain protocols to be used for initial product-type testing of asphalt materials in accordance with BS EN 13108-20.

It has been assumed in the preparation of this British Standard that the execution of its provisions will be entrusted to appropriately qualified and experienced people for whose use it has been produced.

Annex A gives recommendations for delivery and rolling temperatures. Annex B provides indicative rates of spread for average mixture types. Annex C, Annex D, Annex E, Annex F and Annex G give recommendations on protocols for the initial product-type testing of asphalt materials in accordance with BS EN 13108-20; in particular, guidance is given on sampling by coring, assessing for target composition, voids, compaction and deformation resistance. Annex H provides recommendations for a mixture design that determines the design binder content of hot rolled asphalt surface course mixtures. Annex I provides advice on the calibration procedure for indirect density gauges. Annex J provides advice on the use of tack coats. Annex K gives a method for determining the maximum binder content that porous asphalt and other asphalt can carry without excessive binder drainage during transportation and subsequent laying. Annex L provides guidance on the design of BBA mixtures for airfield pavements.

Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its requirements are expressed in sentences in which the principal auxiliary verb is "shall".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

Requirements in this standard are drafted in accordance with *Rules for the structure and drafting of UK standards*, subclause J.1.1, which states, "Requirements should be expressed using wording such as: 'When tested as described in Annex A, the product shall ...'". This means that only those products that are capable of passing the specified test shall conform to this standard.

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

Currently in preview, click buy full version

1 Scope

This British Standard specifies requirements for the transport, laying and compaction of asphalt mixtures conforming to BS EN 13108-1, BS EN 13108-4 and BS EN 13108-5, and described in PD 6691, from the time that they leave the mixing plant until they are placed on the road ready to receive a superimposed layer or traffic. It also includes requirements for preliminary work at the laying site needed to ensure that the substrate is fit to receive the asphalt and for the application of bond coats.

Although this standard does not contain explicit requirements for asphalt materials covered in other parts of BS EN 13108 or other proprietary asphalt mixtures, the general requirements of this standard can be applied to those mixtures, in addition to special requirements for particular mixtures specified in individual quality plans and/or method statements.

NOTE 1 The term "asphalt" used in this standard is the generic term used to describe the wide range of mixtures of aggregate and bituminous binder individually known as asphalt concrete (AC), hot rolled asphalt (HRA), stone mastic asphalt (SMA), porous asphalt (PA) or mastic asphalt and other proprietary materials which are available for use in constructing and maintaining roads and other paved areas that are on the market in the UK.

NOTE 2 Methods for ensuring that the correct surface drainage characteristics are imparted to pavements with PA surface course are outside the scope of this British Standard.

NOTE 3 BS EN 13108-20 specifies tests for determining the conformity of a mix to any of the other parts of BS EN 13108. This is similar to a mix design validation or job mix trial. BS EN 13108-20 offers some choice in the way in which specimens are to be prepared for the purposes of product-type testing. Requirements for sample preparation for the demonstration of product-type test properties are given in PD 6691:2015, Clause 13 and are linked to the relevant protocols/annexes in this British Standard, as relevant.

In the case of HRA, a mixture design protocol is provided as informative text in Annex H, and requirements are specified for providing a rough-textured surface on the surface course to provide skid-resistance.

This standard does not specify requirements for asphalt incorporating bitumen emulsion binder.

This standard does not cover additional or specific requirements relating to the laying and compaction of reduced temperature asphalts.

NOTE 4 BS EN 13108 is being reviewed and it is anticipated that any revisions might cover low-temperature and cold mixtures.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

BS 598-1:2011, *Sampling and examination of bituminous mixtures for roads and other paved areas – Part 1: Methods for the measurement of the rate of spread of coated chippings and the temperature of bituminous mixtures using non-contact temperature-measuring devices and for the assessment of the compaction performance of a roller*

BS 1707, *Specification for hot binder distributors for road surface dressing*

BS 2000-223, *Methods of test for petroleum and its products – Part 223: Determination of ash of petroleum products containing mineral matter*