

Specification for

**Heat-sealable pouches
and tube material
converted from
transparent plastics
film and paper for
steam sterilization for
medical use**

Licensed copy: Techstreet Content, ISO Exchange - Michigan, Version correct as of 11/05/2023.

Currently in preview, clickbuy full version

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Packaging and Freight Containers Standards Policy Committee (PKM/-) to Technical Committee PKM/566 upon which the following bodies were represented:

British Aluminium Foil Rollers' Association
 British Paper and Board Industry Federation
 Department of Health and Social Security
 Institute of Sterile Services Management
 Medical Sterile Products Association
 Ministry of Defence
 Packaging and Industrial Films Association
 Pira (Research Association for the Paper and Board, Printing and Packaging Industries)
 Pharmaceutical Society of Great Britain
 Retail Bag Manufacturers' Association
 Sterilisation Packaging Materials Association
 United Kingdom Sugar Industry Association

This British Standard, having been prepared under the direction of the Packaging and Freight Containers Standards Policy Committee, was published under the authority of the Board of BSI and comes into effect on 28 February 1990.

© BSI 02-1990

First published June 1987
 First revision February 1990

The following BSI references relate to the work on this standard:
 Committee reference PKM/566
 Draft for comment 88/45732 DC

ISBN 0 580 17672 X

Amendments issued since publication

Amd. No.	Date of issue	Comments

Contents

	Page
Committees responsible	Inside front cover
Foreword	ii
1 Scope	1
2 Materials	1
3 Construction and design	1
4 Dimensions and tolerances	1
5 Performance	1
6 Marking	2
7 Packaging	2
Appendix A Method for the determination of the strength of the heat-seal joint	4
Appendix B Method for the determination of the wet strength of the heat-seal joint	4
Appendix C Method for the determination of resistance to high vacuum autoclaving	4
Appendix D Method for the determination of freedom from pinholes	5
Appendix E Method for the determination of fibre lay	5
Figure 1 — End/side view and cross-section of typical gusseted pouch/tube material showing width dimensions to be quoted	3
Publications referred to	Inside back cover