

BS 8605-1:2014



BSI Standards Publication

External timber cladding

Part 1: Method of specifying

Currently in preview, click buy full version

bsi.

...making excellence a habit.™

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2014

Published by BSI Standards Limited 2014

ISBN 978 0 580 81760 1

ICS 79.080

The following BSI references relate to the work on this document:

Committee reference B/543

Draft for comment 14/30277336 DC

Publication history

First published December 2014

Amendments issued since publication

Date	Text affected
------	---------------

Currently in preview, click buy full version

Contents

Foreword *iii*

Introduction 1

1	Scope	1
2	Normative references	2
3	Terms and definitions	3
4	General	12
5	Moisture content	13
6	Durability against biological attack	14
7	Species	17
8	Grade	18
9	Geometrical characteristics	19
10	Warp	21
11	Resistance to fixing	22
12	Dimensional stability	23
13	Reaction to fire	24
14	Resistance to deformation	24
15	Bonding quality	25
16	Coating systems	25
17	Wood density	27
18	Hygrothermal performance	27
19	Release of dangerous substances	27
20	Moisture resistance	27
21	Airborne sound insulation	27

Annexes

Annex A (informative)	CE marking of external timber cladding	28
Annex B (normative)	Sampling of boards	28
Annex C (informative)	Characteristics of timber species	29
Annex D (informative)	Timber durability selection	40
Annex E (normative)	Timber grading for boards	41
Annex F (informative)	Geometrical characteristics of boards	42
Annex G (informative)	Reaction to fire	53

Bibliography 55

List of figures

Figure 1	Typical build-up of a timber-clad rainscreen wall (plan section)	8
Figure F.1	Recommended mounting for timber cladding boards sawn through end-through	44
Figure F.2	Generic profile for tongue and groove boards	44
Figure F.3	Generic profile for rectangular boards	46
Figure F.4	Generic profile for shiplap boards	47
Figure F.5	Generic profile for labyrinth jointed boards	49
Figure F.6	Generic profile for parallelogram boards	50
Figure F.7	Generic profile for feather edge boards	51

List of tables

Table 1	Performance requirements for external timber cladding and support battens	12
Table 2	Cross-sectional tolerances for boards	20
Table 3	Maximum permitted warp in cladding boards	22
Table A.1	Characteristics to be declared by a supplier as part of CE marking	28

Table B.1 – Sample size and maximum number of non-conforming pieces	29
Table C.1 – Relevant characteristics of selected softwood species	31
Table C.2 – Relevant characteristics of selected hardwood species	33
Table C.3 – Natural durability classes against fungi	38
Table C.4 – Movement classes of timber	38
Table C.5 – Shrinkage values for UK timbers	39
Table D.1 – Selection of a level of natural or conferred durability	40
Table E.1 – Limits of timber features on visible face	42
Table F.1 – Compatibility of board profiles with timber characteristics and other criteria	43
Table F.2 – Generic characteristics and dimensions for tongue and groove boards	45
Table F.3 – Generic characteristics and dimensions for rectangular boards	47
Table F.4 – Generic characteristics and dimensions for rebated boards	48
Table F.5 – Generic characteristics and dimensions for labyrinth jointed boards	50
Table F.6 – Generic characteristics and dimensions for parallelogram boards	51
Table F.7 – Generic characteristics and dimensions for feather edge boards	52
Table F.8 – Minimum movement gap	52
Table F.9 – Minimum tongue width for tongue and groove profiles	52
Table F.10 – Minimum tongue thickness for tongue and groove profiles	53
Table G.1 – Indicative transposition between European and UK reaction to fire classes	54

Summary of pages

This document comprises a front cover, an inside front cover, pages i to iv, pages 1 to 58, an inside back cover and a back cover.

Foreword

Publishing information

This part of BS 8605 is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 December 2014. It was prepared by Panel B/543/-/2, *External timber cladding*, under the authority of Technical Committee B/543, *Round and sawn timber*. A list of organizations represented on this committee can be obtained on request to its secretary.

Relationship with other publications

BS 8605 is published in two parts:

- Part 1: *Method of specifying*; and
- Part 2: *Code of practice for design and installation*.

Some types of external timber cladding are covered by harmonized European Standards BS EN 14915 or BS EN 13986. This British Standard offers suppliers and designers additional information relevant to the UK's climate and construction practices.

Use of this document

It has been assumed in the preparation of this part of BS 8605 that the execution of its provisions will be entrusted to appropriately qualified and experienced people, for whose use it has been produced.

Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its requirements are expressed in sentences in which the principal auxiliary verb is "shall".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

Currently in preview, click buy full version

Introduction

External timber cladding assemblies can comprise several types of timber or wood-based components and can be used in a variety of ways. This complexity can cause difficulties when specifying because:

- suppliers need to know what performance characteristics are important and which of these should be declared in product documentation;
- designers need to know what performance characteristics need to be taken into account and which should form part of a cladding specification.

Several factors need to be considered when determining which performance characteristics should be specified. These vary depending upon the type of timber cladding: boards, for example, involve different considerations from shingles. There is, however, no single source of information that suppliers and designers can use when preparing product documentation or specifications.

- External timber cladding made of boards or wood-based panels is within the scope of harmonized standards BS EN 14915 and BS EN 13986, respectively. This means that where a characteristic is covered by one of these standards, manufacturers need to document their products in accordance with that standard. Some provisions only apply in specific circumstances. There is no harmonized standard for shingles and shakes.
- Neither harmonized standard covers all of the performance requirements that apply to external timber cladding. Some additional requirements are given in product standards BS EN 14919, BS EN 14951 and BS EN 15146, although not all criteria are covered.

Accordingly, this standard complements the harmonized standards and product standards for external timber cladding by:

- listing the main performance requirements that might be applicable to external timber cladding in the UK;
- specifying requirements for areas that are outside the scope of harmonized standards; and
- giving guidance on requirements that are covered by BS EN 14915 or BS EN 13986.

As a method of specifying, this part of BS 8605 gives verifiable performance characteristics, which can be controlled by product manufacturers and distributors. Issues, such as cavity ventilation, that become applicable during design and installation are addressed in BS 8605-2.

1 Scope

This part of BS 8605 describes methods of specifying the characteristics of external timber cladding products from which selection has to be made and for which values might have to be agreed between the purchaser and manufacturer.

This part of BS 8605 complements harmonized standards BS EN 14915 and BS EN 13986. It lists all performance requirements that might apply to external timber cladding in the UK and provides a method of specifying those requirements that are outside the scope of those standards, but which are relevant to the UK's climate and construction practices.

This part of BS 8605 specifies characteristics of components at the time they are transferred to the purchaser. It is intended for use by specifiers of external timber cladding components.