



BSI Standards Publication

Vehicle security barriers – Low speed impact testing

Part 1: Trolley impact test method
for bollards

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2017.
Published by BSI Standards Limited 2017

ISBN 978 0 580 84378 5

ICS 93.080.30

Publication history

First published July 2017

Amendments issued since publication

Date	Text affected
------	---------------

Currently in preview, click buy full version

Contents

Foreword	<i>iii</i>
Introduction	1
1	Scope 1
2	Normative references 2
3	Terms and definitions 2
4	Principle 6
5	Prior to testing 6
6	Apparatus 8
7	Apparatus set-up and test preparation 9
8	Test procedure 14
9	Performance rating 16
10	Further impact tests 17
11	Test report 17
Annex A (normative)	Impact trolley 20
Annex B (normative)	Impact trolley calibration 22
Annex C (normative)	Soil properties and standard backfill 26
Bibliography	28

List of figures

Figure 1	– Pre-impact condition 4
Figure 2	– Post-impact condition 5
Figure 3	– Trolley impact 6
Figure 4	– High speed video camera layout 6
Figure A.1	– Impact trolley schematic 20
Figure B.1	– Impact trolley longitudinal force/displacement corridor (visual example using data from Table B.1) 22
Figure B.2	– Example of energy absorber constituent parts 23

List of tables

Table 1	– Concrete sample testing 14
Table 2	– Performance classification example 17
Table A.1	– Impact trolley specification (dimensions and mass) 21
Table B.1	– Longitudinal force/displacement corridor limits 22
Table B.2	– Example of an energy absorber specification 23
Table C.1	– Particle size of soil 26

Summary of pages

This document comprises a front cover, an inside front cover, pages i to iv, pages 1 to 28, an inside back cover and a back cover.

Currently in preview, click buy full version

Foreword

Publishing information

This PAS was sponsored by the UK Government's Centre for the Protection of National Infrastructure (CPNI). Its development was facilitated by BSI Standards Limited and it was published under licence from The British Standards Institution. It came into effect on 31 July 2017.

Acknowledgement is given to the following organizations that were involved in the development of this PAS as members of the steering group:

- ATG Access;
- Centre for the Protection of National Infrastructure (CPNI);
- D.J. Goode and Associates Limited;
- HORIBA MIRA Limited;
- Marshalls;
- MFD International Limited;
- Perimeter Security Suppliers Association (PSSA);
- Transport Research Laboratory (TRL Limited).

The British Standards Institution retains ownership, and copyright of this PAS. BSI Standards Limited as the publisher of the PAS reserves the right to withdraw or amend this PAS on receipt of authoritative advice that it is appropriate to do so. This PAS will be reviewed at intervals not exceeding two years, and any amendments arising from the review will be published as an amended PAS and publicized in *Update Standards*.

This PAS is not to be regarded as a British Standard. It will be withdrawn upon publication of its content in, or as, a British Standard.

The PAS process enables a standardization document to be rapidly developed in order to fulfil an immediate need in industry. A PAS can be considered for further development as a British Standard, or constitute part of the UK input into the development of a European or International Standard.

Assessed capability. Users of this PAS are advised to consider the desirability of quality system assessment and registration against the appropriate standard in the BS EN ISO 9000 series by an accredited third-party certification body.

Test laboratory accreditation. Users of this PAS are advised to consider the desirability of selecting test laboratories that are accredited to BS EN ISO/IEC 17025 by a national or international accreditation body.

Use of this document

It has been assumed in the preparation of this PAS that the execution of its provisions will be entrusted to appropriately qualified and experienced people, for whose use it has been produced.

Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its methods are expressed as a set of instructions, a description, or in sentences in which the principal auxiliary verb is "shall".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a PAS cannot confer immunity from legal obligations.

Currently in preview, click buy full version

Introduction

For many years, CPNI has been working in conjunction with BSI, impact test facilities and vehicle security barrier (VSB) manufacturers to develop technical specifications for the testing and deployment of a full range of VSBs. Such VSBs are a means of providing proportionate protection against vehicle borne threats to key infrastructure, secure events and crowded places. The technical specifications have been developed through an extensive programme of full-scale vehicle impact tests using commercially available vehicles from passenger cars to large goods vehicles at prescribed impact speeds.

The purpose of the PAS 170 series is to provide a quick and inexpensive way of evaluating a vehicle security barrier product, under dynamic impact from an impact trolley. The purpose of PAS 170-1 is for the testing of bollards designed to meet the vehicle threat posed by criminality and accidental impacts (from low speed passenger vehicles). Sites at which a bollard tested to this PAS might be installed are car parks and retail outlets, for example.

PAS 170-1 is not intended to replace any element of the full-scale vehicle impact test methods, e.g. IWA 14-1 or PAS 68. Test methods such as IWA 14-1 and PAS 68 have been created to be used for testing VSBs which have been designed to mitigate the terrorist vehicle-borne threat using unmodified commercially available vehicles. Critical national infrastructure sites are examples of where VSBs might be installed.

Where a test item is tested against PAS 170-1 and meets the specified requirements, it can:

- provide reassurance that the test item design could offer impact resistance against a low speed N1G (2 500 kg) vehicle (as specified in IWA 14-1:2013), based on its performance against an impact trolley travelling at a low speed, which is acting as a surrogate (though this would not be a guarantee of performance); and
- encourage the manufacturer to consider progressing to a full-scale vehicle impact test method (see 3.7), e.g. those given in IWA 14-1 or PAS 68, to determine the impact resistance against higher speed vehicles than those speeds covered in PAS 170-1 (see 3.6).

NOTE PAS 68 and IWA 14-2 cover guidance for the selection, installation and use of VSBs, and their application, respectively.

1 Scope

This PAS describes a method for testing the performance of a single bollard, when subjected to a single impact using a 2 500 kg impact trolley at a speed of 16_{-1}^{+3} km/h or 32_{-1}^{+3} km/h.

PAS 170-1 does not cover testing the performance of blockers, planters or street furniture.

It is not equivalent to a full-scale vehicle impact test method. It does not cover the performance of a test item or its control apparatus when subjected to: blast explosion, ballistic impact, manual attack with the aid of tools or electrical manipulation/attack through a control system.

This PAS is for use by manufacturers, distributors or specifiers of bollards.

NOTE Full-scale vehicle impact test method is defined in 3.7.