

PD 5500:2015



BSI Standards Publication

# Specification for unfired fusion welded pressure vessels

This publication is not to be regarded as a British Standard

**bsi.**

...making excellence a habit.™

Currently in preview, click buy full version

**Publishing and copyright information**

The BSI copyright notice displayed in this document indicates when the document was last issued.

ICS 23.020.30

ISBN 978 0 580 88010 0

© The British Standards Institution 2015

Published by BSI Standards Limited 2015

The following BSI references relate to the work on this standard:

Committee reference PVE/1

**Publication history**

First published as BS 5500 March 1976;  
 Second edition January 1982;  
 Third edition January 1985;  
 Fourth edition January 1988;  
 Fifth edition January 1991;  
 Sixth edition January 1994;  
 Seventh edition January 1997;  
 First published as PD 5500 January 2000;  
 Second edition January 2003;  
 Third edition January 2006;  
 Fourth edition January 2009;  
 Fifth edition June 2012;  
 Sixth (present) edition April 2015

**Amendments issued since publication**

Issue Date	Effective Date	Amendment designation	Comments
------------	----------------	-----------------------	----------

## Contents

Foreword xv

### Section 1. General 1/1

- 1.1 Scope 1/1
- 1.2 Interpretation 1/3
- 1.3 Definitions 1/3
- 1.4 Responsibilities 1/4
  - 1.4.1 Responsibilities of the purchaser 1/4
  - 1.4.2 Responsibilities of the manufacturer 1/5
  - 1.4.3 Responsibilities of the Inspecting Authority 1/9
  - 1.4.4 Certificate of Conformance 1/9
- 1.5 Information and requirements to be agreed and to be documented 1/12
  - 1.5.1 Information to be supplied by the purchaser 1/12
  - 1.5.2 Information to be supplied by the manufacturer 1/12
- 1.6 Thicknesses 1/13

### Section 2. Materials 2/1

- 2.1 Selection of materials 2/1
  - 2.1.1 General 2/1
  - 2.1.2 Materials for pressure parts 2/1
  - 2.1.3 Materials for non-pressure parts 2/2
- 2.2 Materials for low temperature applications 2/24
- 2.3 Nominal design strength 2/26
  - 2.3.1 General 2/26
  - 2.3.2 Notation 2/27
  - 2.3.3 Time-independent design strength 2/27
  - 2.3.4 Time-dependent design strength 2/29

### Section 3. Design 3/1

- 3.1 General 3/1
- 3.2 Application 3/2
  - 3.2.1 Consideration of loads 3/2
  - 3.2.2 Design criteria 3/3
  - 3.2.3 Design pressure 3/4
  - 3.2.4 Maximum design temperature 3/4
  - 3.2.5 Minimum design temperature 3/5
  - 3.2.6 Thermal loads 3/5
  - 3.2.7 Wind and earthquake loads 3/5
- 3.3 Corrosion, erosion and protection 3/5
  - 3.3.1 General 3/5
  - 3.3.2 Additional thickness to allow for corrosion 3/6
  - 3.3.3 Linings and coatings 3/6
  - 3.3.4 Wear plates 3/6
- 3.4 Construction categories and design stresses 3/7
  - 3.4.1 Construction categories 3/7
  - 3.4.2 Design stresses 3/8
- 3.5 Vessels under internal pressure 3/9
  - 3.5.1 Cylindrical and spherical shells 3/9
  - 3.5.2 Dished ends 3/11
  - 3.5.3 Cones and conical ends 3/16
  - 3.5.4 Openings and nozzle connections 3/24
  - 3.5.5 Flat ends and flat plates 3/76
  - 3.5.6 Spherically domed and bolted ends of the form shown in Figure 3.5-39 3/88
- 3.6 Vessels under external pressure 3/95
  - 3.6.1 General 3/95
  - 3.6.2 Cylindrical shells 3/98
  - 3.6.3 Conical shells 3/103

3.6.4	Spherical shells	3/106
3.6.5	Hemispherical ends	3/107
3.6.6	Torispherical ends	3/107
3.6.7	Ellipsoidal ends	3/107
3.6.8	Procedure by which the departure from the mean circle may be obtained	3/107
3.7	Supports, attachments and internal structures	3/131
3.7.1	General	3/131
3.7.2	Supports	3/131
3.8	Bolted flanged connections	3/132
3.8.1	General	3/132
3.8.2	Notation	3/140
3.8.3	Narrow-faced gasketed flanges	3/142
3.8.4	Full-faced flanges with soft ring type gaskets	3/148
3.8.5	Ungasketed seal welded flanges	3/150
3.8.6	Reverse narrow-face flanges	3/150
3.8.7	Reverse full-face flanges	3/151
3.8.8	Full-faced flanges with metal to metal contact	3/152
3.9	Flat heat exchanger tubesheets	3/193
3.9.1	Notation	3/197
3.9.2	Characteristics of perforated plates	3/200
3.9.3	Tubesheets of exchangers with floating heads or tubes	3/201
3.9.4	Tubesheets of fixed tubesheet exchangers	3/210
3.9.5	Allowable shell and tube longitudinal stresses	3/217
3.9.6	Allowable tube joint end load	3/218
3.9.7	Tubesheet flanged extension with narrow-face gasket	3/219
3.10	Design of welds	3/222
3.10.1	General	3/222
3.10.2	Welded joints for principal seams	3/223
3.10.3	Welded joints for other than principal seams	3/225
3.10.4	Welded joints in time dependent applications	3/226
3.11	Vessels with external jackets or limpet coils	3/226
3.11.1	General	3/226
3.11.2	Jacketed cylindrical shells	3/226
3.11.3	Welded jacket connections	3/227
3.11.4	Cylindrical shells with limpet coils	3/230
3.12	Manhole inspection openings and quick release openings	3/232
3.13	Protective devices for excessive pressure or vacuum	3/232
3.13.1	Application	3/232
3.13.2	Capacity of relief device(s)	3/233
3.13.3	Pressure setting of pressure relieving devices	3/233
Section 4	<b>4. Manufacture and workmanship</b>	<b>4/1</b>
4.1	General aspects of construction	4/1
4.1.1	General	4/1
4.1.2	Material identification	4/1
4.1.3	Order of completion of weld seams	4/2
4.1.4	Junction of more than two weld seams	4/2
4.1.5	Localized thinning	4/2
4.1.6	Rectification of departures from tolerance	4/2
4.2	Cutting, forming and tolerances	4/2
4.2.1	Cutting of material	4/2
4.2.2	Forming of shell sections and plates	4/3
4.2.3	Assembly tolerances	4/6
4.2.4	Tolerances for vessels subject to internal pressure	4/7
4.2.5	Tolerances for vessels subject to external pressure	4/11
4.2.6	Structural tolerances	4/11
4.3	Welded joints	4/11
4.3.1	General	4/11
4.3.2	Welding consumables	4/11

4.3.3	Preparation of plate edges and openings	4/12
4.3.4	Assembly for welding	4/12
4.3.5	Attachments and the removal of temporary attachments	4/12
4.3.6	Butt joints	4/14
4.3.7	Welding: general requirements	4/14
4.4	Heat treatment	4/15
4.4.1	Preheat requirements	4/15
4.4.2	Normalizing: ferritic steels	4/15
4.4.3	Post-weld heat treatment	4/16
4.4.4	Methods of heat treatment	4/17
4.4.5	Post-weld heat treatment procedure	4/17
4.4.6	Mechanical properties after heat treatment	4/21
4.5	Surface finish	4/22
<b>Section 5. Inspection and testing</b> 5/1		
5.1	General	5/1
5.2	Approval testing of fusion welding procedures	5/2
5.3	Welder and operator approval	5/5
5.4	Production control test plates	5/6
5.4.1	Vessels in materials other than 9% Ni steel	5/6
5.5	Destructive testing	5/6
5.6	Non-destructive testing	5/6
5.6.1	General	5/6
5.6.2	Parent materials	5/7
5.6.3	Components prepared for welding	5/7
5.6.4	Non-destructive testing of welded joints	5/7
5.6.5	Choice of non-destructive test methods for welds	5/11
5.6.6	Non-destructive testing technique for welds	5/11
5.7	Acceptance criteria for weld defects revealed by visual examination and non-destructive testing	5/14
5.7.1	General	5/14
5.7.2	Assessment of defects	5/14
5.7.3	Repair of welds	5/15
5.8	Pressure tests	5/24
5.8.1	General	5/24
5.8.2	Basic requirements	5/25
5.8.3	Hydraulic testing	5/26
5.8.4	Pneumatic tests	5/26
5.8.5	"Standard" test pressure	5/27
5.8.6	Proof hydraulic test	5/29
5.8.7	Combined hydraulic/pneumatic tests	5/31
5.8.8	Leak testing	5/32
5.8.9	Vessel nameplate	5/32
5.9	Final inspection	5/32
5.9	Inspection requirements for cast components	5/33
5.9.1	Examination	5/33
5.9.2	Defects	5/33
5.9.3	Identification and marking	5/33

**Annexes**

Annex A:	Requirements for design where loadings and components are not covered by Section 3	A/1
Annex B:	Requirements for cylindrical, spherical and conical shells under combined loadings, including wind and earthquakes	B/1
Annex C:	Assessment of vessels subject to fatigue	C/1
Annex D:	Requirements for vessels designed to operate below 0°C	D/1
Annex E:	Recommendations for welded connections of pressure vessels	E/1
Annex G:	Recommendations for the design of local loads, thermal gradients, etc.	G/1

- Annex H: Recommendations for post-weld heat treatment of dissimilar ferritic steel joints *H/1*
- Annex J: Recommendations for pressure relief protective devices *J/1*
- Annex K: Requirements for design stresses for British Standard materials *K/1*
- Annex L: Guidance on structural tolerances *L/1*
- Annex M: Requirements for establishing the allowable external pressure for cylindrical sections outside the circularity limits specified in 3.6 *M/1*
- Annex N: Requirements for vessel design and the provision of information concerning UK statutory requirements for the demonstration of the continued integrity of pressure vessels throughout their service life *N/1*
- Annex Q: Recommendations for preparation and testing of production control test plates *Q/1*
- Annex R: Guidance on additional information for flat ends and flat plates *R/1*
- Annex S: Guidance on optional documentation for supply with vessel *S/1*
- Annex T: Recommendations for arc welded tube to tubeplate joints *T/1*
- Annex U: Guidance on the use of fracture mechanics analyses *U/1*
- Annex V: Requirements for testing and inspection of serially produced pressure vessels *V/1*
- Annex W: Worked examples *W/1*
- Annex Z: Guidance on the application of PD 5500 to pressure vessels falling within the scope of the European Pressure Equipment Directive *Z/1*

### Supplements

- Aluminium supplement: Requirements for aluminium and aluminium alloys in the design and construction of unfired fusion welded pressure vessels *Al/1*
- Copper supplement: Requirements for copper and copper alloys in the design and construction of unfired fusion welded or brazed pressure vessels *Cu/1*
- Nickel supplement: Requirement for nickel and nickel alloys in the design and construction of unfired fusion welded pressure vessels *Ni/1*
- Titanium supplement: Requirements for titanium and titanium alloys in the design and construction of unfired fusion welded pressure vessels *Ti/1*

### Index

#### List of reference

#### List of figures

- Figure 1.6-1 – Relationship of thickness definitions *1/14*
- Figure 3.5-1 – Dished ends *3/12*
- Figure 3.5-2 – Design curves for unpierced dished ends *3/14*
- Figure 3.5-3 – Conical shells: Vapour belt arrangement *3/17*
- Figure 3.5-4 – Values of coefficient  $\beta$  for cone/cylinder intersection without knuckle *3/20*
- Figure 3.5-5 – Geometry of cone/cylinder intersection: large end *3/22*
- Figure 3.5-6 – Geometry of cone/cylinder intersection: small end *3/24*
- Figure 3.5-7 – Offset cone *3/24*
- Figure 3.5-8 – Positions of openings or nozzles in dished ends *3/28*
- Figure 3.5-9 – Design curves for protruding nozzles in spherical vessels ( $d/D < 0.5$ ) and for protruding nozzles in cylindrical and conical vessels ( $d/D < 1/3$ ) *3/31*
- Figure 3.5-10 – Design curves for flush nozzles in spherical shells ( $d/D < 0.5$ ) and for flush nozzles in conical shells ( $d/D < 1/3$ ) *3/32*
- Figure 3.5-11 – Design curves for flush nozzles in cylindrical shells ( $0 < d/D < 0.3$ ) *3/33*
- Figure 3.5-12 – Design curves for flush nozzles in cylindrical shells ( $0.2 < d/D \leq 1.0$ ) *3/34*
- Figure 3.5-13 – Nozzle in a conical shell *3/42*
- Figure 3.5-14 – Notation applicable to spheres *3/42*

- Figure 3.5-15 – Notation applicable to spheres 3/43
- Figure 3.5-15a – Notation applicable to oblique nozzles in spheres 3/43
- Figure 3.5-16 – Notation applicable to spheres 3/44
- Figure 3.5-17 – Notation applicable to spheres 3/44
- Figure 3.5-18 – Notation applicable to cylinders 3/44
- Figure 3.5-19 – Notation applicable to cylinders 3/45
- Figure 3.5-20 – Notation applicable to cylinders 3/45
- Figure 3.5-21 – Notation applicable to cylinders 3/45
- Figure 3.5-22 – Protruding rim 3/46
- Figure 3.5-23 – Flush rim 3/46
- Figure 3.5-24 – Arrangement factor  $g$  3/47
- Figure 3.5-25 – Nozzle compensation 3/48
- Figure 3.5-26 – Notation applicable to spheres and cylinders 3/48
- Figure 3.5-27 – Notation applicable to spheres and cylinders 3/49
- Figure 3.5-28 – Notation applicable to spheres and cylinders 3/49
- Figure 3.5-29 – Modified flush nozzle compensation 3/50
- Figure 3.5-30 – Modified protruding nozzle compensation 3/51
- Figure 3.5-31 – Maximum branch to body thickness ratio 3/59
- Figure 3.5-32 – Reinforcement of openings and branches 3/59
- Figure 3.5-33 – Reinforcement of non-radial branches 3/72
- Figure 3.5-34 – Typical welded flat ends and covers 3/80
- Figure 3.5-35 – Typical non-welded flat ends and covers 3/81
- Figure 3.5-36 – Factor  $C$  for welded flat ends for  $n_{\text{cyl}}/n_{\text{cyl}_0} = 1$  to 3 3/82
- Figure 3.5-37 – Factor  $C$  for welded flat ends for  $n_{\text{cyl}}/n_{\text{cyl}_0} = 3$  to  $> 10$  3/83
- Figure 3.5-38 – Typical stays: areas supported by stays 3/86
- Figure 3.5-39 – Spherically domed and bolted head (narrow faced gasket) 3/90
- Figure 3.6-1 – Effective lengths of cylinder 3/114
- Figure 3.6-2 – Values of  $\varepsilon$  3/116
- Figure 3.6-3 – Values of  $n_{\text{cyl}}$  3/117
- Figure 3.6-4 – Values of  $\Delta$  3/118
- Figure 3.6-5 – Stiffening ring with unsupported section 3/120
- Figure 3.6-6 – Stiffening ring details 3/121
- Figure 3.6-7 – Values of  $\beta$  3/126
- Figure 3.6-8 – Conical sections: typical stiffeners 3/127
- Figure 3.8-1 – Loose keyed flange with mating components 3/147
- Figure 3.8-2 – Forces and lever arms on loose keyed flange 3/148
- Figure 3.8-3 – Typical lip arrangement for swing bolted flange 3/148
- Figure 3.8-4 – Location of gasket load reaction 3/171
- Figure 3.8-5 – Values of  $T$ ,  $U$ ,  $Y$  and  $Z$  3/172
- Figure 3.8-6 – Values of  $F$  (integral method factors) 3/173
- Figure 3.8-7 – Values of  $V$  (integral method factors) 3/173
- Figure 3.8-8 – Values of  $F_L$  (loose hub flange factors) 3/174
- Figure 3.8-9 – Values of  $V_L$  (loose hub flange factors) 3/174
- Figure 3.8-10 – Values of  $f$  (hub stress correction factors) 3/175
- Figure 3.8-11 – Ungasketted, seal-welded-type flanges 3/175
- Figure 3.8-12 – Contact face between loose and stub flanges in a lap joint where diameters  $A_2$  and  $B_2$  are defined by the same component 3/176
- Figure 3.9-1 – Shell and tube heat exchangers 3/195
- Figure 3.9-2 – Tubesheet layout 3/201
- Figure 3.9-3 – Determination of area  $S$  3/201
- Figure 3.9-4 – Design curves: determination of  $C_0$  3/203
- Figure 3.9-5 – Design curves: determination of  $F_0$  3/204
- Figure 3.9-6 – Design curves: determination of  $F_0$  3/205
- Figure 3.9-7 – Design curves: determination of  $F_i$  3/206
- Figure 3.9-8 – Design curves: determination of  $F_i$  3/207
- Figure 3.9-9 – Typical clamped and simply supported configurations for floating head or U-tubesheets 3/208
- Figure 3.9-10 – Flexural efficiency: triangular layout 3/209
- Figure 3.9-11 – Flexural efficiency: square layout 3/210

- Figure 3.9-12 – Tubesheet: determination of  $F_q$  3/213
- Figure 3.9-13 – Tubesheet: determination of  $H$  for  $X_a > 4.0$  3/214
- Figure 3.9-14 – Tubesheet: determination of  $H$  for  $X_a < 4.0$  3/215
- Figure 3.9-15 – Determination of the buckling length  $L_k$  3/218
- Figure 3.10-1 – Butt welds in plates of unequal thickness 3/224
- Figure 3.10-2 – Butt welds with offset of median lines 3/225
- Figure 3.11-1 – Some acceptable types of jacketed vessels 3/229
- Figure 3.11-2 – Typical blocking ring and sealer ring construction 3/230
- Figure 3.11-3 – Typical limpet coil 3/231
- Figure 3.11-4 – Limpet coil arrangements 3/231
- Figure 4.2-1 – Profile gauge details and application 4/10
- Figure 4.3-1 – A thin limpet coil weld detail 4/13
- Figure 5.6-1 – Illustration of welded joints for non-destructive testing 5/10
- Figure 5.7-1 – Partial non-destructive testing (NDT) category 2 construction 5/19
- Figure A.1 – Stress categories and limits of stress intensity A/7
- Figure A.2 – Curve for the evaluation of  $\Delta$  A/12
- Figure A.3 – Use of templates to check tolerances  $\ll$  A/13
- Figure B.1 – Stresses in a cylindrical shell under combined loading B/4
- Figure B.2 – Stresses in a spherical shell under combined loading B/5
- Figure B.3 – Stresses in a conical shell under combined loading B/6
- Figure B.4 – Global loads B/8
- Figure C.1 – Illustration of fluctuating stress C/2
- Figure C.2 – Example of pressure vessel fatigue loading cycle and determination of stress ranges C/7
- Figure C.3 – Fatigue design  $S-N$  curves for weld details applicable to ferritic steels up to and including 350 °C, austenitic stainless steels up to and including 430 °C, aluminium alloys up to and including 100 °C, nickel alloys up to and including 150 °C and titanium alloys up to and including 150 °C C/8
- Figure C.4 – Fatigue design  $S-N$  curves for bolting applicable to ferritic steels up to and including 350 °C, austenitic stainless steels up to and including 430 °C, aluminium alloys up to and including 100 °C, nickel alloys up to and including 150 °C and titanium alloys up to and including 150 °C C/9
- Figure C.5 – Interaction criteria for assessing coplanar embedded slag inclusion C/25
- Figure C.6 – Stress measurement points for determining structural hot spot stress at a weld toe C/26
- Figure C.7 – Deviations from design shape at seam welds C/31
- Figure C.8 – Weld toe dressing C/33
- Figure D.1 – Permissible design reference temperature/design reference thickness/required impact test temperature relationships for as-welded components D/3
- Figure D.2 – Permissible design reference temperature/design reference thickness/required impact test temperature relationships for post-weld heat-treated components D/4
- Figure D.3 – Examples of details for attaching non-critical components to pressure shell D/6
- Figure D.4 – Location of Charpy V-notch specimens in weld metal (as-welded vessels) D/25
- Figure D.5 – Location of Charpy V-notch specimens in weld metal (stress relieved vessels) D/25
- Figure D.6 – Location of Charpy V-notch specimens in heat affected zone D/25
- Figure D.7 – Example of detail for avoidance of severe thermal gradients D/27
- Figure E.1 – Typical weld preparations for butt welds using the manual metal-arc process E/2
- Figure E.2 – Typical weld preparations for circumferential welds where the second side is inaccessible for welding E/3

- Figure E.3 – Typical weld preparations for butt welds using the submerged arc welding process E/6
- Figure E.4 – Typical weld preparations for butt welds using the manual inert gas arc welding for austenitic stainless and heat resisting steels only E/7
- Figure E.5 – Typical weld details for circumferential lap joints E/8
- Figure E.6 – Standard weld details E/14
- Figure E.7a) – Limitations on geometry of fillet weld applied to the edge or a part E/15
- Figure E.7b) – Transverse and longitudinal sections of branch connections E/15
- Figure E.8 – Weld details for set-in branches E/16
- Figure E.9 – Set-on branches E/18
- Figure E.10 – Set-on branches E/19
- Figure E.11 – Set-on branches E/20
- Figure E.12 – Set-on branches E/21
- Figure E.13 – Set-on branches E/22
- Figure E.14 – Set-on branches E/23
- Figure E.15 – Set-on branches E/24
- Figure E.16 – Set-in branches: fillet welded connections E/25
- Figure E.17 – Set-in branches: partial penetration butt welded connections E/26
- Figure E.18 – Set-in branches: full penetration connections E/27
- Figure E.19 – Set-in branches: full penetration connections E/28
- Figure E.20 – Set-in branches: full penetration connections with asymmetrical butt joints E/29
- Figure E.21 – Set-in branches: full penetration connections welded from one side only E/30
- Figure E.22 – Forged branch connections E/31
- Figure E.23 – Forged branch connections E/32
- Figure E.24 – Set-on branches with added compensation rings E/33
- Figure E.25 – Set-in branches with added compensation rings E/34
- Figure E.26 – Set-in branches with added compensation rings E/35
- Figure E.27 – Set-in branches with added compensation rings E/36
- Figure E.28 – Set-in branches with added compensation rings E/37
- Figure E.29 – Studded connections E/38
- Figure E.30 – Socket welded and screwed connections E/40
- Figure E.31 – Flanges E/41
- Figure E.32 – Flanges E/42
- Figure E.33 – Flanges E/44
- Figure E.34 – Jacketted vessels: typical vessel/blocking ring attachments E/45
- Figure E.35 – Jacketted vessels: typical blocking ring/jacket attachments E/45
- Figure E.36 – Jacketted vessels: typical sealer rings E/47
- Figure E.37 – Jacketted vessels: typical through connections E/48
- Figure E.38 – Flat ends and covers E/49
- Figure E.39 – Tubeplate to shell connections: accessible for welding on *both* sides of the shell E/52
- Figure E.40 – Tubeplate to shell connections: accessible for welding from *outside* of shell only E/53
- Figure E.41 – Tubeplate to shell connections: accessible for welding on *both* sides of shell E/54
- Figure E.42 – Tubeplate to shell connections E/55
- Figure E.43 – Tubeplate to shell connections E/57
- Figure E.44 – Tubeplate to shell connections E/58
- Figure G.2.2-1 – Restriction on vessel/attachment geometry G/5
- Figure G.2.2-2 – Vessel with central radial load G/6
- Figure G.2.2-3 – Vessel with radial load out of centre G/6
- Figure G.2.2-4 – Graph for finding equivalent length  $L_e$  G/7
- Figure G.2.2-5 – Chart for finding  $64 \frac{r}{t} \left( \frac{C_x}{r} \right)^2$  G/9
- Figure G.2.2-6 – Cylindrical shells with radial load: circumferential moment per millimetre width G/10

- Figure G.2.2-7 – Cylindrical shells with radial load: longitudinal moment per millimetre width  $G/11$
- Figure G.2.2-8 – Cylindrical shells with radial load: circumferential membrane force per millimetre width  $G/12$
- Figure G.2.2-9 – Cylindrical shells with radial load: longitudinal membrane force per millimetre width  $G/13$
- Figure G.2.2-10 – Circumferential bending moment due to a radial line load variation round circumference  $G/16$
- Figure G.2.2-11 – Longitudinal moment from radial line load variation round circumference  $G/17$
- Figure G.2.2-12 – Circumferential membrane force from radial line load variation round circumference  $G/18$
- Figure G.2.2-13 – Longitudinal membrane force from radial line load variation round circumference  $G/19$
- Figure G.2.2-14 – Circumferential bending moment due to a radial line load variation along cylinder  $G/20$
- Figure G.2.2-15 – Longitudinal moment due to a radial line load variation along cylinder  $G/21$
- Figure G.2.2-16 – Circumferential membrane force due to a radial line load variation along cylinder  $G/22$
- Figure G.2.2-17 – Longitudinal membrane force due to a radial line load variation along cylinder  $G/23$
- Figure G.2.2-18 – Maximum radial deflection of a cylindrical shell subjected to a radial load  $W$  for  $r/t$  between 15 and 100  $G/25$
- Figure G.2.2-19 – Maximum radial deflection of a cylindrical shell subjected to a radial load  $W$  for  $r/t$  between 100 and 500  $G/26$
- Figure G.2.2-20 – Graphs for finding the square  $2C_1 \times 2C_1$  equivalent to a rectangular loading area  $2C_x \times 2C_y$   $G/27$
- Figure G.2.3-1 – Circumferential moment  $G/30$
- Figure G.2.3-2 – Longitudinal moment  $G/30$
- Figure G.2.3-3 – Sector stresses  $G/31$
- Figure G.2.3-4 – Notation for external loads at a nozzle or attachment on a cylindrical shell  $G/36$
- Figure G.2.4-1 – Chart for finding  $s$  and  $u$   $G/43$
- Figure G.2.4-2 – Spherical shell subjected to a radial load  $G/44$
- Figure G.2.4-3 – Deflections of a spherical shell subjected to a radial load  $W$   $G/45$
- Figure G.2.4-4 – Meridional moment  $M_x$  in a spherical shell subjected to radial load  $W$   $G/46$
- Figure G.2.4-5 – Circumferential moment  $M_\phi$  in a spherical shell subjected to a radial load  $W$   $G/47$
- Figure G.2.4-6 – Meridional force  $N_x$  in a spherical shell subjected to a radial load  $W$   $G/48$
- Figure G.2.4-7 – Circumferential force  $N_\phi$  in a spherical shell subjected to a radial load  $W$   $G/49$
- Figure G.2.4-8 – Spherical shell subjected to an external moment  $G/51$
- Figure G.2.4-9 – Deflections of a spherical shell subjected to an external moment  $M$   $G/52$
- Figure G.2.4-10 – Meridional moment  $M_x$  in a spherical shell subjected to an external moment  $M$   $G/53$
- Figure G.2.4-11 – Circumferential moment  $M_\phi$  in a spherical shell subjected to an external moment  $M$   $G/54$
- Figure G.2.4-12 – Meridional force  $N_x$  in a spherical shell subjected to an external moment  $M$   $G/55$
- Figure G.2.4-13 – Circumferential force  $N_\phi$  in a spherical shell subjected to an external moment  $M$   $G/56$
- Figure G.2.5-1 – Maximum stress in sphere for internal pressure (flush nozzles)  $G/61$

- Figure G.2.5-2 – Maximum stress in sphere for internal pressure (protruding nozzles) G/62
- Figure G.2.5-3 – Maximum stress in sphere for thrust loading (flush nozzles) G/62
- Figure G.2.5-4 – Maximum stress in sphere for thrust loading (protruding nozzles) G/63
- Figure G.2.5-5 – Maximum stress in sphere for moment loading (flush nozzles) G/63
- Figure G.2.5-6 – Maximum stress in sphere for moment loading (protruding nozzles) G/64
- Figure G.2.5-7 – Maximum stress in sphere for shear loading (flush nozzles) G/64
- Figure G.2.5-8 – Maximum stress in sphere for shear loading (protruding nozzles) G/65
- Figure G.2.6-1 – Shakedown values for pressure loading (flush nozzle) G/67
- Figure G.2.6-2 – Shakedown values for pressure loading (protruding nozzle) G/67
- Figure G.2.6-3 – Shakedown values for thrust and moment loadings (flush nozzle) G/68
- Figure G.2.6-4 – Shakedown values for thrust and moment loadings (protruding nozzle) G/68
- Figure G.2.6-5 – Shakedown values for thrust and moment loadings (flush nozzle) G/69
- Figure G.2.6-6 – Shakedown values for thrust and moment loadings (protruding nozzle) G/69
- Figure G.2.6-7 – Shakedown values for thrust and moment loadings (flush nozzle) G/70
- Figure G.2.6-8 – Shakedown values for thrust and moment loadings (protruding nozzle) G/70
- Figure G.2.8-1 – Moment and force vectors G/73
- Figure G.2.8-2 – Allowable axial nozzle load G/75
- Figure G.2.8-3 – Allowable nozzle moment G/76
- Figure G.2.8-4 – Calculation factor  $C_2$  G/80
- Figure G.2.8-5 – Calculation factor  $C_3$  G/81
- Figure G.2.8-6 – Calculation factor  $C_4$  G/81
- Figure G.3.1-1 – Typical brackets G/89
- Figure G.3.1-2 – Typical reinforcing plates on cylindrical shells G/90
- Figure G.3.2-1 – Typical ring support G/92
- Figure G.3.2-2 – Typical steelwork under ring support G/93
- Figure G.3.2-3 – Leg supports for vertical vessels G/93
- Figure G.3.2-4 – Typical ring girder G/96
- Figure G.3.3-1 – Typical supports for horizontal vessels G/98
- Figure G.3.3-2 – Cylindrical shell acting as beam over supports G/100
- Figure G.3.3-3 – Factor for bending moment at mid-span G/101
- Figure G.3.3-4 – Factors for bending moment at supports G/102
- Figure G.3.3-5 – Portion of shell ineffective against longitudinal bending G/103
- Figure G.3.3-6 – Circumferential bending moment diagrams G/108
- Figure G.3.3-7 – Saddle supports G/111
- Figure G.3.3-8 – Typical ring stiffeners G/112
- Figure G.3.3-9 – Graph of rigid end factor,  $F_A$  G/117
- Figure G.3.3-10 – Graph of saddle width factor,  $F_B$  G/118
- Figure G.3.3-11 – Graph of saddle interaction factor,  $F_I$  G/119
- Figure G.3.3-12 – Graph of length change factor,  $F_L$  G/120
- Figure G.3.3-13 – Graph of saddle wrap-round factor,  $F_\theta$  G/121
- Figure G.4.3-1 – Nozzle geometry G/127
- Figure G.4.3-2 – Transient fluid and metal temperatures G/127
- Figure G.4.3-3 – Inner surface thermal stress factors  $K_1$  and  $k_1$  G/128
- Figure G.4.3-4 – Outer surface thermal stress factors  $K_2$  and  $k_2$  G/129
- Figure G.4.3-5 – Mean temperature factors  $K_b$  and  $k_s$  G/130

- Figure J.1 – Typical pressure term relationships *J/2*  
 Figure L.1 – Tolerances on nozzles *L/2*  
 Figure L.2 – Tolerances after erection of a vertical vessel *L/3*  
 Figure L.3 – Tolerances on saddles and supports for horizontal vessels *L/4*  
 Figure L.4 – Tolerances on saddles and supports for vertical vessels *L/5*  
 Figure T.1 – Tube to tubeplate connections, tube end fusion *T/4*  
 Figure T.2 – Tube to tubeplate connections, castellated weld *T/5*  
 Figure T.3 – Tube to tubeplate connections, plain fillet weld *T/6*  
 Figure T.4 – Tube to tubeplate connections, front face bore fillet weld *T/7*  
 Figure T.5 – Tube to tubeplate connections, groove plus fillet weld *T/8*  
 Figure T.6 – Tube to tubeplate connections, groove weld *T/9*  
 Figure T.7 – Tube to tubeplate connections, back face inset bore weld *T/10*  
 Figure T.8 – Tube to tubeplate connections, back face stub bore weld *T/11*  
 Figure T.9 – General arrangement of push-out test piece for front face and back face welds *T/14*  
 Figure T.10 – Push-out test piece for tube ends on triangular pitch *T/15*  
 Figure T.11 – Push-out test piece for tube ends on square pitch *T/16*  
 Figure W.1-1 – Stiffener proportions *W/7*  
 Figure W.2-1 – Vessel on saddle supports *W/16*  
 Figure W.2-2 – Internal ring stiffener in plane of saddle *W/27*  
 Figure W.2-3 – External ring stiffeners adjacent to the saddle *W/27*  
 Figure W.2-4 – Vessel on ring and leg support *W/33*  
 Figure W.2-5 – Channel and shell as ring girder *W/36*  
 Figure W.6-1 – Potential failure locations in circumferential lap joint *W/54*  
 Figure W.6-2 – Maximum axisymmetric principal stress contours in lap joint *W/60*  
 Figure W.6-3 – Circumferential stress in lap joint *W/61*  
 Figure W.6-4 – Loading spectrum *W/75*  
 Figure W.6-5 – Reservoir cycle count *W/76*  
 Figure Al.E.1 – Typical full penetration joint preparations for one-sided welding only: aluminium and its alloys *Al/23*  
 Figure Al.E.2 – Typical full penetration joint preparations for two-sided welding only: aluminium and its alloys *Al/24*  
 Figure Al.E.3 – Typical full penetration joint preparations for one-sided welding with temporary backing or permanent backing: aluminium and its alloys *Al/26*  
 Figure Cu.E.1(1) – Typical full penetration joint preparation for one-sided welding only: copper and its alloys only *Cu/15*  
 Figure Cu.E.1(2) – Typical full penetration joint preparation for two-sided welding: copper and its alloys *Cu/16*  
 Figure Cu.E.1(3) – Typical full penetration joint preparation for one-sided welding with either temporary or permanent backing: copper and its alloys *Cu/17*  
 Figure Cu.E.1(4) – Alternative joint preparations *Cu/18*  
 Figure Cu.E.2(1) – Typical brazed joints for gunmetal bosses to copper vessels *Cu/19*

#### List of tables

- Table 1.4-1 – Purchase specification options *1/4*  
 Table 1.4-2 – Items for manufacturer, purchaser and/or Inspecting Authority agreement *1/6*  
 Table 2.1-1 – Material grouping *2/3*  
 Table 2.1-2 – List of materials covered by BS EN material standards *2/5*  
 Table 2.1-3 – Additional materials that may be used for category 3 construction *2/24*  
 Table 2.2-1 – Bolting materials for low-temperature *2/25*  
 Table 2.3-1 – Temperature above which time dependent properties shall be considered *2/26*  
 Table 3.4-1 – Construction categories *3/7*  
 Table 3.5-1 – Values of factor for ellipsoidal ends *3/15*

Table 3.5-2 – Values of $e/D \times 10^3$ for unpierced dished ends in terms of $h_e/D$ and $p/f$	3/15
Table 3.5-3 – Values of coefficient $\beta$ or cone/cylinder intersection without knuckle	3/21
Table 3.5-4 – Thickness of nozzles	3/35
Table 3.5-5 – Design values of $e_{rb}/e_{rs}$	3/36
Table 3.5-6 – Values of $C_{e_{rs}}/e_{ps}$ for Figure 3.5-9, Figure 3.5-10 and Figure 3.5-11 when $e_{rb}/e_{rs} = 0$	3/40
Table 3.5-7 – Allowable taper/taper thread sizes	3/54
Table 3.5-8 – Values of factor $C$ for welded flat ends to Figure 3.5-34b) and Figure 3.5-34c) (for Figure 3.5-36 and Figure 3.5-37)	3/84
Table 3.6-1 – Values for $G$ and $N$	3/108
Table 3.6-2 – Definitions of cylinder lengths	3/108
Table 3.6-3 – $E$ values for ferritic and austenitic steels (Young's modulus)	3/109
Table 3.6-4 – Values of $(\sigma_e/E) (d/e_w)^2$ for internal flat bar stiffeners	3/110
Table 3.6-5 – Values of $(\sigma_e/E) (d/e_w)^2$ for external flat bar stiffeners	3/111
Table 3.6-6 – Values of $L_e/L_s$	3/112
Table 3.6-7 – Values of $Z'$	3/114
Table 3.8-1 – Recommended design stress values for flange bolting materials <sup>a</sup>	3/136
Table 3.8-2 – Bolt root areas	3/138
Table 3.8-3 – Recommended surface finish on gasket contact faces for body flanges and flanges fitted with covers	3/139
Table 3.8-4 – Gasket materials and contact facings: gasket factors ( $m$ ) for operating conditions and minimum design seating stress ( $y$ )	3/154
Table 3.8-5 – Values of $T$ , $Z$ , $Y$ and $U$ (factors involving $K$ )	3/157
Table 3.9-1 – Values of $\Delta C$ as a function of $F_s$ and $R$ for all tubesheets, and $C_o$ for U-tubesheets only	3/200
Table 3.9-2 – Values of $F_r$ for typical tube joints	3/219
Table 4.2-1 – Circumference	4/7
Table 4.2-2 – Tolerance on depth of dished ends	4/8
Table 4.2-3 – Maximum permitted peaking	4/9
Table 4.2-4 – Maximum permitted peaking when special analysis is used	4/10
Table 4.4-1 – Requirements for post-weld heat treatment of ferritic steel vessels	4/19
Table 5.1-1 – Inspection stages in the course of which participation by the Inspecting Authority is mandatory	5/1
Table 5.1-2 – Other principal stages of inspection	5/2
Table 5.2-1 – Tensile test temperature	5/3
Table 5.2-2 – Weld procedure tests for butt welds in 9% Ni steel	5/5
Table 5.6-1 – Thickness limits for examination of internal flaws	5/8
Table 5.7-1 – Radiographic acceptance levels	5/16
Table 5.7-2 – Ultrasonic acceptance levels applicable to ferritic steels and weld metals in the thickness range 7 mm to 100 mm inclusive	5/17
Table 5.7-3 – Visual and crack detection acceptance level	5/20
Table 5.7-4 – Radiographic acceptance levels (reassessment of category 2 construction)	5/23
Table 5.7-5 – Ultrasonic acceptance levels (reassessment of category 2 construction)	5/24
Table A.1 – Classification of stresses for some typical cases	A/9
Table C.1 – Details of fatigue design curves	C/6
Table C.2 – Classification of weld details	C/11
Table C.3 – Values of $M_1$ , $M_2$ and $M_3$	C/23
Table C.4 – Weld defect acceptance levels	C/25
Table C.5 – Fatigue test factor $F$	C/27
Table D.1 – Design reference temperature for heat exchanger tubes	D/5
Table D.2 – Required impact energy	D/8
Table D.3 – Minimum design reference temperature for omission of impact test	D/8

Table D.4 – Reference thickness of weld joint components $e$	D/9
Table G.2.2-1 – Values of $K_1$ and $K_2$	G/14
Table G.2.8-1 – Coefficients to define factors $C_2$ , $C_3$ or $C_4$	G/80
Table G.3.2-1 – Moments in a ring girder	G/94
Table G.3.3-1 – Design factors $K_1$ and $K_2$	G/104
Table G.3.3-2 – Design factors $K_3$ and $K_4$ and allowable tangential shearing stresses	G/106
Table G.3.3-3 – Design factor $K_6$	G/107
Table G.3.3-4 – Values of constants $C_4$ , $C_5$ , $K_5$ , $K_7$ , and $K_8$	G/110
Table G.3.3-5 – Values of $K_9$	G/113
Table G.3.3-6 – Coefficients for $F_A$ , with $x = A/r$	G/115
Table G.3.3-7 – Coefficients for $F_B$ , with $x = b_1/r$	G/115
Table G.3.3-8 – Coefficients for $F_I$ , with $x = L_s/r$	G/115
Table G.3.3-9 – Coefficients for $F_L$ , with $x = L/r$	G/116
Table G.3.3-10 – Coefficients for $F_\theta$ , with $x = \theta$ (in degrees)	G/116
Table G.3.3-11 – Values of $K_{10}$ and $K_{11}$	G/122
Table G.4.3-1 – Circumferential stress factor $C_1$	G/133
Table G.4.3-2 – Bending stress factor $C_2$	G/134
Table G.4.3-3 – Meridional stress factor $C_3$	G/135
Table G.4.3-4 – Branch bending stress factor $C_4$	G/136
Table H.1 – Classification of materials	H/1
Table K.1-1 – Design strength values: index of steels	K/2
Table K.1-2 – Design strength values (N/mm <sup>2</sup> )	K/4
Table K.1-3 – Design strength values (N/mm <sup>2</sup> )	K/8
Table K.1-4 – Design strength values (N/mm <sup>2</sup> )	K/12
Table K.1-5 – Design strength values (N/mm <sup>2</sup> )	K/14
Table K.1-6 – Design strength values (N/mm <sup>2</sup> )	K/17
Table K.1-7 – Design strength values (N/mm <sup>2</sup> )	K/23
Table K.1-8 – Design strength values (N/mm <sup>2</sup> )	K/26
Table K.1-9 – Design strength values (N/mm <sup>2</sup> )	K/29
Table K.1-10 – Design strength values (N/mm <sup>2</sup> )	K/31
Table K.1-11 – Design strength values (N/mm <sup>2</sup> )	K/33
Table K.1-12 – Design strength values (N/mm <sup>2</sup> )	K/35
Table T.1 – Tube to tubesheet joints: essential tests and the suitability of joint types for optional tests	T/11
Table W.1-1 – Design data assumed for cylindrical sections	W/4
Table W.1-2 – Summary of calculation for $e$	W/4
Table W.1-3 – Derivation of $L_e/L_s$	W/5
Table W.1-4 – Design data assumed for complete vessel	W/8
Table W.1-5 – Values required for stiffener design	W/10
Table W.1-6 – Design data assumed for cylindrical sections	W/10
Table W.1-7 – Measured radii and departure from mean circle	W/12
Table W.1-8 – Values of $a_n$ , $b_n$ and $p_{m(n)}$	W/12
Table W.1-9 – Values of $\sigma_{br(n)}$	W/13
Table W.2-1 – Design data	W/15
Table W.2-2 – Interpolation of Table G.3.3-3 for $K_6$	W/22
Table W.2-3 – Summary of stresses (N/mm <sup>2</sup> )	W/37
Table W.6-1 – Results of calculations of allowable stress range	W/60
Table W.6-2 – Summary of results from Example 1	W/62
Table W.6-3 – Summary of results for Example 2	W/69
Table W.6-4 – Cyclic loading regime for case A	W/73
Table W.6-5 – Fatigue load cycle stress ranges	W/73
Table W.6-6 – Summary of damage calculation values for case A	W/73
Table W.6-7 – Cyclic loading regime for case B	W/74
Table W.6-8 – Fatigue load cycle stress ranges	W/76
Table W.6-9 – Summary of damage calculation for case B	W/77
Table W.6-10 – Summary of results	W/78
Table W.C.1 – Thermal stress	W/82
Table Z.1 – PD 5500 compliance with PED ESRs	Z/1

Table Al.2.3-1 – Design strength values: aluminium and aluminium alloys	A/2
Table Al.3.4-1 – Construction categories	A/4
Table Al.3.6-3 – <i>E</i> values for aluminium alloys (Young's modulus)	A/5
Table Al.3.8-1 – Recommended design stress values for flange bolting materials	A/5
Table Al.5.7-1 – Acceptance levels	A/13
Table Al.5.8-1 – Principal stages of inspection	A/19
Table Al.5.8-1 – Principal stages of inspection	A/20
Table Al.5.8-1 – Principal stages of inspection	A/21
Table Cu.2.3-1 – Design strength values of copper and copper alloys	Cu/2
Table Cu.3.4-1 – Construction categories for copper and copper alloy construction	Cu/4
Table Cu.3.5-2 – Thickness of nozzles	Cu/4
Table Cu.3.6-3 – <i>E</i> values for copper and copper alloys (Young's modulus)	Cu/5
Table Cu.4.2-1 – Hot forming temperatures	Cu/6
Table Cu.5.5-1 – Mechanical test requirements for butt weld procedure and welder approval	Cu/10
Table Cu.5.7-1 – Acceptance levels	Cu/12
Table Ni.2.3-1 – Design strength values for nickel and nickel alloy plate conforming to BS 3072	Ni/2
Table Ni.2.3-2 – Design strength values for nickel and nickel alloy seamless tube conforming to BS 3074	Ni/2
Table Ni.2.3-3 – Design strength values for nickel and nickel alloy seamless tube conforming to BS 3074	Ni/3
Table Ni.2.3-4 – Design strength values for nickel and nickel alloy seamless tube conforming to BS 3074	Ni/3
Table Ni.2.3-5 – Design strength values for nickel and nickel alloy forgings conforming to BS 3076	Ni/3
Table Ni.3.4-1 – Construction categories	Ni/5
Table Ni.3.6-3 – <i>E</i> values for nickel alloys (Young's modulus)	Ni/6
Table Ni.4.2-1 – Maximum temperature for heating nickel and nickel alloys	Ni/7
Table Ni.4.4-1 – Annealing temperature for nickel and nickel alloys	Ni/8
Table Ti.2.3.1 – Design strength values: commercially pure titanium and titanium alloys of material specifications ASTM B265, B338, B348, B363, B381, B861, and B862	Ti/2
Table Ti.3.4-1 – Construction categories	Ti/4
Table Ti.3.6-3 – <i>E</i> values for titanium alloys (Young's modulus)	Ti/4
Table Ti.4.2.2-1 – Minimum bend radii	Ti/6
Table Ti.4.4-1 – Heat treatment temperatures for commercially pure titanium and titanium alloys	Ti/8

### Summary of pages

This document comprises a front cover, an inside front cover, pages i to xviii, pages 1/1 to 5/34, pages A/1 to Z/10, pages Al/1 to Ti/10, pages I to XIV, an inside back cover and a back cover.