



BSI Standards Publication

Electric-electronic interface between chassis-cab and bodywork of refuse collection vehicles (RCVs)

National foreword

This Published Document is the UK implementation of CEN/TR 16596:2013.

The UK participation in its preparation was entrusted to Technical Committee B/508/1, Waste containers and associated lifting devices on refuse collection vehicles.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2013. Published by BSI Standards Limited 2013

ISBN 978 0 580 82400 5

ICS 43.040.15; 43.160

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 November 2013.

Amendments issued since publication

Date	Text affected
------	---------------

TECHNICAL REPORT

CEN/TR 16596

RAPPORT TECHNIQUE

TECHNISCHER BERICHT

November 2013

ICS 43.040.15; 43.160

English Version

Electric-electronic interface between chassis-cab and bodywork of refuse collection vehicles (RCVs)

Interface électrique-électronique entre le châssis-cabine et
la superstructure des bennes de collecte des déchets

CAN-Schnittstelle zwischen Fahrgestell und Aufbau von
Abfallsammel-Fahrzeugen

This Technical Report was approved by CEN on 24 September 2013. It has been drawn up by the Technical Committee CEN/TC 183.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

	Page
Foreword.....	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Electric interface	5
4.1 Objective	5
4.2 Description	6
4.3 Plugs	6
4.4 Pin-out and defined signals	6
4.5 Video cable	6
4.6 Plugs location	7
5 CAN Interface	7
5.1 Objective	7
5.2 SAE J1939/71 messaging for RCV	7
5.3 Management of the information between bodywork and chassis	7
Annex A (normative) Architecture of the electric-electronic interface	23
Annex B (normative) Plugs	24
Annex C (normative) Pin-out and defined signals	25
Annex D (normative) Characteristics of the engine revolution signal	29
Annex E (normative) Characteristics of the driving speed signal	30
Annex F (normative) Configuration of the information: chassis ready	31
Annex G (normative) Control of the beacon	32
Annex H (normative) CAN messages transmitted by bodywork	33
Annex I (normative) CAN messages received by bodywork	43
Bibliography	73

Foreword

This document (CEN/TR 16596:2013) has been prepared by Technical Committee CEN/TC 183 "Waste management", the secretariat of which is held by DIN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

Currently in preview, click buy full version

Introduction

On September 29, 2009, CEN/TC 183/WG 2 mandated its PWG 5 to work on a proposal for the CAN communication between the chassis-cab and the bodywork of RCVs. Based on an earlier proposal (PWG 5 from 2002 to 2005), the experts of PWG 5 discussed the possibilities and concluded in the results shown in this document.

To comply with the requirements of the relevant safety Directives and Standards, it is unavoidable to use electronic controls on the RCV chassis-cab and on the bodywork of RCVs because the control devices have to communicate to get the RCV working in proper and safe conditions.

This document contains a proposal for an interface between the chassis-cab and the bodywork in terms of electrical wiring including plugs and positions for the plugs as well as an adequate CAN protocol.

1 Scope

This Technical Report proposes a standardized interface between the chassis-cab and the bodywork of refuse collection vehicles. The solution, initially for vehicles with hard wired interface and CAN interface, is developed into full CAN communication between the bodywork and the chassis-cab.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1501-1:2011, *Refuse collection vehicles — General requirements and safety requirements — Part 1: Rear loaded refuse collection vehicles*

EN 1501-5:2011, *Refuse collection vehicles — General requirements and safety requirements — Part 5: Lifting devices for refuse collection vehicles*

SAE J1939/71:2010-02, *Vehicle application layer*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 1501-1:2011 and the following apply.

3.1

electric interface

provisions for power supply and control signals to ensure safe connections between the chassis-cab and the bodywork

3.2

electronic interface

provisions for communication between the chassis-cab and the bodywork by means of CanBus

3.3

Electronic Control Unit

ECU

embedded system that controls one or more electrical systems or subsystems in a RCV

4 Electric interface

4.1 Objective

This clause describes the electric interface between all chassis and the bodywork of refuse collection vehicles. Plugs, pin-outs and signals are defined.

The chassis-cab shall be provided with an electric-electronic interface ready to be connected inside the cab and outside the cab. From inside to outside of the cab, there is a defined wiring loom to connect the chassis information and which is also used for information reserved for the bodywork. By this means, the bodywork manufacturer does not need to rework the wiring and can therefore avoid wrong handling and damages on the chassis-cab side.

Annex A shows the architecture of the electric-electronic interface and examples of possible ways the bodybuilder can use it.