



BSI Standards Publication

Road and airfield surface characteristics

Part 15: Procedure for determining the skid resistance of a pavement surface using a device with longitudinal controlled slip (LFCI): The IMAG

Currently in preview, click buy full version

National foreword

This Published Document is the UK implementation of CEN/TS 15901-15:2014.

The UK participation in its preparation was entrusted to Technical Committee B/510/5, Surface characteristics.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014. Published by BSI Standards Limited 2014

ISBN 978 0 580 84236 8

ICS 93.080.20; 93.120

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 November 2014.

Amendments issued since publication

Date	Text affected
------	---------------

TECHNICAL SPECIFICATION
 SPÉCIFICATION TECHNIQUE
 TECHNISCHE SPEZIFIKATION

CEN/TS 15901-15

October 2014

ICS 93.080.20; 93.120

English Version

Road and airfield surface characteristics - Part 15: Procedure for determining the skid resistance of a pavement surface using a device with longitudinal controlled slip (LFCI): The IMAG

Caractéristiques de surface des routes et aéroports - Partie 15: Mode opératoire de détermination de l'adhérence d'un revêtement de chaussée à l'aide d'un dispositif à glissement longitudinal contrôlé (CFLI): IMAG

Oberflächeneigenschaften von Straßen und Flugplätzen - Teil 15: Verfahren zur Bestimmung der Griffigkeit von Fahrbahndecken durch Verwendung eines Geräts mit geregelterm Schlupf in Längsrichtung (LFCE): Das IMAG-Gerät

This Technical Specification (CEN/TS) was approved by CEN on 1 March 2014 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years, the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
 COMITÉ EUROPÉEN DE NORMALISATION
 EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

	Page
Foreword.....	3
1 Scope	5
2 Normative references	5
3 Recommended uses	5
4 Terms and definitions	6
5 Safety	9
6 Essential characteristics.....	9
6.1 Principle of measurements.....	9
6.2 Description of IMAG	9
7 Key characteristics	11
7.1 General.....	11
7.2 Test speed	11
7.3 Braking system	11
7.4 Static wheel load.....	11
7.5 Dynamic wheel load	11
7.6 Test wheel arrangement.....	11
7.7 Test tyre	11
7.8 Tyre and rim	12
7.9 Force-measuring transducer	12
7.10 Pavement wetting system, water film thickness	12
7.11 Minimum sampling interval	12
7.12 General requirements for measuring system	12
8 Test Procedure.....	12
8.1 Standard test conditions.....	12
8.2 Prior to testing	13
8.3 Testing	13
9 Data recording.....	14
10 Calibration	14
10.1 General.....	14
10.2 Calibration of the static vertical test wheel force.....	14
10.3 Calibration of the static braking force	14
10.4 Dynamic calibration of the travelled distance sensor	14
10.5 Calibration of the water delivery system.....	14
10.6 Dynamic comparison of friction devices	15
11 Precision	15
12 Test report	15
Bibliography	17

Foreword

This document (CEN/TS 15901-15:2014) has been prepared by Technical Committee CEN/TC 227 "Road materials", the secretariat of which is held by DIN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. CEN [and/or] CENELEC shall not be held responsible for identifying any or all such patent rights.

CEN/TS 15901, *Road and airfield surface characteristics*, is composed with the following parts:

- *Part 1: Procedure for determining the skid resistance of a pavement surface using a device with longitudinal fixed slip ratio (LFCS): RoadSTAR;*
- *Part 2: Procedure for determining the skid resistance of a pavement surface using a device with longitudinal controlled slip (LFCRNL): ROAR (Road Analyser and Recorder of Norsemeter);*
- *Part 3: Procedure for determining the skid resistance of a pavement surface using a device with longitudinal controlled slip (LFCA): The ADHERA;*
- *Part 4: Procedure for determining the skid resistance of pavements using a device with longitudinal controlled slip (LFCT): Tatra Runway Tester (TRT);*
- *Part 5: Procedure for determining the skid resistance of a pavement surface using a device with longitudinal controlled slip (LFCRDK): ROAR (Road Analyser and Recorder of Norsemeter);*
- *Part 6: Procedure for determining the skid resistance of a pavement surface by measurement of the sideway force coefficient (SFCS): SCRIM®;*
- *Part 7: Procedure for determining the skid resistance of a pavement surface using a device with longitudinal fixed slip ratio (LFCG): the Grip Tester®;*
- *Part 8: Procedure for determining the skid resistance of a pavement surface by measurement of the sideway-force coefficient (SFCO): SKM;*
- *Part 9: Procedure for determining the skid resistance of a pavement surface by measurement of the longitudinal friction coefficient (LFCD): DWWNL skid resistance trailer;*
- *Part 10: Procedure for determining the skid resistance of a pavement surface using a device with longitudinal block measurement (LFCSK): the Skiddometer BV-8;*
- *Part 11: Procedure for determining the skid resistance of a pavement surface using a device with longitudinal block measurement (LFCSR): the SRM;*
- *Part 12: Procedure for determining the skid resistance of a pavement surface using a device with longitudinal controlled slip: the BV 11 and Saab friction tester (SFT);*
- *Part 13: Procedure for determining the skid resistance of a pavement surface by measurement of a sideway force coefficient (SFCO): the Odoliograph;*
- *Part 15: Procedure for determining the skid resistance of a pavement surface using a device with longitudinal controlled slip (LFCl): The IMAG [the present document].*

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Bulgaria, Croatia, Cyprus,

Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

License copy: Tech Street, ISO Exchange - Michigan, Version correct as of 11/11/2014, (c) The British Standards Institution 2014

Currently in preview, click buy full version

1 Scope

This Technical Specification describes a method only used on airports for determining the skid resistance of pavements by measurement of the longitudinal friction coefficient LFCI.

The method provides a measure of the wet skid resistance properties of a bound surface by measurement of the longitudinal friction coefficient using a trailer with a standard slip ratio of 15 %. The slip ratio can be chosen between 0 % and 100 % for research application.

The test tyre is dragged over a pre-wetted pavement under vertical force and constant speed conditions while the test tyre is parallel to the direction of motion.

This Technical Specification covers the operation of the IMAG device.

The skid resistance of a pavement is determined by friction measurements at different speeds. Tests can be performed between 40 km/h and 120 km/h but standard test speeds are 40 km/h, 65 km/h and 95 km/h. Low speed measurements assess the microtexture while high speed measurements assess the macrotexture. The skid resistance is reported as friction measurements at these speeds and by comparison with the minimum friction level.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5725-2, *Accuracy (trueness and precision) of measurement methods and results — Part 2: Basic method for the determination of repeatability and reproducibility of a standard measurement method*

ASTM E670-09, *Standard Test Method for Surface Friction on Paved Surfaces Using the Mu-Meter*

ASTM E2100-04, *Standard Practice for Calculating the International Runway Friction Index*

PIARC Technical Document. *Specification for a standard test tyre for friction coefficient measurement of a pavement surface: Smooth test tyre (2004-03)*

3 Recommended uses

The IMAG is used in the following fields of application:

- monitoring of airport pavements (Pavement Management) according to ICAO Annex 14 Attachment A 7,
- approval of new surfacing according to ICAO Annex 14 Attachment A 7,
- investigation of surface skid resistance,
- measurements on project-level compliance,
- comparative measurements among different devices,
- measurements on contaminated (ice or snow covered) airport pavements (not covered by this Technical Specification) according to ICAO Annex 14 Attachment A 6,