



BSI Standards Publication

**Liming materials – Determination of the
lime requirement in soil – Ammonium
acetate buffer method pH 5.5**

National foreword

This Published Document is the UK implementation of CEN/TS 17338:2019.

The UK participation in its preparation was entrusted to Technical Committee CII/37, Fertilisers and related chemicals.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2019
Published by BSI Standards Limited 2019

ISBN 978 0 539 00052 8

ICS 65.080

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 May 2019.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

English Version

**Liming materials - Determination of the lime
requirement in soil - Ammonium acetate buffer
method pH 5,5**

Amendements minéraux basiques - Détermination
du besoin en chaux d'un sol - Méthode
tampon d'acétate d'ammonium pH 5,5

Kalkdünger — Bestimmung des Kalkbedarfs von
Böden — Ammoniumacetat-Pufferverfahren pH 5,5

This Technical Specification (CEN/TS) was approved by CEN on 15 March 2019 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

	Page
European foreword	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Principle	5
5 Reagents	5
6 Apparatus	6
6.2 Shaking machine	6
7 Preparation of the test portion	6
8 Procedure and determination	6
9 Calculation and expression of the results	7
10 Test report	8
Annex A (informative) Regression equations to predict the maintenance of a range of pH levels at different times after liming in mineral and organic soils in Europe	9
Bibliography	12

European foreword

This document (CEN/TS 17338:2019) has been prepared by Technical Committee CEN/TC 260 "Fertilizers and liming materials", the secretariat of which is held by DIN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Currently in preview, click buy full version.

Introduction

pH target levels for liming of soils depend on soil types, crops to be grown and regional climatic conditions.

When pH targets have been fixed under each condition, this buffer method can be used, in addition to determine total soil acidity, to predict the amount of an effective liming material to be used to achieve this required lime status, irrespective of soil type. The buffer method will reveal the buffering capacity of any soil prior to its admixture of a liming material.

Currently in preview, click buy full version

1 Scope

This document specifies a method for the determination of the lime requirement of acid soils to target pH levels at requested time of maintenance as determined by reaction with 0,1 mol/l ammonium acetate pH 5,5.

Due to general soil buffering systems, the method is applicable to all soils which are acid enough to dissociate hydrogen ions from the soil colloid system to depress the pH of the buffer solution.

NOTE 1 The method originates from research in Canada and Norway, see [1] and [2].

NOTE 2 [Annex A](#) gives regression equations to predict the maintenance of a range of pH levels at different times after liming in mineral and organic soils in Europe.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 12944-3, *Fertilizers and liming materials — Vocabulary — Part 3: Terms relating to liming materials*

EN ISO 3696, *Water for analytical laboratory use — Specification and test methods (ISO 3696)*

EN ISO 11272, *Soil quality — Determination of dry bulk density (ISO 11272)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 12944-3 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp/>

4 Principle

The acidity of a test portion of the soil sample is liberated by reaction with an aliquot of ammonium acetate pH 5,5, corresponding to the immediate lime requirement to achieve soil neutrality or another defined pH target. To determine the lime requirement in the field the density of the soil is measured simultaneously in the laboratory.

5 Reagents

All reagents shall be of recognized analytical grade unless otherwise stated.

- 5.1 **Water**, grade 3 according to EN ISO 3696.
- 5.2 **Hydrochloric acid solution**, $c = 0,1$ mol/l.
- 5.3 **Sodium hydroxide solution**, $c = 0,1$ mol/l.