



BSI Standards Publication

Specification for radio disturbance and immunity measuring apparatus and methods

Part 4-5: Uncertainties, statistics and limit modelling —
Conditions for the use of alternative test methods

National foreword

This Published Document is the UK implementation of CISPR TR 16-4-5:2006+A2:2021. It supersedes PD CISPR/TR 16-4-5:2006+A1:2014, which is withdrawn.

The text of CISPR amendment 2:2021 has been provided in its entirety at the end of this document. BSI's policy of providing consolidated content remains unchanged; however, in the interest of expediency, in this instance BSI have chosen to collate the relevant content at the end of this document.

The start and finish of text introduced or altered by amendment is indicated in the text by tags. Tags indicating changes to CISPR text carry the number of the CISPR amendment. For example, text altered by CISPR amendment 1 is indicated by A1 A1.

Attention is drawn to the fact that during the development of CISPR/TR 16-4-5:2014+A1, the UK committee voted against its approval.

The concern is that in Annex C.3, the use of a coupling/decoupling network for emission – Mains (CDNE-M) in the conducted and radiated tests will have had the effect of making the round robin test (RRT) insensitive to both nominal values and tolerances of parameters of the CDNE-M. This is because such parameters will have affected the two measurements that are to be compared to the same extent.

The UK committee also noted that the amendment states that the calculated Standards Compliance Uncertainty of 5,5 dB is very low for the field strength measurement with a connected cable. The UK committee is concerned that this result is at least partly due to the CDNE-M's balanced absorption of Differential Mode (DM) emission which consequently cannot contribute to either conducted (clause C.2) or radiated (clause C.3) measurements. This lack of contribution will be a significant gap and a cause of uncertainty if the CDNE-M is used in applications where the emission of the EUT in DM is comparable with or greater than the emission in Common Mode (CM).

Technical justification was presented at the Tokyo EMC conference in May 2014 in the paper: *"Measurement Method, Uncertainty and Cable Balance - with Implications for the CDNE-M"* by D M Lauder & R C Marshall, Paper 14A-A3, 2014 International Symposium on Electromagnetic Compatibility. This academic paper is available from the British Library.

The UK participation in its preparation was entrusted to Technical Committee GEL/210, EMC - Policy committee.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication is not to be regarded as a British Standard.

© The British Standards Institution 2022
Published by BSI Standards Limited 2022

ISBN 978 0 539 03513 1

ICS 33.100.10; 33.100.20

Compliance with a Published Document cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 29 December 2006.

Amendments/corrigenda issued since publication

Date	Text affected
31 October 2014	Implementation of CISPR amendment 1:2014. Additional national foreword text inserted
31 May 2022	CISPR amendment 2:2021 collated amendment of document.

Currently in preview, click buy full version

TECHNICAL REPORT

CISPR 16-4-5

First edition
2006-10

INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

**Specification for radio disturbance and
immunity measuring apparatus and methods –**

Part 4-5:

**Uncertainties, statistics and limit modelling –
Conditions for the use of alternative test methods**



Reference number
CISPR 16-4-5/TR:2006(E)

CONTENTS

1	Scope.....	4
2	Normative references.....	4
3	Terms and definitions.....	4
4	Symbols and abbreviated terms.....	6
5	Introduction.....	6
6	Procedure to derive limits for an alternative test method.....	7
6.1	Overview.....	7
6.2	Select the reference quality X	10
6.3	Describe the test methods and measurands.....	11
6.4	Determine the deviations of the measured quantities from the reference quantity.....	11
6.5	Determine the average values of the deviations.....	11
6.6	Estimate the standard uncertainties of the test methods.....	12
6.7	Estimate the expanded uncertainties of the test methods.....	13
6.8	Calculate the average conversion factor.....	14
6.9	Verify the calculated values.....	15
6.10	Apply the conversion.....	15
A1 7	Measurement-based procedure to derive limits for an alternative test method based on measurement results.....	16
7.1	General.....	16
7.2	Application of practical measurement results to determine the conversion factors A1	16
	Annex A (informative) Remarks on EUT modelling.....	20
	Annex B (informative) Examples of application of the test method comparison procedure.....	21
A1	Annex C (informative) Example of the application of the test method comparison procedure based on measurement results A1	51
	Bibliography.....	57
	Figure 1 – Overview of quantities to estimate for use in conversion procedure.....	8
	Figure 2 – Overview of limit conversion procedure using estimated quantities.....	9
	Figure B.1 – Example reference quantity.....	21
	Figure B.2 – EUT and antenna set-up for fully anechoic room emission measurement.....	22
	Figure B.3 – EUT and antenna set-up for open-area test site measurement.....	22
	Figure B.4 – Radiation characteristics of elementary radiator (left), and scheme of EUT-model (right).....	23
	Figure B.5 – Maximum average deviations for 3 m FAR (top) and 10 m OATS (bottom).....	26
	Figure B.6 – Sample cumulative distribution function.....	28
	Figure B.7 – Uncertainties due to the unknown EUT characteristic for 3 m FAR (top) and 10 m OATS (bottom).....	30
	Figure B.8 – Expanded uncertainties ($k = 2$) of alternative (3 m FAR, top) and established (10 m OATS, bottom) test methods.....	34
	Figure B.9 – Maximum average conversion factors for different volumes.....	35
	Figure B.10 – Photo (left) and cut-view of simulation model (right) of the specimen EUT.....	37
	Figure B.11 – Deviations of the specimen EUT: 3 m fully anechoic room (top) and 10 m open area test site (bottom).....	38

Figure B.12 – Sample FAR measurement	39
Figure B.13 – OATS 10 m limit line converted to FAR 3 m conditions.....	39
Figure B.14 – Expanded uncertainties	39
Figure B.15 – Comparison of the measured values with the corrected converted limit.....	40
Figure B.16 – EUT and antenna set-up of 3 m open area test site measurement.....	41
Figure B.17 – Maximum average deviations for 3 m OATS	42
Figure B.18 – Uncertainties due to the unknown EUT characteristic for 3 m OATS.....	43
Figure B.19 – Expanded uncertainties ($k = 2$) of alternative test method [OATS (3 m)]	45
Figure B.20 – Maximum average conversion factors	46
Figure B.21 – Deviations of the specimen EUT: Open area test site (3 m).....	48
Figure B.22 – Sample OATS (3 m) measurement	48
Figure B.23 – OATS (10 m) limit line converted to OATS (3 m) conditions.....	49
Figure B.24 – Expanded uncertainties	50
Figure B.25 – Comparison of the corrected values with the converted limit	50
A1 Figure C.1 – EUTs used during RRT	51
Figure C.2 – Measurement results of the asymmetrical voltage using both C and NE	52
Figure C.3 – Measured disturbance field strength	53
Figure C.4 – Conversion factors of all measurements	54
Figure C.5 – Mean conversion factors for each EUT.....	54
Figure C.6 – Measured polarization	54
Figure C.7 – Comparison with CISPR 15:2013.....	54
Figure C.8 – Deviation of the conversion factors from the average conversion factor of each EUT.....	55
Figure C.9 – Deviation of the conversion factors from the trend line [poly (mean value $K(f)$)] A1	55
Table 1 – Summary of steps in conversion procedure.....	7
Table 2 – Overview of quantities and defining equations for conversion process.....	10
Table B.1 – Instrumentation uncertainty of the 3 m fully anechoic chamber test method	27
Table B.2 – Uncertainties in dB due to the unknown EUT characteristic for 3 m FAR.....	32
Table B.3 – Uncertainties in dB due to the unknown EUT characteristic for 10 m OATS.....	33
Table B.4 – Maximum average conversion factors in dB between 10 m OATS and 3 m FAR	36
Table B.5 – Uncertainties in dB due to the unknown EUT characteristic for 3 m OATS	44
Table B.6 – Maximum average conversion factors in dB between 10 m and 3 m OATS.....	47

SPECIFICATION FOR RADIO DISTURBANCE AND IMMUNITY MEASURING APPARATUS AND METHODS –

Part 4-5: Uncertainties, statistics and limit modelling – Conditions for the use of alternative test methods

1 Scope

This part of CISPR 16-4 specifies a method to enable product committees to develop limits for alternative test methods, using conversions from established limits. This method is generally applicable for all kinds of disturbance measurements, but focuses on radiated disturbance measurements (i.e. field strength), for which several alternative methods are presently specified. These limits development methods are intended for use by product committees and other groups responsible for defining emissions limits in situations where it is decided to use alternative test methods and the associated limits in product standards.

2 Normative references

IEC 60050-161 [A1]:1990 [A1], *International Electrotechnical Vocabulary (IEV) – Chapter 161: Electromagnetic compatibility*

CISPR 16-4-1 [A1] *Text deleted* [A1], *Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-1: Uncertainties, statistics and limit modelling – Uncertainty in standardized EMC tests*

CISPR 16-4-2:2003, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-2: Uncertainties, statistics and limit modelling – Uncertainty in EMC measurements*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-161 and the following apply.

3.1

established test method

test method described in a basic standard with established emissions limits defined in corresponding product or generic standards. An established test method consists of a specific test procedure, a specific test set-up, a specific test facility or site, and an established emissions limit.

[A1] NOTE The following test methods have been considered to be established test methods in CISPR:

– conducted disturbance measurements at mains ports using an AMN in the frequency range 9 kHz to 30 MHz; this method is defined in CISPR 16-2-1;

– radiated disturbance measurements in the frequency range 30 MHz to 1 GHz at 10 m distance on an OATS or in a SAC; this method is defined in CISPR 16-2-3;

– radiated disturbance measurements in the frequency range 1 GHz to 18 GHz at 3 m distance on an FSOATS; this method is defined in CISPR 16-2-3. [A1]

3.2

alternative test method

test method described in a basic standard without established emissions limits. The alternative test method is designed for the same purpose as the established test method. An alternative test method consists of a specific test procedure, a specific test set-up, a specific test facility or site, and a derived emissions limit that was determined by the application of the proposed method stated in this document