



BSI Standards Publication

Satellite signal distribution over a single coaxial cable

Part 10: Implementation guideline

National foreword

This Published Document is the UK implementation of CLC/TR 50607-10:2015.

The UK participation in its preparation was entrusted by Technical Committee EPL/100, Audio, video and multimedia systems and equipment, to Subcommittee EPL/100/4, Cable distribution equipment and systems.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2016.

Published by BSI Standards Limited 2016

ISBN 978 0 580 90362 5

ICS 33.060.40

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 19 February 2016.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

TECHNICAL REPORT

CLC/TR 50607-10

RAPPORT TECHNIQUE

TECHNISCHER BERICHT

November 2015

ICS 33.060.40

English Version

Satellite signal distribution over a single coaxial cable - Part 10: Implementation guideline

Distribution de signaux satellites sur un seul câble coaxial -
Partie 10: Lignes directrices de mise en œuvre

Verteilen von Satellitensignalen über ein Koaxialkabel -
Teil 10: Anwendungsleitfaden

This Technical Report was approved by CENELEC on 2015-09-14.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents		Page
European foreword.....		3
Introduction.....		4
1	Scope.....	5
2	Normative references.....	5
3	Terms, definitions and abbreviations.....	5
3.1	Terms and definitions.....	5
3.2	Abbreviations.....	5
4	Standard applications.....	5
4.1	General note for all application examples.....	5
4.2	SCD2 Universal LNB.....	6
4.3	SCD2 Multi-switch with feed by Quatro LNB.....	6
4.4	SCD2 LNB with wideband architecture.....	7
4.5	SCD2 Multi-switch with wideband feed.....	8
4.6	SCD2 multi-switch (two satellite reception).....	9
4.7	SCD2 C-Band LNB.....	9
4.8	SCD2 Ka-Band LNB (dual wideband hardware).....	10
4.9	SCD2 multi-switch with Ka-Band LNB (dual wideband feed).....	10
4.10	SCD2 Ka-Band LNB (ultra-wideband hardware).....	11
5	Conclusion.....	11
Figures		
Figure 1 — SCD2 Universal- LNB — Example for Ku Band.....		6
Figure 2 — SCD2 Multi-switch with standard feed by Universal LNB — Example for Ku Band.....		6
Figure 3 — SCD2 LNB with wideband architecture — Example for Ku Band.....		7
Figure 4 — SCD2 Multi-switch with wideband feed — Example for Ku Band.....		8
Figure 5 — SCD2 multi-switch (two satellite reception).....		9
Figure 6 — SCD2 C-Band LNB.....		9
Figure 7 — SCD2 Ka-Band LNB (dual wideband hardware).....		10
Figure 8 — SCD2 multi-switch with Ka-Band LNB (dual wideband feed).....		10
Figure 9 — SCD2 Ka-Band LNB (ultra-wideband hardware).....		11

European foreword

This document (CLC/TR 50607-10:2015) has been prepared by CLC/TC 209, "Cable networks for television signals, sound signals and interactive services".

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Currently in preview, click buy full version

Introduction

EN 50607 specifies the second generation of channel stacking systems for satellite reception. The second generation allows more reception possibilities by increasing the number of user bands and the number of satellite feeds.

This Technical Report provides implementation examples to assist manufacturers and installers of satellite distribution and satellite receiving equipment to implement EN 50607 in the most convenient way and ease installation of products according to EN 50607.

1 Scope

This Technical Report describes a number of different satellite reception scenarios and how to use SCD2 here. In particular, Universal and Wideband LNB architectures for different SHF bands (Ku-, Ka- and C-Band) are taken into account.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50607, *Satellite signal distribution over a single coaxial cable - Second generation*

3 Terms, definitions and abbreviations

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 50607 apply.

3.2 Abbreviations

For the purposes of this document, the abbreviations given in EN 50607 apply.

4 Standard applications

4.1 General note for all application examples

The following examples show block diagrams for one user band only. For more user bands, switch matrix and converter blocks can be multiplied accordingly.

Function blocks are simplified (no pre-selection, filters etc.).

Data format is simplified (offset of 100 MHz to transmitted data is ignored).

Only analogue converters are shown, the examples can be adapted for dCSS solutions accordingly.

Basically, the examples describe communications with:

- a) Universal LNB (see 4.2);
- b) Multi-switch with feed by Quatro LNB (see 4.3);
- c) LNB's with wideband architecture (see 4.4.);
- d) Multi-switch with wideband feed see (4.5);
- e) Two satellite reception (see 4.6);
- f) C-Band LNB's (see 4.7);
- g) Universal Ka Band LNB with dual wideband hardware (see 4.8);
- h) Multi-switch with feed by LNB (dual wideband feed) in 4.9;
- i) Ka Band LNB (ultra-wideband hardware) in 4.10.