



BSI Standards Publication

Collection, logistics & treatment requirements for end-of-life household appliances containing volatile fluorocarbons or volatile hydrocarbons

Part 2: Specification for de-pollution

National foreword

This Published Document is the UK implementation of CLC/TS 50574-2:2014.

The UK participation in its preparation was entrusted to Technical Committee GEL/111, Electrotechnical environment committee.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014.

Published by BSI Standards Limited 2014

ISBN 978 0 580 86173 4

ICS 13.030.30; 13.030.40; 97.030

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 10 November 2014.

Amendments/corrigenda issued since publication

Date	Text affected
-------------	----------------------

ICS 13.030.30; 13.030.40; 97.030

English Version

Collection, logistics & treatment requirements for end-of-life household appliances containing volatile fluorocarbons or volatile hydrocarbons - Part 2: specification for de-pollution

Exigences de collecte, logistique et traitement pour la fin de vie des appareils domestiques contenant des fluorocarbures volatils ou des hydrocarbures volatils - Partie 2: Spécifications de dépollution

Anforderungen an die Sammlung, Logistik und Behandlung von Altgeräten aus dem Haushalt, die flüchtige Fluorkohlenwasserstoffe oder flüchtige Kohlenwasserstoffe enthalten - Teil 2: Spezifikation zur Schadstoffentfrachtung

This Technical Specification was approved by CENELEC on 2014-09-30.

CENELEC members are required to announce the existence of this TS in the same way as for an EN and to make the TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	5
Introduction.....	6
1 Scope	7
2 Normative references	7
3 Terms and definitions	7
4 Target values.....	7
4.1 Step 1.....	7
4.2 Step 2: t_{VFC} , t_{VHC}	7
4.2.1 General.....	7
4.2.2 Target values based on the quantity of potentially recoverable VFC and VHC blowing agent calculated from the plant's PU input stream.....	8
4.2.3 Target values based on the theoretical mass of VFC and VHC blowing agent calculated from the PU output fraction.....	8
5 Characteristic numbers.....	8
5.1 Step 1.....	8
5.1.1 Maximal ratio of VFC (according to rating plate) to mass of mixture of VFC and oil sucked off: t_{max}	8
5.1.2 Ratio of total quantity of VFC and oil recovered by vacuum extraction to the reduction in the appliance mass after vacuum extraction has been completed: q_{Mtot}	8
5.1.3 Number of oil containing refrigerating system: N_{oil}	9
5.1.4 Residual oil in compressors.....	9
5.2 Step 2.....	9
5.2.1 Masses of PU for the individual appliance categories VFC 1–3 (i) and VHC 1–3 (i): $w_{i,VFC}$ and $w_{i,VHC}$	9
5.2.2 Concentration of VFC in VFC-PU (input): f_{VFC} and Concentration of VHC in VHC-PU (input): f_{VHC}	10
6 Monitoring system and regular reporting (5.2 to 5.6 / Annex C of EN 50574:2012).....	10
6.1 General.....	10
6.2 Information to be monitored.....	10
6.3 Targets for day-to-day business.....	10
6.3.1 General.....	10
6.3.2 Step 2.....	10
6.3.3 Step 2 and Step 3.....	11
6.4 Reporting.....	11
7 Compliance evaluation.....	11
8 Sampling and analytical methods.....	11
8.1 General.....	11
8.2 Sampling methods.....	11
8.2.1 General.....	11
8.2.2 Sampling of oil as base for the determination of residual VFC content.....	12
8.2.3 Sampling of refrigerant as base for the determination of the chemical composition.....	12
8.2.4 Sampling of PU fraction as base for the determination of residual VFC, VHC and foreign matters content.....	12
8.2.5 Sampling of metallic and plastics fractions as base for the determination of remaining PU parts.....	14
8.2.6 Sampling of blowing agents as base for the determination of chemical composition.....	14

8.3	Analytical methods.....	15
	Annex A (normative) List of countries in the geographical areas	16
	Annex B (informative) Structure of the monitoring and reporting system for the Step 1 and Step 2 activities	18
	Annex C (normative) Compliance evaluation	20
C.1	Introduction.....	20
C.2	Calculations for performance test step 1.....	20
C.2.1	General	20
C.2.2	Defective refrigeration systems	20
C.2.3	Compressed air in refrigeration vessels.....	20
C.2.4	Plausibility checks referring to the step 1 test.....	20
C.3	Calculations for performance test step 2.....	21
C.3.1	General	21
C.3.2	Density of the blowing agents	21
C.3.3	Determination of water in the vessel.....	21
C.3.4	Plausibility checks	21
	Annex D (informative) Analytical procedures	23
D.1	Determination of Residual VFC Content in Oil – Example 1.....	23
D.1.1	Extraction	23
D.1.2	Analysis.....	23
D.1.3	Chromatography Settings	23
D.2	Determination of Residual VFC Content in Oil – Example 2.....	23
D.2.1	Analysis.....	23
D.2.2	Analysis Repetition	24
D.2.3	Chromatographic Settings.....	24
D.3	Determination of Chemical Composition of the Output Refrigerants (VFCs/VHCs) from the Step 1.....	24
D.4	Determination of Residual VFC and VHC in PU fraction – Example 1	24
D.4.1	Preparation for Analysis in the Laboratory	24
D.4.2	Analysis.....	25
D.4.3	Analysis Repetition	25
D.4.4	Chromatographic Settings	25
D.5	Determination of Residual VFC in PU Fraction – Example 2	25
D.5.1	Analysis.....	25
D.5.2	Analysis Repetition	26
D.5.3	Chromatographic Settings	26
D.6	Determination of foreign matters content in PU fraction.....	26
D.6.1	Thermogravimetric Analysis- Example 1.....	26
D.6.2	Selective extraction Method- Example 2.....	27

D.7	Visual analysis method for residual PU on metal and plastics fractions	28
D.8	Determination of chemical composition of the output blowing agents (VFCs/VHCs) from the step 2	29
D.9	Determination of chemical composition of the collected acids or their neutralization products from the combustion in step 3	29
D.9.1	General.....	29
D.9.2	Chlorine analysis	29
D.9.3	Fluorine analysis.....	29
D.9.4	Sodium analysis.....	29
D.9.5	pH measurement.....	30
D.9.6	Analysis repetition.....	30
D.10	Determination of Chemical composition of the alkaline solution from the step 3	30
D.10.1	General.....	30
D.10.2	Chlorine analysis	30
D.10.3	Fluorine and Sodium analysis.....	30
D.10.4	pH measurement.....	30
D.10.5	Analysis repetition.....	30
D.11	Determination of VFC and VHC mass flow in raw gas and clean gas for step 3	31
D.11.1	General.....	31
D.11.2	Blowing agent in the raw gas	31
D.11.3	Blowing agent in the clean gas	31
D.11.4	Blowing agent recovered	31
	Bibliography	32

Foreword

This document (CLC/TS 50574-2:2014) has been prepared by CLC/TC 111X "Environment".

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association.

Currently in preview, click buy full version

Introduction

This Technical Specification is intended to support EN 50574:2012 by providing further normative requirements for the assessment of de-pollution for treatment of end-of-life household appliances containing volatile fluorocarbons or volatile hydrocarbons.

Any characteristic numbers and target values within this Technical Specification are based on evidence gathered by technical experts over a time period of more than two years when performing test according to EN 50574:2012.

Currently in preview, click buy full version

1 Scope

EN 50574:2012 gives the responsible take-back parties the task of defining target values. This Technical Specification provides applicable target values, characteristic numbers; sampling and analysis procedures, as well as monitoring and reporting requirements. Furthermore, this Technical Specification provides validation methodologies for tests and the daily business of the treatment plants as defined in EN 50574:2012.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50574:2012, *Collection, logistics & treatment requirements for end-of-life household appliances containing volatile fluorocarbons or volatile hydrocarbons*

3 Terms and definitions

For the purposes of this document the terms and definitions given in EN 50574:2012 and the following apply.

3.1

characteristic numbers

values of parameters (except target values and limit values) used to determine VFC and VHC recovery performance for step 1 (e.g. q_{Mtot} , S_k), step 2 (e.g. f_{VFC} , f_{VHC}) and step 3, and values of parameters used to assess certain results of the plant performance audit (e.g. t_{max} in step 1 and $w_{i,VFC}$ and $w_{i,VHC}$ in step 2)

3.2

monitoring

system to acquire and store quantitative information about the material input and material output streams of the treatment facility (step 1, step 2, step 3) and related calculation of the recovery performance

Note 1 to entry: The scope of the required monitoring procedures is detailed in 5.5 in EN 50574:2012.

3.3

reporting

all information used to notify the results of the monitoring system

Note 1 to entry: The scope and content of the information to be reported is detailed in 5.6 in EN 50574:2012.

4 Target values

4.1 Step 1

A.2.7 of EN 50574:2012 define the target values for step 1 treatment.

4.2 Step 2: tv_{VFC} , tv_{VHC}

4.2.1 General

Clause 6 of EN 50574:2012 requires that target values for the recovery of VFCs and VHCs for Step 2 treatment (tv_{VFC} , tv_{VHC}) shall be defined.

The target values (tv_{VFC} and tv_{VHC}) represent the minimum masses of VFC and VHC to be recovered per kilogram of VFC-PU or VHC-PU foam respectively. The target value tv_{VFC} is calculated either from M_{VFC} , which is the "potentially recoverable" mass of VFC based on the VFC-PU foam in the plant's PU input stream, or from D_{VFC} , which is the mass of VFC blowing agent determined based on the plant's PU output stream. The