



BSI Standards Publication

**Electricity metering data
exchange — Lower layer
PLC profile using Adaptive
Multi Carrier Spread-Spectrum
(AMC-SS) modulation**

National foreword

This Published Document is the UK implementation of CLC/TS 50590:2015.

The UK participation in its preparation was entrusted to Technical Committee PEL/13, Electricity Meters.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2015.

Published by BSI Standards Limited 2015

ISBN 978 0 580 85918 2

ICS 35.240.60; 91.140.50

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 May 2015.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

ICS 35.240.60; 91.140.50

English Version

Electricity metering data exchange - Lower layer PLC profile using Adaptive Multi Carrier Spread-Spectrum (AMC-SS) modulation

This Technical Specification was approved by CENELEC on 2014-11-11.

CENELEC members are required to announce the existence of this TS in the same way as for an EN and to make the TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

CONTENTS

Foreword	5
1 Scope.....	6
2 Normative references	6
3 Terms, definitions and acronyms	6
3.1 Terms and definitions	6
3.2 Acronyms	8
4 General description	9
5 PHY layer specification	12
5.1 Overview	12
5.2 PHY protocol data unit	13
5.2.1 PPDU structure	13
5.2.2 PHY header	15
5.2.3 PHY data	15
5.3 PHY frame transmission	16
5.3.1 General	16
5.3.2 Forward error correction encoding	18
5.3.3 Interleaving	19
5.3.4 PSK / DPSK mapping	20
5.3.5 Carrier frequency mapping	22
5.3.6 Modulation	24
5.4 EMC requirements	27
5.5 PHY layer services	27
5.5.1 General	27
5.5.2 P_data.request	28
5.5.3 P_data.indication	28
6 Data link layer specification	30
6.1 Overview	30
6.2 MAC protocol data unit	30
6.2.1 MAC PDU structure	30
6.2.2 Frame forwarding sector number	32
6.2.3 MAC-channel identification number	33
6.2.4 Network identification number	33
6.2.5 Link address	33
6.2.6 Data block length	33
6.2.7 Total number of frame retransmissions	33
6.2.8 Frame retransmission down counter	34
6.2.9 Reference zero-crossing delay	34
6.2.10 Logical link control field	34
6.2.11 Frame header check sequence	38
6.2.12 Data block and frame check sequence	38
6.2.13 Scrambling	38
6.3 MAC frame transmission	38
6.4 The LLC protocol data unit	41

6.5	Message transmission in LLC layer	41
6.5.1	General	41
6.5.2	DL_data.request	42
6.5.3	DL_data_identifier.confirm	43
6.5.4	DL_data.indication	45
6.5.5	DL_data.response	46
6.5.6	DL_data.confirm	47
6.5.7	DL_data_ack.response	47
6.5.8	DL_data_ack.confirm	48
6.5.9	DL_control.indication	49
6.5.10	Transmission from slave node	50
6.5.11	Transmission from master node	53
6.5.12	Acknowledged unicast transmission	55
6.6	Clock synchronisation	61
6.7	Status enquiry	62
6.8	PHY-link test	62
6.9	PHY quality data enquiry	63
7	Layer-2-network capability	63
7.1	Overview	63
7.2	Registration procedure	64
7.2.1	General	64
7.2.2	Registration of a new slave node	65
7.2.3	Data link connection time-out	68
7.2.4	Re-establishing of data link connection after power-down	68
7.3	Coordination of master nodes	69
7.4	Cell change by slave node	69
Annex A	(normative)	72
A.1	Window functions	72
Annex B	(normative) Logical Link Control Functions	101
B.1	Master node messages for data link control (PRM=1, DLS=0)	101
B.2	Master node messages for higher layer servicing (PRM=1, DLS=1)	111
B.3	Slave node messages for data link control functions (PRM=0, DLS=0)	117
B.4	Slave node messages for higher layer servicing (PRM=0, DLS=1)	125
Annex C	(informative) Examples of network scenarios	127
C.1	Example of a network	127
C.1.1	General	127
C.2	Examples of an s-MN becoming a master node	127
Annex D	(normative) Configuration and time parameters	130
TABLE OF FIGURES		
Figure 1	– Layers of AMC-SS profile	10
Figure 2	– Primitives	11
Figure 3	– PHY layer processing steps during PPDU transmission	12
Figure 4	– Bit-oriented PPDU structure without TS	13
Figure 5	– Structure of transmit signal (PHY frame) consisting of overlapped modulated symbols	14

Figure 6 – General structure of a convolutional encoder with constraint length 7, used in this particular example (solid connections) for rate $\frac{1}{2}$ encoder	18
Figure 7 – Combining of overlapped modulated symbols	26
Figure 8 – Combining of overlapped modulated symbols followed by IFI	27
Figure 9 – Primitives between layer 2 and layer 1	28
Figure 10 – MPDU structure	31
Figure 11 – Formats of logical link control field	31
Figure 12 – Pseudo-noise sequence generator	31
Figure 13 – Frame transmission procedure used by SEND/NO REPLY service	39
Figure 14 – Frame transmission procedure with simultaneous forwarding	40
Figure 15 – Frame transmission procedures used by REQUEST/RESPOND service	41
Figure 16 – Example of data collection by polling	51
Figure 17 – Example of data collection using quick-check procedure	53
Figure 18 – Example of acknowledged unicast transmission with retry	56
Figure 19 – – Example of acknowledged multicast/broadcast transmission	58
Figure 20 – – Example of two multicast/broadcast transmissions with an error	59
Figure 21 – – Example of broadcast with message retransmission	60
Figure 22 – Example of non-acknowledged multicast/broadcast transmission	61
Figure 23 – Example of PHY link test	62
Figure 24 – Example of link quality enquiry	63
Figure 25 – Example of slave node registration procedure	66
Figure 26 – Example of new multicast address assignment	67
Figure 27 – Example of cell change by slave node	70
Figure C.1 – Example of NSC	140
Figure C.2 – Example of an s-MN becoming a master node	141
Figure C.3 – Example of cell splitting	141
Figure C.4 – Example of switching off a p-MN	142
Figure C.5 – Example of cell spreading in NSC	142

Foreword

This document (CLC/TS 50590:2015) has been prepared by CLC/TC 13 "Electrical energy measurement and control".

The following date is fixed:

- latest date by which the existence of (doa) 2015-07-24
this document has to be announced
at national level

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association.

1 Scope

This Technical Specification specifies the physical layer, medium access control layer and logical link control layer for communication on an electrical distribution network between a master node and one or more slave nodes using a compatibly extendable form (CX1) of Adaptive Multi-Carrier Spread Spectrum (AMC-SS) technique. The adaptive cellular communication network technology provided in this specification may be used for automated meter reading as well as for other distribution network applications.

The physical layer provides a modulation technique that efficiently utilizes the allowed bandwidth within the CENELEC A band (3 kHz – 95 kHz), offering a very robust communication in the presence of narrowband interference, impulsive noise, and frequency selective attenuation. The physical layer of AMC-SS is defined in Clause 5 of CLC/TS 50590:2015.

The data link (DL) layer consists of three parts, the 'Medium Access Control' (MAC) sub-layer, the Logical Link Control (LLC) sub-layer and the 'Convergence' sub-layer. The data link layer allows the transmission of data frames through the use of the power line physical channel. It provides data services, frame integrity control, routing, registration, multiple access, and cell change functionality. The MAC sub-layer and the LLC sub-layer of AMC-SS are defined in Clause 6 of CLC/TS 50590:2015. The Convergence sub-layer is defined in this document.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments), applies.

EN 50065-1, *Signaling on low-voltage electrical installations in the frequency range 3 kHz to 148,5 kHz – Part 1: General requirements, frequency bands and electromagnetic disturbances*

DIN 43863–5:2012-04, *Identification number for measuring devices applying for all manufacturers*

3 Terms, definitions and acronyms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1

device identifier

property that universally identifies a node

3.1.2

frame forwarding

procedure of PHY frame retransmission by a slave node or simultaneously by several slave nodes