



BSI Standards Publication

Packaging of components for automatic handling

Part 3-4: Packaging of surface mount components on continuous embossed tapes for Auto Loading Feeder

National foreword

This Published Document is the UK implementation of IEC TR 60286-3-4:2021.

The UK participation in its preparation was entrusted to Technical Committee W/-, Consumer Products and Services Sector Policy and Strategy Committee.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication is not to be regarded as a British Standard.

© The British Standards Institution 2021
Published by BSI Standards Limited 2021

ISBN 978 0 399 15671 3

ICS 21.010; 31.240

Compliance with a Published Document cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 November 2021.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------



IEC TR 60286-3-4

Edition 1.0 2021-10

TECHNICAL REPORT



**Packaging of components for automatic handling –
Part 3-4: Packaging of surface mount components on continuous embossed
tapes for Auto Loading Feeder**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.020; 31.240

ISBN 978-2-8322-1041-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms, definitions and symbols.....	7
3.1 Terms and definitions.....	7
3.2 Symbols.....	8
4 Overview of Auto Loading Feeder.....	8
4.1 Overview and features of Auto Loading Feeder.....	
4.2 Methods and mechanisms of automatically exposing the pockets in using Auto Loading Feeder.....	9
5 Discussion items for requirements for emboss taping for Auto Loading Feeder.....	10
5.1 General.....	10
5.2 Required dimensions for the cover tape sealed positions	10
5.3 Required dimensions for the distance between the upper side of the carrier tape and the top surface of a component in using Auto Loading Feeder.....	11
5.4 Necessity of M_1 and M_2 as the cover tape sealed positions.....	11
5.5 Necessity of K_1 as the distance between the upper side of the carrier tape and the top surface of a component	12
5.6 Necessity of K_2 as the recessed part in a cross-bar section.....	13
5.7 Necessity of K_3 as the distance between the upper side of the recessed part in a cross-bar section and the top surface of a component.....	14
5.8 Sealing method for the cover tape	15
5.9 Dent of the cover tape over the pockets.....	15
5.10 Lower limit of peel-off strength of the cover tape.....	16
5.11 Adhesion of component's component cover tape.....	16
5.12 Bottom hole of pockets of the carrier tape.....	16
5.13 Maximum trailer length	17
5.14 Fixing the tail end of the carrier tape.....	17
6 Summary of the discussions: considered requirements and dimensions for emboss taping for Auto Loading Feeder.....	17
6.1 General.....	17
6.2 Required dimensions for the cover tape sealed positions	18
6.3 Required dimensions for the distance between the upper side of the carrier tape and the top surface of a component	18
6.4 Required specifications for the sealing method of the cover tape	18
6.5 Required specifications for maximum trailer length	18
7 Possible problems for emboss taping for Auto Loading Feeder.....	18
7.1 General.....	18
7.2 Relationship between sealed positions of the cover tape and openings of the pockets.....	18
7.3 Recessed part in a cross-bar section	19
7.4 Dot seals	19
7.5 Thickness of embossed carrier tape.....	20
7.6 Relationship between Auto Loading Feeder and tape camber specified in IEC 60286-3	21

Annex A (informative) Methods and mechanisms of automatically exposing pockets in using Auto Loading Feeder	22
A.1 General.....	22
A.2 Single-door method.....	22
A.3 Double-door method	22
Annex B (informative) Glossary.....	24
Bibliography.....	26
Figure 1 – Specified dimensions for emboss taping for Auto Loading Feeder	8
Figure 2 – Operation and features when another tape is re-supplied automatically by the Auto Loading Feeder.....	9
Figure 3 – Example of a part of embossed carrier tape with a recessed part in a cross-bar section.....	13
Figure 4 – Relationship between the cover tape and the exposure processing mechanism of the pocket	13
Figure 5 – Relationship between the exposure processing mechanism of the pocket and convex of carrier tape	14
Figure 6 – Example dent of the cover tape over the pocket.....	15
Figure 7 – Leader part and trailer part.....	18
Figure 8 – Dimension B_1 and sealed positions	19
Figure 9 – Example of dot seal.....	20
Figure 10 – Relationship between embossed carrier tape thickness and component exposure process	21
Figure 11 – Tape camber (top view).....	21
Figure A.1 – Overview of the single-door method.....	22
Figure A.2 – Overview of the double-door method.....	23
Table 1 – Symbols used in figures and tables	8
Table 2 – The cover tape sealed positions required for emboss taping for Auto Loading Feeder.....	11
Table 3 – Distance between the upper side of the carrier tape and the top surface of a component required for emboss taping for Auto Loading Feeder.....	11
Table B.1 – Glossary of mounter and feeder related terms.....	24

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PACKAGING OF COMPONENTS FOR AUTOMATIC HANDLING –**Part 3-4: Packaging of surface mount components
on continuous embossed tapes for Auto Loading Feeder**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. For this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publications"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TR 60286-3-4 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment. It is a Technical Report.

The text of this Technical Report is based on the following documents:

Draft	Report on voting
40/2844/DTR	40/2866/RVDTR

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Report is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available

at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 60286 series, published under the general title *Packaging of components for automatic handling*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This Technical Report was developed by the technical committee 40 working group 36 on components packaging, in which the members, such as mounter manufacturers, component manufacturers and packaging material manufacturers, had proposed, considered and discussed the possible standardization of the application of Auto Loading Feeder to enable automatically exchange SMD continuous tapes, using paper carrier tape during mounter operation, aiming to support IEC 60286-3, Edition 6, issued in 2019.

This document includes data expressed in the form of provisions, such as requirements or recommendations. These data, however, do not claim to be provisions and are just suggested as the results of the discussion.

The International Electrotechnical Commission (IEC) draws attention to the fact that it is pointed out that compliance with this document may involve the use of a trademark concerning Auto Loading Feeder given in 3.1.1.

- Trademark ... AUTO LOADING FEEDER™
- Trademark registration number ... No.5983611 (Japan)

IEC takes no position concerning the evidence, validity and scope of this trademark right.

The holder of this trademark right has assured the IEC that he/she is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this trademark right is registered with IEC. Information may be obtained from:

- Name of holder of trademark right ... **Yamaha Motor Co., Ltd.**
Address ... 2500 Shingai, Iwata, Shizuoka, Japan
- Name of holder of trademark right ... **FUJI CORPORATION**
Address ... 19 Chausuyama., Yamamachi, Chiryu, Aichi, Japan
- Name of holder of trademark right ... **Panasonic Corporation**
Address ... 2-7, Matsuba-cho, Kadoma, Osaka, Japan

Attention is drawn to the possibility that some of the elements of this document may be the subject of trademark rights other than those identified above. IEC shall not be held responsible for identifying any or all such trademark rights.

PACKAGING OF COMPONENTS FOR AUTOMATIC HANDLING –

Part 3-4: Packaging of surface mount components on continuous embossed tapes for Auto Loading Feeder

1 Scope

This part of IEC 60286 considers the proposed requirements for emboss taping for the Auto Loading Feeder mechanism to mount electric components without leads or with stump type leads used for electric circuits. This document is applicable to the embossed carrier tape, with single round sprocket holes, with tape pitches of 2 mm or more (nominal tape width: 8 mm only) among the tapes of Type 2a in IEC 60286-3.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes the statement of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60286-3:2019, *Packaging of components for automatic handling – Part 3: Packaging of surface mount components on continuous tapes*

3 Terms, definitions and symbols

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

NOTE Annex B features a glossary of mounter and feeder related terms.

3.1.1

Auto Loading Feeder

AUTO LOADING FEEDER™

tape feeder that can keep supplying components by automatically carrying a tape of re-supplied SMD at the filling-in position into the components supply position, just after the components in the tape of previously supplied SMD are fed up during the assembly production

Note 1 to entry: Auto Loading Feeder has the mechanism that the cover tape of a SMD tape is automatically cut or peeled off to expose the pockets during the operation to supply components.

3.1.2

seal

bonding of a part of the top cover tape and a part of the carrier tape

Note 1 to entry: The top cover tapes are classified as heat welding type and adhesive type by the way to bond itself on the carrier tape.