



BSI Standards Publication

# Mechanical structures for electrical and electronic equipment — Dimensions of mechanical structures of the 482,6 mm (19 in) series

Part 3-1: Technological schemes and applications

## National foreword

This Published Document is the UK implementation of IEC TR 60297-3-1:2023.

The UK participation in its preparation was entrusted to Technical Committee EPL/48, Electromechanical components and mechanical structures for electronic equipment.

A list of organizations represented on this committee can be obtained on request to its committee manager.

### Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2023  
Published by BSI Standards Limited 2023

ISBN 978 0 539 21341 2

ICS 31.240

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 28 February 2023.

### Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

---



# IEC TR 60297-3-1

Edition 1.0 2023-02

## TECHNICAL REPORT



**Mechanical structures for electrical and electronic equipment – Dimensions of mechanical structures of the 482,6 mm (19 in) series  
Part 3-1: Technological schemes and applications**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

ICS 31.240

ISBN 978-2-8322-6398-3

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	8
2 Normative references.....	8
3 Terms and definitions.....	9
4 Technological scheme of the IEC 60297 series.....	10
4.1 Development history and technological background.....	10
4.1.1 General.....	10
4.1.2 Development of the 482,6 mm (19 in) subracks and associated plug-in units (19-inch subrack system).....	10
4.1.3 Adoption of IEC 60603-2 connector in the 482,6 mm (19 in) subracks and associated plug-in units ("19-inch subrack system").....	13
4.1.4 Modular structure of the 482,6 mm (19 in) series.....	14
4.2 Extended specifications of the 486,2 mm (19 in) series.....	16
4.2.1 General.....	16
4.2.2 Extended specifications of 19-inch subrack system from the IEC 60917 series.....	16
4.2.3 Enhanced 19-inch subrack system from the market applications.....	18
5 Definition domains of the 482,6 mm (19 in) series standards.....	18
6 Prospect for further applications and standards development of the 19-inch subrack system.....	20
Annex A (informative) Applicable connectors to the 482,6 mm (19 in) subracks and associated plug-in units.....	21
A.1 General conditions of the applicable connectors.....	21
A.2 List of applicable connectors.....	22
Annex B (informative) IEEE and VITA standards related with the 482,6 mm (19 in) series.....	25
B.1 Subracks and associated plug-in units.....	25
B.2 Mezzanine card standards.....	25
B.3 Conduction cooling.....	28
B.4 Environmental specifications.....	31
Bibliography.....	33
Figure 1 – Unified printed board size accommodated with height and depth of the subracks (recommended dimension matrix).....	12
Figure 2 – Typical image of 19-inch subrack system (6U subrack with plug-in units, where the plug-in units are interconnected by a backplane fixed on the subrack frame).....	13
Figure 3 – Modular structure of the 482,6 mm (19 in) series.....	15
Figure 4 – Basic dimensions of the modular structure of the 482,6 mm (19 in) series.....	16
Figure 5 – Definition domains of the 482,6 mm (19 in) series standards.....	20
Figure A.1 – Dimensional relations of the connectors within mating condition, in the 482,6 mm (19 in) subracks and associated plug-in units.....	22
Figure B.1 – Examples of mezzanine card size (coordination dimensions as 25 mm grid) and mezzanine card boundary envelope in IEEE 1301.4.....	26
Figure B.2 – Example of adoption of CMC single size on 6U depth 160 mm plug-in unit, and outline of single size CMC (common mezzanine card) in IEEE 1386.....	26
Figure B.3 – Outline of the CCA of 6U VME module in IEEE 1101.2.....	29

Figure B.4 – Assembly of VPX-REDI 3U conduction cooled plug-in unit .....	30
Figure B.5 – Assembly of VPX-REDI 3U conduction cooled chassis .....	30
Table A.1 – Applicable connectors to the 482,6 mm (19 in) subracks and associated plug-in units .....	23
Table B.1 – IEEE and VITA standards for mezzanine cards applied on 19-inch subrack system .....	27
Table B.2 – Environmental class for the plug-in units in ANSI/VITA 47 .....	31

Currently in preview, click buy full version

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MECHANICAL STRUCTURES FOR ELECTRICAL AND  
ELECTRONIC EQUIPMENT – DIMENSIONS OF MECHANICAL  
STRUCTURES OF THE 482,6 mm (19 in) SERIES**

**Part 3-1: Technological schemes and applications**

**FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use, and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, accept IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the informative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TR 60297-3-1 has been prepared by subcommittee 48D: Mechanical structures for electrical and electronic equipment, of IEC technical committee 48: Electrical connectors and mechanical structures for electrical and electronic equipment. It is a Technical Report.

The text of this Technical Report is based on the following documents:

Draft	Report on voting
48D/756/DTR	48D/757/RVDTR

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Report is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/publications](http://www.iec.ch/publications).

A list of all parts in the IEC 60297 series, published under the general title *Mechanical structures for electrical and electronic equipment – Dimensions of mechanical structures of the 482,6 mm (19 in) series*, can be found on the IEC website.

Future documents in this series will carry the new general title as cited above. Titles of existing documents in this series will be updated at the time of the next edition.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## INTRODUCTION

The IEC 60297 series contains dimensional definitions of the entire mechanical structure layers from level 1 to level 4 for electrical and electronic equipment practices. Nowadays, the IEC 60917-1 generic standard defines all the elements and components in the mechanical structure layers from level 1 to level 4, and they are adopted for the IEC 60917-2 (metric) series. The original concept of the mechanical structure layers was established in DIN 41494 and introduced into the former IEC 297 series, later republished as the IEC 60297 series. Therefore, the second edition of IEC 60917-1:2019 (generic) categorizes the existing IEC 60297 series as a "conventional standard (legacy system)", which contains the detail dimensions of the structure levels from level 1 to level 4 as well as the structure levels of the IEC 60917-2 series (metric).

Applications of the IEC 60297 series are divided into two different perceptions by the users:

- a) the traditional 19-inch racks and chassis configurations, and
- b) the 19-inch subrack system.

The latter has been providing effective and rational solutions for the critical issues on interconnection and packaging for electronic equipment, which have been in a close relationship with the IEC connector standards of IEC SC 48B, in the microelectronics era since the 1960s.

In the 1980s, the 19-inch subrack system was adopted as the mechanical specifications for open computer bus standards in the IEEE and other manufacturers' associations or industrial consortia. In such fields, not only newly developed high-performance connectors have been applied, but also advanced mechanical features have been developed, based on the 19-inch subrack system. These new technologies have been standardized, and their efforts considered as development for extended specifications for the 19-inch subrack system in IEC SC 48D.

From these points of view, this Technical Report has been prepared to provide the following information, not only for users of the IEC 60297 series standards, but also for the engineers who will develop new architectures or hardware for advanced ICT equipment or systems for the current IoT or Industry 4.0 era:

- information on technological schemes of the IEC 60297 series standards, which have been in development for over 40 years in IEC TC 48/SC 48D. (In the market for industrial electronics and information and communication technology (ICT), there are active users who take the two different approaches regarding the application or adoption of the technologies from the IEC 60297 series standards);
- the technological background of the standards, and the principles or concepts, which had been adopted to cope with the technological evolutions through the development process of the IEC 60297 series standards in IEC SC 48D;
- in standardization for mechanical structures for electrical and electronic equipment in IEC SC 48D, IEC 60917-1 has been published as the generic standard for modular order for the development of mechanical structures for electrical and electronic equipment practices. The IEC 60297 series also considered that the dimensions of the mechanical structure are partly in accordance with IEC 60917-1. This document clarifies the relationship between the IEC 60917 series and the IEC 60297 series;
- to introduce the domain of each part of the IEC 60297 series for structures for electrical and electronic equipment.

Annex A introduces applicable connectors for the 19-inch subrack system, including newly developed high-performance connectors which are not (yet) published as IEC SC 48B standards.

Annex B introduces relationships and compatibilities between the 19-inch subrack system standards in IEC SC 48D, the IEEE standards for the 19-inch subrack and plug-in units, and other industrial standards for the mechanical specifications. It also shows outlines of the extended mechanical features adopted for the 19-inch subrack system. These features include the implementations of the mezzanine cards and the conduction cooled system, and they are not yet defined in IEC SC 48D standards.

Through the study of the additional information given in Annex A and Annex B, further prospects on applications of the 19-inch subrack system will be seen, and the directions of the next standards development in IEC TC 48/SC 48D will be provided.

Currently in preview, click buy full version

# MECHANICAL STRUCTURES FOR ELECTRICAL AND ELECTRONIC EQUIPMENT – DIMENSIONS OF MECHANICAL STRUCTURES OF THE 482,6 mm (19 in) SERIES

## Part 3-1: Technological schemes and applications

### 1 Scope

This part of IEC 60297 provides information on the technological schemes of the IEC 60297 series, and shows how to apply the 19-inch series standards for the mechanical structure practices for electrical and electronic equipment.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60297-3-100:2008, *Mechanical structures for electronic equipment – Dimensions of mechanical structures of the 482,6 mm (19 in) series – Part 3-100: Basic dimensions of front panels, subracks, chassis, racks and cabinets*

IEC 60297-3-101:2004, *Mechanical structures for electronic equipment – Dimensions of mechanical structures of the 482,6 mm (19 in) series – Part 3-101: Subracks and associated plug-in units*

IEC 60297-3-102:2004, *Mechanical structures for electronic equipment – Dimensions of mechanical structures of the 482,6 mm (19 in) series – Part 3-102: Injector/extractor handle*

IEC 60297-3-103:2004, *Mechanical structures for electronic equipment – Dimensions of mechanical structures of the 482,6 mm (19 in) series – Part 3-103: Keying and alignment pin*

IEC 60297-3-104:2006, *Mechanical structures for electronic equipment – Dimensions of mechanical structures of the 482,6 mm (19 in) series – Part 3-104: Connector dependent interface dimensions of subracks and plug-in units*

IEC 60297-3-105:2008, *Mechanical structures for electronic equipment – Dimensions of mechanical structures of the 482,6 mm (19 in) series – Part 3-105: Dimensions and design aspects for 1U high chassis*

IEC 60297-3-106:2010, *Mechanical structures for electronic equipment – Dimensions of mechanical structures of the 482,6 mm (19 in) series – Part 3-106: Adaptation dimensions for subracks and chassis applicable with metric cabinets or racks in accordance with IEC 60917-2-1*

IEC 60297-3-107:2012, *Mechanical structures for electronic equipment – Dimensions of mechanical structures of the 482,6 mm (19 in) series – Part 3-107: Dimensions of subracks and plug-in units, small form factor*

IEC 60297-3-108:2014, *Mechanical structures for electronic equipment – Dimensions of mechanical structures of the 482,6 mm (19 in) series – Part 3-108: Dimensions of R-type subracks and plug-in units*