



BSI Standards Publication

Performance of high-voltage direct current (HVDC) systems with line-commutated converters

Part 3: Dynamic conditions

National foreword

This Published Document is the UK implementation of IEC TR 60919-3:2009+A2:2021. It supersedes PD IEC/TR 60919-3:2009+A1:2016, which is withdrawn.

The start and finish of text introduced or altered by amendment is indicated in the text by tags. Tags indicating changes to IEC text carry the number of the IEC amendment. For example, text altered by IEC amendment 1 is indicated by A1 A1.

The UK participation in its preparation was entrusted to Technical Committee PEL/22, Power electronics.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided "as is", and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication is not to be regarded as a British Standard.

© The British Standards Institution 2022
Published by BSI Standards Limited 2022

ISBN 978 0 539 16663 7

ICS 29.200; 29.240.99

Compliance with a Published Document cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 January 2010.

Amendments/corrigenda issued since publication

Date	Text affected
30 April 2016	Implementation of IEC amendment 1:2016
30 June 2022	Implementation of IEC amendment 2:2021



IEC/TR 60919-3

Edition 2.0 2009-10

TECHNICAL REPORT

RAPPORT TECHNIQUE

**Performance of high-voltage direct current (HVDC) systems with line-commutated converters –
Part 3: Dynamic conditions**

**Fonctionnement des systèmes à courant continu haute tension (CCHT) munis
de convertisseurs commutés par le réseau –
Partie 3: Conditions dynamiques**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX

X

ICS 29.200; 29.240.99

ISBN 2-8318-1065-0

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references	6
3 Outline of HVDC dynamic performance specifications	7
3.1 Dynamic performance specification.....	7
3.2 General comments	8
4 AC system power flow and frequency control	8
4.1 General.....	8
4.2 Power flow control.....	8
4.2.1 Steady-state power control requirements	8
4.2.2 Step change power requirement.....	9
4.3 Frequency control.....	11
5 AC dynamic voltage control and interaction with reactive power sources	12
5.1 General.....	12
5.2 Voltage and reactive power characteristics of an HVDC substation and other reactive power sources.....	12
5.2.1 General	12
5.2.2 Converter as active/reactive power source.....	13
5.2.3 Voltage characteristics of a.c. networks depending on the power loading at the busbar of the HVDC substation.....	15
5.2.4 Voltage characteristics of a.c. filters, capacitor banks and shunt reactors for power compensation at the HVDC substation	17
5.2.5 Voltage characteristics of static var compensator (SVC).....	17
5.2.6 Voltage characteristics of synchronous compensator (SC).....	18
5.2.7 Voltage characteristics of static synchronous compensator (STATCOM)	18
5.3 Voltage deviations on the busbar of an HVDC substation	18
5.4 Voltage and reactive power interaction of the substation and other reactive power sources	19
5.4.1 HVDC converters, switchable a.c. filters, capacitor banks and shunt reactors.....	19
5.4.2 HVDC converters, switchable reactive power sources, SVC.....	20
5.4.3 HVDC converters, switchable reactive power sources and synchronous compensators.....	21
5.4.4 HVDC converters, switchable reactive power sources, STATCOM	21
6 AC system transient and steady-state stability	22
6.1 General.....	22
6.2 Characteristics of active and reactive power modulation.....	22
6.2.1 General	22
6.2.2 Large signal modulation.....	23
6.2.3 Small signal modulation	24
6.2.4 Reactive power modulation.....	24
6.3 Classification of network situations	25
6.4 AC network in parallel with the HVDC link.....	25
6.5 Improvement of the stability within one of the connected a.c. networks.....	29
6.6 Determination of the damping control characteristics.....	29
6.7 Implementation of the damping controller and telecommunication requirements.....	30

7	Dynamics of the HVDC system at higher frequencies	30
7.1	General	30
7.2	Types of instability	31
7.2.1	Loop instability (harmonic instability)	31
7.2.2	Current loop instability	31
7.2.3	Core saturation instability	31
7.2.4	Harmonic interactions	31
7.3	Information required for design purposes	32
7.4	Means available for preventing instabilities	32
7.5	Damping of low order harmonics by control action	33
7.6	Demonstration of satisfactory performance at higher frequencies	33
8	Subsynchronous oscillations	34
8.1	General	34
8.2	Criteria for subsynchronous torsional interaction with an HVDC system	35
8.3	Screening criteria for identifying generator units susceptible to torsional interactions	36
A1) 8.4	Performance considerations for utilizing subsynchronous damping controls	37 A1)
8.5	Performance testing	37
8.6	Turbine generator protection	37
9	Power plant interaction	38
9.1	General	38
9.2	Specific interactions	38
9.2.1	General	38
9.2.2	Frequency variation effects	38
9.2.3	Frequency controls interactions	38
9.2.4	Overvoltage effects	39
9.2.5	Harmonics	39
9.2.6	Subsynchronous and shaft impact effects	39
9.2.7	Resonance	40
9.2.8	Overvoltages	40
9.2.9	Stresses on a.c. switching equipment	40
9.2.10	Under-frequency	40
9.2.11	Starting procedure for an HVDC converter	40
9.3	Special considerations for a nuclear plant	40
	Bibliography	41
	Figure 1 – Elements for reactive power compensation at an HVDC substation	13
	Figure 2 – P/Q diagram of a converter	14
	Figure 3 – Reactive power requirements of a weak a.c. system depending on the active power loading for various constant voltage characteristics at the a.c. bus of an HVDC substation	16
	Figure 4 – Representation of the a.c. network	16
	Figure 5 – An example of voltage – current characteristic showing possible current modulation range in the absence of telecommunication between rectifier and inverter	24
	Figure 6 – Reactive power modulation in an HVDC transmission operating at minimum extinction angle γ_{min}	26
	Figure 7 – Reactive power modulation in an HVDC transmission operating at extinction angle $\gamma > \gamma_{min}$	27
	Figure 8 – Stability improvement of an a.c. link or network	28
	Figure 9 – Principle arrangements of a damping controller	28

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**PERFORMANCE OF HIGH-VOLTAGE DIRECT CURRENT (HVDC)
SYSTEMS WITH LINE-COMMUTATED CONVERTERS –****Part 3: Dynamic conditions**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as far as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC 60919-3, which is a technical report, has been prepared by subcommittee 22F: Power electronics for electrical transmission and distribution systems, of IEC technical committee 22: Power electronic systems and equipment.

This second edition cancels and replaces the first edition, which was issued as a technical specification in 1999. It constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) this report concerns only line-commutated converters;
- b) significant changes have been made to the control system technology;
- c) some environmental constraints, for example audible noise limits, have been added;
- d) the capacitor coupled converters (CCC) and controlled series capacitor converters (CSCC) have been included.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
22F/183/DTR	22F/192/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60919 series, under the general title: *Performance of high-voltage direct current (HVDC) systems with line-commutated converters*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

PERFORMANCE OF HIGH-VOLTAGE DIRECT CURRENT (HVDC) SYSTEMS WITH LINE-COMMUTATED CONVERTERS –

Part 3: Dynamic conditions

1 Scope

This Technical Report provides general guidance on the dynamic performance of high-voltage direct current (HVDC) systems. Dynamic performance, as used in this specification, is meant to include those events and phenomena whose characteristic frequencies or time domain cover the range between transient conditions and steady state. It is concerned with the dynamic performance due to interactions between two-terminal HVDC systems and related a.c. systems or their elements such as power plants, a.c. lines and buses, reactive power sources, etc. at steady-state or transient conditions. The two-terminal HVDC systems are assumed to utilize 12-pulse converter units comprised of three-phase bridge (double way) connections. The converters are assumed to use thyristor valves as bridge arms with gapless metal oxide arresters for insulation coordination and to have power flow capability in both directions. Diode valves are not considered in this specification. While multi-terminal HVDC transmission systems are not expressly considered, much of the information in this specification is equally applicable to such systems.

Only line-commutated converters are covered in this report, which includes capacitor commutated converter circuit configurations. General requirements for semiconductor line-commutated converters are given in IEC 60146-1-1, IEC 60146-1-2 and IEC 60146-1-3. Voltage-sourced converters are not considered.

This report (IEC 60919-3) which covers dynamic performance, is accompanied by publications for steady-state (IEC 60919-1) and transient (IEC 60919-2) performance. All three aspects should be considered when preparing two-terminal HVDC system specifications.

A difference exists between system performance specifications and equipment design specifications for individual components of a system. While equipment specifications and testing requirements are not defined herein, attention is drawn to those which would affect performance specification for a system. There are many possible variations between different HVDC systems, therefore these are not considered in detail. This report should not be used directly as a specification for a specific project, but rather to provide the basis for an appropriate specification tailored to fit actual system requirements for a particular electric power transmission scheme. This report does not intend to discriminate between the responsibility of users and manufacturers for the work specified.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60146-1-1, *Semiconductor converters – General requirements and line commutated converters – Part 1-1: Specification of basic requirements*

IEC/TR 60146-1-2, *Semiconductor converters – General requirements and line commutated converters – Part 1-2: Application guide*

IEC 60146-1-3, *Semiconductor converters – General requirements and line commutated converters – Part 1-3: Transformers and reactors*