



BSI Standards Publication

Environmental conditions — Vibration and shock of electrotechnical equipment

Part 7: Transportation by rotary wing aircraft

National foreword

This Published Document is the UK implementation of IEC TR 62131-7:2020.

The UK participation in its preparation was entrusted to Technical Committee GEL/104, Environmental conditions, classification and testing.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2020
Published by BSI Standards Limited 2020

ISBN 978 0 539 00168 6

ICS 19.040

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 May 2020.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------



TECHNICAL REPORT



**Environmental conditions – Vibration and shock of electrotechnical equipment –
Part 7: Transportation by rotary wing aircraft:**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 19.040

ISBN 978-2-8322-8237-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	7
4 Data source and quality.....	8
4.1 Vibration of Boeing CH-47 rotorcraft	8
4.2 Set down of underslung cargo from a Boeing CH-47 rotorcraft.....	9
4.3 Supplementary data.....	10
5 Intra data source comparison	12
5.1 General.....	13
5.2 Vibration of Boeing CH-47 rotorcraft	13
5.3 Set down of underslung cargo from a Boeing CH-47 rotorcraft.....	13
5.4 Supplementary data.....	14
6 Inter data source comparison	14
7 Environmental description	14
7.1 Physical sources producing mechanical vibrations	14
7.2 Environmental characteristics and severities.....	16
7.3 Derived test severities	17
8 Comparison with IEC 60721 (all parts) [16].....	18
9 Recommendations.....	21
Bibliography.....	50
Figure 1 – Typical vibration spectra for CH-47 rotorcraft during straight and level flight at 160 kn [1]	22
Figure 2 – Typical vibration spectra for CH-47 rotorcraft during hover [1].....	22
Figure 3 – Typical vibration spectra for CH-47 rotorcraft during transition to hover [1].....	23
Figure 4 – Typical vibration spectra for CH-47 rotorcraft during autorotation [1].....	23
Figure 5 – Comparison of CH-47 vibration overall RMS for different flight conditions [1]	24
Figure 6 – Comparison of CH-47 vibration RMS severities at rotor shaft frequency (r) for different flight conditions [1].....	25
Figure 7 – Comparison of CH-47 vibration RMS severities at rotor blade passing frequency (nr) for different flight conditions [1].....	26
Figure 8 – Comparison of CH-47 vibration RMS severities at second rotor blade passing frequency ($2nr$) for different flight conditions [1].....	27
Figure 9 – Comparison of CH-47 vibration RMS severities at third rotor blade passing frequency ($3nr$) for different flight conditions [1].....	28
Figure 10 – Comparison of CH-47 vibration RMS severities at fourth rotor blade passing frequency ($4nr$) for different flight conditions [1].....	29
Figure 11 – Comparison of CH-47 vibration RMS severities across cargo bay floor during hover [1].....	30
Figure 12 – Comparison of CH-47 vibration RMS severities across cargo bay floor during transition to hover manoeuvre [1].....	30
Figure 13 – Comparison of CH-47 vibration RMS severities across cargo bay floor during a transition to autorotation manoeuvre [1].....	31
Figure 14 – Comparison of CH-47 vibration RMS severities across cargo bay floor during straight and level flight [1].....	31

Figure 15 – CH-47 rotorcraft ISO container set down shock severities [2]	32
Figure 16 – Relative amplitude variations with airspeed for the Lynx rotorcraft [3].....	32
Figure 17 – Relative amplitude variations with airspeed for the Seaking rotorcraft [3]	33
Figure 18 – Relative amplitude variations with airspeed for the Chinook rotorcraft [3]	33
Figure 19 – Airframe to airframe relative amplitude variations for the Lynx rotorcraft [3]	34
Figure 20 – Comparison of fleet vibration statistics [5]	35
Figure 21 – Super Frelon rotorcraft measurements for X axis [6].....	36
Figure 22 – Super Frelon rotorcraft measurements for Y axis [6].....	36
Figure 23 – Super Frelon rotorcraft measurements for Z axis [6].....	37
Figure 24 – Vibration test severity derived for the CH-47 rotorcraft using the approach of Mil Std 810 [9]	37
Figure 25 – Vibration test severity derived for the transportation of equipment in CH-47 rotorcraft using the approach of STANAG 4370 AECTP 400 Method 401 Annex D [10]	38
Figure 26 – Vibration test severity for equipment carried as underslung loads in STANAG 4370 AECTP 400 Method 401 Annex D [10].....	38
Figure 27 – Rotorcraft specific vibration test severities for Chinook (CH-47) from Def Stan 00-35 [5].....	39
Figure 28 – Rotorcraft specific vibration test severities for Merlin from Def Stan 00-35 [5] ...	39
Figure 29 – Rotorcraft specific vibration test severities for Lynx Wildcat from Def Stan 00-35 [5].....	40
Figure 30 – Vibration test severities for underslung loads from Def Stan 00-35 [5]	40
Figure 31 – Rotorcraft specific vibration test severities for CH-47 from RTCA/DO-160 [11] and EUROCAE/ED-14 [12].....	41
Figure 32 – IEC 60721-3-2:1997 [17] – Stationary vibration random severities	41
Figure 33 – IEC TR 60721-4-2:2001 [18]– Stationary vibration random severities	42
Figure 34 – IEC 60721-3-2:1997 [17] – Stationary vibration sinusoidal severities	42
Figure 35 – IEC TR 60721-4-2:2001 [18] – Stationary vibration sinusoidal severities	43
Figure 36 – IEC 60721-3-2:1997 [17] – Shock severities	43
Figure 37 – IEC TR 60721-4-2:2001 [18] – Shock severities for IEC 60068-2-29:1987 [20] test procedure.....	44
Figure 38 – IEC TR 60721-4-2:2001 [18] – Shock severities for IEC 60068-2-27 [19] test procedure	44
Figure 39 – Comparison of CH-47 rotorcraft vibrations [1] with IEC 60721-3-2:1997 [17]	45
Figure 40 – Comparison of Super Frelon rotorcraft X axis vibrations [6] with IEC 60721-3-2:1997 [17].....	45
Figure 41 – Comparison of Super Frelon rotorcraft Y axis vibrations [6] with IEC 60721-3-2:1997 [17].....	46
Figure 42 – Comparison of Super Frelon rotorcraft Z axis vibrations [6] with IEC 60721-3-2:1997 [17].....	46
Figure 43 – Comparison of Mil Std 810 vibration test severity [9] with IEC 60721-3-2:1997 [17].....	47
Figure 44 – Comparison of AECTP 400 vibration test severity [10] with IEC 60721-3-2:1997 [17].....	47
Figure 45 – Comparison of Def Stan 00-35 vibration test severity [5] with IEC 60721-3-2:1997 [17].....	48
Figure 46 – Comparison of DO160 vibration test severity [11] with IEC 60721-3-2:1997 [17].....	48

Figure 47 – Comparison of underslung load vibration test severities [5] and [10] with IEC 60721-3-2:1997 [17]..... 49

Figure 48 – Comparison of CH-47 rotorcraft set down shock severities [2] with IEC 60721-3-2:1997 [17]..... 49

Table 1 – Typical structural dynamic excitation frequencies and their source 15

Currently in preview, click buy full version

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ENVIRONMENTAL CONDITIONS – VIBRATION AND
SHOCK OF ELECTROTECHNICAL EQUIPMENT –****Part 7: Transportation by rotary wing aircraft**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 62131-7, which is a Technical Report, has been prepared by IEC technical committee 104 Environmental conditions, classification and methods of test.

The text of this Technical Report is based on the following documents:

Enquiry draft	Report on voting
104/839/DTR	104/854/RVDTR

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62131 series, published under the general title *Environmental conditions – Vibration and shock of electrotechnical equipment*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

ENVIRONMENTAL CONDITIONS – VIBRATION AND SHOCK OF ELECTROTECHNICAL EQUIPMENT –

Part 7: Transportation by rotary wing aircraft

1 Scope

This part of IEC 62131, reviews the available dynamic data relating to the transportation of electrotechnical equipment by rotorcraft (helicopters). The intent is that from all the available data an environmental description will be generated and compared to that set out in IEC 60721 (all parts) [16]¹.

For each of the sources identified the quality of the data is reviewed and checked for self-consistency. The process used to undertake this check of data quality and that used to intrinsically categorize the various data sources is set out in IEC TR 62131-1 [2].

This document primarily addresses data extracted from a number of different sources for which reasonable confidence exist in its quality and validity. This document also reviews some data for which the quality and validity cannot realistically be verified. These data are included to facilitate validation of information from other sources. This document clearly indicates when utilizing information in this latter category.

This document addresses data from a number of data gathering exercises. The quantity and quality of data in these exercises varies considerably as does the range of conditions encompassed.

Not all of the data reviewed were made available in electronic form. To permit comparison to be made, in this assessment, a quantity of the original (non-electronic) data has been manually digitized.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

¹ Numbers in square brackets refer to the bibliography.