



BSI Standards Publication

Marine energy - Wave, tidal and other water current converters

Part 30: Electrical power quality requirements

National foreword

This Published Document is the UK implementation of IEC TS 62600-30:2018.

The UK participation in its preparation was entrusted to Technical Committee PEL/114, Marine energy - Wave, tidal and other water current converters.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018
Published by BSI Standards Limited 2018

ISBN 978 0 580 97327 7

ICS 27.140

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 September 2018.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------



IEC TS 62600-30

Edition 1.0 2018-08

TECHNICAL SPECIFICATION



**Marine energy – Wave, tidal and other water current converters –
Part 30: Electrical power quality requirements**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 27.140

ISBN 978-2-8322-5978-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references	9
3 Terms and definitions	9
4 Symbols and units	10
5 Abbreviated terms	12
6 Marine energy converter power quality characteristic parameters	12
6.1 Overview.....	12
6.2 Marine energy converter specification.....	12
6.3 Voltage fluctuations (continuous operations).....	13
6.3.1 General	13
6.3.2 Continuous operation: MV connected systems.....	13
6.3.3 Continuous operation: LV connected system	14
6.4 Current harmonics, interharmonics and higher frequency components.....	14
6.5 Response to voltage drops.....	15
6.6 Active power	16
6.6.1 Maximum measured power	16
6.6.2 Ramp rate limitation.....	16
6.6.3 Set-point control	16
6.7 Reactive power	17
6.7.1 Reactive power capability	17
6.7.2 Set-point control	17
7 Test procedures	17
7.1 General.....	17
7.1.1 Overview	17
7.1.2 Test validity	18
7.1.3 Test conditions	18
7.1.4 Test equipment	19
7.2 Voltage fluctuations (continuous operation).....	23
7.2.1 MV connected marine energy converters	23
7.2.2 Fictitious grid.....	23
7.2.3 Continuous operation – MV connected marine energy converters	25
7.2.4 Continuous operation – LV connected marine energy converters	26
7.3 Current harmonics, interharmonics and higher frequency components.....	26
7.4 Response to temporary voltage drop.....	27
7.5 Active power	29
7.5.1 General	29
7.5.2 Maximum measured power	29
7.5.3 Ramp rate limitation.....	30
7.5.4 Set point control	30
7.6 Reactive power	30
7.6.1 General	30
7.6.2 Reactive power capability	30
7.6.3 Set point control	31

8	Determination of power quality	32
8.1	General.....	32
8.2	Voltage fluctuations (continuous operation).....	32
8.2.1	MV connected marine energy converter units	32
8.2.2	LV connected marine energy converter.....	33
8.3	Current harmonics, interharmonics and higher frequency components	34
Annex A	(informative) Sample report format.....	36
A.1	General.....	36
A.2	Marine energy converter rated data at terminals	37
A.3	Voltage fluctuations (continuous operation).....	37
Annex B	(informative) Voltage fluctuations and flicker.....	39
B.1	Medium voltage (MV) connected converters.....	39
B.2	Low voltage (LV) connected converters.....	40
Annex C	(informative) Measurement of active power, reactive power and voltage	41
	Bibliography.....	43
	Figure 1 – Adjustment of active power set-point.....	16
	Figure 2 – Adjustment of reactive power set-point.....	17
	Figure 3 – Assumed elements of measurement system (MV-connected marine energy converter unit)	19
	Figure 4 – Assumed elements of measurement system (LV-connected marine energy converter)	20
	Figure 5 – Assumed elements of wave energy converter power quality measurement system.....	21
	Figure 6 – Assumed elements of tidal energy converter unit power quality measurement system.....	22
	Figure 7 – Fictitious grid for simulation of fictitious voltage	23
	Figure 8 – System with short circuit emulator for testing MEC unit response to temporary voltage drop	28
	Figure 9 – Tolerance of voltage drop.....	29
	Figure B.1 – Measurement and assessment procedures for flicker during continuous operation of the marine energy converter (MV-connected converter).....	39
	Figure B.2 – Measurement and assessment procedures for flicker during continuous operation of the marine energy converter (LV-connected converter).....	40
	Table 1 – Marine energy – resource classification.....	14
	Table 2 – Specification of per unit voltage drops (the specified magnitudes, duration and source are for the voltage drop occurring as if the MEC under test is not connected i.e. without contribution from the installation)	15
	Table 3 – Measurement ranges to be excluded	18
	Table 4 – General specification of requirements for measurement equipment	20
	Table 5 – Specification of requirements for wave measurement equipment.....	21
	Table 6 – Specification of requirements for tidal velocity measurement equipment.....	22
	Table 7 – Specification of exponents according to IEC TR 61000-3-6	34
	Table A.1 – General marine energy converter information.....	36
	Table A.2 – Marine energy converter nameplate ratings.....	36
	Table A.3 – Test information	37

Table A.4 – Marine energy converter rated data at terminals	37
Table A.5 – Reactive set-point control.....	37
Table A.6 – Flicker index (coefficient or disturbance factor) data	38
Table A.7 – Flicker coefficient as a function of resource conditions.....	38

Currently in preview, click buy full version

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARINE ENERGY –
WAVE, TIDAL AND OTHER WATER CURRENT CONVERTERS –**

Part 30: Electrical power quality requirements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, accept IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 62600-30, which is a technical specification, has been prepared by IEC technical committee 114: Marine energy – Wave, tidal and other water current converters.

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting
114/238/DTS	114/253A/RVDTS

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 62600 series, under the general title *Marine energy – Wave, tidal and other water current converters*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- transformed into an International standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Marine energy conversion systems, as viable electric power sources for utility and community-based applications, require close attention to the quality of the power produced. Poor power quality has negative impacts on both the electrical power source and the load. Therefore, guidance is needed for the manufacturer, developer and user on how to mitigate power quality issues during the design of the device. Electrical system planners also need to identify the requirements for grid integration of such variable and intermittent energy sources, while maintaining high reliability and power quality standards.

Conceptually, except for wave energy converters, many marine energy converter unit devices operate in a manner similar to wind turbines. As power quality is a mature topic within other renewable and conventional power generation schemes, there are numerous standards, codes, and guidelines in existence. In contrast, there are no standards or technical specifications for marine power generation systems that deal with the power quality issues and the associated integration needs. Therefore, this knowledge-gap needs to be addressed through incremental, detailed and collaborative standards development.

This technical specification aims at:

- identifying power quality issues and parameters (non-device specific and non-prescriptive) for single/three-phase, grid-connected/off-grid (including micro-grid) marine wave, tidal and other water current converter-based power systems;
- establishing the measurement methods, application techniques and result-interpretation guidelines.

In addition to containing the associated definitions, normative references, symbols and units, forms, annexes, as well as other supporting material, the core of this technical specification would contain the following key items:

- identify characteristic parameters, define and specify the quantities required to characterize the power quality impacts of marine energy conversion devices,
- develop measurement procedures as pertains to marine energy devices,
- outline standardized procedures for measuring the characteristic parameters, including test and measurement conditions and test equipment requirements.

It is expected that this technical specification will provide evaluation guidelines for device developers and applied researchers.

Assessment of power quality for utilities will be part of a separate, future technical specification that is currently being developed under IEC TC 8 SC 8A.

MARINE ENERGY – WAVE, TIDAL AND OTHER WATER CURRENT CONVERTERS –

Part 30: Electrical power quality requirements

1 Scope

This part of IEC 62600 includes:

- definition and specification of the quantities to be determined for characterizing the power quality of a marine energy (wave, tidal and other water current) converter unit;
- measurement procedures for quantifying the characteristics of a marine energy (wave, tidal and other water current) converter.

The measurement procedures are valid for a single marine energy converter (MEC) unit (or farm) with three-phase grid or an off-grid connection. The measurement procedures are valid for any size of MEC unit, though this document only requires MEC unit types intended for PCC (Point of Common Coupling) at Medium Voltage (MV) or High Voltage (HV) to be tested and characterized. In addition, a simplified measurement and reporting procedure is outlined for MEC units connected at Low Voltage (LV) networks. MV-connected and LV-connected devices are defined as:

- MV connected units – typically multiple three-phase MEC units operating as a marine power farm and delivering power through a HV or MV network;
- LV connected units – typically single-phase or three-phase units deployed in isolated, hybrid or micro-grid type systems supplying small-scale loads.

Considering the nascent status of the marine energy sector, the following limitations of this document are to be recognized:

- voltage fluctuations under switching operation – the current revision only considers voltage fluctuations under continuous operation;
- resource classifications – to categorize the measured flicker quantities, various resource classes are suggested only as guidelines. The user is advised to use these resource classes judiciously.

The measurement procedures are designed to be as non-site-specific as possible so that power quality characteristics measured at a test site, for example, can be considered valid at other sites also providing the same MEC unit configuration and operation modes (for example control parameters). If the configuration or operation mode is changed in any way that might cause the MEC unit to behave differently with respect to power quality, the power quality measurement procedures must be repeated.

This document is for testing of wave, tidal and other water current energy converter units, though it contains information that may also be useful for testing of MEC farms. The cases described are not intended for Ocean Thermal Energy Conversion (OTEC) systems.

NOTE This document uses the following terms for system voltage:

- low voltage (LV) refers to $U_n \leq 1$ kV;
- medium voltage (MV) refers to 1 kV $< U_n \leq 35$ kV;
- high voltage (HV) refers to $U_n > 35$ kV.