



BSI Standards Publication

Distributed energy resources connection with the grid

Part 41: Requirements for frequency measurement used to
control distributed energy resources (DER) and loads

National foreword

This Published Document is the UK implementation of IEC TS 62786-41:2023.

The UK participation in its preparation was entrusted to Technical Committee GEL/8, Systems Aspects for Electrical Energy Supply.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication is not to be regarded as a British Standard.

© The British Standards Institution 2023
Published by BSI Standards Limited 2023

ISBN 978 0 55 04098 2

ICS 91.40.50

Compliance with a Published Document cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 July 2023.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------



IEC TS 62786-41

Edition 1.0 2023-07

TECHNICAL SPECIFICATION



**Distributed energy resources connection with the grid –
Part 41: Requirements for frequency measurement used to control distributed
energy resources (DER) and loads**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 91.140.50

ISBN 978-2-8322-7225-1

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD..... 7

1 Scope..... 9

2 Normative references 9

3 Terms and definitions 10

4 Performance description..... 14

 4.1 General..... 14

 4.2 Input energizing quantities 14

 4.3 Delay time 15

 4.3.1 Description 15

 4.3.2 Reporting of delay time declaration..... 15

 4.4 Effective resolution and accuracy..... 15

 4.4.1 Description 15

 4.4.2 Effective measurement resolution 16

 4.4.3 Reporting of the frequency and ROCOF accuracy..... 16

 4.5 Measuring range, operating range, and rejection of interfering signals 16

 4.6 Timing characteristics 19

 4.6.1 Reporting rate..... 19

 4.6.2 Settling time 19

5 Summary of typical performances associated with different use cases..... 20

6 Description of functional test principles..... 22

 6.1 General..... 22

 6.2 Test reference conditions..... 24

 6.3 Verification of delay time for frequency and ROCOF measurement 24

 6.3.1 Test description..... 24

 6.3.2 Example determination of delay time 25

 6.4 Verification of effective resolution for frequency and ROCOF measurement..... 27

 6.4.1 Test description..... 27

 6.4.2 Example determination of effective resolution 29

 6.5 Verification of measurement and operating ranges..... 29

 6.5.1 Verification of measurement and operating ranges under steady state conditions..... 29

 6.5.2 Measuring and operating ranges under dynamic conditions 31

 6.5.3 Verification of rejection of interfering interharmonics..... 33

 6.5.4 Verification of rejection of harmonics 35

 6.6 Verification of settling time 38

 6.6.1 Test description..... 38

 6.6.2 Verification of settling time for frequency measurement 39

 6.6.3 Example of verification of frequency settling time 39

 6.6.4 Verification of settling time for ROCOF measurement 40

 6.6.5 Example of verification of ROCOF settling time 40

 6.7 Type test report 41

Annex A (informative) Measurement classes..... 43

Annex B (informative) Description of frequency or ROCOF measurement use cases..... 44

 B.1 Use case "PLL in photovoltaic power generating systems" 44

 B.1.1 Technical background of the use case 44

 B.1.2 Resulting requirements for measurement..... 45

B.2	Use case "Primary reserve"	46
B.2.1	Technical background of the use case	46
B.2.2	Resulting requirements for measurement.....	46
B.2.3	Example of "frequency-watt" function in photovoltaic power generating systems	47
B.3	Use case "Secondary reserve – frequency measurement used for centralized control"	48
B.3.1	Technical background of the use case	48
B.3.2	Resulting requirements for measurement.....	48
B.4	Use case "Fast frequency-active power proportional controller with dead band"	49
B.4.1	Technical background of the use case	49
B.4.2	Resulting requirements for measurement.....	50
B.5	Use case "Fast frequency response".....	51
B.5.1	Technical background of the use case	51
B.5.2	Resulting requirements for measurement.....	51
B.6	Use case "Synthetic inertia"	51
B.6.1	Technical background of the use case	51
B.6.2	Resulting requirements for measurement.....	52
B.7	Use case "Passive anti-islanding detection"	52
B.7.1	Technical background of the use case	52
B.7.2	Resulting requirements for measurement.....	53
B.8	Use case "Active anti-islanding detection".....	54
B.8.1	Technical background of the use case	54
B.8.2	Resulting requirements for measurement.....	54
B.9	Use case "ROCOF measurement used for centralized control".....	55
B.9.1	Technical background of the use case	55
B.9.2	Resulting requirements for measurement.....	55
B.10	Use case "Load control with reactive power management"	55
B.10.1	Technical background of the use case	55
B.10.2	Resulting requirements for measurement.....	55
B.11	Use case "Self-dispatchable loads" (microgrid applications).....	56
B.11.1	Technical background of the use case	56
B.11.2	Resulting requirements for measurement.....	56
B.12	Use case "Inter-frequency load shedding" (UFLS)	57
B.12.1	Technical background of the use case	57
B.12.2	Resulting requirements for measurement	57
Annex C (informative) Summary of requirements expressed in standards and grid codes related to frequency and ROCOF measurements		58
Annex D (informative) Maximum ROCOF to be considered on power systems in case of incidents		65
D.1	General.....	65
D.2	UK	65
D.3	European continent.....	65
D.4	Islands.....	65
Annex E (informative) Frequency and rotating vectors		66
Annex F (informative) Synthesizing input signals with sudden frequency change without discontinuity in voltage waveform.....		68
Annex G (informative) Step test equivalent time sampling technique.....		71
G.1	Overview.....	71

G.2	Equivalent time sampling	72
G.3	Determination of settling time using instrument errors	73
Annex H (informative) Voltage and phase angle changes during transmission line faults related to the type of transformer connection		75
H.1	Overview	75
H.2	Power line short circuit fault and protection	75
H.3	Voltage magnitude and phase angle change at line fault	77
H.3.1	General	77
H.3.2	Balanced-three-phase short circuit fault	77
H.3.3	Line-to-line short circuit fault	77
H.4	Conclusion	79
Annex I (informative) Influencing factors and functional tests		80
I.1	Influencing factors	80
I.2	Functional tests	80
I.2.1	General	80
I.2.2	Phase step change	80
I.2.3	Magnitude step change	82
I.2.4	Combined magnitude and phase step change	85
I.2.5	Voltage magnitude drop and restoration	89
I.2.6	Noise	95
I.2.7	Unbalanced input signal magnitude	97
I.2.8	Linear ramp of frequency	99
Bibliography		104
Figure 1 – Measuring range and operating range without interfering signals		17
Figure 2 – Measuring range and operating range in the presence of interfering signals		17
Figure 3 – Settling time description with input signal added		20
Figure 4 – Example of frequency delay time validation: measurement of delay time for a power frequency of 50 Hz		26
Figure 5 – Example of cross-correlations of the normalized frequencies and ROCOF		26
Figure 6 – Example of frequency modulation used to determine frequency effective resolution		29
Figure 7 – Example of frequency modulation used to determine ROCOF effective resolution		29
Figure 8 – Example of verification of measurement bandwidth under steady state conditions		31
Figure 9 – Example of verification of measuring and operating ranges under dynamic conditions		33
Figure 10 – Example of verification of rejection of interfering interharmonics		34
Figure 11 – Waveforms with superimposed harmonics		36
Figure 12 – Three-phase harmonic test signals, 0° and 180° harmonic phases		37
Figure 13 – Example of verification of rejection of harmonics		38
Figure 14 – Example of verification of frequency settling time using positive 1 Hz step in frequency		39
Figure 15 – Example of verification of frequency settling time using negative 1 Hz step in input frequency		40
Figure 16 – Example of verification of ROCOF settling time using positive 1 Hz/s step in ROCOF		41

Figure 17 – Example of verification of ROCOF settling time using negative 1 Hz/s step in ROCOF	41
Figure B.1 – Example of a system diagram of a PV system with a three-phase DC to AC converter.....	44
Figure B.2 – Example of system diagram of a three-phase PV system for voltage control	45
Figure B.3 – Example of system diagram of PV system with frequency-watt function	47
Figure B.4 – Application example of frequency-watt function for PV systems	48
Figure B.5 – Example of fast frequency-active power proportional controller with dead band (LFSM-O and LFSM-U characteristics from European Grid Code)	50
Figure E.1 – Phasor representation of a power system signal, which has amplitude (a), angle (ϕ) and angular velocity (ω)	66
Figure F.1 – Example of voltage waveform without discontinuity at $t_0 = 0,02$ s.....	69
Figure F.2 – Example of voltage waveform with discontinuity at $t_0 = 0,02$ s.....	70
Figure G.1 – Example of reports during step response.....	71
Figure G.2 – Example of reports during step response with higher resolution	72
Figure G.3 – Example of reports during step response with higher resolution.....	73
Figure H.1 – Voltage phase change by transmission line short circuit fault.....	76
Figure H.2 – Transmission line protection sequence and line voltage, frequency change.....	76
Figure H.3 – Voltage and phase angle change at three-phase short circuit	77
Figure H.4 – Relationship of voltage phase angle between Y-connection side and Δ -connection side	78
Figure H.5 – Voltage magnitude and phase angle change at two-phase short circuit fault 78	
Figure I.1 – Frequency error response to +1,3 radian phase step followed by -0,3 radian step.....	82
Figure I.2 – ROCOF error response to +0,3 radian phase step followed by -0,3 radian step 82	
Figure I.3 – Frequency error response to magnitude step changes	84
Figure I.4 – ROCOF error response to steps in magnitude	85
Figure I.5 – Voltage vectors for test case a).....	86
Figure I.6 – Voltage vectors for test case b).....	87
Figure I.7 – Frequency error responses to combined phase and magnitude steps	88
Figure I.8 – ROCOF error responses to combined phase and magnitude steps	89
Figure I.9 – Representation of the input energizing quantity (voltage, RMS) injection.....	91
Figure I.10 – Frequency response to voltage drop and restoration	92
Figure I.11 – ROCOF response to voltage drop and restoration	94
Figure I.12 – Frequency error absolute values from noise test scenarios a) and b)	96
Figure I.13 – ROCOF error absolute values from noise test scenarios a) and b)	97
Figure I.14 – Frequency absolute error due to unbalanced input signal magnitude	98
Figure I.15 – ROCOF absolute error due to unbalanced input signal magnitude	99
Figure I.16 – Frequency ramp test scenarios	100
Figure I.17 – Absolute frequency error during linear ramp of frequency test scenarios	102
Figure I.18 – Absolute ROCOF error during linear ramp of frequency test scenarios	103

Table 1 – Performance characteristics presented in Clause 4	14
Table 2 – Example of delay time	15
Table 3 – Example of measurement resolution and maximum absolute error for frequency and ROCOF measurements	16
Table 4 – Example of measuring range and operating range for frequency and ROCOF measurements (taken from an actual instrument)	18
Table 5 – Example of reporting of settling time and reporting rate	19
Table 6 – List of use cases and associated requirements	21
Table 7 – Input signal harmonic magnitudes	35
Table A.1 – Measurement classes for frequency measurements	43
Table A.2 – Measurement classes for ROCOF measurements	43
Table B.1 – Typical requirements for frequency measurement of PLL in PV systems	46
Table B.2 – Typical requirements for frequency measurement – use case "Primary reserve"	46
Table B.3 – Example of requirements of frequency-Watt function of PV systems	48
Table B.4 – Typical requirements for use case "Secondary reserve – frequency measurement used for centralized control"	49
Table B.5 – Typical requirements for frequency measurement – use case "Fast frequency-active power proportional controller with dead band"	51
Table B.6 – Typical requirements for frequency measurement – use case "Fast frequency response"	51
Table B.7 – Typical requirements for ROCOF measurement – use case "Synthetic inertia"	52
Table B.8 – Set of typical requirements for frequency measurement – use case "Passive anti-islanding detection"	53
Table B.9 – Typical requirements for ROCOF measurement – use case "Passive anti-islanding detection"	53
Table B.10 – Typical requirements for frequency measurement – use case "Active anti-islanding detection"	54
Table B.11 – Typical requirements for ROCOF measurement – use case "ROCOF measurement used for centralized control"	55
Table B.12 – Typical requirements for frequency measurement – use case "Load control with active power management"	55
Table B.13 – Typical requirements for frequency measurement – use case "Self-dispatchable loads"	56
Table B.14 – Typical requirements for frequency measurement – use case "Under-frequency load shedding"	57
Table B.15 – Typical requirements for ROCOF measurement – use case "Under-frequency load shedding"	57
Table C.1 – Requirements expressed in standards and grid codes related to frequency and ROCOF measurements	59
Table I.1 – Influencing factors of frequency and ROCOF measurements	80
Table I.2 – Test case a) for combined magnitude and phase step change	86
Table I.3 – Test case b) for combined magnitude and phase step change	86
Table I.4 – Magnitudes and phase angles for three phase voltages	97

INTERNATIONAL ELECTROTECHNICAL COMMISSION

DISTRIBUTED ENERGY RESOURCES CONNECTION WITH THE GRID –**Part 41: Requirements for frequency measurement used to control distributed energy resources (DER) and loads**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. For this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publications"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as far as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 62786-41 has been prepared by IEC technical committee 8: System aspects of electrical energy supply. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

Draft	Report on voting
8/1649/DTS	8/1661/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

It has been developed as part of measurement series together with IEC TS 62786-42 on voltage measurement.

A list of all parts in the IEC 62786 series, published under the general title *Distributed energy resources connection with the grid*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

DISTRIBUTED ENERGY RESOURCES CONNECTION WITH THE GRID –

Part 41: Requirements for frequency measurement used to control distributed energy resources (DER) and loads

1 Scope

This part of IEC 62786, which is a Technical Specification, defines minimum requirements for frequency and rate of change of frequency measurements used to control distributed energy resources (DER) and loads connected to electrical power networks.

This document specifies the characteristics of frequency and rate of change of frequency measurements to evaluate their performances. It describes the main use cases of frequency and rate of change of frequency measurements, with associated level of performances. It describes the principle of functional tests to evaluate the specified characteristics and defines the influencing factors that affect these performances, under steady state or dynamic conditions.

This document defines the functional requirements applicable to frequency and rate of change of frequency measurements which can be inside or outside the DER or loads. In the case of DER, this document provides requirements additional to those which are defined in the other parts of IEC 62786 or standards produced by the relevant IEC technical committees (e.g. TC 82 for photovoltaic systems, TC 88 for wind systems, TC 120 for electrical energy storage systems (EES)).

This document is applicable to DER and loads regardless of the voltage level of the point of connection to the grid.

This document does not specify hardware, software or a method for frequency or rate of change of frequency measurement. It does not specify tests linked to environmental conditions associated with hardware devices (climatic, electromagnetic disturbances above 3 kHz, mechanical stress, etc.).

Frequency and rate of change of frequency measurements associated with time stamping are not in the scope of this document. These measurements are already covered by IEC 60255-118-1 [1]¹.

Frequency and rate of change of frequency measurements associated with protection functions or protection relays are not in the scope of this document. These requirements are already covered by IEC 60255-181 [2].

NOTE As defined in the first paragraph, this document is focused on frequency and rate of change of frequency measurements used to control DER and loads. But the technical requirements defined in this document, with the list of declared characteristics and their associated functional tests, can also be applicable for other uses where "fast" frequency and ROCOF measurement is required (small or large generators of power substations connected to transmission or distribution grids, power meter devices, power quality instruments, etc.).

2 Normative references

There are no normative references in this document.

¹ Numbers in square brackets refer to the Bibliography.