



BSI Standards Publication

**Direct current (DC) appliance couplers
for information and communication
technology (ICT) equipment installed in
data centres and telecom central offices**

Part 2: 5,2 kW system

National foreword

This Published Document is the UK implementation of IEC TS 63236-2:2021.

The UK participation in its preparation was entrusted to Technical Committee PEL/23, Electrical accessories.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication is not to be regarded as a British Standard.

© The British Standards Institution 2021
Published by BSI Standards Limited 2021

ISBN 978 0 55 04460 7

ICS 29.20.01; 29.120.30

Compliance with a Published Document cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 July 2021.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------



IEC TS 63236-2

Edition 1.0 2021-06

TECHNICAL SPECIFICATION

**Direct current (DC) appliance couplers for information and communication technology (ICT) equipment installed in data centres and telecom central offices –
Part 2: 5,2 kW system**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.120.01, 29.120.30

ISBN 978-2-8322-9928-9

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references.....	7
3 Terms and definitions.....	7
4 General requirements.....	7
5 General notes on tests.....	7
6 Standard ratings.....	7
7 Classification of appliance coupler.....	7
8 Marking.....	8
9 Dimensions and compatibility.....	8
10 Protection against electric shock.....	8
11 Provision for earthing.....	8
12 Terminals and terminations.....	8
13 Construction.....	8
14 Insulation resistance and electric strength.....	9
15 Forces necessary to insert and to withdraw the connector.....	9
15.1 General.....	9
16 Operation of contact.....	9
17 Resistance to heating of appliance coupler.....	9
18 Breaking capacity.....	10
19 Normal operation.....	10
20 Temperature rise.....	10
21 Cords and their connection.....	11
21.1 Cords for non-rewirable connectors.....	11
21.2 Cable anchorage.....	11
22 Mechanical strength.....	12
23 Resistance to heat and ageing.....	12
24 Screws, current-carrying parts and connections.....	12
24.1 General.....	12
25 Creepage distances, clearances and distances through sealing compound.....	12
26 Resistance of insulating material to heat, fire and tracking.....	12
27 Resistance to rusting.....	13
28 Electromagnetic compatibility (EMC) requirements.....	13
1010 (zero) current operated appliance inlet systems.....	13
Annex A (xxx) Safety-related routine tests for factory-wired accessories (protection against electric shock and correct polarity).....	14
Annex B (xxx) Test schedule.....	15
Annex C (xxx) Alternative gripping tests.....	16
Annex D (xxx) Standard sheets and gauges.....	17
D.1 Standard sheets.....	17
D.2 Gauges.....	22
D.2.1 Distance to the point of first contact.....	22

D.2.2	"GO" gauges for appliance inlets according to standard sheet 1 (Figure D.1).....	23
D.2.3	"GO" gauge for connectors according to standard sheet 2 (Figure D.2).....	25
D.2.4	Gauge for checking the maximum withdrawal force (see 15.2).....	26
D.2.5	Gauges for checking the minimum withdrawal force (see 15.3).....	26
D.2.6	Position of switch cam of optional micro switches.....	27
	Bibliography.....	28
	Figure D.1 – Appliance inlet.....	19
	Figure D.2 – Connector.....	21
	Figure D.3 – Positioning of the “+” and “–” pins/connector-contacts.....	22
	Figure D.4 – Gauges for checking point of first contact.....	23
	Figure D.5 – "GO" gauges for appliance inlets according to standard sheet 1 (Figure D.1).....	24
	Figure D.6 – "GO" gauges for connector according to standard sheet 2 (Figure D.2).....	25
	Figure D.7 – Gauge representing the counterpart inlet designed to accept D.1 only for checking the maximum withdrawal force, for breaking capacity test and for normal operation test.....	26
	Figure D.8 – Gauge for checking the minimum withdrawal force for “+” and “–” connector-contact.....	26
	Figure D.9 – Gauge for checking the minimum withdrawal force for “+”, “–” and “PE” socket-contact.....	27
	Table 1 – Relationship between rated power and connectable nominal cross-sectional areas or American Wire Gauges (AWG) size of copper conductors.....	8
	Table 2 – Maximum diameters of the cords.....	9
	Table 3 – Maximum and minimum withdrawal forces.....	9
	Table 4 – Cords and conductors for the tests of Clause 21.....	11
	Table 5 – Type and nominal cross-sectional area of cords.....	11
	Table 6 – Types of cable for the reversible connector test.....	11
	Table 7 – Value for the lateral pulls applied.....	12
	Table 8 – Values for straight and lateral pull forces.....	12
	Table D.1 – Dimension of contact gauge.....	23

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**DIRECT CURRENT (DC) APPLIANCE COUPLERS FOR INFORMATION
AND COMMUNICATION TECHNOLOGY (ICT) EQUIPMENT INSTALLED
IN DATA CENTRES AND TELECOM CENTRAL OFFICES –**

Part 2: 5,2 kW system

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use, and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, accept IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 63236-2 has been prepared by IEC technical committee 23: Electrical accessories. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

DTS	Report on voting
23/916/DTS	23/958A/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

This Part 2 is to be used in conjunction with IEC TS 63236-1:2021.

The clauses of this document supplement or modify the corresponding clauses in IEC 63236-1. When a particular subclause or annex of Part 1 is not mentioned in this Part 2, the subclause or annex of IEC 63236-1 applies as far as is reasonable. Where this document states “addition”, “amendment” or “replacement”, the relevant requirement, test specification or explanatory matter in IEC 63236-1 is to be adapted accordingly.

Clauses or subclauses which are additional to those in Part 1 are numbered starting from 101.

A list of all parts in the IEC 63236 series, published under the general title *Direct current (DC) appliance couplers for information and communication technology (ICT) equipment installed in data centres and telecom central offices*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch on the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

DIRECT CURRENT (DC) APPLIANCE COUPLERS FOR INFORMATION AND COMMUNICATION TECHNOLOGY (ICT) EQUIPMENT INSTALLED IN DATA CENTRES AND TELECOM CENTRAL OFFICES –

Part 2: 5,2 kW system

1 Scope

This part of IEC 63236, which is a Technical Specification, applies to DC appliance couplers for class I equipment with two active contacts plus an earthing contact, a rated power of 5,2 kW and a rated voltage range from 294 V to 400 V DC. They are intended to power DC information and communication technology equipment only, as specified in IEC 62368-1.

The accessories according to this document are intended to be used by ordinary persons in data centres only where the value of the DC voltage distribution system is defined as follows:

- 380 V with a tolerance of ± 20 V for installations with no backup battery or with a voltage regulation system;
- 380 V with a voltage range of 294 V to 400 V for installations with a backup battery where voltage regulation is not guaranteed;
- the voltage value between each live conductor and earth does not exceed 200 V DC during normal operation;
- there are two abnormal voltage ranges (duration below 10 min):
 - 260 V up to 294 V, and
 - above 400 V to 410 V.

The maximum current of the appliance couplers is

- 13 A when the voltage between live contacts is 400 V DC,
- 17,6 A when the voltage between live contacts is 294 V DC,

and can rise up to 20 A when the voltage between live contacts decreases to 260 V DC for 10 min maximum.

The voltage between live conductors can fall down to 260 V DC when the voltage discharge value of the battery reaches the disconnecting level. The consequence is that the current increases accordingly.

The accessories according to this document do not require maintenance.

The accessories according to this document are intended for use in circuits where

- basic protection,
- an overcurrent protection (of 17,6 A or less for each socket-outlet or multiple socket-outlet),
- the fault protection (indirect contact protection), and
- additional protection

are already assured.