



BSI Standards Publication

Utility connections in ports

Part 3: Low Voltage Shore Connection (LVSC)
Systems — General requirements

National foreword

This Published Document is the UK implementation of IEC/PAS 80005-3:2014.

The UK participation in its preparation was entrusted to Technical Committee JPEL/18, Electrical installations of ships and of mobile and fixed offshore units.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014.
Published by BSI Standards Limited 2014

ISBN 978 0 580 87341 6
ICS 47.020.60

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 November 2014.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------



PUBLICLY AVAILABLE SPECIFICATION

PRE-STANDARD



**Utility connections in port –
Part 3: Low Voltage Shore Connection (LVSC) Systems – General requirements**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XA**

ICS 47.020.60

ISBN 978-2-8322-1832-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	9
2 Normative references.....	9
3 Terms and definitions	10
4 General requirements	12
4.1 System description.....	12
4.2 Distribution system.....	13
4.2.1 General	13
4.2.2 Equipotential bonding.....	13
4.3 Compatibility assessment before connection.....	14
4.4 LVSC system design and operation	14
4.4.1 System design	14
4.4.2 System operation	14
4.5 Personnel safety	15
4.6 Design requirements	15
4.6.1 General	15
4.6.2 Protection against moisture and condensation	15
4.6.3 Location and construction.....	15
4.6.4 Electrical equipment in hazardous areas.....	15
4.7 Electrical requirements.....	16
4.8 System study and calculations.....	16
4.9 Emergency shutdown including emergency-stop facilities.....	17
5 LV shore supply system requirements	18
5.1 Voltages and frequencies	18
5.2 Quality of LV shore supply	19
6 Shore-side installation	20
6.1 General.....	20
6.2 System component requirements.....	20
6.2.1 Circuit-breaker and disconnectors.....	20
6.2.2 Transformer.....	20
6.2.3 Neutral earthing resistor.....	20
6.2.4 Equipment earthing conductor bonding.....	21
6.3 Ship-to-ship electrical protection system.....	21
6.4 LV interlocking	22
6.4.1 General	22
6.4.2 Operating of the low-voltage (LV) circuit-breakers and disconnectors	22
6.5 Shore connection convertor equipment	22
6.5.1 General	22
6.5.2 Degree of protection	23
6.5.3 Cooling.....	23
6.5.4 Protection	23
7 Ship-to-shore connection and interface equipment	23
7.1 General.....	23

7.2	Cable management system	24
7.2.1	General	24
7.2.2	Monitoring of cable tension.....	24
7.2.3	Monitoring of the cable length	25
7.2.4	Connection conductor current unbalance protection	25
7.3	Plugs and socket-outlets	25
7.3.1	General	25
7.3.2	Pilot contacts	28
7.3.3	Earth contact	28
7.4	Ship-to-shore connection cable	28
7.5	Independent control and monitoring cable.....	28
7.6	Storage.....	28
8	Ship requirements	29
8.1	General.....	29
8.2	Ship electrical distribution system protection.....	29
8.2.1	Short-circuit protection	29
8.2.2	Earth fault protection, monitoring and alarm.....	29
8.3	Shore connection switchboard	29
8.3.1	General	29
8.3.2	Circuit-breaker and disconnectors	29
8.3.3	Instrumentation and protection	30
8.4	On-board transformer	30
8.5	On-board receiving switchboard connection point.....	30
8.5.1	General	30
8.5.2	Circuit-breaker	30
8.5.3	Instrumentation	31
8.5.4	Protection	31
8.5.5	Operation of the circuit breaker	32
8.6	Ship power restoration	33
9	LVSC system control and monitoring.....	33
9.1	General requirements.....	33
9.2	Load transfer via a linkout	33
9.3	Load transfer via automatic synchronization.....	33
9.3.1	General	33
9.3.2	Protection requirements	34
10	Verification and testing	34
10.1	General.....	34
10.2	Initial tests of shore-side installation	35
10.2.1	General	35
10.2.2	Tests	35
10.3	Initial tests of ship-side installation	35
10.3.1	General	35
10.3.2	Tests	35
10.4	Tests at the first call at a shore supply point	36
10.4.1	General	36
10.4.2	Tests	36

11	Periodic tests and maintenance	36
11.1	General.....	36
11.2	Tests at repeated calls of a shore supply point.....	36
11.2.1	General	36
11.2.2	Verification	36
12	Documentation	37
12.1	General.....	37
12.2	System description.....	37
Annex A	(normative) Ship-to-shore connection cable	38
A.1	Rated voltage.....	38
A.2	Rated section / type	38
A.3	General design.....	38
A.3.1	General	38
A.3.2	Conductors	38
A.3.3	Earth conductors.....	39
A.3.4	Pilot conductors	39
A.3.5	Cabling	39
Annex B	(normative) Ship-to-shore connection plugs, socket-outlets, ship connectors and ship inlets	40
B.1	Rated voltage.....	40
B.2	Rated type	40
B.3	General design.....	40
B.3.1	General	40
B.3.2	Configuration	41
Annex C	(normative) Additional requirements for Offshore Supply, Service and Working Ships	42
C.1	Scope	42
Annex D	(normative) Additional requirements for Container Ships.....	44
D.1	Scope	44
Annex E	(normative) Additional requirements for Tankers	46
E.1	Scope	46
Annex F	(normative) General operating procedures	49
Bibliography	50
Figure 1	– Block diagram of a typical LVSC system	13
Figure 2	– Phase sequence rotation – Positive direction	18
Figure 3	– Balanced three-phase variables in time domain.....	19
Figure 4	– Safety loop circuit for one feeder (a) or three feeders (b), for LVSC system.	27
Figure 5	– Diagram showing the use of accessories.....	37
Figure B.1	– Connection with mobile cable reel	41
Figure B.2	– Connection with fixed cable reel	41
Figure C.1	– Example for general system layout	42
Figure C.2	– Power plug and socket-outlet contact assignment	43
Figure D.1	– Example for general system layout	44
Figure D.2	– Power plug and socket-outlet contact assignment	45
Figure E.1	– Example for general system layout	46

Figure E.2 – Power plug and socket pin assignment47

Figure E.3 – IS Barrier and cable properties (to be developed)48

Figure E.4 – Safety loop circuit for LVSC system in tankers (to be developed)48

Figure F.1 – LVSC general operating procedures for connection a) and disconnection b)49

Table B.1 – Number of feeders function of power demand and voltage.....41

Currently in preview, click buy full version

INTERNATIONAL ELECTROTECHNICAL COMMISSION

UTILITY CONNECTIONS IN PORT –

**Part 3: Low Voltage Shore Connection (LVSC) Systems –
General requirements**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any assessment of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC/ISO Publication may be the subject of patent rights. IEC or ISO shall not be held responsible for identifying any or all such patent rights.

PAS is a technical specification not fulfilling the requirements for a standard, but made available to the public.

This Publicly Available Specification (PAS) IEC/ISO 80005-3 has been prepared by IEC technical committee 18: Electrical installations of ships and of mobile and fixed offshore units, in cooperation with IEC subcommittee 23H: Plugs, socket-outlets and couplers for industrial and similar applications, and for electric vehicles, of IEC technical committee 23: Electrical accessories and IEC technical committee 20: Electric cables, ISO technical committee 8: Ships and marine technology, subcommittee 3: Piping and machinery, and IEEE IAS Petroleum and Chemical Industry Committee (PCIC) of the Industry Applications Society of the IEEE.

This PAS will eventually be replaced with an IEC/IEEE prefix and IEC/ISO/IEEE triple logo standard.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

Draft PAS	Report on voting
18/1377/PAS	18/1390/RVD

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

A list of all the parts in the IEC 80005 series, published under the general title *Utility Connections In Port*, can be found on the IEC website.

This PAS shall remain valid for an initial maximum period of 3 years starting from the publication date. The validity may be extended for a single period up to a maximum of 3 years, at the end of which it shall be published as another type of normative document, or shall be withdrawn.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This Publicly Available Specification (PAS) was developed jointly by IEC technical committee 18: Electrical installations of ships and of mobile and fixed offshore units in cooperation with IEC subcommittee 23H: Plugs, socket-outlets and couplers for industrial and similar applications, and for electric vehicles, of IEC technical committee 23: Electrical accessories and IEC technical committee 20: Electric cables, ISO technical committee 8: Ships and marine technology, subcommittee 3: Piping and Machinery, and IEEE IAS PCIC Marine Industry subcommittee.

For a variety of reasons, including environmental considerations, it is becoming an increasingly common requirement for ships to shut down ship generators and to connect to shore power for as long as practicable during stays in port.

The intention of this PAS is to define requirements that support, with the application of suitable operating practices, efficiency and safety of connections by compliant ships to compliant low-voltage shore power supplies through a compatible shore-to-ship connection.

With the support of sufficient planning, cooperation between ship and terminal facilities, and appropriate operating procedures and assessment, compliance with the requirements of this PAS is intended to allow different ships to connect to low-voltage shore connection (LVSC) systems at different berths. This provides the benefits of standard, straightforward connection without the need for adaptation and adjustment at different locations that can satisfy the requirement to connect for as long as practicable during stays in port.

Ships that do not apply this PAS may find it impossible to connect to compliant shore supplies.

Where deviations from the requirements and recommendations in this PAS may be considered for certain designs, the potential effects on compatibility are highlighted.

Where the requirements and recommendations of this PAS are complied with, low-voltage shore supplies arrangements are likely to be compatible for visiting ships for connection.

Clauses 1 to 12 are intended for application to all LVSC systems. They are intended to address mainly the safety and effectiveness of LVSC systems with a minimum level of requirements that would standardise on one solution. This PAS includes the requirement to complete a detailed compatibility assessment for each combination of ship and shore supply prior to a given ship arriving to connect to a given shore supply for the first time.

The other annexes in this PAS are ship-specific annexes which include additional requirements related to agreed standardisation of solutions to achieve compatibility for compliant ships at different compliant berths and to address safety issues that are considered to be particular to that ship type. These annexes use the same numbering as Clauses 1 to 12 with an annex letter prefix. Hence, the numbering is not necessarily continuous. Where no additional requirements are identified, the clause is not shown.

UTILITY CONNECTIONS IN PORT –

Part 3: Low Voltage Shore Connection (LVSC) Systems – General requirements

1 Scope

This PAS describes low voltage shore connection (LVSC) systems, on board the ship and on shore, to supply the ship with electrical power from shore.

This PAS is applicable to the design, installation and testing of LVSC systems and addresses:

- LV shore distribution systems;
- shore-to-ship connection and interface equipment;
- transformers/reactors;
- semiconductor/rotating convertors;
- ship distribution systems; and
- control, monitoring, interlocking and power management systems.

NOTE It does not apply to the electrical power supply during docking periods, e.g. dry docking and other out-of-service maintenance and repair.

Additional and/or alternative requirements may be imposed by national administrations or the authorities within whose jurisdiction the ship is intended to operate and/or by the owners or authorities responsible for a shore supply or distribution system.

It is expected that LVSC systems will have practicable applications for ships requiring up to 1 MVA. Low-voltage shore connection systems not exceeding 250 A, with a maximum of 125 A per cable and not exceeding 300 V to earth are not covered by this PAS. High-voltage shore connection systems are covered by IEC/ISO/IEEE 80005-1.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60034 (all parts), *Rotating electrical machines*

IEC 60076 (all parts), *Power transformers*

IEC 60079 (all parts), *Explosive atmospheres*

IEC 60092-101:1994, *Electrical installations in ships – Part 101: Definitions and general requirements*

IEC 60092-201:1994, *Electrical installations in ships – Part 201: System design – General*

IEC 60092-301:1980, *Electrical installations in ships – Part 301: Equipment – Generators and motors*