



BSI Standards Publication

Process management for avionics – Electronic components capability in operation

Part 1: Temperature uprating

National foreword

This Published Document is the UK implementation of IEC TR 62240-1:2018. It supersedes PD IEC/TR 62240-1:2013, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee GEL/107, Process management for avionics.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018
Published by BSI Standards Limited 2018

ISBN 978 0 580 51225 4

ICS 31.020; 03.100.50; 49.060

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 April 2018.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------



TECHNICAL REPORT



**Process management for avionics – Electronic components capability in operation –
Part 1: Temperature uprating**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 03.100.50; 31.020; 49.060

ISBN 978-2-8322-5364-9

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references.....	8
3 Terms, definitions and abbreviated terms.....	8
3.1 Terms and definitions.....	8
3.2 Abbreviated terms.....	12
4 Selection provisions.....	12
4.1 General.....	12
4.2 Device selection, usage and alternatives.....	14
4.2.1 General.....	14
4.2.2 Alternatives.....	14
4.2.3 Device technology.....	14
4.2.4 Compliance with the electronic component management plan.....	15
4.3 Device capability assessment.....	15
4.3.1 General.....	15
4.3.2 Device package and internal construction capability assessment.....	15
4.3.3 Risk assessment (assembly level).....	15
4.3.4 Device uprating methods.....	16
4.3.5 Device reliability assurance.....	17
4.4 Device quality assurance (QA) over wider temperature ranges.....	18
4.4.1 Decision for the optimum QA method.....	18
4.4.2 Device level testing.....	19
4.4.3 Higher level assembly testing.....	19
4.5 QA process.....	19
4.5.1 General.....	19
4.5.2 Semiconductor device change monitoring.....	19
4.5.3 Failure data collection and analysis.....	19
4.6 Final electronic equipment assurance.....	20
4.7 Documentation and identification.....	20
4.7.1 Documentation.....	20
4.7.2 Device identification.....	20
4.7.3 Customer notification.....	20
Annex A (informative) Device parameter re-characterisation.....	22
A.1 Glossary of symbols.....	22
A.2 Rationale for parameter re-characterisation.....	23
A.2.1 General.....	23
A.2.2 Assessment for uprateability.....	23
A.3 Capability assurance.....	24
A.3.1 Description.....	24
A.3.2 Parameter re-characterisation process.....	24
A.3.3 Application capability assessment.....	29
A.4 Quality assurance.....	30
A.5 Factors to be considered in parameter re-characterisation.....	30
A.6 Report form for documenting device parameter re-characterisation.....	32
Annex B (informative) Stress balancing.....	34

B.1	General.....	34
B.2	Glossary of symbols.....	34
B.3	Stress balancing.....	34
B.3.1	General.....	34
B.3.2	Determine the ambient temperature extremes.....	35
B.3.3	Determine parameter relationship to power dissipation.....	35
B.3.4	Determine the dissipated power versus ambient temperature relationship.....	35
B.3.5	Assess applicability of the method.....	37
B.3.6	Determine the new parameter values.....	37
B.3.7	Conduct parametric and functional tests.....	38
B.4	Application example.....	38
B.4.1	General.....	38
B.4.2	Determine the ambient temperature extremes.....	39
B.4.3	Select the parameters that can be derated.....	39
B.4.4	Construct an Iso- T_J plot.....	40
B.4.5	Determine whether or not the device can be uprated.....	40
B.4.6	Determine the new parameter values.....	40
B.4.7	Conduct parametric and functional tests.....	41
B.5	Other notes.....	41
B.5.1	Margins.....	41
B.5.2	Cautions and limitations.....	41
Annex C (informative)	Parameter conformance assessment.....	44
C.1	General.....	44
C.2	Test plan.....	44
C.2.1	General.....	44
C.2.2	Critical parameters.....	44
C.2.3	Minimum allowable test margins.....	44
C.2.4	Test options.....	45
C.2.5	Quality assurance.....	48
Annex D (informative)	Higher assembly level testing.....	51
D.1	General.....	51
D.2	Process.....	51
D.2.1	General.....	51
D.2.2	Analysis of assembly test definition.....	51
D.2.3	Perform assembly test.....	51
D.2.4	Document results.....	52
D.2.5	Maintenance notification.....	52
Bibliography.....		54
Figure 1	– Flow chart for semiconductor devices over wider temperature ranges.....	13
Figure 2	– Report form for documenting device usage over wider temperature ranges.....	21
Figure A.1	– Parameter re-characterisation.....	23
Figure A.2	– Flow diagram of parameter re-characterisation capability assurance process.....	25
Figure A.3	– Margin in electrical parameter measurement based on the results of the sample test.....	28
Figure A.4	– Schematic diagram of parameter limit modifications.....	29

Figure A.5 – Parameter re-characterisation device quality assurance 30

Figure A.6 – Schematic of outlier products that can invalidate sample testing 31

Figure A.7 – Example of intermediate peak of an electrical parameter: Voltage feedback input threshold change for Motorola MC34261 power factor controller, see [4]..... 32

Figure A.8 – Report form for documenting device parameter re-characterisation 33

Figure B.1 – Iso- T_J curve: Relationship between ambient temperature and dissipated power 36

Figure B.2 – Graph of electrical parameters versus dissipated power..... 38

Figure B.3 – Iso- T_J curve for the Fairchild MM74HC244 40

Figure B.4 – Power versus frequency curve for the Fairchild MM74HC244 41

Figure B.5 – Flow chart for stress balancing 42

Figure B.6 – Report form for documenting stress balancing 43

Figure C.1 – Relationship of temperature ratings, requirements and margins 45

Figure C.2 – Typical fallout distribution versus $T_{req-max}$ 47

Figure C.3 – Parameter conformance assessment flow 49

Figure C.4 – Report form for documenting parameter conformance testing 50

Figure D.1 – Flow chart of higher level assembly testing 52

Figure D.2 – Report form for documenting higher level assembly test at temperature extremes..... 53

Table A.1 – Example of sample size calculation 26

Table A.2 – Parameter re-characterisation example: SN74ALS244 octal buffer/driver 29

currently in preview, click buy full vers.

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**PROCESS MANAGEMENT FOR AVIONICS – ELECTRONIC
COMPONENTS CAPABILITY IN OPERATION –****Part 1: Temperature uprating**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, accept IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 62240-1, which is a Technical Report, has been prepared by IEC technical committee 107: Process management for avionics.

This second edition cancels and replaces the first edition published in 2013. This edition constitutes a technical revision. This edition includes the following significant technical changes with respect to the previous edition:

- a) Revised the wording in 4.1 and the corresponding Figure 1 to reflect current industry practices.

The text of this Technical Report is based on the following documents:

CDTR	Report on voting
107/313/DTR	107/322/RVDTR

Full information on the voting for the approval of this Technical Report can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62240 series, published under the general title *Process management for avionics – Electronic components capability in operation*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Traditionally, industries that produced electronic equipment for ADHP (aerospace, defence and high performance) applications have relied on the military specification system for semiconductor device standards and upon manufacturers of military-specified devices as device sources. This assured the availability of semiconductor devices specified to operate over the temperature ranges required for electronic equipment in ADHP applications. In the past, several device manufacturers have exited the military market, resulting in the decreased availability of devices specified to operate over wide temperature ranges. Following are some typical ambient temperature ranges at which devices are marketed:

Military:	–55 °C to + 125 °C
Automotive:	–40 °C to + 125 °C
Industrial:	–40 °C to + 85 °C
Commercial:	0 °C to + 70 °C

If there are no reasonable or practical alternatives, then a potential response is for electronic equipment manufacturers to use devices at temperature ranges that are wider than those specified by the device manufacturer.

This document provides information on selecting semiconductor devices, assessing their capability to operate, and assuring their intended quality in the wider temperature ranges. It also reports the need for documentation of such usage.

This can be supported by exchanging technical information with the original device manufacturer.

Operation of the device beyond the manufacturer's limits can result normally in loss of warranty by the device manufacturer.

PROCESS MANAGEMENT FOR AVIONICS – ELECTRONIC COMPONENTS CAPABILITY IN OPERATION –

Part 1: Temperature uprating

1 Scope

This part of IEC 62240, which is a technical report, provides information when using semiconductor devices in wider temperature ranges than those specified by the device manufacturer. The uprating solutions described herein are considered exceptions, when no reasonable alternatives are available; otherwise devices are utilized within the manufacturers' specifications.

The terms “uprating” and “thermal uprating” are being used increasingly in avionics industry discussions and meetings, and clear definitions are included in Clause 3. They were coined as shorthand references to a special case of methods commonly used in selecting electronic components for circuit design.

This document describes the methods and processes for implementing this special case of thermal uprating. All of the elements of these methods and processes employ existing, commonly used best engineering practices. No new or unique engineering knowledge is needed to follow these processes, only a rigorous application of the overall approach.

Even though the device is used at wider temperatures, the wider temperatures usage will be limited to those that do not compromise applications performance and reliability, particularly for devices with narrow feature size geometries (for example, 90 nm and less). This document does not imply that applications use the device to function beyond the absolute maximum rating limits specified by the original device manufacturer and assumes that:

- device usage outside the original device manufacturers' specified temperature ranges is done only when no reasonable alternative approach is available and is performed with appropriate justification;
- if it is necessary to use devices outside the original device manufacturers' specified temperature ranges, it is done with documented and controlled processes that assure integrity of the electronic equipment.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC TR 62239-1, *Process management for avionics – Management plan – Part 1: Preparation and maintenance of an electronic components management plan*

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.