



BSI Standards Publication

Dynamic modules

Part 6-9: Design guide — Study of mechanisms and measurements of crosstalk in wavelength-selective switches

National foreword

This Published Document is the UK implementation of IEC/TR 62343-6-9:2015.

The UK participation in its preparation was entrusted by Technical Committee GEL/86, Fibre optics, to Subcommittee GEL/86/3, Fibre optic systems and active devices.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2015.

Published by BSI Standards Limited 2015

ISBN 978 0 580 86722 4

ICS 33.180.01; 33.180.99

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 11 July 2015.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------



TECHNICAL REPORT



**Dynamic modules –
Part 6-9: Design guide – Study of mechanisms and measurements of crosstalk
in wavelength-selective switches**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.180.01; 33.180.99

ISBN 978-2-8322-2769-5

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....4

INTRODUCTION.....6

1 Scope.....7

2 Normative references.....7

3 Abbreviations7

4 Study of dynamic crosstalk for WSS.....8

4.1 Static crosstalk and dynamic crosstalk.....8

4.2 Generation mechanism of dynamic crosstalk.....8

4.2.1 Configuration example of optical switching functionality8

4.2.2 Generation mechanism9

5 Measurement methods of dynamic crosstalk.....11

5.1 Study of measurement methods of dynamic crosstalk.....11

5.1.1 Referenced standard documents11

5.1.2 Test configuration of tuneable laser source (TLS) and optical power meter.....12

5.1.3 Test configuration of tuneable laser source, Optical converter and oscilloscope.....12

5.1.4 Comparison of the measurement methods.....13

5.2 Evaluation of the measurement methods.....13

6 Measurement result of dynamic crosstalk14

6.1 MEMS type WSS.....14

6.1.1 Measurement conditions14

6.1.2 Measurement of different channel crosstalk.....14

6.1.3 Measurement of same channel crosstalk15

6.2 LCOS type WSS.....16

6.2.1 Measurement conditions16

6.2.2 Measurement of different-channel crosstalk.....17

6.2.3 Measurement of same-channel crosstalk17

6.3 DLP type WSS.....18

6.3.1 Measurement conditions18

6.3.2 Measurement procedure and result.....18

6.4 Summary.....20

7 Conclusion.....21

Bibliography22

Figure 1 – Block diagram of optical switching function9

Figure 2 – Dynamic crosstalk at WSS.....10

Figure 3 – Dynamic crosstalk at optical coupler for multiplexing.....11

Figure 4 – Dynamic crosstalk at receiver (Rx).....11

Figure 5 – Test configuration of tuneable laser source (TLS) and optical power meter12

Figure 6 – Test configuration of tuneable laser source and oscilloscope.....13

Figure 7 – Experimental set-up14

Figure 8 – Measurement set-up of different-channel crosstalk.....15

Figure 9 – Measurement result of different-channel crosstalk for MEMS type WSS 15

Figure 10 – Measurement result of same-channel crosstalk for MEMS type WSS 16

Figure 11 – Measurement result of different-channel crosstalk for LCOS type WSS 17

Figure 12 – Measurement result of same-channel crosstalk for LCOS type WSS 18

Figure 13 – Switching characteristics for 1 × 2 DLP type WSS 19

Figure 14 – Crosstalk measurement result of case a) for DLP type WSS 19

Figure 15 – Crosstalk measurement result of case b) for DLP type WSS 20

Figure 16 – Crosstalk measurement result of case c) for DLP type WSS 20

Table 1 – Static crosstalk and dynamic crosstalk 7

Table 2 – Same-channel crosstalk and different-channel crosstalk 8

Table 3 – Generating mechanism of same-channel crosstalk and different-channel crosstalk 10

Currently in preview, click buy full version

INTERNATIONAL ELECTROTECHNICAL COMMISSION

DYNAMIC MODULES –

Part 6-9: Design guide – Study of mechanisms and measurements of crosstalk in wavelength-selective switches

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, accept IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example, the "state of the art".

IEC TR 62343-6-9, which is a Technical Report, has been prepared by subcommittee SC86C: Fibre optic systems and active devices, of IEC technical committee TC 86: Fibre optics.

The text of this Technical Report is based on the following documents:

Enquiry draft	Report on voting
86C/1300/DTR	86C/1321/RVC

Full information on the voting for the approval of this Technical Report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62343 series, published under the general title *Dynamic modules*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

A dense wavelength division multiplexing (DWDM) system for fibre optic communication was developed in the late 1990's. The first generation DWDM systems were point-to-point optical networks. In the mid-2000's, second generation DWDM systems, typically ring networks, were developed. One of the key optical components for DWDM systems is a wavelength division multiplexing device. An AWG (arrayed waveguide grating) module has been mainly deployed for first and second generation DWDM systems.

Due to the increasing demand for communication capacity, more flexible optical communication systems, such as mesh networks, have been required. In the past several years, the third generation of DWDM systems, the optical cross-connect system, has been developed and deployed by some communication network carriers and is expected to be deployed worldwide. A wavelength-selective switch (WSS) module plays a key role in realizing the optical switch function in the optical cross-connect system, so that the performance of the WSS directly impacts on the performance of the optical cross-connect systems, such as the capacity, transmission distance, etc.

For AWG modules, only static performance, such as insertion loss, bandwidth, pass-band ripple, polarization dependent loss (PDL), polarization mode dispersion (PMD), coherent crosstalk, etc., has been evaluated. In addition to static performance, dynamic performance during switching or changing attenuation should be taken into consideration for the WSS as a key module of optical cross-connect systems.

For dynamic performance parameters, the influence not only on the controlled channel but also on other channels should be considered.

Considering this background, the influence of WSS dynamic crosstalk on cross-connect system performance and the measurements of dynamic crosstalk has been demonstrated.

This Technical Report is based on Optoelectronic Industry and Technology Development Association (OITDA) – Technical Paper (TP), TP15/TP-2013, "Dynamic crosstalk measurement for wavelength selective switches".

DYNAMIC MODULES –

Part 6-9: Design guide – Study of mechanisms and measurements of crosstalk in wavelength-selective switches

1 Scope

This part of IEC 62343, which is a Technical Report, describes a study of the impact of WSS dynamic crosstalk on the optical network and includes dynamic crosstalk measurement examples for three types of WSS. The generating mechanism and the generation factors of dynamic crosstalk in WSS are clarified, and the evaluation of same-channel crosstalk and different-channel crosstalk is shown to be necessary.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61300-3-21, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-21: Examinations and measurements – Switching time*

IEC 61300-3-29, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-29: Examinations and measurements – Spectral transfer characteristics of DWDM devices*

3 Abbreviations

ADD	add port
AWG	arrayed waveguide grating
COM	common port
CW	continuous wave
DLP	digital light processor
DRP	drop port
DUT	device under test
DWDM	dense wavelength division multiplexing
EXP	express port
LCO	liquid crystal on silicon
MEMS	micro electro mechanical system
OE	optical-to-electrical
PDL	polarization dependent loss
PMD	polarization mode dispersion
TLS	tuneable laser source
Tx	transmitter
Rx	receiver
WSS	wavelength selective switch