



BSI Standards Publication

Hydrogen effects in optical fibre cables – Guidelines

Currently in preview, click buy full version

National foreword

This Published Document is the UK implementation of IEC/TR 62690:2014.

The UK participation in its preparation was entrusted by Technical Committee GEL/86, Fibre optics, to Subcommittee GEL/86/1, Optical fibres and cables.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014.
Published by BSI Standards Limited 2014

ISBN 978 0 580 72082 6
ICS 33.180.10

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 1 July 2014.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------



TECHNICAL REPORT



Hydrogen effects in optical fibre cables – Guidelines

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

J

ICS 33.180.10

ISBN 978-2-8322-1657-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....3

INTRODUCTION.....5

1 Scope.....6

2 Normative references6

3 General6

4 Evaluation of hydrogen induced effects6

5 Hydrogen effects in optical fibre cables7

Bibliography.....7

Table 1 – Evaluation criteria for single-mode (SM) optical fibre cables.....7

Currently in preview, click buy full version

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HYDROGEN EFFECTS IN OPTICAL FIBRE CABLES – GUIDELINES

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 62690, which is a technical report, has been prepared by subcommittee 86A: Fibres and cables, of IEC technical committee 86: Fibre optics.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
86A/1586/DTR	86A/1605/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

There is extensive application of optical fibre cables worldwide, both for terrestrial and submarine environments, with the provision of stable transmission characteristics over many years.

In the early 1980s, it was established that some optical fibre designs in certain cable constructions were prone to hydrogen-induced attenuation increases. The mechanism of the hydrogen induced loss was quickly established and after extensive research and development programs, fibre designs were optimized to minimize the effects. Cable designers established suitable design rules and optimized the selection of cable materials so as to also minimize the effects of hydrogen induced attenuation increases during service life.

Currently in preview, click buy full version

HYDROGEN EFFECTS IN OPTICAL FIBRE CABLES – GUIDELINES

1 Scope

The purpose of this technical report is to provide information concerning the behaviour of fibres and cables when exposed to hydrogen effects.

The application of multimode fibres is very rarely subject to hydrogen effects. For that reason, this technical report only highlights the effects of hydrogen to single-mode fibres.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60794-3, *Optical fibre cables – Part 3: Sectional specification – Outdoor cables*

IEC 60794-4, *Optical fibre cables – Part 4: Sectional specification – Aerial optical cables along electrical power lines*

IEC 60794-5, *Optical fibre cables – Part 5: Sectional specification – Microduct cables for installation by blowing*

3 General

The magnitude of any hydrogen induced effect depends on the cable type (including fibre design) and its operational environment.

In the case of suitably designed, single-mode fibre cables for terrestrial applications, there is sufficient experience to not require any test in cables for significant concentrations of hydrogen which could cause an increase in optical attenuation.

The induced loss for single-mode fibre due to hydrogen at a partial pressure of up to $1,0 \times 10^4$ Pa ($9,9 \times 10^{-2}$ atm) is not greater than 0,03 dB/km and 0,06 dB/km, at 1 310 nm and 1 550 nm, respectively. The dynamic equilibrium pressure or balance of hydrogen within a terrestrial cable with perfect hermetic barrier will be significantly less than $1,0 \times 10^4$ Pa, and therefore, optical reliability is ensured. Typical values of 40,5 Pa equivalent to $4,0 \times 10^{-4}$ atm have been measured for duct cable several years after installation [1]¹. At these partial pressures, the attenuation increase is insignificant.

4 Evaluation of hydrogen induced effects

Depending on the cable type and its planned operational environment, an evaluation of hydrogen induced effects [2] may or may not be warranted. Table 1 offers a guide to the necessity to evaluate cables for hydrogen induced attenuation increases.

¹ Numbers in square brackets refer to the Bibliography