



BSI Standards Publication

Nanomanufacturing — Key control characteristics

Part 5-1: Thin-film organic/inorganic electronic devices — Carrier transport measurements

National foreword

This Published Document is the UK implementation of IEC/TS 62607-5-1:2014.

The UK participation in its preparation was entrusted to Technical Committee NTI/1, Nanotechnologies.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014.

Published by BSI Standards Limited 2014

ISBN 978 0 580 82584 2

ICS 07.030

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 December 2014.

Amendments issued since publication

Date	Text affected
------	---------------



TECHNICAL SPECIFICATION



**Nanomanufacturing – Key control characteristics –
Part 5-1: Thin-film organic/nano electronic devices – Carrier transport
measurements**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

P

ICS 07.030

ISBN 978-2-8322-1812-9

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD..... 3

INTRODUCTION..... 5

1 Scope..... 6

2 Normative references 6

3 Terms, definitions and abbreviations 6

 3.1 Terms and definitions..... 6

 3.2 Symbols and abbreviated terms 7

4 Sample structures of OTFTs 8

 4.1 Typical device structures of OTFTs..... 8

 4.2 Contact-area-limited doping in OTFTs..... 8

5 Appropriate data format..... 9

Annex A (informative) Experimental studies on contact-area-limited doping in OTFTs..... 11

 A.1 Contact-area-limited doping in bottom-gate, top-contact OTFTs..... 11

 A.2 Contact-area-limited doping in bottom-gate, bottom-contact OTFTs..... 13

Bibliography..... 15

Figure 1 – Typical device structures of OTFTs 8

Figure 2 – Contact-area-limited doping in OTFTs..... 9

Figure 3 – Summary of this Technical Specification 9

Figure A.1 – Sample preparation of bottom-gate, top-contact (BGTC) pentacene OTFTs using contact-area-limited doping..... 12

Figure A.2 – Contact-area-limited doping effect in bottom-gate, top-contact (BGTC) pentacene OTFTs 12

Figure A.3 – Sample preparation of bottom-gate, bottom-contact (BGBC) p-channel OTFTs using contact-area-limited doping 13

Figure A.4 – Contact-area-limited doping effect in bottom-gate, bottom-contact (BGBC) pentacene OTFTs 14

Figure A.5 – Contact-area-limited doping effect in bottom-gate, bottom-contact (BGBC) oligothiophene OTFTs 14

Table 1 – Possible data format to be given together with carrier transport properties of OTFTs 10

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**NANOMANUFACTURING –
KEY CONTROL CHARACTERISTICS –****Part 5-1: Thin-film organic/nano electronic devices –
Carrier transport measurements**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with the conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, issue to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 62607-5-1, which is a technical specification, has been prepared by IEC technical committee 113: Nanotechnology standardization for electrical and electronic products and systems.

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting
113/212/DTS	113/221/RVC

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62607 series, published under the general title *Nanomanufacturing key control characteristics*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- transformed into an International standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

Organic/nano thin-film devices have many attractive features such as being light-weight and flexible, and having a low-cost, low-temperature fabrication process. Organic/nano electronic devices have been widely researched by academic institutions, research institutes, and materials and device industries. One of their possible applications is therefore expected to be in flexible and rollable devices. Many thin-film transistors based on organic semiconductor materials, called organic thin-film transistors (OTFTs), are expected to be mounted on organic electroluminescence display to drive each organic light-emitting diode pixel circuit. These OTFTs are also promising candidates for molecular nanoelectronics.

OTFTs show a relatively smaller carrier mobility (thin-film mobility: at most $10 \text{ cm}^2/\text{Vs}$, but usually less than $1 \text{ cm}^2/\text{Vs}$) compared with other thin-film transistors based on inorganic semiconductors (silicon, III-V compounds, metal oxides). Carrier transport properties such as thin-film mobility and thin-film carrier concentration in OTFTs are usually measured by simply applying the device physics of silicon metal-oxide-semiconductor transistors to OTFTs. Both the intrinsic bulk mobility of organic semiconductors and extrinsic effects such as contact resistance, carrier trap, interface, and surface state can limit thin-film mobility in OTFTs. Therefore, reliable methods of evaluating carrier transport properties for micrometer-scale thin-film materials have not yet been established and urgently need to be developed.

NANOMANUFACTURING – KEY CONTROL CHARACTERISTICS –

Part 5-1: Thin-film organic/nano electronic devices – Carrier transport measurements

1 Scope

This part of IEC 62607, which is a Technical Specification, provides a standardized sample structure for characterizing charge transport properties in thin-film organic/nano electronic devices and a format to report details of the structure which shall be provided with the measurement results. The standardized OTFT testing structure with a contact area limited doping can mitigate contact resistance and enable reliable measurement of the charge carrier mobility. The purpose of this Technical Specification is to provide test sample structures for determining the intrinsic charge transport properties of organic thin-film devices. The intention is to provide reliable materials information for OTFTs and to set guidelines for making test sample structures so that materials information is clear and consistent throughout the research community and industry.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050 (all parts), *International Electrotechnical Vocabulary* (available at <http://www.electropedia.org/>)

IEC 62860, *Test methods for the characterization of organic transistors and materials*

3 Terms, definitions and abbreviations

For the purposes of this document, the terms and definitions given in IEC 60050-521 as well as the following apply.

3.1 Terms and definitions

3.1.1

organic thin-film transistor

OTFT

field-effect transistor that has a conduction channel made of thin films consisting of organic compounds

3.1.2

thin-film mobility

charge carrier mobility of the conduction channel (the semiconductor layer) in an OTFT

3.1.3

contact-area-limited doping

doping at around interface regions between the source and drain electrodes and the conduction channel in an OTFT