



BSI Standards Publication

**Process management for avionics  
– Aerospace and defence electronic  
systems containing lead-free solder**

---

Part 4: Ball grid array (BGA) re-balling

## National foreword

This Published Document is the UK implementation of IEC TS 62647-4:2018.

The UK participation in its preparation was entrusted to Technical Committee GEL/107, Process management for avionics.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018  
Published by BSI Standards Limited 2018

ISBN 978 0 580 97334 5

ICS 03.100.50; 49.060; 31.020

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 April 2018.

### Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

---



# IEC TS 62647-4

Edition 1.0 2018-04

## TECHNICAL SPECIFICATION

---

**Process management for avionics – Aerospace and defence electronic systems  
containing lead-free solder –  
Part 4: Ball grid array (BGA) re-balling**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 03.100.50; 31.020; 49.060

ISBN 978-2-8322-5530-8

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references .....	8
3 Terms and definitions .....	9
4 Process approach.....	12
4.1 Typical process.....	12
4.2 Awareness .....	14
5 General requirements .....	14
5.1 Process control at the customer level.....	14
5.1.1 Customer's responsibilities .....	14
5.1.2 Electronic components classes .....	14
5.2 Process control at re-balling provider level.....	15
5.2.1 Re-balling provider's responsibilities.....	15
5.2.2 Electronic component classes.....	15
5.2.3 Counterfeit prevention and traceability management.....	15
5.2.4 Quality.....	16
5.2.5 Records.....	16
5.2.6 Facility requirements .....	16
5.2.7 Electrostatic discharge (ESD).....	16
5.2.8 Physical handling of BGA components.....	16
5.2.9 Moisture/reflow sensitivity.....	16
5.2.10 Configuration management.....	17
5.2.11 Personnel proficiency .....	17
5.2.12 Order of precedence.....	17
5.3 Customer and re-balling provider relationship.....	17
6 Technical requirements .....	17
6.1 Receipt of BGA components and separate balls.....	17
6.1.1 General .....	17
6.1.2 Incoming inspection of BGA components.....	17
6.1.3 Incoming inspection of separate solder balls.....	19
6.2 Specific analysis based on component balls alloy .....	19
6.3 BGA component de-balling.....	20
6.3.1 General .....	20
6.3.2 Temperature excursions .....	20
6.3.3 Flux .....	20
6.3.4 Preheat.....	20
6.3.5 Solder balls removal (de-balling) .....	20
6.3.6 Cool down .....	21
6.3.7 Cleaning (post de-balling).....	21
6.3.8 Complete removal and cleanliness verification.....	21
6.4 BGA component re-balling .....	21
6.4.1 General .....	21
6.4.2 Capability .....	21
6.4.3 Solder paste .....	22
6.4.4 Flux .....	22

6.4.5	Ball placement (alignment and co-planarity) .....	22
6.4.6	Preheating .....	22
6.4.7	Reflow temperature profile .....	22
6.4.8	Cooling down .....	22
6.4.9	Cleaning (post re-balling) .....	23
6.5	Post-process inspection of re-balled BGA components .....	23
6.5.1	General .....	23
6.5.2	Production lot tests .....	23
6.5.3	Process monitoring and control .....	23
6.5.4	Case of failures .....	24
6.5.5	Records .....	24
6.6	Rework .....	24
6.6.1	General .....	24
6.6.2	Rework if authorized by the customer .....	24
6.7	New BGA component part number qualification .....	24
6.7.1	General .....	24
6.7.2	New BGA component part number qualification by similarity .....	25
6.7.3	New BGA component part number qualification .....	25
6.7.4	Records .....	26
6.7.5	Customer's approval .....	26
6.7.6	Cases of BGA component re-qualification .....	26
6.8	Physical marking .....	27
6.9	Packaging and shipping .....	27
6.10	Re-balled BGA components segregation .....	27
Annex A (informative)	Template for tailoring the requirements of IEC TS 62647-4 .....	28
Annex B (informative)	Requirement matrix for IEC TS 62647-4 .....	29
Annex C (normative)	Test methods .....	37
Annex D (informative)	Template for test methods tailoring in the frame of a BGA component production lot test plan or new BGA component part number qualification test plan .....	39
Bibliography	.....	40
Figure 1	– Typical flow chart of de-balling/re-balling operations .....	13
Table 1	– Electronic component class .....	14
Table 2	– Typical control and inspection test methods .....	19
Table 3	– Typical production lot test methods .....	23
Table 4	– Typical test methods for process monitoring and control .....	24
Table 5	– Typical test methods used for inspection of re-balled BGA components within the framework of new BGA component part number qualification .....	25
Table 6	– Typical optional additional tests for new BGA component part number qualification .....	26
Table A.1	– Template for tailoring of requirements .....	28
Table B.1	– Requirement matrix .....	29
Table C.1	– Test methods .....	37
Table D.1	– Template for requirements tailoring .....	39

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**PROCESS MANAGEMENT FOR AVIONICS –  
AEROSPACE AND DEFENCE ELECTRONIC  
SYSTEMS CONTAINING LEAD-FREE SOLDER –****Part 4: Ball grid array (BGA) re-balling**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, accreditation to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 62647-4, which is a Technical Specification, has been prepared by IEC technical committee 107: Process management for avionics.

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting
107/314/DTS	107/331/RVDTS

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 62647 series, published under the general title *Process management for avionics – Aerospace and defence electronic systems containing lead-free solder*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- transformed into an International standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

## INTRODUCTION

As the result of RoHS directives, soldering assembly processes have migrated predominantly from tin-lead to Pb-free, and a majority of BGA components manufacturers have converted from tin-lead solder balls to Pb-free solder balls. This has introduced well documented reliability concerns. In the case of a leaded soldering process, a solution can be to replace the Pb-free solder balls on the BGA components with tin-lead solder balls. This will prevent mixing solder alloys.

This document was prepared to standardize the requirements and guidelines for replacing the solder balls on applicable BGA components. The requirements within this document are derived from existing industry standards and a collaboration of service providers and customers, typically avionics original equipment manufacturers (OEMs).

This document is intended to be used by de-balling/re-balling providers and customers to incorporate these requirements into their operations to provide a consistent and well-controlled process, or to create a de-balling/re-balling plan that augments their existing processes.

There are two major reasons to de-ball/re-ball BGA components: alloy compatibility and replacement of damaged balls.

The customer should understand the potential risks of the BGA de-balling/re-balling process for a specific package.

To avoid reliability problems, the BGA de-balling/re-balling process should be qualified and carefully controlled to prevent the possibility of BGA failure after re-balling. Generally, automated processes contribute positively to this objective and are encouraged in the electronic industry.

This document does not guarantee a particular yield or reliability of BGA components going through the de-balling/re-balling process. BGA component construction and materials used should be evaluated for compatibility with the solder re-balling process to ensure that BGA component reliability and integrity are maintained.

Because of the dynamic nature of the transition to lead-free (Pb-free) electronics, this and other similar documents are based on the best information and expertise available; its update will be considered as future knowledge and data are obtained.

# PROCESS MANAGEMENT FOR AVIONICS – AEROSPACE AND DEFENCE ELECTRONIC SYSTEMS CONTAINING LEAD-FREE SOLDER –

## Part 4: Ball grid array (BGA) re-balling

### 1 Scope

This part of IEC 62647, which is a Technical Specification, defines the requirements for replacing solder balls on ball grid array (BGA) component packages in the context of an electronic components management plan (ECMP) for aerospace, defence and high reliability products.

NOTE 1 IEC TS 62239-1 and EIA-STD-4899 describe the electronic components management program (ECMP).

It does not apply to column grid array (CGA) components or chip scale components.

This re-balling document addresses two types of configurations. For other configuration types, see Annex A for tailoring.

- Configuration 1: A BGA package that will be de-balled and then re-balled with tin-lead balls compatible with a tin-lead soldering assembly process.
- Configuration 2: A BGA package that will be de-balled and then re-balled with Pb-free balls compatible with a Pb-free soldering assembly process.

The intent of this document is to provide re-balling companies (hereinafter referred to as the re-balling provider) with the administrative and technical requirements to be incorporated within existing processes or for establishing, implementing and maintaining a new set of processes or the creation of a stand-alone re-balling process.

This document is intended to be used by de-balling/re-balling providers and customers, typically avionics original equipment manufacturers (OEM); it defines the requirements for re-balling providers who are providing services to the aerospace, defence, high performance and high reliability electronics industry.

Requirements for new BGA component part number qualification are also included. This document identifies the need for the creation of new part numbers for re-balled BGA components, covers process and testing requirements for the de-balling/re-balling process and encourages the automated processes due to the ability to control the process.

Companies engaged in re-balling are supposed to have the necessary knowledge, experience and tools, and to customize if needed their own methods for defining a de-balling/re-balling process that meets the requirements in this document.

Each customer determines the applicability of this document and the need for full replacement of the existing solder balls. Some applications can have unique requirements that exceed the scope of this document and are therefore specified separately.

This document is not intended to address all procedures and processes associated with a de-balling/re-balling facility; it is assumed there are management, quality, manufacturing, safety, calibration and training processes/procedures in place as well as all the necessary tools and equipment to accomplish the work.

NOTE 2 For the purposes of this document, if the term "BGA" is used alone, it is stated as "BGA component".