



BSI Standards Publication

Industrial electroheating and electromagnetic processing equipment - Evaluation of hazards caused by magnetic nearfields from 1 Hz to 6 MHz

National foreword

This Published Document is the UK implementation of IEC/TS 62997:2017.

The UK participation in its preparation was entrusted to Technical Committee PEL/27, Electroheating.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2017
Published by BSI Standards Limited 2017

ISBN 978 0 580 92220 6

ICS 25.180.10

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 September 2017.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------



IEC TS 62997

Edition 1.0 2017-06

TECHNICAL SPECIFICATION



**Industrial electroheating and electromagnetic processing equipment –
Evaluation of hazards caused by magnetic near fields from 1 Hz to 6 MHz**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 25.180.10

ISBN 978-2-8322-4449-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	7
INTRODUCTION.....	9
1 Scope.....	11
2 Normative references	11
3 Terms, definitions, symbols and abbreviated terms.....	11
3.1 Terms and definitions.....	11
3.2 Quantities and units	14
4 Organisation and use of the technical specification.....	15
5 The basic relationship for determination of the in situ induced electric field	16
6 Requirements related to immediate nerve and muscle reactions.....	16
6.1 General.....	16
6.2 Method using the conductor geometry and current restriction (CGCR)	17
6.3 Volunteer test method	18
6.3.1 Volunteer basic test method	18
6.3.2 Method based on volunteer tests and similarity with pre-existing scenario	19
6.3.3 Method based on volunteer tests, using available elevated conductor current or shorter distance between the conductor and bodypart	19
6.3.4 Method using magnetic nearfield reference levels (RLs)	19
7 Requirements related to body tissue overheating.....	19
7.1 General.....	19
7.2 Intermittent conditions with 6 minutes time integration	20
7.3 Intermittent conditions in fingers and hands with shorter integration times	21
8 Calculations and numerical computation of induced E field and SAR by magnetic nearfields: inaccuracies, uncertainties and safety factors	21
8.1 Principles for handling levels of safety – general.....	21
8.2 The C value variations with E field curvature	22
8.3 Location of parts of the body, instrumentation and measurement issues	22
8.4 Handling of inaccuracies of <i>in situ</i> E field and SAR numerical values	22
8.5 Approaches to compliance	23
8.5.1 General	23
8.5.2 Cases where verification of levels being below the RL is sufficient	23
8.5.3 Cases where only B flux measurements are sufficient.....	23
8.5.4 Cases where the volunteer test method is applicable	23
8.5.5 Cases where the CGCR method is applicable	23
8.5.6 Cases where numerical modelling is carried out	24
8.6 Summary of inaccuracy/uncertainty factors to be considered	24
9 Risk group classification and warning marking.....	24
9.1 General.....	24
9.2 Induced electric fields from 1 Hz to 1 kHz	25
9.3 Induced electric fields from 1 kHz to 100 kHz.....	25
9.4 Induced electric fields from 100 kHz to 6 MHz.....	25
9.5 Magnetic flux fields from 1 Hz to 6 MHz	25
9.6 Warning marking.....	25
Annex A (informative) Survey of basic restrictions, reference levels in other standards, etc.....	27

A.1	Basic restrictions – general and deviations	27
A.2	The coupling values C in ICNIRP guidelines and IEEE standards.....	27
A.3	Basic restrictions – immediate nerve and muscle reactions	28
A.4	Basic restrictions – specific absorption rates (SAR)	29
A.5	Reference levels – external magnetic B field.....	29
Annex B (normative) Analytical calculations of magnetically induced internal E field phenomena.....		30
B.1	Some basic formulas – magnetic fields and Laws of Nature	30
B.2	Induced field deposition in tissues by magnetic nearfields.....	31
B.3	Coupling of a homogeneous B field to homogeneous objects with simple geometries.....	31
B.4	Starting points for numerical modelling	32
B.4.1	Relevant bodyparts.....	32
B.4.2	The use of external B field and internal power density in numerical modelling.....	32
Annex C (normative) Reference objects representing parts of the body: tissue conductivities.....		33
C.1	Reference bodyparts.....	33
C.1.1	General	33
C.1.2	The wrist/arm models	33
C.1.3	The hand model with tight fingers	33
C.1.4	The hand model with spread-out fingers.....	33
C.1.5	The finger model.....	33
C.2	Dielectric properties of human tissues.....	33
C.2.1	General data for assessments	33
C.2.2	Inner parts of the body.....	34
C.2.3	Skin data	34
Annex D (informative) Results of numerical modelling with objects in a Helmholtz coil and at a long straight conductor.....		35
D.1	General and a large Helmholtz coil scenario with a diameter 200 mm sphere – FDTD 3D modelling.....	35
D.2	Other reference objects in the Helmholtz coil – FDTD 3D modelling.....	36
D.2.1	The scenario	36
D.2.2	Numerical modelling results with smaller spheres	36
D.2.3	Numerical results with other objects	37
Annex E (informative) Numerical FDTD modelling with objects at a long straight wire conductor.....		38
E.1	Scenario and general information.....	38
E.2	Two 200 mm diameter spheres	39
E.3	The hand model with tight fingers at different distances from the wire – FDTD modelling.....	40
E.3.1	General information and scenario	40
E.3.2	Modelling results – power deposition patterns.....	40
E.4	The hand model with tight fingers at 100 mm from the wire – Flux® 12 FEM modelling	42
E.5	Coupling data and analysis for the hand model with tight fingers above the wire – FDTD modelling.....	42
E.6	Coupling data and analysis for the wrist/arm model above the wire.....	43
Annex F (informative) Numerical modelling and volunteer experiments with the hand models at a coil.....		45
F.1	General and on the B field amplitude	45

F.2	The hand model with tight fingers 2 mm, 4 mm, 6 mm and 50 mm above the coil and with its right side above the coil axis – FDTD modelling	46
F.2.1	The scenario.....	46
F.2.2	Modelling results	47
F.3	The hand model with tight fingers 6 mm above the coil and with variable position in the x direction – FDTD modelling	51
F.4	The hand model with spread-out fingers, 6 mm straight above the coil – FDTD modelling	51
F.5	The hand model with tight fingers near a coil with metallic workload – FDTD modelling	52
F.6	The finger model 2 mm above the coil – FDTD numerical modelling.....	54
F.6.1	The scenarios	54
F.6.2	Modelling results	54
F.7	Analysis of the FDTD modelling results	56
F.7.1	General	56
F.7.2	With the hand model.....	56
F.7.3	With the finger model.....	56
F.8	Volunteer studies	56
F.8.1	General	56
F.8.2	Calculations of the induced electric field strength in F.7.1.....	57
F.9	Comparisons with conventional electric shock effects and contact current	57
F.10	Conclusions from the data in Annexes E and F.....	58
F.10.1	Coupling factor <i>C</i> data in relation to reference object geometries and magnetic flux characteristics without workload.....	58
F.10.2	Coupling factor <i>C</i> modifications by workloads	58
F.10.3	Rationales for the CGCR basic value with the volunteer method	58
Annex G (informative)	Some examples of CGCR values of a hand near conductors as function of frequency, conductor current and configuration	60
G.1	Frequency and conductor current relationships: adopted CGCR value	60
G.2	A hand above a thin wire.....	60
G.3	A hand above a coil	61
Annex H (informative)	Frequency upscaling with numerical modelling.....	64
H.1	General and energy penetration depth	64
H.2	Actual penetration depth data	64
H.3	The penetration depth issue of representativity with frequency upscaling.....	65
H.4	Separation of the internal power density caused by direct capacitive coupling, and that caused by the external magnetic field.....	65
H.5	The frequency upscaling procedures.....	66
H.5.1	General	66
H.5.2	Choices of conductivity and control procedures	66
Bibliography	68
Figure 1	– Examples of warning marking.....	26
Figure A.1	– ICNIRP, IEEE and 2013/35/EU basic restrictions (RMS)	28
Figure D.1	– The z-directed magnetic field momentaneous maximal amplitude in the central y plane of the Helmholtz coil with the conductive 200 mm diameter sphere	36
Figure D.2	– The power density patterns in the central y plane (left) and central z (equatorial) plane of the 200 mm diameter sphere	36
Figure D.3	– The power density patterns in the central z plane of the reference objects, with maximal <i>C</i> values in m.....	37

Figure E.1 – Long straight wire scenario	38
Figure E.2 – Power deposition patterns in the central z planes of the two spheres at 10 mm and 20 mm away from the sphere axis; $\sigma = 20 \text{ Sm}^{-1}$	39
Figure E.3 – Power deposition pattern in the central y plane of the sphere at 10 mm distance from the wire axis; $\sigma = 20 \text{ Sm}^{-1}$	39
Figure E.4 – Scenario with the hand model above the wire axis	40
Figure E.5 – Power density in the hand model 2,5 mm above the wire axis	40
Figure E.6 – Power density in the hand model 14 mm above the wire axis	41
Figure E.7 – Power density in the hand model 100 mm above the wire axis	41
Figure E.8 – Current density in the central cross section of the hand model at 9 mm from the wire – Flux® 12 FEM modelling	42
Figure E.9 – Wrist/arm model above a long straight wire	43
Figure E.10 – Linear power density (left, power scaling) and electric field amplitude (linear scale) in the x plane of wrist/arm model 10 mm straight above a long straight wire	43
Figure F.1 – Illustration of the B field at a single turn coil, with the coil centre at the left margin of the image – Flux® 12 FEM modelling	45
Figure F.2 – Hand above the coil scenario	46
Figure F.3 – Power density pattern in the central vertical plane and in the bottom 1 mm layer of the hand model, $z = 2 \text{ mm}$ above the top of the coil; $a = -51 \text{ mm}$	47
Figure F.4 – Power density pattern in the central vertical plane and in the bottom 1 mm layer of the hand model, $z = 4 \text{ mm}$; $a = -51 \text{ mm}$	47
Figure F.5 – Power density pattern in the central vertical plane and in the bottom 1 mm layer of the hand model, $z = 50 \text{ mm}$; $a = -51 \text{ mm}$	48
Figure F.6 – The $\pm x$ -directed (left image) and $\pm y$ -directed momentaneous maximal E field at the hand underside, $z = 4 \text{ mm}$; $a = -51 \text{ mm}$	49
Figure F.7 – The local power density pattern of the condition in Figure F.3, showing the $1 \text{ mm} \times 1 \text{ mm}$ voxel size and the 5 mm^2 integration region 2 mm above the hand underside	50
Figure F.8 – The local y -directed momentaneous maximal electric field pattern of the condition in Figure F.3, showing the $1 \text{ mm} \times 1 \text{ mm}$ voxel size and the 5 mm^2 integration region 2 mm above the hand underside	50
Figure F.9 – The power density pattern in the hand model centred above the coil and 6 mm above it; left image: bottom region, right image: 10 mm up	51
Figure F.10 – The hand model with spread-out fingers located 6 mm straight above the coil (left); relative power densities at the height of maximum power density between fingers (right)	51
Figure F.11 – The hand model 6 mm above the coil and a 100 mm diameter metallic workload in the coil	52
Figure F.12 – Quiver plot of the magnetic (H) field amplitude in logarithmic scaling, in the scenario in Figure F.11 with a non-magnetic (left) and magnetic (right) workload	52
Figure F.13 – The power density pattern in the central vertical cross section in the same scenario in Figure F.11	53
Figure F.14 – The power density in the central vertical cross section of the hand as in the scenario in Figure F.11, but 50 mm above the coil; with no workload (left) and with permeable metallic workload (right)	53
Figure F.15 – The two finger positions above the coil; left = y -directed finger	54
Figure F.16 – Power density maximum pattern in the y -directed 17 mm diameter finger model	54
Figure F.17 – Power density maximum pattern in the x -directed 17 mm diameter finger model	55

Figure F.18 – Momentaneous maximal electric field maximum pattern in the x-directed 17 mm diameter finger model..... 55

Figure F.19 – Plastic plate above the coil..... 57

Figure G.1 – Allowed RMS current at 11 kHz, based on CGCR = 40 Vm⁻¹ 60

Figure G.2 – CGCR coil currents at 11 kHz for the hand model with the side at the coil axis, at various heights above the coil..... 62

Figure G.3 – CGCR coil currents at 11 kHz for the hand model at 6 mm above the coil with different sideways positions 63

Table C.1 – Examples of dielectric data of human tissues at normal body temperature 34

Table E.1 – Coupling factors for the hand model with tight fingers at various heights above the wire axis 42

Table G.1 – Coupling factors and allowed coil currents at 11 kHz for the hand model with the side at the coil axis, at various heights above the coil 61

Table G.2 – Coupling factors and allowed coil currents at 11 kHz for the hand model at 6 mm above the coil with different sideways positions 62

Currently in preview, click buy full vers.

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INDUSTRIAL ELECTROHEATING AND
ELECTROMAGNETIC PROCESSING EQUIPMENT –

**Evaluation of hazards caused by magnetic nearfields
from 1 Hz to 6 MHz**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization, comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with the conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, issue to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 62997, which is a technical specification, has been prepared by IEC technical committee 27: Industrial electroheating and electromagnetic processing.

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting
27/1000A/DTS	27/1007/RVDTS

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

In this technical specification, the following print types are used:

- terms used throughout this specification which have been defined in Clause 3: in bold type.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

An external alternating magnetic flux can induce electric fields inside the human body. Such induced fields constitute an important category of possible hazards. This technical specification deals with the sub-category of non-radiating magnetic nearfields in the frequency range between 1 Hz and 6 MHz being the source of the induced electric fields. The primary focus is on technical applications in industrial electroheating and electromagnetic processing installations and equipment, with the applicable safety standards in the IEC 60519 series.

IEC 62110:2009 deals with measurement procedures applicable to the characterisation of magnetic and electric field levels with regard to public exposure. IEC 62822-2:2016 provides assessments of exposure restrictions for electric arc welding equipment from 0 Hz to 300 GHz. There is, however, no other IEC standard or technical specification covering more general kinds of equipment and hazard assessments in the range of up to 6 MHz.

Magnetic field hazards are dependent on the source characteristics, including such without and with magnetic materials in the source circuit or workload. Such materials enhancing the magnetic flux density are required for creating an induced electric shock hazard below some few kHz. Static magnetic fields can cause other hazards than those by conventionally induced electric fields and are dealt with in IEC 60519-1:2015. The lower frequency limit in this technical specification is therefore 1 Hz.

NOTE A parallel IEC technical specification IEC TS 62996¹ is developed by IEC TC 27, to cover touch and contact currents and voltages in the frequency range 1 kHz to 6 MHz. It also includes measurements of capacitively coupled currents through the body. Touch and contact currents and voltages at lower frequencies are covered by IEC 61140:2016.

The upper frequency limit 6 MHz is chosen, since

- higher frequencies are not expected to be employed by internal frequency converters for DC voltage transformation in equipment;
- the free space wavelength of 6 MHz is 50 m, which results in wave phenomena that essentially do not exist in or at parts of the human body which have less than 10 % characteristic dimensions of this;
- the power penetration depth limitation by the equivalent complex permittivity of body tissues has not yet set in at 6 MHz, so the magnetic flux completely penetrates the parts of the body under study with no shielding effects, resulting in an overall simpler and linear frequency dependence of the induced electric fields;
- the equivalent complex permittivity of the parts of the body under study is typically so high in this frequency range that external electric fields are efficiently hindered from entering the part of the body and causing internal electric fields – as a consequence, the separation of capacitively coupled and induced electric fields is therefore strong;
- processing frequencies below 6 MHz are typically low impedance; higher impedance dielectric heating has its lowest ISM frequency at 6,8 MHz, being dealt with in IEC 60519-9:2005.

Electromagnetic exposure is commonly defined to occur whenever and wherever a person is subjected to electric, magnetic or electromagnetic fields, and the allowed acceptable levels of exposure are usually specified by national radiation protection or worker protection agencies in the framework of health and safety regulations addressing the user of equipment. Since different sources of information on the associated safety requirements exist and these sources tend to apply quite different safety margins, there are unfortunately significant discrepancies among their levels of the in principle pathophysiologically based so-called basic restrictions.

¹ Under preparation. Stage at the time of publication: IEC/CDTS 62996:2016.

When the source is well defined and is the basis for calculations and computations, the technical treatment of emission is preferred to the consideration of exposure. That is the case in this technical specification, also since the external magnetic nearfield is not modified by the presence of the part of the body nearby. Furthermore, the resulting induced and potentially hazardous internal electric fields depend on the size, shape and orientation of the part of the body in relation to the source, and on the spatial characteristics of the field. Since the induced electric field by magnetic nearfields is directed essentially parallel to the bodypart surface, whereas it is perpendicular for contact current fields, the hazard criteria applied in this technical specification differ from those in some standards.

This technical specification provides complete information for assessments.

The treatment of magnetic nearfields as defined in this technical specification deals with discontinuous presence of the operator in the nearfield, as well as intermittent operation. Cases which do result in shorter term higher body tissue temperature rise in very small tissue volumes are also dealt with in this technical specification. The information and requirements are thus useful for other similar cases in science and industry.

As to measurement procedures and equipment, IEC 60519-1:2015 provides an overview. IEC TC 106 has published standards which provide guidance for situations where the source of the magnetic field and the exposed person are typically further apart than in the situations addressed in this technical specification. As a consequence, those standards tend to define magnetic field sensors neither well suited for measurements very close to current-carrying conductors nor on magnetic fields which vary considerably over the region where the nearest part of the body being submitted to the emission is located.

IEC 62822-2:2016 developed by IEC TC 26 deals with the reduction of the coupling from magnetic nearfields compared with homogeneous fields, as does this technical specification, but in somewhat different ways.

Hazard estimations related to magnetic nearfields pose problems with the use of some existing exposure standards, either by an exaggerated safety margin of the so-called reference levels, or by complicated and expensive numerical modelling in applying the so-called basic restrictions. The methods in this technical specification reduce costs to industry by being simple and direct. They are also realistic, in particular since the number of reported accidents or incidents caused by magnetic nearfields as addressed in this technical specification are exceptionally few in relation to the occurrence of strong such fields in industry.

This technical specification specifies a volunteer test method for assessments of perception of immediate muscle and nerve reactions in fingers and hands at frequencies below 100 kHz. A first argument is that the test ends at the perception level when the person's finger or hand slowly approaches the current-carrying conductor without contacting it, and a distance is measured. There is no risk of harm, unlike with medical tests using volunteers, which require ethical permits, etc. A second argument is that the computational alternative in cases with intricate conductor geometries and possible magnetic materials in the source circuit or workload is highly complicated and therefore expensive, requiring numerical modelling since measurements of the magnetic nearfield is virtually impossible and the induced electric field depends on the positioning of the finger or hand. A third argument is that realistic data are immediately obtained and typically result in the safety distance in most cases being very short and therefore easy to control.

INDUSTRIAL ELECTROHEATING AND ELECTROMAGNETIC PROCESSING EQUIPMENT –

Evaluation of hazards caused by magnetic nearfields from 1 Hz to 6 MHz

1 Scope

This IEC technical specification specifies the characteristics of external magnetic nearfields, computations of and requirements on induced electric fields in body tissues in the frequency range from 1 Hz to 6 MHz with respect to induced electric shock phenomena, for electroheating (EH) based treatment technologies and for electromagnetic processing of materials (EPM). The phenomena include specific absorption rates with time integration.

NOTE The overall safety requirements for the various types of equipment and installations for electroheating or electromagnetic processing in general result from the joint application of the General Requirements specified in IEC 60519-1:2015 and Particular Requirements covering specific types of installations or equipment. This technical specification complements the General Requirements and applies to internal frequency converters for creating high or low DC voltages, and to processing frequencies.

Induced electric shock phenomena dealt with in this technical specification are caused by the alternating magnetic nearfield external to a current-carrying conductor or permeable object, inducing an electric field in a part of the body in the vicinity of the conductor.

Relaxed criteria compared with the general **basic restrictions** for exposure apply. Simplified hazard assessment procedures apply for situations when only fingers, hands and/or extremities are in the magnetic nearfield.

This technical specification does not apply to equipment within the scope of IEC 60519-9. i.e. equipment or installations for high frequency dielectric heating.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60417, *Graphical symbols for use on equipment* (available at <http://www.graphical-symbols.info/equipment>)

IEC 60519-1:2015, *Safety in installations for electroheating and electromagnetic processing – Part 1: General requirements*

3 Terms, definitions, symbols and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60519-1:2015 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses: