



BSI Standards Publication

Car multimedia systems and equipment – Drive monitoring system

Part 1: General

National foreword

This Published Document is the UK implementation of IEC TS 63033-1:2017.

The UK participation in its preparation was entrusted to Technical Committee EPL/100, Audio, video and multimedia systems and equipment.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2017
Published by BSI Standards Limited 2017

ISBN 978 0 580 96520 3

ICS 33.160.99; 43.040.15

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 September 2017.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------



IEC TS 63033-1

Edition 1.0 2017-05

TECHNICAL SPECIFICATION



**Car multimedia systems and equipment – Drive monitoring system
Part 1: General**

Currently in preview, click buy full version





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
 3, rue de Varembe
 CH-1211 Geneva 20
 Switzerland

Tel.: +41 22 919 02 11
 Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - www.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.



IEC TS 63033-1

Edition 1.0 2017-05

TECHNICAL SPECIFICATION



Car multimedia systems and equipment – Drive monitoring system
Part 1: General

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.160.99; 43.040.15

ISBN 978-2-8322-4282-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms, definitions and abbreviated terms	7
3.1 Terms and definitions.....	7
3.2 Abbreviated terms.....	7
4 System model.....	7
4.1 General.....	7
4.2 Number of cameras and camera field of view	8
4.3 Method for projecting visual image to 3D projection surface.....	9
4.4 Visualizing the projection image at free eye point.....	10
4.5 Free eye point capability.....	11
5 Camera configuration	11
5.1 Camera.....	11
5.2 Lens distortion data	11
5.2.1 Distortion data of rotationally symmetric lens	11
5.2.2 Distortion data of non-rotationally symmetric lens.....	12
5.3 Optical axis shift data	13
6 Rendering.....	14
6.1 General.....	14
6.2 Composite view data.....	14
6.2.1 3D projection surface data.....	14
6.2.2 Capture size	14
6.2.3 Conversion of eye point parameter	15
6.2.4 Virtual 3D image car model data.....	16
6.2.5 Guide line and bit map data.....	17
6.2.6 Layout data and color setting data.....	18
Annex A (informative) Camera mounting to the car	20
A.1 Camera mounting position	20
A.2 Camera mounting height.....	20
A.3 Camera mounting angle.....	20
Annex B (informative) Camera field of view.....	22
Annex C (informative) Camera calibration.....	23
Annex D (informative) Display.....	24
D.1 Display specification data	24
D.2 Composite view change mode.....	24
Annex E (informative) Time behaviour	25
E.1 Start-up time.....	25
E.2 Frame rate.....	25
E.3 Latency.....	25
Bibliography.....	26
Figure 1 – System model for the drive monitoring system	8
Figure 2 – Horizontal angle of view of the camera.....	8

Figure 3 – Vertical angles of view of the camera	9
Figure 4 – 3D projection surface	10
Figure 5 – Projecting to 3D projection surface.....	10
Figure 6 – Distortion data of a rotationally symmetric lens	11
Figure 7 – Distortion data format of a rotationally symmetric lens.....	12
Figure 8 – Distortion data of a non-rotationally symmetric lens	12
Figure 9 – Distortion data format of a non-rotationally symmetric lens.....	13
Figure 10 – Texture normalization coordinate at the centre of each optical axis	13
Figure 11 – The format of optical shift data	14
Figure 12 – 3D projection surface data	14
Figure 13 – Capture specification data format.....	15
Figure 14 – Camera angle in conversion of eye point.....	15
Figure 15 – Camera position/scaling in conversion of eye point	16
Figure 16 – Virtual 3D image car model at original dimension	16
Figure 17 – Virtual 3D image car model at real dimension.....	17
Figure 18 – Guide line and bitmap data.....	17
Figure 19 – Camera image coordinate system	18
Figure 20 – Screen coordinate system	18
Figure 21 – Object coordinate system	19
Figure 22 – Layout data and layer setting data.....	19
Figure A.1 – Camera mounting position	20
Figure A.2 – Camera mounting height.....	20
Figure A.3 – Camera mounting angle	21
Figure C.1 – Camera calibration	23

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**CAR MULTIMEDIA SYSTEMS AND EQUIPMENT –
DRIVE MONITORING SYSTEM****Part 1: General****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, accept IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 63033-1, which is a technical specification, has been prepared by IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting
100/2819/DTS	100/2877/RVDTS

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 63033 series, published under the general title *Car multimedia systems and equipment*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- transformed into an International standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The drive monitoring system is a camera-based visual system enabling the car user to record and view in real time the surrounding visual image of their vehicle from anywhere within a 360° surround view perspective. The purpose of this document is to specify the model for generating the desired surrounding visual image of the drive monitoring system. Typically, the drive monitoring system is defined by the audio-visual monitoring system requirements of the car multimedia system and equipment.

To ensure the correct positioning of the car in relation to its surroundings, the rear-view monitor for parking assistance, the blind spot monitor for displaying views of the blind spots, and the bird's-eye view monitor are used. Each drive monitoring system provides a different viewpoint to the car's driver. It's a heavy burden for a car driver to switch between these systems and quickly recognize the multiple fields of view. In addition, the fields of view are limited to these camera systems which cannot freely change the eye point depending on the driving situation. As a result, the usage cases for these types of systems are limited to singular functions such as parking assistance. Furthermore, on commercial vehicles such as trucks, buses and other special vehicles, ranging from construction to agricultural machinery, the usage cases for these systems is even more limited. In these vehicle types, there might exist situations in which no one is available to assist the driver in properly ensuring the car's correct and safe position.

To resolve these problems, the drive monitoring system provides the driver with the optimal surround view image as constructed by the model explained in this document. It provides the optimal viewpoint of the vehicle and its surroundings to the driver for ensuring the car's good positioning in various driving situations (parking, turning, high traffic situations, etc.). This is not only true for passenger cars, but good positioning can also be quickly ensured for commercial vehicles and other special vehicles as well.

Part 1 specifies the model for generating the surrounding visual image of the drive monitoring system. Part 2 specifies the information sets that are provided by the drive monitoring system, which include recording methods for that information and the actual visual images. Part 3 specifies the measurement methods of surrounding visual images for the drive monitoring system.

CAR MULTIMEDIA SYSTEMS AND EQUIPMENT – DRIVE MONITORING SYSTEM

Part 1: General

1 Scope

This document specifies the model for generating the surrounding visual image of the drive monitoring system.

2 Normative references

There are no normative references in this document.

3 Terms, definitions and abbreviated terms

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1 Terms and definitions

3.1.1

car

any kind of powered wheeled vehicle

3.2 Abbreviated terms

3D	three dimensional
camera ECU	camera electronic control unit
CAN	controller area network
GUI	graphical user interface

4 System model

4.1 General

The system model of the drive monitoring system is described in Figure 1. Cameras, which are mounted on the outside the car, capture the visual image of the environment outside the car. The visual images are projected onto a virtual 3D projection surface that is then displayed as a composite image onto the monitor. The images displayed can be rendered from any viewpoint within the 3D projection surface, thus enabling the optimal viewing perspective onto the display based on the scenario. The number of cameras required on vehicles other than passenger cars may be more than four depending on the size and shape of the car. This model defines a drive monitoring system with four cameras as typical for most car type applications. The number of cameras used in generating each composite image may change depending on the viewpoint. The mounting positions and angles for the four cameras should be calibrated as per the method described in 4.2 and 4.3.