



BSI Standards Publication

Gas cylinders — Guidance for design of composite cylinders

Part 2: Bonfire test issues

National foreword

This Published Document is the UK implementation of ISO/TR 13086-2:2017.

The UK participation in its preparation was entrusted to Technical Committee PVE/3/3, Gas containers - Transportable gas containers - Cylinder design, construction and testing at the time of manufacture.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018
Published by BSI Standards Limited 2018

ISBN 978 0 580 94722 3

ICS 23.020.35

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 28 February 2018.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

TECHNICAL
REPORT

ISO/TR
13086-2

First edition
2017-12-15

**Gas cylinders — Guidance for design
of composite cylinders —**

**Part 2:
Bonfire test issues**

*Bouteilles à gaz — Recommandations pour la conception des
bouteilles en matière composite*

Partie 2: Aspects concernant les essais à la flamme vive



Reference number
ISO/TR 13086-2:2017(E)

© ISO 2017



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017. Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Background.....	1
5 Statement of safety.....	2
6 Components of fire testing.....	2
6.1 Composite materials.....	2
6.2 Fire 3	
6.2.1 General.....	3
6.2.2 Fire tests in standards.....	6
6.2.3 Standardized fire test.....	8
6.2.4 Considerations for future standardized fire tests.....	9
6.3 Pressure relief devices.....	10
6.4 Venting.....	12
6.5 Interaction.....	13
6.6 Availability of reports.....	16
6.7 Optimized test method using thermally activated pressure relief devices.....	17
6.7.1 Explanation of optimized test method.....	17
6.7.2 Procedures for optimized test method.....	20
7 Summary.....	23
Annex A (informative) Comparison of fire tests in standards and reports.....	24
Annex B (informative) Standardized test requirements using thermally active pressure relief devices.....	28
Bibliography.....	33

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 58, *Gas cylinders*, Subcommittee SC 3, *Cylinder design*.

Introduction

Composite reinforced cylinders have been used in commercial service for about 40 years. Common fibres used in composite cylinders include glass, aramid, and carbon. Resin matrix materials are commonly epoxy or vinyl ester.

Composite cylinders are known to be exposed to the action of fire, ranging from radiant heating to full engulfment in the fire. Cylinder performance during exposure to fire might depend on the cylinder materials of construction, size of the fire, dimensions of the cylinder, its orientation, its contents, and the use of temperature or pressure activated relief devices.

Fire exposure tests are often included in composite cylinder standards, sometimes as a mandatory test and sometimes as an optional test. This document addresses issues related to composite cylinders exposed to fire, summarizes test requirements, and offers a new approach to qualifying cylinders with relief devices.

Currently in preview, click buy full version

Gas cylinders — Guidance for design of composite cylinders —

Part 2: Bonfire test issues

1 Scope

This document addresses the topic of safety and performance of composite cylinders in a fire situation. A statement of safety addresses the topics which should be understood in order to operate cylinders safely in service. The remainder of this document provides a basic level of understanding of these topics.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

4 Background

Composite cylinders began service in the 1950s, initially as rocket motor cases with glass fibre reinforcement. This led shortly to glass fibre pressure vessels with rubber liners, and then to glass fibre pressure vessels with metal liners. Metal liners were typically either aluminium or steel. Eventually, new structural fibres, such as aramid and carbon, came into use for reinforcing pressure vessels. Today, typical reinforcements are glass and carbon, either individually or together as a hybrid. Typical liner materials are steel, aluminium, or polymers, often high density polyethylene (HDPE) or a polyamide (PA).

Composite cylinders offer certain advantages, particularly light weight and corrosion resistance. However, there are some performance requirements that tax the abilities of composite cylinders. One of these is the ability to withstand exposure to fire conditions without rupture. Fire conditions might include both direct exposure to fire, and to the elevated temperatures resulting from a fire. Direct exposure might include localized flames, or an engulfing fire.

Sources for a fire could include discharge of flammable gases from nearby cylinders, spilled liquid fuel from motor vehicles, car fires, house or building fires, and grass or forest fires, to name a few. There is significant variation in the fire conditions that arise from each of these causes, and there are issues on reproducibility of any of these types of fires.

Composite cylinders might be able to withstand a certain level of fire exposure on their own. However, it is more common in certain applications to use a system approach that could include isolation from fire, insulation, pressure activated relief valves or devices, and/or thermally activated relief devices. However, there might be conditions where the risk of rupture is less than the risk and consequence of leakage, and a pressure relief device (PRD) or similar device would not be used. Individual cylinders