



BSI Standards Publication

**Road vehicles — Test  
procedures for evaluating  
child restraint system  
interactions with deploying  
air bags**

**National foreword**

This Published Document is the UK implementation of ISO/TR 14645:2015.

The UK participation in its preparation was entrusted to Technical Committee AUE/15, Safety related to vehicles.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2015.

Published by BSI Standards Limited 2015

ISBN 978 0 580 84008 1

ICS 43.040.80

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 5 March 2015.

**Amendments/corrigenda issued since publication**

<b>Date</b>	<b>Text affected</b>
-------------	----------------------

---

---

---

**Road vehicles — Test procedures  
for evaluating child restraint system  
interactions with deploying air bags**

*Véhicules routiers — Méthodes d'essai pour l'évaluation des  
interactions des systèmes de retenue pour enfants et des sacs  
gonflables en cours de déploiement*





**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
<b>Foreword</b> .....	<b>v</b>
<b>Introduction</b> .....	<b>vi</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Test device</b> .....	<b>2</b>
4.1 General.....	2
4.2 Six-month-old infant dummies.....	2
4.2.1 CRABI 6-month.....	2
4.3 Nine-month-old infant dummy.....	2
4.3.1 P-3/4.....	2
4.4 Twelve-month-old infant dummy.....	2
4.4.1 CRABI 12-month.....	2
4.5 Three-year-old child dummies.....	2
4.5.1 Three-year-old child Hybrid III.....	2
4.5.2 P-3.....	2
4.5.3 Q-3.....	2
4.6 Six-year-old child dummies.....	3
4.6.1 P-6.....	3
4.6.2 Hybrid-III six-year.....	3
4.6.3 Q-6.....	3
<b>5 Instrumentation</b> .....	<b>3</b>
5.1 Measurements.....	3
5.2 CRABI 6-month and 12-month.....	3
5.3 P-3/4 nine-month.....	3
5.4 Hybrid III three-year.....	3
5.5 P-3 three-year.....	4
5.6 Q-3 Three-year.....	4
5.7 Hybrid III six-year.....	4
5.8 P-6 six-year.....	5
5.9 Q-6 six-year.....	5
5.10 Dummy test temperature.....	5
<b>6 Sled pulse</b> .....	<b>5</b>
6.1 General.....	5
6.2 Mild-severity crash pulse.....	5
<b>7 Static tests</b> .....	<b>6</b>
7.1 General.....	6
7.2 Test set-up.....	6
<b>8 Dynamic tests</b> .....	<b>6</b>
8.1 General.....	6
8.2 Test set-up.....	6
8.3 Simulation of sensing time.....	7

## Contents

Page

<b>9</b>	<b>CRS configurations and dummy combinations</b> .....	<b>7</b>
9.1	General.....	7
9.2	Rear-facing CRSs.....	8
9.2.1	General.....	8
9.2.2	CRS configuration R1 .....	8
9.2.3	CRS rear facing ISOFIX/LATCH configuration R2.....	8
9.2.4	CRS configuration R3 .....	8
9.3	Laterally-positioned CRSs.....	9
9.3.1	General.....	9
9.3.2	CRS configuration L1 .....	9
9.3.3	CRS configuration L2.....	10
9.3.4	ISOFIX/LATCH L3.....	10
9.4	Forward-facing CRSs.....	10
9.4.1	General.....	10
9.4.2	CRS configuration F1 .....	10
9.4.3	CRS configuration F2.....	10
9.4.4	CRS configuration F3.....	11
9.5	Boosters.....	11
9.5.1	General.....	11
9.5.2	CRS configuration B1 .....	11
9.5.3	CRS configuration B2 .....	11
9.5.4	CRS Configuration B3.....	12
<b>10</b>	<b>Primary dummy measurements</b> .....	<b>12</b>
<b>11</b>	<b>CRABI fixture</b> .....	<b>12</b>
	<b>Bibliography</b> .....	<b>15</b>

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: [Foreword — Supplementary information](#).

The committee responsible for this document is ISO/TC 22, *Road vehicles*, Subcommittee SC 36, *Safety aspects and impact testing*.

This second edition cancels and replaces the first edition (ISO/TR 14645:1998), which has been technically revised.

This document is published as a Technical Report, rather than as an International Standard, because of the general inexperience in testing the interaction between child restraint systems (CRS) and deploying air bags, and the lack of real-world accident data. When statistically significant, real-world data are available, in which air bags have contacted a variety of child restraints, and there is more testing experience with this interaction, it may be appropriate to develop an International Standard.

## Introduction

During its inflation process, an air bag generates a considerable amount of kinetic energy and, as a result, substantial forces can be developed between the deploying air bag and the child restraint system (CRS). (For background on air bag design and deployment, see References [1] and [2]. With passenger air bags, laboratory tests have indicated that these forces can be sufficient to produce serious injury to the CRS occupant. The National Highway Traffic Safety Administration has recommended that rear-facing child restraints of current design be used only in the rear seat of vehicles equipped with such air bags (see Reference [3]). Even so, many children can be restrained in either rear- or forward-facing CRSs in the front seat of such vehicles, and the child and/or the CRS can interact with the air bag. These guidelines were developed to improve the understanding of such interactions and to aid in the assessment of future designs.

A mild-severity crash pulse is described in this Technical Report. This pulse is not vehicle-specific, but represents general acceleration-time histories. This mild-severity pulse approximates a crash that would just deploy a typical air bag. This pulse is used to evaluate the effect of the energy of the deploying air bag when the CRS and dummy are exerting the least amount of inertial force in the forward direction, but the dummy and/or CRS is moved forward by that inertial force. This generic pulse or other vehicle-specific pulses can be used as appropriate. Differences in shape between the generic and the vehicle-specific pulses are expected with corresponding differences expected in dummy responses.

This Technical Report encourages the use of a wide range of test configurations and conditions, while recognizing that the range of possible interactions is essentially limitless and beyond testing capability. Furthermore, measurements of primary importance for the various configurations are given in [Table 1](#), but performance limits are not specified. References [4] to [9] give some background on human impact tolerance and criteria, describe scaling techniques for different size occupants, and offer interpretations of dummy responses relative to human injury potential that can be helpful in the evaluation. These and additional background papers on air bag development and deployment can be found in References [10] and [11].

# Road vehicles — Test procedures for evaluating child restraint system interactions with deploying air bags

## 1 Scope

This Technical Report describes dummies, procedures, and configurations that can be used to investigate the interactions that occur between a deploying air bag and a Child Restraint System (CRS) that would have been considered properly installed and used in the outer and centre front passenger positions. Static tests can be used to sort CRS/air bag interaction on a comparative basis in either an actual or a simulated vehicle environment. Systems that appear to warrant further testing can be subjected to an appropriate dynamic test at a speed near that needed to deploy an air bag or at a higher speed commonly used to evaluate CRS performance. No test matrix is specified at this time for evaluating either a CRS or an air bag during interaction with each other. Instead, engineering judgment based on prior experience with CRS and/or air bag testing should be used in selecting the tests to be conducted with each individual system. Such tests can be aimed not only at producing interactions with the most severe results but also at identifying those conditions that produce the least interaction and/or satisfactory CRS performance results. Baseline tests to indicate the performance of a CRS in the absence of air bag deployment are also recommended for comparison purposes.

## 2 Normative references

There are no normative references.

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1

#### rear-facing

R

child restraint that positions the child to face the rear of the vehicle

### 3.2

#### laterally-positioned

L

child restraint that positions a prone or supine child perpendicular to the direction of vehicle travel

### 3.3

#### forward-facing

F

child restraint that positions the child to face the front of the vehicle

### 3.4

#### booster

B

normally used to better position adult belt restraints on the child

### 3.5

#### ISOFIX/LATCH

“plug-in” system designed for fitting child safety seats in cars quickly and with ease per ISO 13216