



BSI Standards Publication

Road vehicles — Local Interconnect Network (LIN)

Part 5: Application program programmers interface (API)

National foreword

This Published Document is the UK implementation of ISO/TR 17987-5:2016.

The UK participation in its preparation was entrusted to Technical Committee AUE/16, Data Communication (Road Vehicles).

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2016.
Published by BSI Standards Limited 2016

ISBN 978 0 580 90705 0
ICS 43.040.15

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 10 November 2016.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

TECHNICAL
REPORT

ISO/TR
17987-5

First edition
2016-11-15

**Road vehicles — Local Interconnect
Network (LIN) —**

Part 5:
**Application programmers interface
(API)**

Véhicules routiers — Réseau Internet local (LIN) —

Partie 5: Interface du programmeur d'application (API)



Reference number
ISO/TR 17987-5:2016(E)

© ISO 2016



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016. Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms, definitions and abbreviated terms	1
3.1 Terms and definitions.....	1
3.2 Symbols.....	1
3.3 Abbreviated terms.....	1
4 API definitions	1
4.1 LIN cluster generation.....	1
4.2 Concept of operations.....	2
4.2.1 General.....	2
4.2.2 LIN core API.....	2
4.2.3 LIN node configuration and identification API.....	2
4.2.4 LIN transport layer API.....	2
4.3 API conventions.....	3
4.3.1 General.....	3
4.3.2 Data types.....	5
4.3.3 Driver and cluster management.....	5
4.3.4 Signal interaction.....	5
4.3.5 Notification.....	7
4.3.6 Schedule management.....	9
4.3.7 Interface management.....	10
4.3.8 User provided call outs.....	16
4.4 Node configuration and identification.....	17
4.4.1 Overview.....	17
4.4.2 Node configuration.....	17
4.4.3 Identification.....	22
4.5 Transport layer.....	23
4.5.1 Overview.....	23
4.5.2 Raw- and message-based API.....	23
4.5.3 Initialization.....	24
4.5.4 Raw API.....	24
4.5.5 Overview.....	24
4.5.6 Message-based API.....	26
4.6 Examples.....	30
4.6.1 Overview.....	30
4.6.2 Master node example.....	30
4.6.3 Slave node example.....	32
Bibliography	34

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*.

A list of all parts in the ISO 17987 series can be found on the ISO website.

Introduction

ISO 17987 (all parts) specifies the use cases, the communication protocol and physical layer requirements of an in-vehicle communication network called Local Interconnect Network (LIN).

The LIN protocol as proposed is an automotive focused low speed Universal Asynchronous Receiver Transmitter (UART) based network. Some of the key characteristics of the LIN protocol are signal-based communication, schedule table-based frame transfer, master/slave communication with error detection, node configuration and diagnostic service communication.

The LIN protocol is for low cost automotive control applications, for example, door module and air condition systems. It serves as a communication infrastructure for low-speed control applications in vehicles by providing:

- signal-based communication to exchange information between applications in different nodes;
- bit rate support from 1 kbit/s to 20 kbit/s;
- deterministic schedule table-based frame communication;
- network management that wakes up and puts the LIN cluster into sleep mode in a controlled manner;
- status management that provides error handling and error signalling;
- transport layer that allows large amount of data to be transmitted (such as diagnostic services);
- specification of how to handle diagnostic services;
- electrical physical layer specifications;
- node description language describing properties of slave nodes;
- network description file describing behaviour of communication;
- application programmer's interface;

ISO 17987 (all parts) is based on the open systems interconnection (OSI) Basic Reference Model as specified in ISO/IEC 7498-1 which structures communication systems into seven layers.

The OSI model structures data communication into seven layers called (top down) *application layer* (layer 7), *presentation layer*, *session layer*, *transport layer*, *network layer*, *data link layer* and *physical layer* (layer 1). A subset of these layers is used in ISO 17987 (all parts).

ISO 17987 (all parts) distinguishes between the services provided by a layer to the layer above it and the protocol used by the layer to send a message between the peer entities of that layer. The reason for this distinction is to make the services, especially the application layer services and the transport layer services, reusable also for other types of networks than LIN. In this way, the protocol is hidden from the service user and it is possible to change the protocol if special system requirements demand it.

ISO 17987 (all parts) provides all documents and references required to support the implementation of the requirements related to.

- ISO 17987-1: This part provides an overview of the ISO 17987 (all parts) and structure along with the use case definitions and a common set of resources (definitions, references) for use by all subsequent parts.
- ISO 17987-2: This part specifies the requirements related to the transport protocol and the network layer requirements to transport the PDU of a message between LIN nodes.
- ISO 17987-3: This part specifies the requirements for implementations of the LIN protocol on the logical level of abstraction. Hardware-related properties are hidden in the defined constraints.

- ISO 17987-4: This part specifies the requirements for implementations of active hardware components which are necessary to interconnect the protocol implementation.
- ISO/TR 17987-5: This part specifies the LIN application programmers interface (API) and the node configuration and identification services. The node configuration and identification services are specified in the API and define how a slave node is configured and how a slave node uses the identification service.
- ISO 17987-6: This part specifies tests to check the conformance of the LIN protocol implementation according to ISO 17987-2 and ISO 17987-3. This comprises tests for the data link layer, the network layer and the transport layer.
- ISO 17987-7: This part specifies tests to check the conformance of the LIN electrical physical layer implementation (logical level of abstraction) according to ISO 17987-4.

The LIN API is a network software layer that hides the details of a LIN network configuration (e.g. how signals are mapped into certain frames) for a user making an application program for an arbitrary ECU. The user is provided an API, which is focused on the signals transported on the LIN network. A tool takes care of the step from network configuration to program code. This provides the user with configuration flexibility. The LIN API is only one possible API existing today besides others like defined for LIN master nodes in the AUTOSAR standard. Therefore, the LIN API is published as a Technical Report and all definitions given here are informative only.

Road vehicles — Local Interconnect Network (LIN) —

Part 5: Application programmers interface (API)

1 Scope

This document has been established in order to define the LIN application programmers interface (API).

2 Normative references

There are no normative references in this document.

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 17987-2 and ISO 17987-3 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.2 Symbols

|| logical OR binary operation

3.3 Abbreviated terms

API application programmers interface
ms millisecond
OSI open systems interconnection
PDU protocol data unit
Rx Rx pin of the transceiver
UART universal asynchronous receiver transmitter

4 API definitions

4.1 LIN cluster generation

The LIN Description file (LDF; see ISO 17987-2) is parsed by a tool and generates a configuration for the LIN device driver. The node capability language specification (NCF) is normally not used in this