



BSI Standards Publication

Plain bearings — Spray nozzle type directed lubrication for tilting pad bearings

National foreword

This Published Document is the UK implementation of ISO/TR 21784:2018.

The UK participation in its preparation was entrusted to Technical Committee MCE/12, Plain bearings.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018
Published by BSI Standards Limited 2018

ISBN 978 0 539 00114 3

ICS 21.100.10

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 September 2018.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

TECHNICAL
REPORT

ISO/TR
21784

First edition
2018-09-30

**Plain bearings — Spray nozzle
type directed lubrication for tilting
pad bearings**

Titre manque



Reference number
ISO/TR 21784:2018(E)

© ISO 2018



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018. Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Symbols and abbreviated terms.....	1
5 Reduction effect of power loss by spray nozzle type directed lubrication systems.....	2
6 Lubrication system.....	5
6.1 Tilting pad thrust bearing.....	5
6.2 Tilting pad journal bearing.....	6
7 Oil supply system of spray nozzle type directed lubrication.....	7
7.1 General.....	7
7.2 Tilting pad thrust bearing.....	7
7.3 Tilting pad journal bearing.....	8
7.4 Oil flow.....	8
7.5 Oil supply pressure.....	9
8 Structure of oil inlet and outlet (drainage) on nozzle type directed lubrication.....	9
8.1 Tilting pad thrust bearing.....	9
8.2 Tilting pad journal bearing.....	11
Bibliography.....	13

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 123, *Plain bearings*, Subcommittee SC 7, *Special types of plain bearings*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

These days, rotating machines such as turbines, generators, compressors, pumps, etc. tend to be increasing in speed and reducing in size. Bearings used in such machines can cause large power losses, which not only degrades machine performance but also results in the associated cooling system being larger in size. Directed lubrication type bearings can reduce the power loss significantly. They are energy-saving bearings that can simplify facilities and improve plant efficiency.

Currently in preview, click buy full version.

Currently in preview, click buy full version

Plain bearings — Spray nozzle type directed lubrication for tilting pad bearings

1 Scope

Directed lubrication is an advanced technology that is capable of reducing the power loss and improving the performance of tilting pad type bearings. Unlike flooded lubrication, where the bearing components remain permanently submerged in an oil filled housing, with directed lubrication the components are not submerged and the oil is delivered from an external source directly to the working surfaces of the tilting pads after which it falls freely away to be drained from the bottom of the housing. There are several alternative methods of realising the benefits of directed lubrication in tilting pad bearing designs. As an example, this document specifies a spray nozzle type directed lubrication system where lubricant is supplied to each pad through nozzles mounted between the pads in tilting pad thrust and journal bearings. The design concept of this type of lubrication is described.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Symbols and abbreviated terms

For the purposes of this document, the following symbols apply.

Table 1 — Symbols and units

Symbol	Explanation	Unit
B_{tc}	Thrust collar width	m
c_p	Specific heat capacity of lubricant	J/(kg·K)
D_d	Diameter of discharge oil hole	m
d_h	Hole diameter of nozzle	m
Q	Coefficient of oil flow rate	1
n_h	Number of holes per nozzle	1
n_n	Number of nozzles per bearing	1
P	Power loss	W
p_{en}	Oil supply pressure	Pa
Q	Total oil flow rate	m ³ /s
Q_n	Oil flow rate per nozzle	m ³ /s
ΔT	Oil temperature rise	K
ρ	Density of lubricant	kg/m ³