



BSI Standards Publication

**Hydraulic fluid power — Hose and hose assemblies  
— Method of collecting a fluid sample for analyzing  
the cleanliness of a hose or hose assembly**

---

## National foreword

This Published Document is the UK implementation of ISO/TS 18409:2018.

The UK participation in its preparation was entrusted to Technical Committee MCE/18/-/4, Connectors and associated components.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018  
Published by BSI Standards Limited 2018

ISBN 978 0 580 88093 3

ICS 23.100.40

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 April 2018.

### Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

---

---

---

**Hydraulic fluid power — Hoses and hose assemblies — Method of collecting a fluid sample for analyzing the cleanliness of a hose or hose assembly**

*Transmissions hydrauliques — Flexibles et flexibles de raccordement — Méthode de collecte d'échantillon de fluide pour l'évaluation de la propreté de flexibles ou flexibles de raccordement*





**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2018. Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
copyright@iso.org  
www.iso.org

## Contents

Page

Foreword.....	iv
Introduction.....	v
<b>1 Scope.....</b>	<b>1</b>
<b>2 Normative references.....</b>	<b>1</b>
<b>3 Terms and definitions.....</b>	<b>1</b>
<b>4 Test equipment.....</b>	<b>2</b>
<b>5 Contaminant collection methods.....</b>	<b>3</b>
5.1 General.....	3
5.2 Procedure for collecting a sample using the agitation (“slosh”) method.....	4
5.3 Procedure for collecting a sample using the quick rinse method.....	5
<b>6 Identification statement (reference to this document).....</b>	<b>6</b>
<b>Annex A (informative) Choice of the contaminant collection method.....</b>	<b>7</b>
<b>Annex B (normative) Determination of the controlled volume and controlled surface.....</b>	<b>8</b>
<b>Annex C (normative) Agitation (slosh) method — Instructions on filling and rotating the test item, and collecting the test liquid.....</b>	<b>9</b>
<b>Annex D (normative) Requirements for the dispensing system for quick rinse method.....</b>	<b>11</b>
<b>Bibliography.....</b>	<b>13</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 151, *Fluid power systems*, Subcommittee SC 4, *Connectors and similar products and components*.

## Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a pressurized liquid within a circuit where piping allows the fluid to flow between components. Part of the piping may consist of hose assemblies, usually manufactured by assembling a length of hose, cut out from a hose coil, with specific connectors at its ends.

One of the functions of the hydraulic liquid in a system is to separate and lubricate the moving parts of components. The presence of solid particles produces wear, resulting in loss of efficiency, reduced component life and subsequent unreliability. Thus, hydraulic liquid cleanliness is very important for the system's uninterrupted operation and long life.

The amount of solid contamination present in a hydraulic system at start-up has a great influence on reliability during initial operation and subsequent component life. Components should be cleaned to an appropriate level after manufacturing and prior to use.

Hose assemblies are potential sources of contamination because of the bulk hose manufacturing processes, which can be intrinsically dirty, and because of other contaminants coming from assembly operations (hose cutting, dirty connectors, etc.) and/or storage.

It may be required to assess the actual built-in solid contamination of hose assemblies before installation (e.g. ISO 4413: 2010, 5.4.6.4, in general requirements for piping).

Currently in preview, click buy full version

# Hydraulic fluid power — Hose and hose assemblies — Method of collecting a fluid sample for analyzing the cleanliness of a hose or hose assembly

## 1 Scope

This document specifies two methods for collecting a fluid sample to be used to analyse the cleanliness of hydraulic fluid power hoses or hose assemblies within a certain inside diameter and length range (this range includes the majority of hose assemblies of real fluid power applications).

The two methods described in this document are intended for collecting only solid particulate contamination; they may not be appropriate for collecting contamination in liquid or grease form.

This document is a specific application of ISO 18413:2015, specifically Annexes A and B.

The scope of this document does not include providing efficient and effective cleaning methods for hose assemblies. These methods are recommended for statistical validation of other hose cleaning methods, which are more suitable for systematic processing of large production batches.

Contamination analysis is excluded from the scope of this document.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3722, *Hydraulic fluid power — Fluid sample containers — Qualifying and controlling cleaning methods*

ISO 4405, *Hydraulic fluid power — Fluid contamination — Determination of particulate contamination by the gravimetric method*

ISO 4406, *Hydraulic fluid power — Fluids — Method for coding the level of contamination by solid particles*

ISO 4407, *Hydraulic fluid power — Fluid contamination — Determination of particulate contamination by the counting method using an optical microscope*

ISO 4788, *Laboratory glassware — Graduated measuring cylinders*

ISO 5598, *Fluid power systems and components — Vocabulary*

ISO 11500, *Hydraulic fluid power — Determination of the particulate contamination level of a liquid sample by automatic particle counting using the light-extinction principle*

ISO 18413, *Hydraulic fluid power — Cleanliness of components — Inspection document and principles related to contaminant extraction and analysis, and data reporting*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5598 and ISO 18413 and the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— IEC Electropedia: available at <http://www.electropedia.org/>