



BSI Standards Publication

## Road vehicles — Connection interface for pyrotechnic devices, two-way and three-way connections

---

Part 5: Pyrotechnic device and harness connector assembly — type 3 (only two-way)

## National foreword

This Published Document is the UK implementation of ISO/TS 19072-5:2019.

The UK participation in its preparation was entrusted to Technical Committee AUE/32, Electrical and electronic components and general system aspects (Road vehicles).

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2019  
Published by BSI Standards Limited 2019

ISBN 978 0 580 89270 7

ICS 43.040.10

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 September 2019.

### Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

---

**TECHNICAL  
SPECIFICATION**

**ISO/TS  
19072-5**

First edition  
2019-09-13

---

---

**Road vehicles — Connection interface  
for pyrotechnic devices, two-way and  
three-way connections —**

**Part 5:  
Pyrotechnic device and harness  
connector assembly — type 3  
(only two-way)**



Reference number  
ISO/TS 19072-5:2019(E)

© ISO 2019



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2019. Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
copyright@iso.org  
www.iso.org

## Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Dimensional features and performance requirements</b> .....	<b>2</b>
4.1 General.....	2
4.2 Retainer and squib holder assembly.....	2
4.3 Coding and polarisation.....	3
4.4 Figure 4 illustrates the dimensional features and properties for retainer function.....	6
4.5 Figure 5 illustrates the mating orientation view.....	10
<b>5 Material characteristics - Retainer</b> .....	<b>10</b>
<b>Bibliography</b> .....	<b>11</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 32, *Electrical and electronic components and general system aspects*.

A list of all parts in the ISO 19072 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

Road vehicles integrate an increasing number of pyrotechnic devices contributing to occupant safety in vehicles (for example frontal and side airbag, safety belt pre-tensioner, etc.).

Building the complete system requires a supply of various components from several different equipment suppliers. There is a need for vehicle manufacturers to define a common specification to ensure that connectors designed and produced for the various equipment suppliers can be mated without any difficulty.

In the current design of this vehicle equipment, three areas of connection have been identified:

- connection between the pyrotechnic device (e.g. initiator) and the harness connector;
- connection between the tab holder and the clip holder of the harness connector; and
- connection between the harness connector and the electronic control module.

The connection between the pyrotechnic device and the harness connector is the only connection that can be standardised, and it forms the subject of this document. Due to the location of the safety device in the vehicle, the connector design could be right angle or straight.

Currently in preview, click buy full version

# Road vehicles — Connection interface for pyrotechnic devices, two-way and three-way connections —

## Part 5: Pyrotechnic device and harness connector assembly — type 3 (only two-way)

### 1 Scope

This document defines the general minimum specifications of a type 3 two-way connection interface, linking the pyrotechnic device and harness connector built into a road vehicle.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8092-2, *Road vehicles — Connections for on-board electrical wiring harnesses — Part 2: Definitions, test methods and general performance requirements*

ISO 19072-1, *Road vehicles — Connection interface for pyrotechnic devices, two-way and three-way connections — Part 1: Pocket interface definition*

ISO 19072-2, *Road vehicles — Connection interface for pyrotechnic devices, two-way and three-way connections — Part 2: Test methods and general performances requirements*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8092-2 and the following apply.

#### 3.1

##### **connector**

assembly used to connect several conductors together or a single conductor to an appliance

Note 1 to entry: A male (female) connector is a *housing* (3.2) containing male (female) contacts and accessory items. A male connector may be permanently fixed to a wiring harness or to an appliance [an electronic control unit (ECU) for example]. A female connector is generally permanently fixed to a wiring harness.

#### 3.2

##### **housing**

connector (3.1) without its contacts

#### 3.3

##### **initiator**

part of the pyrotechnical device with two male contacts

#### 3.4

##### **pocket**

*squib holder* (3.6) inner interface including male contacts