



BSI Standards Publication

Calculation of load capacity of spur and helical gears

Part 21: Calculation of scuffing load capacity (also applicable to bevel and hypoid gears) — Integral temperature method

National foreword

This Published Document is the UK implementation of ISO/TS 6336-21:2017. It supersedes BS ISO/TR 13989-2:2000, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee MCE/5/-/6, Calculation of gear performance.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2017
Published by BSI Standards Limited 2017

ISBN 978 0 580 98181 4

ICS 21.200

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 December 2017.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

**TECHNICAL
SPECIFICATION****ISO/TS
6336-21**First edition
2017-11-16

**Calculation of load capacity of spur
and helical gears —**

Part 21:

**Calculation of scuffing load
capacity (also applicable to bevel
and hypoid gears) — Integral
temperature method***Calcul de la capacité de charge des engrenages cylindriques à
dentures droite et hélicoïdale —**Partie 21: Calcul de la capacité de charge au grippage (applicable
également aux engrenages conique et hypoïde) - Méthode de la
température intégrale*Reference number
ISO/TS 6336-21:2017(E)

© ISO 2017



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017. Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and units	1
3.1 Terms and definitions.....	1
3.2 Symbols and units.....	1
4 Field of application	6
4.1 General.....	6
4.2 Scuffing damage.....	6
4.3 Integral temperature criterion.....	6
5 Influence factors	6
5.1 Mean coefficient of friction, μ_{mC}	6
5.2 Run-in factor, X_E	9
5.3 Thermal flash factor, X_M	10
5.4 Pressure angle factor, $X_{\alpha\beta}$	11
6 Calculation	12
6.1 Cylindrical gears.....	12
6.1.1 General.....	12
6.1.2 Scuffing safety factor, S_{ints}	12
6.1.3 Permissible integral temperature, ϑ_{intP}	12
6.1.4 Integral temperature, ϑ_{int}	12
6.1.5 Flash temperature at pinion tooth tip, ϑ_{flaE}	13
6.1.6 Bulk temperature, ϑ_M	13
6.1.7 Mean coefficient of friction, μ_{mC}	14
6.1.8 Run-in factor, X_E	14
6.1.9 Thermal flash factor, X_M	14
6.1.10 Pressure angle factor, $X_{\alpha\beta}$	14
6.1.11 Geometry factor at tip of pinion, X_{BE}	14
6.1.12 Approach factor, X_Q	15
6.1.13 Tip relief factor, X_{Ca}	16
6.1.14 Contact ratio factor, X_ϵ	17
6.2 Bevel gears.....	19
6.2.1 General.....	19
6.2.2 Scuffing safety factor, S_{ints}	20
6.2.3 Permissible integral temperature, ϑ_{intP}	20
6.2.4 Permissible integral temperature, ϑ_{intP}	20
6.2.5 Flash temperature at pinion tooth tip, ϑ_{flaE}	20
6.2.6 Bulk temperature, ϑ_M	20
6.2.7 Mean coefficient of friction, μ_{mC}	20
6.2.8 Run-in factor, X_E	20
6.2.9 Thermal flash factor, X_M	21
6.2.10 Pressure angle factor, $X_{\alpha\beta}$	21
6.2.11 Geometry factor at tip of pinion, X_{BE}	21
6.2.12 Approach factor, X_Q	21
6.2.13 Tip relief factor, X_{Ca}	21
6.2.14 Contact ratio factor, X_ϵ	22
6.3 Hypoid gears.....	22
6.3.1 General.....	22
6.3.2 Scuffing safety factor, S_{ints}	22
6.3.3 Permissible integral temperature, ϑ_{intP}	22
6.3.4 Integral temperature, ϑ_{nt}	22

6.3.5	Bulk temperature, ϑ_M	22
6.3.6	Mean coefficient of friction, μ_{mC}	23
6.3.7	Run-in factor, X_E	23
6.3.8	Geometry factor, X_G	23
6.3.9	Approach factor, X_Q	25
6.3.10	Tip relief factor, X_{Ca}	25
6.3.11	Contact ratio factor, X_ε	25
6.3.12	Calculation of virtual crossed axes helical gears.....	25
6.4	Scuffing integral temperature.....	29
6.4.1	General.....	29
6.4.2	Scuffing integral temperature, ϑ_{ints}	29
6.4.3	Relative welding factor, X_{WrelT}	34
Annex A (informative) Examples		35
Annex B (informative) Contact-time-dependent scuffing temperature		44
Bibliography		49

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 60, *Gears*, Subcommittee SC 2, *Gear capacity calculation*.

This first edition of ISO/TS 6336-21 cancels and replaces ISO/TR 13989-2.

A list of all parts in the ISO 6336 series can be found on the ISO website. See also the Introduction for an overview.

Introduction

The ISO 6336 series consists of International Standards, Technical Specifications (TS) and Technical Reports (TR) under the general title *Calculation of load capacity of spur and helical gears* (see [Table 1](#)).

- International Standards contain calculation methods that are based on widely accepted practices and have been validated.
- TS contain calculation methods that are still subject to further development.
- TR contain data that is informative, such as example calculations.

The procedures specified in ISO 6336-1 to ISO 6336-19 cover fatigue analyses for gear ratings. The procedures described in ISO 6336-20 to ISO 6336-29 are predominantly related to the tribological behaviour of the lubricated flank surface contact. ISO 6336-30 to ISO 6336-39 include example calculations. The ISO 6336 series allows the addition of new parts under appropriate numbers to reflect knowledge gained in the future.

Requesting standardized calculations according to ISO 6336 without referring to specific parts requires the use of only those parts that are currently designated as International Standards (see [Table 1](#) for listing). When requesting further calculations, the relevant part or parts of ISO 6336 need to be specified. Use of a Technical Specification as acceptance criteria for a specific design needs to be agreed in advance between manufacturer and purchaser.

Table 1 — Overview of ISO 6336

Calculation of load capacity of spur and helical gears	International Standard	Technical Specification	Technical Report
<i>Part 1: Basic principles, introduction and general influence factors</i>	X		
<i>Part 2: Calculation of surface durability (pitting)</i>	X		
<i>Part 3: Calculation of tooth bending strength</i>	X		
<i>Part 4: Calculation of tooth flank fracture load capacity</i>		X	
<i>Part 5: Strength and quality of materials</i>	X		
<i>Part 6: Calculation of service life under variable load</i>	X		
<i>Part 20: Calculation of scuffing load capacity (also applicable to bevel and hypoid gears) — Flash temperature method (Replaces ISO/TR 13989-1)</i>		X	
<i>Part 21: Calculation of scuffing load capacity (also applicable to bevel and hypoid gears) — Integral temperature method (Replaces ISO/TR 13989-2)</i>		X	
<i>Part 22: Calculation of micropitting load capacity (Replaces ISO/TR 15144-1)</i>		X	
<i>Part 30: Calculation examples for the application of ISO 6336-1, ISO 6336-2, ISO 6336-3 and ISO 6336-5</i>			X
<i>Part 31: Calculation examples of micropitting load capacity (Replaces ISO/TR 15144-2)</i>			X

At the time of publication of this document, some of the parts listed here were under development. Consult the ISO website.

This document describes the surface damage "warm scuffing" for cylindrical (spur and helical), bevel and hypoid gears for generally used gear materials and different heat treatments. "Warm scuffing" is characterized by typical scuffing and scoring marks, which can lead to increasing power loss, dynamic load, noise and wear. For "cold scuffing", generally associated with low temperature and low speed, under approximately 4 m/s, and through-hardened, heavily loaded gears, the formulae are not suitable.

There is a particularly severe form of gear tooth surface damage in which seizure or welding together of areas of tooth surfaces occurs due to absence or breakdown of a lubricant film between the contacting tooth flanks of mating gears caused by high temperature and high pressure. This form of damage is

termed "scuffing" and most relevant when surface velocities are high. Scuffing may also occur for relatively low sliding velocities when tooth surface pressures are high enough, either generally or, because of uneven surface geometry and loading, in discrete areas.

Risk of scuffing damage varies with the properties of gear materials, the lubricant used, the surface roughness of tooth flanks, the sliding velocities and the load. Excessive aeration or the presence of contaminants in the lubricant such as metal particles in suspension, also increases the risk of scuffing damage. Consequences of the scuffing of high speed gears include a tendency to high levels of dynamic loading due to increase of vibration, which usually leads to further damage by scuffing, pitting and tooth breakage.

High surface temperatures due to high surface pressures and sliding velocities can initiate the breakdown of lubricant films. On the basis of this hypothesis, two approaches to relate temperature to lubricant film breakdown are presented:

- the flash temperature method (presented in ISO/TS 6336-20), based on contact temperatures which vary along the path of contact;
- the integral temperature method (presented in this document), based on the weighted average of the contact temperatures along the path of contact.

The integral temperature method is based on the assumption that scuffing is likely to occur when the mean value of the contact temperature (integral temperature) is equal to or exceeds a corresponding critical value. The risk of scuffing of an actual gear unit can be predicted by comparing the integral temperature with the critical value, derived from a gear test on scuffing resistance of lubricants. The calculation method takes account of all significant influencing parameters, i.e. the lubricant (mineral oil with and without EP-additives, synthetic oils), the surface roughness, the sliding velocities, the load, etc.

In order to ensure that all types of scuffing and comparable forms of surface damage due to the complex relationships between hydrodynamical, thermodynamical and chemical phenomena are dealt with, further methods of assessment may be necessary. The development of such methods is the objective of ongoing research.

Currently in preview, click buy full version

Calculation of load capacity of spur and helical gears —

Part 21:

Calculation of scuffing load capacity (also applicable to bevel and hypoid gears) — Integral temperature method

1 Scope

This document specifies the integral temperature method for calculating the scuffing load capacity of cylindrical, bevel and hypoid gears.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 53, *Cylindrical gears for general and heavy engineering — Standard basic rack tooth profile*

ISO 1122-2, *Vocabulary of gear terms — Part 2: Definitions related to worm gear geometry*

ISO 1328-1, *Cylindrical gears — ISO system of flank tolerance classification — Part 1: Definitions and allowable values of deviations relevant to flanks of gear teeth*

ISO 10300-1, *Calculation of load capacity of bevel gears — Part 1: Introduction and general influence factors*

3 Terms, definitions, symbols and units

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 1122-2 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.2 Symbols and units

The symbols used in this document are given in [Table 2](#).