

**CGA E-1—2022
STANDARD FOR RUBBER
WELDING HOSE AND
HOSE CONNECTIONS
FOR GAS WELDING,
CUTTING, AND ALLIED
PROCESSES**

EIGHTH EDITION

PLEASE NOTE:

The information contained in this document was obtained from sources believed to be reliable and is based on technical information and experience currently available from members of the Compressed Gas Association, Inc. and others. However, the Association or its members, jointly or severally, make no guarantee of the results and assume no liability or responsibility in connection with the information or suggestions herein contained. Moreover, it should not be assumed that every acceptable commodity grade, test or safety procedure or method, precaution, equipment or device is contained within, or that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedure.

This document is subject to periodic review, and users are cautioned to obtain the latest edition. The Association invites comments and suggestions for consideration. In connection with such review, any such comments or suggestions will be fully reviewed by the Association after giving the party, upon request, a reasonable opportunity to be heard. Proposed changes may be submitted via the Internet at our web site, www.cganet.com.

This document should not be confused with federal, state, provincial, or municipal specifications or regulations; insurance requirements; or national safety codes. While the Association recommends reference to or use of this document by government agencies and others, this document is purely voluntary and not binding unless adopted by reference in regulations.

A listing of all publications, audiovisual programs, safety and technical bulletins, and safety posters is available via the Internet at our website at www.cganet.com. For more information contact CGA. Phone: 703-788-2700, ext. 799. E-mail: customerservice@cganet.com.

Work Item 21-035
Industrial Gases Apparatus Committee

NOTE—Technical changes from the previous edition are underlined

NOTE—Appendix A (Informative) is for information only.

NOTE—Appendix B (Normative) is a requirement.

EIGHTH EDITION: 2022
SEVENTH EDITION: 2016
SIXTH EDITION: 2009
FIFTH EDITION: 2005

© 2022X The Compressed Gas Association, Inc. All rights reserved.

All materials contained in this work are protected by United States and international copyright laws. No part of this work may be reproduced or transmitted in any form or by any means, electronic or mechanical including photocopying, recording, or any information storage and retrieval system without permission in writing from The Compressed Gas Association, Inc. All requests for permission to reproduce material from this work should be directed to The Compressed Gas Association, Inc., 8484 Westpark Drive, Suite 220, McLean, VA 22102. You may not alter or remove any trademark, copyright or other notice from this work.

Contents	Page
1 Introduction.....	1
2 Scope	1
3 Definitions.....	1
4 Connections	2
4.1 Materials	2
4.2 Connectors	2
4.3 Nuts	2
4.4 Tailpieces	2
4.5 Clamps or Ferrules.....	2
5 Hose	3
5.1 Materials and construction.....	3
5.2 Hose grade	3
5.3 Hose types.....	3
5.4 Hose sizes	3
5.5 Hose tube and cover	4
5.6 Hose color	4
5.7 Hose marking	4
6 Fitted hose assembly	4
6.1 Physical tests.....	5
6.2 Operating temperature range	5
6.3 Production test.....	5
7 Design requirements for fitted hose assemblies	5
7.1 Physical strength	5
7.2 Pressure capabilities	6
8 References	16
9 Additional references.....	16
Figures	
Figure 1—Examples of tailpiece configurations	3
Figure 2—Fitted hose assembly	5
Tables	
Table 1—Inside diameter (ID), hose sizes and tolerances	4
Table 2—Hose color code	4
Table 3—Minimum pull strength for axial and right angle pulling.....	6
Appendices	
Appendix A—Use of rubber welding hose (Informative)	17
Appendix B—Universal part numbering system for the identification of standard items used in fitted hose assemblies (Normative).....	18
Appendix figure	
Figure B-1—Universal part numbering system	18
Appendix table	
Table B-1—Assigning a value (for tailpieces) to the other detail field of the universal part number	19

This page is intentionally blank.

Currently in preview, click buy full version

1 Introduction

Specifications describing hose connections for welding and cutting equipment were formulated and adopted in 1925 by the International Acetylene Association (IAA), the Gas Products Association, and various manufacturers. Similar specifications were adopted by the National Screw Thread Commission in 1926. Revised specifications were adopted by the IAA in 1939 and amended in 1953 and 1954. Until 1954, the specifications dealt with connections for oxygen and fuel gases for welding and cutting. With the advent of inert gases used for blanketing (to prevent oxidation) and water used for cooling in inert gas metal arc welding processes, significant additions to the specifications were adopted by IAA in 1957. In 1962 the IAA ceased to exist, and its activities were taken over by the Compressed Gas Association, Inc. (CGA). IAA specifications were revised in accordance with similar CGA standards. In this standard, each connection size and style is presented on a separate page with the right-hand and left-hand connections shown on the same page with a single drawing.

It should be noted that Connection No. 022 for oxygen is similar to Connection No. 1240 in CGA V-5, *Standard for Diameter Index Safety System (Noninterchangeable Low Pressure Connections for Medical Gases Applications)* [1].¹ Dimensions and other information on hose connections for welding and cutting equipment are found in FED-STD-H28, *Screw-Thread Standards for Federal Services*, Section 11, "Hose Connections for Welding and Cutting Equipment" [2].

For years, CGA jointly issued a rubber welding hose standard, ARPM IP7, *Specification for Rubber Welding Hose*, with the Association for Rubber Products Manufacturers (ARPM) [3]. CGA became aware that incidents can occur if the wrong grade of hose was selected for the particular gas being used. Therefore, in 2004, CGA recommended the exclusive use of Grade T hose in CGA SB-11, *Use of Rubber Welding Hose* since Grade T hose eliminates the gas compatibility, oil resistance, and flammability issues.

NOTE—CGA SB-11, *Use of Rubber Welding Hose*, was incorporated into the seventh edition of CGA E-1 as an informative appendix, see Appendix A.

2 Scope

This standard provides specifications for multi-service rubber hose used for welding, cutting, and allied processes. This standard also describes connections for regulator outlets, torches, and fitted hose for welding and cutting equipment. It provides the dimensions of components (threaded connector, tailpiece, and coupling nut) for 18 different connections (Connection No. 022 through Connection No. 037) that can be used to connect gas hoses with torches and regulator outlets.

To promote safety and reliability in service, the performance requirements that shall be met by the completed assemblies at the time of manufacture or rebuilding are specified.

This standard does not apply to liquefied petroleum (LP) gas hose covered under National Fire Protection Association (NFPA) 58, *Liquefied Petroleum Gas Code* applicable to the propane industry [4].

This standard describes the performance requirements of the hose that is fitted on the tailpiece with a clamp or ferrule.

3 Definition

For the purpose of this publication, the following definitions apply.

3.1 Publication terminology

3.1.1 Shall

Indicates that the procedure is mandatory. It is used wherever the criterion for conformance to specific recommendations allows no deviation.

3.1.2 Should

Indicates that a procedure is recommended.

¹ References are shown by bracketed numbers and are listed in order of appearance in the reference section.