

**CGA G-1—2021**  
**ACETYLENE**  
FOURTEENTH EDITION

Currently in preview, click buy full version

**PLEASE NOTE:**

The information contained in this document was obtained from sources believed to be reliable and is based on technical information and experience currently available from members of the Compressed Gas Association, Inc. and others. However, the Association or its members, jointly or severally, make no guarantee of the results and assume no liability or responsibility in connection with the information or suggestions herein contained. Moreover, it should not be assumed that every acceptable commodity grade, test or safety procedure or method, precaution, equipment or device is contained within, or that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedure.

This document is subject to periodic review, and users are cautioned to obtain the latest edition. The Association invites comments and suggestions for consideration. In connection with such review, any such comments or suggestions will be fully reviewed by the Association after giving the party, upon request, a reasonable opportunity to be heard. Proposed changes may be submitted via the Internet at our website, [www.cganet.com](http://www.cganet.com).

This document should not be confused with federal, state, provincial, or municipal specifications or regulations; insurance requirements; or national safety codes. While the Association recommends reference to or use of this document by government agencies and others, this document is purely voluntary and not binding unless adopted by reference in regulations.

A listing of all publications, audiovisual programs, safety and technical bulletins, and safety posters is available via the Internet at our website at [www.cganet.com](http://www.cganet.com). For more information contact CGA. Phone: 703-788-2700, ext. 799. E-mail: [customerservice@cganet.com](mailto:customerservice@cganet.com).

Work Item 20-014  
Acetylene Committee

---

NOTE—Technical changes from the previous edition are underlined

FOURTEENTH EDITION: 2021  
THIRTEENTH EDITION: 2015  
TWELFTH EDITION: 2009  
ELEVENTH EDITION: 2003  
TENTH EDITION: 2001

© 2021 The Compressed Gas Association, Inc. All rights reserved.

All materials contained in this work are protected by United States and international copyright laws. No part of this work may be reproduced or transmitted in any form or by any means, electronic or mechanical including photocopying, recording, or any information storage and retrieval system without permission in writing from The Compressed Gas Association, Inc. All requests for permission to reproduce material from this work should be directed to The Compressed Gas Association, Inc., 8484 Westpark Drive, Suite 220, McLean, VA 22102. You may not alter or remove any trademark, copyright or other notice from this work.

<b>Contents</b>	<b>Page</b>
1 Introduction.....	1
2 Scope .....	1
3 Acetylene.....	1
3.1 Composition.....	1
3.2 Physical and chemical properties.....	1
3.3 Physiological effects.....	3
3.4 Manufacture.....	5
3.5 Pipeline use of acetylene .....	5
3.6 Cylinder use.....	5
4 Acetylene cylinders .....	5
4.1 General.....	5
4.2 Valves.....	6
4.3 Pressure relief devices .....	6
4.4 Filling limits.....	7
4.5 Marking and labeling .....	7
4.6 Refilling.....	8
5 Storing acetylene cylinders at user's premises .....	8
5.1 General.....	8
5.2 Rules for storing acetylene cylinders.....	8
6 Handling and using acetylene cylinders .....	9
6.1 Moving cylinders.....	10
6.2 Withdrawing acetylene from cylinders.....	10
6.3 Determining cylinder contents .....	11
6.4 Returning empty cylinders .....	12
6.5 Handling leaking cylinders.....	12
6.6 Prevention of fire .....	12
7 Piping, fittings, and equipment .....	12
8 References .....	13
 <b>Table</b>	
Table 1—Physical constants of acetylene .....	2
 <b>Figure</b>	
Figure 1—Acetylene vapor-liquid equilibrium curve.....	3
Figure 2—Typical acetylene cylinder shell constructions.....	4

## 1 Introduction

This publication is one of a series compiled by the Compressed Gas Association, Inc. (CGA) to satisfy the demand for information relative to the production, transportation, handling, and storage of compressed gases. NFPA 55, *Compressed Gases and Cryogenic Fluids Code*, provides information relative to the manufacture, handling, and storage of acetylene by cylinder charging plants [1].<sup>1</sup>

## 2 Scope

This publication presents general information on the characteristics of acetylene and its handling. Requests for specialized technical information should be directed to the manufacturers of this gas.

The following references may also be useful to acetylene users:

- NFPA 51, *Standard for the Design and Installation of Oxygen-Fuel Gas Systems for Welding, Cutting and Allied Processes* [2];
- NFPA 51B, *Standard for Fire Prevention During Welding, Cutting, and other Hot Work* [3];
- ANSI/AWS Z49.1, *Safety in Welding and Cutting and Allied Processes* [4]; and
- CGA G-1.11, *Guideline for Handling Acetylene Cylinders and Ancillary Equipment in Fires* [5].

## 3 Acetylene

### 3.1 Composition

Acetylene is a compound of the elements carbon and hydrogen. Its composition is expressed by the chemical symbol  $C_2H_2$ . On a weight basis, the proportion of the elements in acetylene is approximately 12 parts of carbon to 1 part of hydrogen, or 92.3% to 7.7%, respectively.

### 3.2 Physical and chemical properties

At atmospheric temperatures and pressures, acetylene is a colorless gas that is slightly lighter than air. Acetylene of 100% purity is odorless, but acetylene of ordinary commercial purity has a distinctive, garlic-like odor. Some physical constants of acetylene are given in Table 1.

Acetylene burns in air with an intensely hot, luminous, and smoky flame. The ignition temperatures of acetylene and mixtures of acetylene with air or acetylene with oxygen will vary according to composition, pressure, water vapor content, and initial temperature. As a typical example, mixtures containing 30% acetylene by volume with air at atmospheric pressure can be ignited at approximately 581 °F (305 °C). The flammable limits of mixtures of acetylene with air and acetylene with oxygen will depend on the initial pressure, temperature, and water vapor content. In air at atmospheric pressure, the upper limit of flammability is approximately 81% acetylene in air. The lower limit is 2.5% acetylene in air.

Acetylene can be liquefied and solidified with relative ease, but both liquid and solid acetylene are unstable. Liquefied acetylene has a higher shock sensitivity and energy density than compressed gaseous acetylene. Thus, the liquefaction of acetylene shall be absolutely avoided. Figure 1 presents the vapor pressure curve for acetylene. Maintaining the pressure-temperature combination of acetylene below the curve will keep acetylene in the gaseous phase. Note that at low temperatures, acetylene could liquefy at common operating pressures.

<sup>1</sup> References are shown by bracketed numbers and are listed in order of appearance in the reference section.