

ANSI/CGA G-13— 2024

4TH EDITION

**STORAGE AND
HANDLING OF
SILANE AND
SILANE MIXTURES**



Currently in preview, click buy full version

PREFACE:

As part of a program of harmonization of industry standards, the Compressed Gas Association (CGA) has published CGA G-13, *Storage and Handling of Silane and Silane Mixtures*, jointly produced by members of the International Harmonization Council.

This publication is intended as an international harmonized standard for the worldwide use and application of all members of the Asia Industrial Gases Association (AIGA), Compressed Gas Association (CGA), European Industrial Gases Association (EIGA), and Japan Industrial and Medical Gases Association (JIMGA). Each association's technical content is identical, except for regional regulatory requirements and minor changes in formatting and spelling.

PLEASE NOTE:

The information contained in this document was obtained from sources believed to be reliable and is based on technical information and experience currently available from members of the Compressed Gas Association, Inc. and others. However, the Association or its members, jointly or severally, make no guarantee of the results and assume no liability or responsibility in connection with the information or suggestions herein contained. Moreover, it should not be assumed that every acceptable commodity grade, test or safety procedure or method, precaution, equipment or device is contained within, or that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedure.

This document is subject to periodic review, and users are cautioned to obtain the latest edition. The Association invites comments and suggestions for consideration. In connection with such review, any such comments or suggestions will be fully reviewed by the Association after giving the party, upon request, a reasonable opportunity to be heard. Proposed changes may be submitted via the Internet at our website, www.cganet.com.

This document should not be confused with Federal, state, provincial, or municipal specifications or regulations; insurance requirements; or national safety codes. While the Association recommends reference to or use of this document by government agencies and others, this document is purely voluntary and not binding.

A listing of all publications, audiovisual programs, safety and technical bulletins, and safety posters is available via the Internet at our website at www.cganet.com. For more information contact CGA at Phone: 703-788-2700, ext. 799. E-mail: customerservice@cganet.com.

Work Item 16-057
Specialty Gases Committee

NOTE—Technical changes from the previous edition are underlined.

NOTE—Appendices A, B, and C (Informative) are for information only.

NOTE—Appendices and D (Normative) are requirements.

FOURTH EDITION: 2023 (ANSI APPROVED 2024)

THIRD EDITION: 2015

SECOND EDITION: 2006

FIRST EDITION: 2000

© 2023 The Compressed Gas Association, Inc. All rights reserved.

All materials contained in this work are protected by United States and international copyright laws. No part of this work may be reproduced or transmitted in any form or by any means, electronic or mechanical including photocopying, recording, or any information storage and retrieval system without permission in writing from The Compressed Gas Association, Inc. All requests for permission to reproduce material from this work should be directed to The Compressed Gas Association, Inc., 8484 Westpark Drive, Suite 220, Mclean, VA 22102. You may not alter or remove any trademark, copyright or other notice from this work.

AMERICAN NATIONAL STANDARD

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: The American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken to periodically reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute, 11 West 42nd Street, New York, NY 10036.

Approved as an American National Standard on May 20, 2024.

Contents	Page
1 Introduction.....	1
2 Scope and purpose	1
2.1 Scope	1
2.2 Purpose	2
2.3 Equivalency	2
3 Definitions.....	2
4 Physical and chemical properties	9
4.1 Description.....	9
4.2 Properties	9
4.3 Pyrophoric nature of silane.....	9
5 Packaging information.....	11
5.1 General.....	11
5.2 Container outlet	11
5.3 Cap (plug) of container outlet	11
6 Outdoor storage and use.....	11
6.1 Applicability.....	11
6.2 General.....	11
6.3 Distances to exposures and separation	13
6.4 Silane delivery systems	19
7 Indoor storage and use	21
7.1 Applicability.....	21
7.2 Indoor storage	22
7.3 Nonbulk sources and systems.....	22
7.4 Barricade construction—unattended operations	22
7.5 Egress	22
7.6 Explosion control	22
7.7 Electrical requirements.....	22
7.8 Ventilation.....	22
7.9 Quantity limits.....	22
7.10 Separation from incompatible materials.....	22
7.11 Gas cabinets.....	23
7.12 Shutdown and source isolation	23
8 System configuration—cylinder sources	23
8.1 Outdoor installations	23
8.2 Indoor installations	24
9 System configuration—bulk sources	26
9.1 Use equipment	26
9.2 Outdoor installations.....	27
9.3 Bulk containers	27
9.4 Bulk source process gas panel.....	28
9.5 Valve manifold boxes	28
10 Piping and components.....	28
10.1 Piping system design	28
10.2 Components	30
10.3 Support of piping systems	32
11 Gas and flame detection	33
11.1 Gas monitoring	33
11.2 Flame detection	34

12	Fire protection system	34
12.1	General.....	34
12.2	Outdoor systems	35
12.3	Indoor systems	35
13	Ventilation systems	36
13.1	Outdoor systems	36
13.2	Indoor systems	36
14	Venting and treatment	38
14.1	General.....	38
14.2	Disposal options	38
14.3	Treatment system requirements.....	38
14.4	Direct venting into exhaust ducts.....	38
14.5	Dedicated process vent.....	38
15	Purge gas system.....	39
15.1	Purging of the delivery system	39
15.2	Dedicated purge source	39
15.3	Controls	40
15.4	Vacuum generator purge gas source	40
16	Electrical requirements	40
16.1	General.....	40
16.2	Emergency power.....	40
16.3	Outdoor electrical systems	41
17	Fundamental supervisory control requirements	41
17.1	Indoor requirements	41
17.2	Outdoor requirements.....	41
18	Container filling.....	42
18.1	Container filling facilities	42
18.2	Filling system.....	44
18.3	Filling safeguards	45
18.4	Manufacturing/Filling plant storage	46
19	References	47
20	Additional references.....	49

Figures

Figure 1—Instrument nomenclature.....	5
Figure 2—Support structure protection against flame impingement	19
Figure 3—Typical end user outdoor cylinder layout.....	20
Figure 4—Typical bulk source container layout	21
Figure 5—Typical silane process gas panel	23
Figure 6—Typical silane purge gas panel.....	24
Figure 7—Valve manifold box flow schematic	26
Figure 8—Typical bulk system process flow diagram	27
Figure 9—Inert purge gas flow schematic.....	39

Tables

Table 1—Physical and chemical properties of silane.....	9
Table 2—Occupational exposure limits (OELs)	10
Table 3—ADR packaging information	11
Table 4—DOT packaging information	11
Table 5—Distances to exposure for outdoor cylinders in storage or use up to 50 L.....	16
Table 6—Distance to exposures for outdoor silane tube trailers, ISO modules, ton tank, and cylinder packs in use.....	17

Table 7—Distance to exposures for outdoor silane tube trailers, ISO modules, and ton tanks in storage	18
Table 8—Minimum ventilation volumetric flow rate for gas cabinets and valve manifold boxes— unattended operations	37
Table 9—Indoor requirements for supervisory control—silane systems containing silane in concentrations exceeding 1.4% by volume	41
Table 10—Outdoor requirements for supervisory control—silane systems containing silane in concentrations exceeding 1.4% by volume	41
Table 11—Minimum ventilation volumetric flow rate for exhausted enclosures	43

Appendices

Appendix A—Personnel protection (Informative)	50
Appendix B—Explanatory material (Informative)	52
Appendix C—Possible code interpretation for use of a low concentration mixtures of silane in nitrogen (Informative)	55
Appendix D—Thermal radiation (Normative)	56
Appendix E—Guidance on overpressure based separation distances for bulk silane storage or use (Normative)	78

Appendices Figures

Figure B-1—Silane compressability	52
Figure B-2—Observed ignition distance for different silane flow velocity from 4.32 mm pipe connectors	53
Figure D-1—Thermal dose for ISO modules or tube trailers with 0.85 in pressure relief device	60
Figure D-2—Thermal dose for ISO modules or tube trailers with 0.64 in pressure relief device	60
Figure D-3—Thermal dose for ISO modules or tube trailers with 0.45 in pressure relief device	61
Figure D-4—Thermal dose for ton tank with 0.57 in pressure relief device, 100% flow for use	61
Figure D-5—Thermal dose for ton tank with 0.57 in pressure relief device, 50% flow for storage	62
Figure D-6—Thermal dose for ton tank with 0.39 in pressure relief device, 100% flow for use	62
Figure D-7—Thermal dose for ton tank with 0.39 in pressure relief device, 50% flow for storage	63
Figure D-8—Thermal dose for ton tank with 0.28 in pressure relief device, 100% flow for use	63
Figure D-9—Thermal dose for ton tank with 0.28 in pressure relief device, 50% flow for storage	64
Figure D-10—Pressure relief device release time for a ton tank (450 L container)	64
Figure D-11—Pressure relief device release time for tube in ISO container (40 ft tube for .85 in & .64 in pressure relief device and 20 ft tube for .45 in pressure relief device)	65
Figure D-12—Thermal radiation for tube trailer and ISO module with 0.85 in pressure relief device	66
Figure D-13—Thermal radiation for tube trailer and ISO module with 0.64 in pressure relief device	67
Figure D-14—Thermal radiation for tube trailer and ISO module with 0.45 in pressure relief device	68
Figure D-15—Thermal radiation for ton tank (450 L) with .57 in pressure relief device, 100% flow for use	69
Figure D-16—Thermal radiation for ton tank (450 L) with .57 in pressure relief device, 50% flow for storage ..	70
Figure D-17—Thermal radiation for ton tank (450 L) with .39 in pressure relief device, 100% flow for use	71
Figure D-18—Thermal radiation for ton tank (450 L) with .39 in pressure relief device, 50% flow for storage ..	72
Figure D-19—Thermal radiation for ton tank (450 L) with .28 in pressure relief device, 100% flow for use	73
Figure D-20—Thermal radiation for ton tank (450 L) with .28 in pressure relief device, 50% flow for storage ..	74
Figure D-21—Thermal radiation for package without pressure relief device and in use—pigtail release with 0.125 in restrictive flow orifice	75
Figure D-22—Thermal radiation for package without pressure relief device and in use— pigtail release with 0.060 in restrictive flow orifice	76
Figure D-23—Thermal radiation for package without pressure relief device and in use— pigtail release with no restrictive flow orifice	77

Appendices Tables

Table D-1—Thermal radiation data for cylinders with pressure relief devices	57
Table E-1—Flammable mass coefficient c_1 when d is specified in mm	79
Table E-2—Flammable mass coefficient c_1 when d is specified in inches	79
Table E-3—Coefficient α_{PRD} for use in distance formula with unobstructed, unconfined, vertical pressure relief device releases	80
Table E-4—Coefficient α_{PRD} for use in distance formula with obstructed pressure relief device release	80

1 Introduction

The use of the pyrophoric gas silane as a source of silicon has grown with its consumption by semiconductor manufacturers, video display manufacturers, producers of solar cells, and allied technologies. Systems once imagined to be rare are now commonplace and are in use worldwide. Hazards of this material are noteworthy due to the ability of this material to self-ignite with visible flame upon release or in other cases to be released with either no ignition or delayed ignition. This material has been the subject of technical study by users and suppliers [1].¹ Studies conducted by the Compressed Gas Association (CGA) of the release of both large and small scale quantities of silane have produced new technical data [2, 3, 4]. The data have been used to establish minimum separation distances for delivery system installations as well as for the storage of this material. Distance limitations are used to lessen risk to property and personnel in the event of an inadvertent release. The distances determined recognize the probability for immediate ignition as well as the probability of latent ignition with its potential explosive effects. Although the uncontrolled release of compressed gas is a cause for concern, this is the application of engineering and administrative controls to prevent the release of material that allows the users to handle this material at a reduced level of risk. Suppliers and users have contributed to the development of these controls presented in this standard as a means to provide reasonable safeguards for handling this unique material that is characterized by its chemical and physical nature.

It is intended that this standard applies to storage and use of silane containers with the exception of small containers with 0.5 scf (14 L) or less of silane content.

2 Scope and purpose

2.1 Scope

This standard governs the installation of systems and sources that are used to store, transfer, or contain silane or silane mixtures. This standard includes guidance for siting, design of equipment, piping and controls, and the fabrication and installation of silane gas storage and closed-use systems. Additional guidance on operational steps associated with the use of silane and silane mixtures as well as fire protection, gas monitoring, ventilation, and related safeguards are provided.

2.1.1 Application

The requirements of this standard apply to pure silane and silane mixtures with a silane content greater than 1.4% by volume [5]. A concentration of 1.4% has been chosen as it represents the lower flammability limit (LFL) for this material in air under conditions of normal temperature and pressure. Silane containers include tube trailers, International Organization for Standardization (ISO) modules, cylinder packs with manifolded cylinders, and individual cylinders. Silane mixtures containing other hazardous components (e.g., toxics) may have additional requirements beyond this standard. These other requirements shall also be taken into consideration and may exceed requirements in this standard.

2.1.2 Limitations

This standard is not intended to provide requirements beyond the first point of control within a user's facility where connections are made to piping systems associated with internal transmission and/or use of this material.

The following subjects are outside the scope of this standard:

- Equipment downstream of a gas cabinet with the exception of valve manifold boxes (VMBs) when used;
- On-site transportation of compressed gases regulated by the U.S. Department of Transportation (DOT), European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), or other regulatory authorities; and
- Requirements within the jurisdiction of local, state, provincial/territorial, and national regulatory authorities with laws or regulations that preempt the provisions of this standard. When such is the case, it is recommended that the authority having jurisdiction (AHJ) be guided by this standard in determining requirements.

¹References are shown by bracketed numbers and are listed in order of appearance in the reference section.